

Packet Tracer - Investigate STP Loop Prevention

Objectives

In this lab, you will observe spanning-tree port states and watch the spanning-tree convergence process.

- Describe the operation of Spanning Tree Protocol.
- Explain how Spanning Tree Protocol prevents switching loops while allowing redundancy in switched networks.

Background / Scenario

In this activity you will use Packet Tracer to observe the operation of Spanning Tree Protocol in a simple switched network that has redundant paths.

Instructions

Part 1: Observe a Converged Spanning-Tree Instance

Step 1: Verify Connectivity.

Ping from PC1 to PC2 to verify connectivity between the hosts. Your ping should be successful.

Step 2: View spanning-tree status on each switch.

Use the **show spanning-tree vlan 1** command to gather information about the spanning tree status of each switch. Complete the table. For the purposes of the activity, only consider information about the Gigabit trunk ports. The Fast Ethernet ports are access ports that have end devices connected and are not part of the inter-switch trunk-based spanning tree.

Switch	Port	Status (FWD, BLK...)	Root Bridge?
S1	G0/1	FWD	No
	G0/2	FWD	No
S2	G0/1	FWD	Yes
	G0/2	FWD	Yes
S3	G0/1	FWD	No
	G0/2	BLK	No

Packet Tracer uses a different link light on one of the connections between the switches.

What do you think this link light means?

- **The port is currently in a "blocking" state, part of the spanning-tree protocol, which prevents it from forwarding data packets.**

Packet Tracer - Investigate STP Loop Prevention

What path will frames take from PC1 to PC2

- **The frames will be routed from switch S1 to switch S2.**

Why do the frames not travel through S3?

- **The spanning-tree protocol has disabled port G0/2 on S3, effectively shutting off data transmission on that port.**

Why has a spanning tree placed a port in a blocking state?

- **Unrestricted frame forwarding across all ports results in a switching loop within the network. These loops are detrimental to network performance, potentially causing network instability and failure.**

Part 2: Observe spanning-tree convergence

Step 1: Remove the connection between S1 and S2.

Open a CLI window on switch S3 and issue the command `show spanning-tree vlan 1`. Leave the CLI window open.

Select the delete tool from the menu bar and click the cable that connects S1 and S2.

Step 2: Observe spanning-tree convergence.

Quickly return to the CLI prompt on switch S3 and issue the `show spanning-tree vlan 1` command. Use the up-arrow key to recall the `show spanning-tree vlan 1` command and issue it repeatedly until the orange link light on the cable turns green. Observe the status of port G0/2.

What do you see happen to the status of the G0/2 port during this process?

- **The port's state transitioned from BLK to LSN, then to LRN, and finally to FWD.**

You have observed the transition in port status that occurs as a spanning-tree port moves from blocking to forwarding state.

Verify Connectivity by pinging from PC1 to PC2. Your ping should be successful.

Are any ports showing an orange link light that indicates that the port is in a spanning-tree state other than forwarding? Why or why not?

- **The orange link lights are off due to the elimination of redundant paths in the network.**

