Donproof Primer PU1000

Single component solvent based polyurethane primer

DESCRIPTION

Donproof Primer PU1000 is a single component solvent based moisture cure polyurethane primer especially formulated as an adhesion promoter on old Donproof PU polyurea waterproofing membranes, in addition to repairs and membrane overlapping of Donproof PU polyurea waterproofing membranes.

APPLICATIONS

- As an adhesion promoter on old Donproof PU polyurea waterproofing membranes.
- Repairs and membrane overlap on Donproof PU polyurea waterproofing membranes.
- Increase bonding and improve the surface leveling of the substrates such mortar and concrete prior to the application of Donproof PU polyurea waterproofing systems.

ADVANTAGES

- Easy to use, single component product that does not need mixing.
- Increases the service life of the waterproofing system.
- Economical solution in waterproofing systems.

METHOD OF USE

SURFACE PREPARATION

The substrate should be sound, clean and free from laitance, oils, release agents, contaminations and without excessive irregularities.

Concrete floors must have a maximum relative humidity of 80% (max. moisture content of 4%). Surface should be prepared by light scrabbling or grit blasting to achieve a CSP values 3 to 5.

Ensure that all pinholes and grooves are properly filled using suitable epoxy putty materials in the prepared substrate prior to the application of subsequent layers.

TECHNICAL PROPERTIES:	
Density:	1.12 ± 0.08 g/cm³
Volume solid:	70 ± 5%
Overcoating time:	3 to 48 hr @ 25°C
Bond strength on concrete: EN 1542	≥ 2 MPa
Application temperature:	5 to 30°C

APPLICATION

Stir the product well before use, Donproof Primer PU1000 can be applied by a brush or short nap acrylic wool roller. Donproof Primer PU1000 should be applied in thin coats at a rate of 0.10 - 0.15 kg/m² depending on the porosity of the substrate.

In applications of repairs/overlaps/joining bridge between already cured membranes, the consumption could be less. Care must be taken in the application of the material according to the coverage rate in thin coat, never thick.

CLEANING

All tools should be cleaned immediately with paper towels after finishing and then wiped using DCP Solvent PU.

PACKAGING

Donproof Primer PU1000 is available in 5 kg, and 20 kg packs.

COVERAGE

Donproof Primer PU1000 should be applied in thin coats at a rate of 0.10 - 0.15 kg/m² depending on the substrate porosity. Apply as many coats as the substrate needs.

In applications of repairs/overlaps/joining bridge between already cured membranes, the consumption could be les.

Donproof Primer PU1000

STORAGE

Donproof Primer PU1000 has a shelf life of 12 months from the date of manufacturing if stored at temperatures between 5 and 35°C in its original unopened package.

If these conditions are exceeded, contact DCP Technical Department for advice.

CAUTIONS

HEALTH AND SAFETY

Apply in well ventilated areas. Do not smoke. Do not apply near naked flames. In closed areas use force ventilation and carbon active masks. Keep in mind that solvents are heavier than air so vapour concentration is higher in air closer to floor.

For further information, refer to the Material Safety Data Sheet.

FIRE

Donproof Primer PU1000 and DCP Solvent PU are flammable materials.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- Concrete admixtures.
- Surface treatments
- Grouts and anchors.
- Concrete repair.
- Flooring systems.
- Protective coatings.
- Sealants.
- Waterproofing.
- Adhesives.
- Tile adhesives and grouts.
- Building products.
- Structural strengthening.

Note:
We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.