

Technical Specification Sheet

Model: GS7018E	Made: Girbau - Spain	Reference:	Quantity:
-----------------------	-----------------------------	-------------------	------------------

Wet Cleaning Washer Extractor: High Speed, Freestanding, Electric Heated

Capacity: 20kg (1/9), 18kg (1/10)

Drum: Diameter: 700 mm, Depth: 459 mm, Volume: 177 dm³

Door Opening: 470 mm

Floor to Door Height: 521 mm

Washing Speed INTEL: 45 rpm

Spin Speed: 1071 rpm

G force: 450



Robustness, durability and reliability

The redesigned floating system together with the Motion Guard sensor to monitor the machine at all times ensure the robustness and reliability our customers need

Optimised features

The new GENIUS goes a step further in terms of optimum operation thanks to the above-mentioned accelerometer. This device monitors and corrects any out-of-balance to ensure rapid positioning and outstanding spinning, and adapts to meet each customer's needs.

Care Plus

The innovative dimpling design ensures not only top-quality washing but better care of linen and prolonging its useful life, which means lower power consumption thanks to better extraction of moisture from the linen.

GENIUS, control over every variable

Powerful, easy, intuitive and versatile. New Genius control allows total versatility in programming, switching from control for professional laundries to vended at the press of a button. The two interfaces are completely different, adapting to any Wet Cleaning laundry process with endless options to boost the profitability of your business.

Constant 450G

GENIUS dryers have a powerful 450 G-force extract speed, kept up throughout the spin phase. This powerful spin enables us to increase productivity by 10% and cut the residual moisture level of linen during the wash, at the same time cutting heat energy costs and drying times by up to 20%.



Smart Connectivity Corner

When we talk about the new GENIUS we're talking about CONNECTIVITY.

A totally revolutionary machine in the world of laundry.

Supplied with Internet of Things-ready, it offers:

- Comprehensive data retrieval: productivity, alarms, reports and more.
- Different modules for productivity (PMP), disinfection (DMP) and improvements in services (SMP).
- A smart machine: all the parameters are connected to Genius control.

Wifi and BLE connection are also featured in this range.

360 Vision

The new light status corner gives complete visibility, intuitiveness and agility in the laundry, showing the status of the washers at all times. This is thanks to an LED system at the top right corner connected to the Genius system.

10-inch user-interface screen

The new user-interface screen on the Genius series is the biggest, easiest to use, most intuitive and robust on the market: it can be used even while wearing industrial gloves, and is waterproof and scratch/impact resistant.

Genius Load

Automatic weight detection for automatic adjustment of water, energy and chemicals, thanks to a precision weighing system connected to Genius control, to give a simple, intuitive and sustainable experience.

Installation Details	Units	Data		
Power	Kw	15.4		
Applied Voltage	V/Hz/Ph	380-415/50/3		
Isolator	Amps	32A		
Normal Temp. Water Connection (Soft Water)	mmØ	2X19		
Pressure	PSI	58		
Consumption	lit/hr	270		
Drain Dia.	mmØ	76		
Static load	Kg	499		
Dynamic Load	Kg	119		
Dimensions of the Machine	WxDxHmm	870	975	1433

Technical Specification Sheet

Model: ED340E	Made: GIRBAU - Spain	Reference:	Quantity:
----------------------	-----------------------------	-------------------	------------------

Wet Cleaning Tumbler Dryer: High Performance & Energy Saving (Heat Capture) Electric Heated

Capacity: 17 kg; Ratio: 1/20

Drum (Diameter: 736 mm, Length: 800 mm, Volume: 340 lit)

Door Opening Height: 570 mm

Power Capacity of Motor: 0.45 KW

Power Capacity of Fan: 0.25 KW

G. Drive to control connection to the inverter, motor and microprocessor

Speed Control in manual or automatic mode

Humidity Control residual moisture control system is highly accurate & reliable

Care Touch Dryer Drum designed to achieve extremely delicate clothing treatment

Trans Flow the combination of radial air flow and axial allows achieving an optimum drying cycle with reduced time

Heat Capture that avoid any air leakage and heat to the environment of the laundry

1. **Stainless steel drum with care touch**
2. **Drum speed control**
3. **Drum reversing action**
4. **Humidity Control**
5. **Radial and axial air flow through the drum**
6. **Management control between invert motor & microprocessor**

<i>SN</i>	<i>Installation Details</i>	<i>Units</i>	<i>Data</i>
1	Power Consumption	KW	19
	Applied Voltage	V/Ph/Hz	380-415/3/50
	Isolator	Amps	40
2	Exhaust Outlet	mm	150Ø
	Airflow	CFM	391
3	Dimensions of the Machine	mm	798x985x1522
	Weight	kg	249



Technical Specification Sheet

Model: LS100 VENTURI	Made: Seko - Italy	Reference:	Quantity:
-----------------------------	---------------------------	-------------------	------------------

DESCRIPTION: CHEMICAL DOSING PUMP

LS100 Venturi is venturi eductors based dosing system for OPL laundry applications designed for Low maintenance and easy installation. With a modular design the range is composed by 2 main unit by 4 and 6 chemical inlets and an extension for 4 chemical inlets to manage up to 10 chemicals. A Multi Washer module to manage installations with any combination of up to 4 washer extractors with a maximum machines load of around 150-200Kg.

Max flowrates: Low Flow rate: 650 ml/min @ 1.5bar *
 High Flow rate: 1300 ml/min @ 2 bar *
 (flow derates with high viscosity fluids)

Max suction: 6 meters long, 3 m lift

SN	Installation Details	Units	Data
1	Normal Temp. Water Connection (Soft Water) Pressure	mm bar	19Ø 6 max
2	Power Applied Voltage Isolator	Kw V/Hz/Ph Amps	0.27 220/1/50 13
3	Dimensions of the Machine	mm(WxDxH)	1166x160x270



Chemical start-up kit

1. OZERA COLOR GREEN 20kg
2. LIZERNA CARAT 20kg
3. LIZERNA CITRO 25kg
4. LIZERNA PROTEXER 20kg
5. LIZERNA OLDOPOL QUICK 20kg

