



Honeypot Threat Intelligence Report

Generated: 28 July 2026, 18:31 UTC

ACTIVE SENSOR

Sessions Logged: 19 | Unique Usernames: 5 | Payload Fetches: 1

This report summarizes attacker behavior captured by a self-hosted Cowrie SSH/Telnet honeypot deployed for security research purposes. The honeypot simulates a vulnerable Linux server to observe brute-force login patterns, command execution attempts, and malware download behavior.

■ Top Attempted Usernames

Username	Attempts
root	4
test	4
user	3
ubuntu	3
admin	2

■ Top Attempted Passwords

Password	Attempts
root123	5
123456	4
password	3
toor	2
admin123	1

■ Top Username / Password Combinations

Combination	Attempts
root/root123	2

ubuntu/123456	2
root/123456	1
admin/toor	1
root/password	1

■ MITRE ATT&CK; Mapping

Technique ID	Technique Name	Observed Behavior
T1110	Brute Force	Repeated login attempts with common credential pairs
T1078	Valid Accounts	Successful fake logins using weak/default credentials
T1105	Ingress Tool Transfer	wget/curl attempts to fetch external payloads
T1082	System Information Discovery	Commands like uname -a, cat /etc/passwd

■ Conclusion

The captured data confirms common automated attack patterns targeting SSH services — primarily credential-stuffing attempts using default and weak passwords across common usernames (root, admin, ubuntu, test, user). This aligns with real-world internet-wide scanning behavior and highlights the importance of disabling password authentication, enforcing key-based SSH access, and monitoring for repeated failed login attempts.