

HIGH

PCAP: portscan_attack.pcap | Findings: 1

Findings Summary

Total Findings	1
Critical	0
High	1
Medium	0

Packet Statistics

Total Packets	2040
TCP	2038
UDP	0
ICMP	0
ARP	2
DNS Queries	0

Top Source IPs

192.168.56.102	1038 packets
192.168.56.10	1000 packets

Threat Findings (1)

HIGH

#1 Port Scan - 192.168.56.102

Scanned 1000 unique ports (SYN count: 1029)

Ports: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20



Recommendations

Port Scan / Horizontal Scan

Implement IDS rules (Snort/Suricata) to alert on rapid port sweep activity. Consider geo-blocking and rate-limiting at the firewall level.

ARP Spoofing

Enable Dynamic ARP Inspection (DAI) on managed switches. Use static ARP entries for critical hosts. Deploy ARP monitoring tools.

Suspicious DNS

Deploy a DNS filtering solution (e.g., Pi-hole, Cisco Umbrella). Block queries to known malicious TLDs at the DNS resolver level.

ICMP Flood

Rate-limit ICMP traffic at the firewall. Consider blocking external ICMP echo requests to internal hosts.

Large Data Transfer

Implement DLP (Data Loss Prevention) policies. Alert on outbound transfers exceeding baseline thresholds.

Sana Simran | Cybersecurity Portfolio | github.com/sanasimran1403-jpg

For educational and authorized security assessment purposes only.