
SPARSH
INTERIOR EMULSION

DIRECTION FOR USE

Remove all dirt, loose material etc. by scrapping and stiff brooming. Ensure that all surface are completely dry before painting. Levelling with wall putty is advisable for new surfaces.In case of old surfaces fill all cracks and miner surfaces damages with cracks filler and putty. Apply 1 coat of primer, Acrylic emulsion can be applied by brush, roller or spray.

Application : Thin 2 parts of paint with 1 to 1.5 parts of clean water. Give 2 to 3 coats keeping an interval of 3-4 hours.

USE ACRYLIC EMULSION
FOR EXTRA COVERAGE AND DURABILITY.



AWANTIKA & AARADHYA GROUP

DUCON
IMPERIAL

SPARSH
INTERIOR EMULSION



20ℓ. Nett

BONDING FOREVER

SPARSH
INTERIOR EMULSION

M.R.P. ₹
(Incl. of all Taxes)

Date of Mfg.:

Batch No.:

Shade :

MANUFACTURED BY:
AWANTIKA AND AARADHYA INDUSTRIES PVT. LTD.
18-19, SECTOR-D, INDUSTRIAL AREA, MANDIDEEP,
DISTRICT RAISEN - 462046 CUSTOMER CARE : 72250-20180
GST : 23ABBCA2181R1ZI

MAKE IN INDIA