SPARSH
INTERIOR EMULSION

AWANTIKA & AARADHYA GROUP

DIRECTIONS FOR USE:

Clean the surface thoroughly using a wire brush and remove loose material from the surface. Surface imperfections such as holes and fine cracks are to be filled with Wall Putty or a mixture of white cement and fine sand only (in the ratio of 1.3) In the case of freshly-plastered completely cured surfaces only, apply one coat of Exterior Primer by mixing water and paint in the ratio of 1:1. Allow drying for 4 hours. For best results apply a coat of Exterior Sealer, as such or with up to 10% dilution with potable water, and allow to dry for 4 hours. The exterior sealer coat should be applied prior to the application of Exterior Primer. Apply 2-3 coats by diluting 1 litre of Weather Safe Premium Exterior Emulsion with maximum 750 ml of water. A gap of 4-6 hours should be given between two coats.

Stir Contents Well Before Use
Keep Lid Closed When Not In Use

DUCON
IMPERIAL
SPARSH
INTERIOR EMULSION



20ℓ. Nett

SPARSH
INTERIOR EMULSION

M.R.P. ₹
(Incl. of all Taxes)

Date of Mfg.:

Batch No.:

Shade :

MANUFACTURED BY:
AWANTIKA AND AARADHYA INDUSTRIES PVT. LTD.
18-19, SECTOR-D, INDUSTRIAL AREA, MANDIDEEP,
DISTRICT RAISEN 462046
GST : 23ABBCA2181R1ZI