



Northeastern
University

Lecture 12: A Bag Implementation that Links Data - 1

Prof. Chen-Hsiang (Jones) Yu, Ph.D.
College of Engineering

Materials are edited by Prof. Jones Yu from

Data Structures and Abstractions with Java, 5th edition. By Frank M. Carrano and Timothy M. Henry.
ISBN-13 978-0-13-483169-5 © 2019 Pearson Education, Inc.

Problems with Array Implementation

- Array has a **fixed size**.
- May become **full**.
- Alternatively, may have **wasted space**.
- Resizing is possible but requires **overhead of time**.

Alternative Approach?!

- Introduces a new data organization that uses memory only as needed for a new entry.
- Returns the unneeded memory to the system after an entry is removed.

Analogy

- Empty classroom
- Numbered desks stored in hallway
 - » Number on **back of desk** is the “**address**”
- Number on **desktop** references **another desk in chain of desks**
- Desks are linked by the numbers

Analogy




Figure 3-1: A chain of five desks

Forming a Chain by Adding to Its Beginning




Figure 3-2: One desk in the room




Figure 3-3: Two linked desks,
with the newest desk first




Figure 3-4: Three linked desks,
with the newest desk first.

Question

- The instructor knows the address of **only one desk**.
 - » A. Where in the chain is that desk?
 - » First
 - » Last
 - » Somewhere else
 - » B. Who is sitting at that desk?
 - » the student who arrived first
 - » the student who arrived last
 - » Someone else

Answer

- The instructor knows the address of only one desk.
 - » A. Where in the chain is that desk?
 - » First
 - » Last
 - » Somewhere else
 - » B. Who is sitting at that desk?
 - » the student who arrived first
 - » the student who arrived last
 - » Someone else

Forming a Chain by Adding to Its Beginning

// Process the first student

`newDesk` represents the new student's desk

New student sits at `newDesk`

Instructor memorizes the address of `newDesk`

// Process the remaining students

while (students arrive)

{

`newDesk` represents the new student's desk

New student sits at `newDesk`

Write the instructor's memorized address on `newDesk`

Instructor memorizes the address of `newDesk`

}

Pseudocode details the steps taken to form a chain of desks

The Private Class **Node**

```
private class Node
{
    private T    data; // Entry in bag
    private Node next; // Link to next node

    private Node(T dataPortion)
    {
        this(dataPortion, null);
    } // end constructor

    private Node(T dataPortion, Node nextNode)
    {
        data = dataPortion;
        next = nextNode;
    } // end constructor
} // end Node
```

Listing 3-1: The private inner class **Node**

The Private Class **Node**




Figure 3-5: Two linked nodes that each reference **object data**

An Outline of the Class `LinkBag` - Part 1

```
/** A class of bags whose entries are stored in a chain  
    of linked nodes. The bag is never full.*/
```

```
public class LinkBag<T> implements BagInterface<T>  
{  
    private Node firstNode; // reference to first node  
    private int numberOfEntries;  
  
    public LinkBag()  
    {  
        firstNode = null;  
        numberOfEntries = 0;  
    } // end default constructor  
  
    // . . .
```

Listing 3-2: An outline of the class `LinkBag`

An Outline of the Class `LinkedList` - Part 2

```
private class Node
{
    private T    data; // Entry in bag
    private Node next; // Link to next node

    private Node(T dataPortion)
    {
        this(dataPortion, null);
    } // end constructor


    private Node(T dataPortion, Node nextNode)
    {
        data = dataPortion;
        next = nextNode;
    } // end constructor
} // end Node

} // end LinkedList
```

Listing 3-2: An outline of the class `LinkedList`

Beginning a Chain of Nodes

(a) An empty chain and a new node



(b) After adding a new node to a chain that was empty





Figure 3-6: Adding a new node to an empty chain. (a) An empty chain and a new node; (b) after adding a new node to a chain that was empty

Beginning a Chain of Nodes

(a) Before adding a node at the beginning



(b) After adding a node at the beginning




Figure 3-7: A chain of nodes just before and just after adding a node at the beginning.
(a) Before adding a node at the beginning; (b) After adding a node at the beginning.

Beginning a Chain of Nodes

```
/** Adds a new entry to this bag.
    @param newEntry The object to be added as a new entry.
    @return True. */
public boolean add(T newEntry) // OutOfMemoryError possible
{
    // Add to beginning of chain:
    Node newNode = new Node(newEntry);
    newNode.next = firstNode; // Make new node reference rest of chain
                             // (firstNode is null if chain is empty)
    firstNode = newNode;     // New node is at beginning of chain
    numberOfEntries++;

    return true;
} // end add
```

The method `add`

Method `toArray`

```
/** Retrieves all entries that are in this bag.
    @return A newly allocated array of all the entries in the bag. */
public T[] toArray()
{
    // The cast is safe because the new array contains null entries
    @SuppressWarnings("unchecked")
    T[] result = (T[])new Object[numberOfEntries]; // Unchecked cast

    int index = 0;
    Node currentNode = firstNode;
    while ((index < numberOfEntries) && (currentNode != null))
    {
        result[index] = currentNode.data;
        index++;
        currentNode = currentNode.next;
    } // end while

    return result;
} // end toArray
```

The method `toArray` returns an array of the entries currently in a bag

Question

- In the previous definition of `toArray`, the `while()` statement uses following Boolean expression to control the loop.

`(index < numberOfEntries) && (currentNode != null)`

- Is it necessary to involve the values of both `index` and `currentNode`? Why?

Answer

- Testing the value of both `index` and `currentNode` is not necessary.
- Although testing either of these values is sufficient, testing both values provides a check against mistakes in your code.

Testing the Core Methods

Test Program - Part 1

```
/** A test of the methods add, toArray, isEmpty, and getCurrentSize,
    as defined in the first draft of the class LinkedBag. */
public class LinkedBagDemo1
{
    public static void main(String[] args)
    {
        System.out.println("Creating an empty bag.");
        BagInterface<String> aBag = new LinkedBag1<>();
        testIsEmpty(aBag, true);
        displayBag(aBag);

        String[] contentsOfBag = {"A", "D", "B", "A", "C", "A", "D"};
        testAdd(aBag, contentsOfBag);
        testIsEmpty(aBag, false);
    } // end main
}
```

Listing 3-3: A sample program that tests some methods in the class `LinkedBag`

Test Program - Part 2

```
// Tests the method isEmpty.  
// Precondition: If bag is empty, the parameter empty should be true;  
// otherwise, it should be false.  
private static void testIsEmpty(BagInterface<String> bag, boolean empty)  
{  
    System.out.print("\nTesting isEmpty with ");  
    if (empty)  
        System.out.println("an empty bag:");  
    else  
        System.out.println("a bag that is not empty:");  
  
    System.out.print("isEmpty finds the bag ");  
    if (empty && bag.isEmpty())  
        System.out.println("empty: OK.");  
    else if (empty)  
        System.out.println("not empty, but it is: ERROR.");  
    else if (!empty && bag.isEmpty())  
        System.out.println("empty, but it is not empty: ERROR.");  
    else  
        System.out.println("not empty: OK.");  
} // end testIsEmpty
```

Listing 3-3: A sample program that tests some methods in the class [LinkedBag](#)

Test Program - Part 3

```
// Tests the method add.
private static void testAdd(BagInterface<String> aBag, String[] content)
{
    System.out.print("Adding the following strings to the bag: ");
    for (int index = 0; index < content.length; index++)
    {
        if (aBag.add(content[index]))
            System.out.print(content[index] + " ");
        else
            System.out.print("\nUnable to add " + content[index] +
                             " to the bag.");
    } // end for
    System.out.println();

    displayBag(aBag);
} // end testAdd
```

Listing 3-3: A sample program that tests some methods in the class **LinkedBag**

Test Program - Part 4

```
// Tests the method toArray while displaying the bag.
private static void displayBag(BagInterface<String> aBag)
{
    System.out.println("The bag contains the following string(s):");
    Object[] bagArray = aBag.toArray();
    for (int index = 0; index < bagArray.length; index++)
    {
        System.out.print(bagArray[index] + " ");
    } // end for

    System.out.println();
} // end displayBag

} // end LinkedBagDemo1
```

Listing 3-3: A sample program that tests some methods in the class **LinkedBag**

Test Program - Result

Program Output

Creating an empty bag.

Testing isEmpty with an empty bag:

isEmpty finds the bag empty: OK.

The bag contains the following string(s):

Adding the following strings to the bag: A D B A C A D

The bag contains the following string(s):

D A C A B D A

Testing isEmpty with a bag that is not empty:

isEmpty finds the bag not empty: OK.

Method `getFrequencyOf`

```
/** Counts the number of times a given entry appears in this bag.
    @param anEntry The entry to be counted.
    @return The number of times anEntry appears in the bag. */
public int getFrequencyOf(T anEntry)
{
    int frequency = 0;
    int loopCounter = 0;
    Node currentNode = firstNode;

    while ((loopCounter < numberOfEntries) && (currentNode != null))
    {
        if (anEntry.equals(currentNode.data))
        {
            frequency++;
        } // end if

        loopCounter++;
        currentNode = currentNode.next;
    } // end while

    return frequency;
} // end getFrequencyOf
```

Counts the number of times a given entry appears

Method `contains`

```
/** Tests whether this bag contains a given entry.
    @param anEntry The entry to locate.
    @return True if the bag contains anEntry, or false otherwise */

public boolean contains(T anEntry)
{
    boolean found = false;
    Node currentNode = firstNode;

    while (!found && (currentNode != null))
    {
        if (anEntry.equals(currentNode.data))
            found = true;
        else
            currentNode = currentNode.next;
    } // end while
    return found;
} // end contains
```

Determine whether a bag contains a given entry

Question


- If `currentNode` in the previous method `contains()` becomes `null`, what value does the method return when the bag is not empty?

Answer

- The method returns `false`.
- If `currentNode` becomes `null`, the entire chain has been searched without success.

Exercise

- In a **doubly linked chain**, each node can reference the previous node as well as the next node. Following figure shows a doubly linked chain and its head reference.



- **Define a class** to represent **a node** in a doubly linked chain. Write the class **as an inner class of a class** that implements the **ADT bag**. You can omit set and get methods.

Answer

```
private class DoublyLinkedListNode
{
    private T data; // Entry in bag
    private DoublyLinkedListNode next; // Link to next node
    private DoublyLinkedListNode previous; // Link to previous node

    private DoublyLinkedListNode(T dataPortion)
    {
        this(dataPortion, null, null);
    } // end constructor

    private DoublyLinkedListNode(T dataPortion, DoublyLinkedListNode nextNode,
                                   DoublyLinkedListNode previousNode)
    {
        data = dataPortion;
        next = nextNode;
        previous = previousNode;
    } // end constructor
} // end DoublyLinkedListNode
```