


# Computer and Network Security: Transport Layer Attacks and Solutions

Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include: <http://commons.wikimedia.org> (Wikipedia, Wikimedia and workbooks); <http://www.sxc.hu> and <http://www.pixabay.com>

# Outline

- Attacks at different layers of the protocol stack
- Solutions to the same



# Transport Layer Role

- Hosts run many processes. What is the role of transport layer?
  - Process to process delivery
  - Implemented only on end-hosts
- Enhance “best-effort” network layer services to meet application expectations
- Protocols
  - UDP: Simple, provides demultiplexing
  - **TCP**: Complex, provides demultiplexing, reliability, congestion/flow control


# TCP header

0	4	1	1	3					
Source Port			6	Destination Port	1				
Sequence Number									
Acknowledgment									
Hdr Len	0	U	A	P	R	S	F	Advertised Window	
Checksum					Urgent Pointer				
Options (Variable)									
Data									

TCP connection identified by a 4 tuple: src IP, src port, dst IP, dst port


# TCP: 3 Way Handshake

- Used for connection set-up
- Random initial sequence number. Why?
  - Segments from different connections can get mixed up
  - Security risk when ISN's are predictable
    - Spoofing/hijacking (to be covered later)




# TCP: Connection Termination

- Follows simple two-way handshake
- Each side independently closes connection



# Reset

- Either side can terminate connection via RST
  - Triggered by any odd behavior
  - Immediate (no ack needed)
  - Correct sequence number/port/IP is the only check



# Attacks

- Focus on TCP (protocol specific attacks)
- Eavesdropping (does not make sense here; lower layer functionality)
- **Disruption**
  - TCP SYN Flood
  - TCP Session Hijacking
- **Spoofing**
  - TCP Session Spoofing



# TCP SYN Flood Attack


- Type of DOS attack
- Attacker sends many SYNs to target
  - When target sends SYN+ACK, does not respond with ACK
  - Connection left hanging in half-open state
  - Each new connection allocated some memory, this attack exhausts available memory at target
- Target cannot response to legitimate traffic since no memory available

(Will be covered in more detail under DOS)

# TCP Session Hijacking

- Take over an already established connection
- What can one do after taking over?
  - Inject fake data that can cause damage (e.g. transfer money)
  - Close the connection (disrupt service)
- What is required to take over the connection?
  - Need to know the port, seq no information
    - Easy in wireless networks; malicious network operators ([on path attacks](#))
    - Difficult to launch [off-path attacks](#); but one can try to guess/infer


# Injecting Data



Dangerous Data accepted  
from attacker

Valid data rejected  
from valid end-point


# Closing a connection



# TCP Session Spoofing

- Create a fake TCP connection (by taking on some one else's IP address)
- What can one achieve?
  - Cause damage by leveraging the end point's trust (see Mitnick attack)
- What is required to fake connection?
  - Need to know the port, initial seqno information
  - Bring down the machine you are imitating

# Spoofing TCP Handshake



# TCP Defences Summary


## TCP SYN Flood

- Filtering, SYN Cookies, firewalls etc (to be covered later under DOS)

## TCP Session hijacking/spoofing

- Choose random initial TCP sequence number
  - Handles off path attacks, but not on-path attacks
- IPsec or transport level encryption (SSL/TLS)

# Mitnick Attack



## THE MITNICK ATTACK

U.S. Department of Justice  
United States Marshals Service

# WANTED BY U.S. MARSHALS

NOTICE TO ARRESTING AGENCY: Before arrest, validate warrant through National Crime Information Center (NCIC).  
United States Marshals Service NCIC entry number: (NIC/ 1271460921 )

NAME: .....MITNICK, KEVIN DAVID  
AKS (S): .....MITNICK, KEVIN DAVID  
KENRILL, BRIAN ALLEN

DESCRIPTION:

Sex: .....MALE  
Race: .....WHITE  
Place of Birth: .....VAN NUYS, CALIFORNIA  
Date of Birth: .....06/06/63; 10/18/70  
Height: .....5'11"  
Weight: .....190  
Eyes: .....BLUE  
Hair: .....BROWN  
Skin tone: .....LIGHT  
Scars, Marks, Tattoos: .....NONE KNOWN  
Social Security Number (s): .....550-39-5495  
NCIC Fingerprint Classification: .....30PM2OPH13DIPK19PM9

ADDRESS AND LOCALITY: KNOWN TO RESIDE IN THE SAN FERNANDO VALLEY AREA OF CALIFORNIA AND LAS VEGAS, NEVADA

WANTED FOR: VIOLATION OF SUPERVISED RELEASE  
ORIGINAL CHARGES: POSSESSION UNAUTHORIZED ACCESS DEVICE; COMPUTER FRAUD  
Warrant issued: CENTRAL DISTRICT OF CALIFORNIA  
Warrant Number: 9312-1112-0194-0

DATE WARRANT ISSUED: NOVEMBER 10, 1992

MISCELLANEOUS INFORMATION: SUBJECT SUFFERS FROM A WEIGHT PROBLEM AND MAY HAVE EXPERIENCED WEIGHT GAIN OR WEIGHT LOSS

VEHICLE/TAG INFORMATION: NONE KNOWN OFTEN USES PUBLIC TRANSPORTATION

If arrested or whereabouts known, notify the local United States Marshals Office, (Telephone: 213-894-2385 )  
If no answer, call United States Marshals Service Communications Center in McLean Virginia.  
Telephone (800)336-6192 (24 hour telephone contact) NLETS access code is VAUSM0000.

Form 125M-132 (Rev. 3/2/92)

FOR EDITIONS ARE OBSOLETE AND NOT TO BE USED



# Information gathering

- Determine TCP sequence number
  - Send SYN to x-term; RST on receiving syn+ack. Repeat 20 times
  - Two successive TCP seq no differed by 128000
- Determine Trust relation
  - Hacked website and used command 'finger' and showmount to find if X-Terminal had trusted relationship with any other computers.

# Other Steps

- Mute Server by TCP SYN flood attack (DOS attack)
  - Use spoofed non-routable IP addresses to send SYN requests
  - Server available memory exhausted from half-open connections
  - Server cannot respond to any more requests
- Trusted relationship hijacking
  - Establish TCP connection with x-term with source IP as Server's (TCP session spoofing)
  - Predict x-term's sequence number and complete 3-way handshake

# Other Steps

- Remote command pump
  - Application on top of TCP is remote shell (like ssh but not secure)
  - Create a backdoor on x-term to allow any computer to connect without verification
  - Exact command: "echo + + >> /.rhosts"
- Clean up
  - Free server by send RST to cancel all SYN requests

# Mitnick: Detection and Prevention

- Attack leveraged many vulnerabilities; All need addressing
- Host/network based intrusion detection and firewalls
  - for flooding; detecting attempts at information gathering; illegal access to resources
- TCP random sequence numbers (for preventing guess work)
- Using secure applications (ssh or SSL/TLS)

# Summary

- Looked at TCP background
  - TCP header, connection establishment and tear down
- Disruption and Spoofing attacks
  - TCP SYN flood, TCP session hijacking, TCP session spoofing
  - Case study: Mitnick Attack
- Some solutions to the same
  - Specifically importance of random initial sequence number