ITE5315 - Assignment 2


I declare that this assignment is my own work in accordance with Humber Academic Policy.

* No part of this assignment has been copied manually or electronically from any other source (including web sites) or distributed to other students.

* Name: Sandeep Das Student ID: N01472825

Date: 29th October 2022


Step 1:



```
Asn2-Sandeep > JS app.js > 分 app.get('*') callback
     var express = require('express');
  2
     var path = require('path');
     var app = express();
  3
     const exphbs = require('express-handlebars');
     const port = process.env.port | 3000;
     app.use(express.static(path.join(__dirname, 'public')));
  6
  7
      app.engine('.hbs', exphbs.engine({ extname: 'hbs' }))
      app.set('view engine', 'hbs');
  8
  9
      app.get('/', function (req, res) {
 10
          res.render('index', { title: 'Express' });
 11
      });
 12
      app.get('/users', function (req, res) {
 13
          res.send('respond with a resource');
 14
      });
 15
      app.get('*', function (req, res) {
          res.render('error', { title: 'Error', message: 'Wrong Route' });
 16
 17
      });
 18
      app.listen(port, () => {
          console.log(`Example app listening at http://localhost:${port}`)
 19
 20
      })
```


```
PS C:\Users\Sandeep Das\Documents\Semester 3\Web prog framework 1\Asn2-Sandeep> nodemon .\app.js [nodemon] 2.0.20 [nodemon] to restart at any time, enter `rs` [nodemon] watching path(s): *.* [nodemon] watching extensions: js,mjs,json [nodemon] starting `node .\app.js` Example app listening at http://localhost:3000
```

Step 3:



Express

Welcome to Express



respond with a resource



Wrong Route

```
EXPLORER
                               JS warmUpActivity.js
                                                    JS firstExpressActivity1.js
                                                                             JS index.js
                                                                                             index.html
✓ WEB PROG FRAMEWOR... ☐ ☐ O Asn2-Sandeep > JS app.js > ☐ app.get('*') callback

✓ Asn2-Sandeep

                                      var express = require('express');
                                      var path = require('path');
  > node_modules
                                  3 var app = express();

∨ public

                                  4 const exphbs = require('express-handlebars');
  > images
                                        const port = process.env.port | 3000;
                                                                                                   Setting the root

✓ stylesheets

                                  6 app.use(express.static(path.join(__dirname, 'public')));
                                                                                                  path for the app
   # style.css
                                  7
                                      app.engine('.hbs', exphbs.engine({ extname: 'hbs' }))
                                  8
                                       app.set('view engine', 'hbs');

∨ views

                                   9
                                        app.get('/', function (req, res) {

✓ layouts

                                  10
                                        res.render('index', { title: 'Express' });
   main.hbs
                                  11 });
  > partials
                                        app.get('/users', function (req, res) {
                                  12
  error.hbs
                                13 res.send('respond with a resource');

✓ index.hbs

                            U
                                14 });
                                        app.get('*', function (req, res) {
 JS app.js
                                15
                                            res.render('error', { title: 'Error', message: 'Wrong Route' });
                                  16
 {} package-lock.json
                                  17
                                      });
                            U
 {} package.json
                                  18
                                        app.listen(port, () => {
 > Assignment1
                                  19
                                         console.log(`Example app listening at http://localhost:${port}`)
 > Day1
                                  20 })
 > Day2
 > Day3
 > Day4
```

a. Firstly in the app we are setting the static root path as the public folder inside our app.

Then main.hbs is located inside the /public.

The default behaviour of handlebars is that whenever a handlebar is called, the control first goes to main.hbs located inside our layout folder and the variables passed are injected into the hbs document. In case we rename main.hbs to anything else. The app wont work as expected.

Then the {{body}} is replaced by the handlebar passed as another parameter after that passed handlebar is substituted with all the variables.

The variables passed as a JS object keys should match the handlebar variables exactly to work.

- b. Error is matched with a wildcard route at the end after defining all valid routes. The message parameter gets injected into the error handlebar and title parameter gets injected to the main handlebar. The {{body} of main.hbs is substituted by error.hbs
- c. If we comment out the below line. The CSS will not load as the static content of CSS to be served remains unknown to our app

```
app.use(express.static(path.join(__dirname, 'public')));
```

```
var express = require('express');
                                                                //Fetch express
module to application
var path = require('path');
                                                                //Fetch path
module to application
var app = express();
                                                                //Initialize app
variable with express
const exphbs = require('express-handlebars');
                                                                //Fetch express-
handlebars module for application
const port = process.env.port || 3000;
                                                                //Serve web app
of env variable port if defined else on 3000
app.use(express.static(path.join(__dirname, 'public')));
                                                                //Configure web
app to use application root path appended with public as the folder to serve
static content
app.engine('.hbs', exphbs.engine({ extname: 'hbs' }))
                                                                //setiing the app
engine with .hbs key and value as exphbs.engine({ extname: 'hbs' })
app.set('view engine', 'hbs');
                                                                //Set app
parameter view engine to hbs value
app.get('/', function (req, res) {
                                                                //Set root route
    res.render('index', { title: 'Express' });
                                                                //Redirect to
index handlebar and pass title as express and inject the value of title in all
relevant handlebars
app.get('/users', function (req, res) {
                                                                //Set /users
route
    res.send('respond with a resource');
                                                                //Just pass text
as response
});
app.get('*', function (req, res) {
                                                                //Set route for
undefined path
    res.render('error', { title: 'Error', message: 'Wrong Route'
});
          //Call the error handlebar and pass message attribute for handlebars
});
app.listen(port, () => {
    console.log(`Example app listening at
http://localhost:${port}`) //initialize the server
})
```

Step 5:





/data route



JSON data is loaded and ready


© 2020 Copyright: sdsts28@gmail.com

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL
   ISBN: '62237101',
   img: 'http://ecx.images-amazon.com/images/I/51xHUTfYvdL.jpg',
   title: 'Hunting Shadows: An Inspector Ian Rutledge Mystery (Inspector Ian Rutledge Mysteries)',
   author: 'Charles Todd',
   inventory: 17,
   category: 'Mystery, Thriller & Suspense'
  },
   ISBN: '399174680',
   img: 'http://ecx.images-amazon.com/images/I/51JLVnuXSDL.jpg',
   title: 'Scandalous Behavior (A Stone Barrington Novel)',
   author: 'Stuart Woods',
   inventory: 17,
   category: 'Mystery, Thriller & Suspense'
   ISBN: '1939454654',
   img: 'http://ecx.images-amazon.com/images/I/417gaArFUIL.jpg',
   title: 'Age of Distraction: The Island',
   author: 'Patricia Mahon',
   inventory: 17,
   category: 'Mystery, Thriller & Suspense'
  },
   ISBN: '1604601604',
   img: 'http://ecx.images-amazon.com/images/I/51BJw1DW90L.jpg',
   title: 'The Ghostly Quilts on Main (Colebridge Communities)',
   author: 'Ann Hazelwood',
   inventory: 17,
   category: 'Mystery, Thriller & Suspense'
   ISBN: '399166726',
   img: 'http://ecx.images-amazon.com/images/I/51IQRzWXmkL.jpg',
   title: 'Saving Jason (A Jason Stafford Novel)',
   author: 'Michael Sears',
   inventory: 17,
   category: 'Mystery, Thriller & Suspense'
  },
   ISBN: '62073508',
   img: 'http://ecx.images-amazon.com/images/I/51yRHlducqL.jpg',
   title: 'Murder on the Orient Express: A Hercule Poirot Mystery (Hercule Poirot Mysteries)',
   author: 'Agatha Christie',
   inventory: 17,
   category: 'Mystery, Thriller & Suspense'
```

/data/isbn/:index

```
Get book ISBN details by ISBN index
app.get('/data/isbn/:index', (req, res) => {
    let queryIndex = req.params.index;
    if(queryIndex>=0 && queryIndex<allBooks.length){
        //console.log(allBooks[queryIndex]);
        var result = [];
        result.push(allBooks[queryIndex])
        res.render('listOfBooks', {books:result});

        //res.status(200).send(allBooks[queryIndex].ISBN);
}
res.render('confirmDataLoaded', {message:"Out of bounds index...Dont play with
})</pre>
```







Out of bounds index...Dont play with me

— Presented by: Moustache handlebars

'/data/search/title'

```
//Get book details by Title
app.route('/data/search/title')
.get(function(req,res) {
   res.render('searchByTitle');
.post(function(req,res){
   let queryTitle = req.body.title;
   console.log(queryTitle);
   var booksWithTitle = JSON.parse('{"foundBooks":[]}');
   var found = 0;
   if(queryTitle!=""){
       allBooks.forEach(element => {
           if(element.title.toLowerCase().includes(queryTitle.toLowerCase())) \{\\
                booksWithTitle['foundBooks'].push(element);
                found++;
       });
   else{
       res.render('confirmDataLoaded',{message: "Looks like you are lost in space and ocean of nothingness"});
   if (found != 0)
   {
        res.render('listOfBooks',{books:booksWithTitle.foundBooks});
   res.render('confirmDataLoaded',{message: "Tried hard! BUT not found"});
})
```





Step 8:




List of books

ISBN	Cover Page	Title	Author	Inventory	Category
1608874257	HALD	Halo: The Poster Collection		Out of stock	Arts & Photography


© 2020 Copyright: sdsts28@gmail.com

grant of the state of the state

a.



```
{{#each books}}
     {{this.ISBN}}
       <img src={{this.img}} class="img-thumbnail" alt="Hollywood Sign on The Hill" />
       {{this.title}}
       {{this.author}}
       {{checkOutOfStock this.inventory}}
       {{this.category}}
     {{/each}}
  </div>
 },
 setRowColor : function(stock){
    if (stock == 0)
        return "style='background-color:#e7b4b4'";
```



C. I did find partials useful for rendering static content that does not change as our main content changes.