Paste Guard

Checking what gets pasted into AI chat tools against a company's own documents and code

Sandeep Paluru, for Eric McIntyre (VP of Technology, Sidekick Labs)
13 October 2026. Version 0.5.0. Repo: github.com/sandeep-paluru/paste-guard

> Paste Guard is a proof of concept I built to show how I work on a problem like this. It is not a product, and the company in it, Calloway Metrics, is fictional.

Summary

Paste Guard is a Chrome extension plus a small backend. When someone pastes text, uploads a file or drops a file into Claude or ChatGPT, it checks the content against the company's own documents and code, then answers allow, nudge, coach or block. It shows which document matched and which passage, and offers one-click redaction.

Nothing is trained. It uses a public pretrained embedding model (all-MiniLM-L6-v2) as-is, next to two cheap lexical checks. The only things I fitted to my data are the thresholds, and I report accuracy on documents the thresholds were never tuned on.

	Default profile (fits a 1 GB VM)	Accurate profile (v0.5)
Signals for documents	MiniLM OR word 3-gram	MiniLM OR word 3-gram OR TF-IDF
Held-out document F1	0.943	0.966
Held-out recall / precision	0.90 / 0.99	0.94 / 0.99
False alarms on document negatives	2.8%	2.8% (2 of 72)
Full /check request, p50 / p95	16 ms / 58 ms	19 ms / 56 ms
Regex and keyword baseline, document F1	0.20	0.20

Latency figures are from my 8 vCPU machine. On the 1 GB VM the default profile runs at p50 208 ms and p95 995 ms (more on that under limitations).

How the idea came about

On our call on 9 October you described a very ordinary way data leaves a company: someone has a confidential document, wants a quick summary, and pastes it or drops the file into Claude or ChatGPT. You also described Sidekick's approach of stepping in at that moment with a nudge, some coaching or a block, rather than banning the tools outright.

That raised a question I wanted to answer properly: at the moment of the paste, can you tell whether the content is *ours*, and not just whether it looks sensitive? People rarely paste a document with "CONFIDENTIAL" on top. They paste a paragraph, reword it, trim it or wrap it in "summarize this for me". I built Paste Guard over 12 and 13 October to see how far a local, cheap approach gets on that question and where it breaks.

The gap it targets


Regex and keyword DLP. Rules for secrets, card numbers and "CONFIDENTIAL" banners are useful, and Paste Guard keeps them for secrets. But on my eval set a regex and keyword baseline (secrets rules, confidentiality markers and a sensitive business keyword list) caught 11% of confidential document pastes and none of the code pastes. It caught 3% of paraphrases.

Category classifiers. From what I could find publicly, most tools in this space (WASViking, Harmonic, LayerX, Nightfall and others) label content by type: PII, secrets, source code, legal text. That tells you a paste looks like a legal document. It does not tell you that it is paragraph three of your own acquisition memo, and it cannot name the source.

Fingerprinting and lineage. Document fingerprinting and exact data match handle verbatim and lightly edited copies but are weak on paraphrase. Microsoft's documentation for Purview's paste-to-browser control says it does not support exact data match or document fingerprinting on paste at all. Cyberhaven tracks where data came from, which misses text that was retyped or copied from somewhere its agent does not see.

Where Paste Guard sits. It matches each paste against an index of the company's own documents and code, locally, and catches rewording as well as copies. From Sidekick's public site I could not tell whether you inspect paste content today, so I see this as a possible extra signal next to what Sidekick already knows (the account, the app, the settings), not as a claim about a gap in Sidekick. A personal Claude account plus a strong match to a board memo is a very different event from a corporate account pasting a public article.

Architecture



Request flow

Extension (Chrome, Manifest V3). A content script on claude.ai, chatgpt.com and chat.openai.com intercepts three things: paste, file picker uploads and drag-and-drop. Text files (.txt, .md) are read in the browser. PDF and DOCX files go to the backend for text extraction. The service worker sends the content to the backend and the overlay shows the verdict, the matched document, the matched passage and a redaction button. The toolbar icon shows a green dot when protection is on, and the settings page allows a per-site pause.

Backend (FastAPI). It runs on the same machine or a company server. For the demo it runs on a 2 vCPU, 1 GB Oracle VM that also hosts my existing Techvista services. Each check does the following:

1. Secrets and marker scan. Cloud keys, tokens, private keys and password assignments are always blocked or redacted.
2. The paste is cut into windows and each window is embedded with all-MiniLM-L6-v2 (ONNX on CPU through fastembed).
3. Nearest passages are found in a sqlite-vec index of documents and code.
4. Word 3-gram containment is computed: the share of the window's 3-word sequences that appear in one indexed passage.
5. In the accurate profile, a TF-IDF cosine check (word 1 and 2 grams) also runs for documents.
6. Per-kind threshold bands turn the scores into allow, nudge, coach or block, plus the matches and a redacted version.

Indexing. Documents are split on paragraph boundaries into 120 to 200 word chunks with overlap, plus shorter 60 word passages so a short excerpt still has a close neighbour. The demo index has 485 document passages and 109 code chunks. `./pasteguard reindex` rebuilds it and the running server picks up the change.

Redaction. Headings and code signatures are kept, and each removed block becomes `[REDACTED: matches <source> paragraphs a-b]` (or `lines a-b` for code), so the AI tool still gets the structure of the

question.

Privacy. Paste text is processed in memory and never written to disk. The model is downloaded once and then runs offline. The verdict log behind the admin page stores only a SHA-256 hash, the length, the verdict, the matched source name and the site, kept for 30 days. The admin page is served only to local connections.

The data

All of it is synthetic. I wrote a corpus of 18 confidential documents for a fictional company, Calloway Metrics: board memos, an M&A term sheet, a layoff plan, compensation bands, pricing, a customer list with contract values, a security incident postmortem, a legal settlement summary, a product roadmap and similar, in .md, .txt, .pdf and .docx. The code side is one real open source Python repository standing in for a company repo.

The eval set has 472 labelled pastes, generated with Claude:

Set	Positives	Negatives
Documents (356)	284 in 8 paste types	72: public business text, alone (36) and wrapped in a prompt (36)
Code (116)	66 in 6 paste types	50: public code, alone (25) and wrapped in a prompt (25)

Document paste types: verbatim (51), partial excerpt (51), paraphrase (36), reordered bullets (29), summary (18), tone rewrite (18), paraphrase wrapped in a prompt (18) and text wrapped in a prompt such as "summarise this for me" (63). Code paste types, 11 each: verbatim, partial, renamed, reformatted, renamed and reformatted, and wrapped in a prompt.

What "the model" is, and how I measured it

To be clear up front: **I did not train or fine-tune any model.** Matching uses `sentence-transformers/all-MiniLM-L6-v2`, a public pretrained sentence embedding model (384 dimensions, 91 MB as ONNX), used zero-shot. The 3-gram and TF-IDF checks are not learned at all, apart from TF-IDF's vocabulary and IDF weights, which come from the indexed corpus. No eval text was ever used as training data.

What I did tune is the thresholds. Each sweep scans 0.40 to 0.95 in 0.01 steps and keeps the best F1 with false alarms at or below 3% (5% before v0.5). Tuning and scoring on the same samples flatters the result, so the benchmark uses a **held-out split by document**: the 18 documents are split into two halves of 9, thresholds are tuned on pastes from one half and scored on pastes from the other, then the halves swap. Code is split by source file. The gap between in-sample and held-out turned out small (1 to 3 points of F1), so the thresholds are not memorising particular documents. It does not tell me whether another company's documents land in the same similarity range. That needs a second corpus.

Why MiniLM

I benchmarked eight pretrained embedding models, three non-neural baselines and a set of hybrids on the same paste windows and index. The rules were a full check p95 under 100 ms on a normal CPU and false alarms at most 3%. Held-out document results (latency is scoring only, on my machine, 2 threads):


Method	F1	Recall	False alarms	Summary recall	p50	p95	Meets both rules
all-MiniLM-L6-v2	0.870	0.77	2.8%	0.50	9 ms	65 ms	yes
bge-small-en-v1.5	0.848	0.74	1.4%	0.67	20 ms	144 ms	no
bge-base-en-v1.5	0.918	0.86	6.9%	0.83	65 ms	474 ms	no
bge-large-en-v1.5	0.883	0.80	2.8%	0.72	196 ms	1159 ms	no
mxbai-embed-large-v1	0.878	0.79	2.8%	0.72	192 ms	1305 ms	no
gte-large	0.887	0.80	2.8%	0.83	212 ms	1339 ms	no
jina-embeddings-v2-base-code	0.559	0.39	2.8%	0.28	75 ms	433 ms	no
nomic-embed-text-v1.5	0.822	0.71	5.6%	0.33	87 ms	590 ms	no
TF-IDF cosine (1-2 grams)	0.946	0.90	1.4%	0.28	1 ms	2 ms	yes
Word 3-gram containment	0.862	0.76	0.0%	0.00	1 ms	2 ms	yes
MinHash Jaccard	0.851	0.74	1.4%	0.06	0 ms	1 ms	yes
MiniLM OR 3-gram (default)	0.943	0.90	2.8%	0.50	9 ms	67 ms	yes
MiniLM OR TF-IDF	0.964	0.94	4.2%	0.56	10 ms	66 ms	no
bge-base OR 3-gram OR TF-IDF	0.970	0.96	8.3%	0.78	67 ms	478 ms	no
mxbai-large OR 3-gram OR TF-IDF	0.971	0.95	2.8%	0.78	194 ms	1309 ms	no
MiniLM OR 3-gram OR TF-IDF (accurate)	**0.966**	**0.94**	**2.8%**	**0.56**	**10 ms**	**69 ms**	**yes**

What I took from it:


- **Bigger is not better here.** The large models (bge-large, mxbai-large, gte-large) reach held-out F1 of 0.88 to 0.89, barely above MiniLM's 0.87, at about 200 ms p50, over 1 second p95 and about 4 GB of RAM. They help on summaries (0.72 to 0.83 against 0.50), but not enough to justify 20 times the latency.
- **bge-base fails on false alarms, not just speed.** It has the best raw recall, but flags 7% to 8% of held-out negatives, mostly public text wrapped in a prompt (14% flagged). Making it faster would

not fix that.

- **The code-specialised model is a poor fit.** jina code is worst on prose (0.56) and no better than MiniLM on code.
- **MiniLM fits the box.** 91 MB on disk, 0.4 s to load, 18 s to index all 594 chunks, and the full backend with the default hybrid used 280 MB of RAM on my machine. bge-base needs 1.4 GB, which does not fit the 1 GB VM.
- **Lexical methods are strong on this data, and that needs a caveat.** TF-IDF alone beats every embedding model, because most of my leaked text keeps names, figures and product terms, exactly what TF-IDF weights. Lexical methods fail on summaries (3-gram 0.00, TF-IDF 0.28). That is where the embedding earns its place.



Held-out and in-sample F1 for every method, documents and code




Accuracy against latency. Bubble size is peak RAM.

The v0.5 accurate profile

Once RAM stopped being the constraint (backend on a desktop instead of the VM), I asked what the most accurate setup is that still meets both rules. The answer was MiniLM OR 3-gram OR TF-IDF. The three signals cover different kinds of paste: MiniLM covers meaning (paraphrase, summary), 3-gram covers exact excerpts, and TF-IDF covers rewording that keeps the rare words.

Held-out documents: **F1 0.966, recall 0.94, precision 0.99, false alarms 2.8% (2 of 72)**, against 0.943, 0.90, 0.99 and 2.8% for the default. Tone rewrites go from 0.50 to 0.72 and summaries from 0.50 to 0.56. Over 120 real /check requests over HTTP on my machine (8 vCPU, 2 threads) it measured **p50 19 ms and p95 56 ms**, with the backend at 379 MB. It uses the same model and index as the default, so switching needs no reindex (`profile = "accurate"` or `PG_PROFILE=accurate`). TF-IDF is turned off for code in this profile, because on code it added false alarms (6% held-out on 50 negatives) without adding recall, which was already 1.00.



Held-out recall by paste type for documents

How the numbers moved

Every number in this section comes from a committed results file or the benchmark script, which can be re-run.


Step	Change	Document result at coach level
1	Embedding model and sqlite-vec index, code only	n/a
2	Documents added: 12 docs, paragraph-aware chunks plus 60 word passages, 280 samples	P 0.98, R 0.82, F1 0.89, FPR 0.03
3	Corpus grown to 18 longer, more varied documents, harder eval set (356 samples), thresholds retuned	P 0.99, R 0.75, F1 0.85, FPR 0.04

Step	Change	Document result at coach level
4	Chunking bug fixed (the same 30 words could appear up to three times in a chunk)	P 0.99, R 0.80, F1 0.88, FPR 0.03
5 (v0.4)	Hybrid matching, MiniLM OR 3-gram, separated threshold bands	P 1.00, R 0.87, F1 0.93, FPR 0.01 (in-sample)
6 (v0.4)	Held-out split by document added	Hybrid F1 0.94, R 0.90, FPR 0.03
7 (v0.5)	False alarm budget tightened to 3%, accurate profile	F1 0.966, R 0.94, FPR 0.028

Step 3 lowered the numbers on purpose. The bigger corpus and harder eval set are closer to reality, and the earlier 0.82 recall was on an easier set.

A correction on short passages. Adding the 60 word passages next to the long chunks is the largest single gain I found. A short excerpt or a one-paragraph summary has no close neighbour among 160 word chunks, because the rest of the chunk dilutes its vector. At one point I summarised this gain as "30% to 80%". When I went back to check, no recorded run supported that figure. The measured result is **51% to 80% recall at a fixed threshold of 0.63**, or 69% to 80% when each index gets its own best threshold. I corrected it in the log, and the measured figure is the one I stand behind.

Threshold bands. v0.3 shipped document bands of nudge 0.62 and coach 0.63, one hundredth apart, so nudge almost never fired on its own. In v0.4 I read the bands off the score distribution: nudge 0.58 (a soft "double check", recall 0.89 but FPR 0.13 in-sample), coach 0.64 (the best-F1 point) and block 0.74 (above every negative I have seen). The 3-gram bands are coach 0.25 and block 0.50. The best tuned value was 0.14, but the highest negative scored 0.13, so I left a margin. Code bands are 0.55, 0.65 and 0.85.



Paste Guard default hybrid against the regex baseline, by paste type (v0.4, in-sample, coach level)

In-sample, the top match named the right source document 98% of the time (314 detected positives). On held-out thresholds the default hybrid named the right one 93% of the time (255 detected).

Live test in ChatGPT and Claude

Beyond the offline eval, I ran it by hand in both ChatGPT and Claude:

Test	Result
Verbatim paste of a confidential document	Blocked
Paraphrased paste of a confidential document	Blocked
Paste of code from the company repo	Coached
One-click redaction	Works
Cancel from the overlay	Works
Normal, unrelated text	Allowed through
PDF upload of a confidential document	Blocked
Drag-and-drop of a file	Not tested yet

Drag-and-drop is implemented in the extension, but I have not checked it end to end in either site, so I am not counting it as working.

Limitations

- **Summaries are the weak spot.** Even the accurate profile catches 56% of summaries. A summary shares meaning with the source but few specific phrases, and that is the paste you described on our call.
- **The negative set is small and easy.** There are 72 document negatives, so one false alarm moves the rate by 1.4 points. 2.8% against 4.2% is a one-sample difference. The negatives are also public text and public code, not same-topic internal text that is not confidential, so the false alarm rates are optimistic for a real company. The strong lexical results could partly be an effect of these easy negatives.
- **Timing is from my machine.** The 16 to 19 ms p50 and 56 to 58 ms p95 figures are on an 8 vCPU desktop CPU. On the shared 1 GB VM the default profile measured p50 208 ms and p95 995 ms. With about 130 MB free next to the other services, part of the process gets paged out, and that drives the p95. The first check after a restart takes about 10 seconds while the model loads.
- **One synthetic company.** The corpus and the eval pastes were generated with Claude for one fictional company. Real documents may land in a different similarity range.
- **Coverage.** Chrome only, on two AI sites. Not desktop apps, Claude's own browser agent, mobile, or text typed in by hand.

Next steps

1. Build harder negatives: same-topic internal text that is not confidential. That is the real test of the false alarm rate and of whether the lexical gains hold.
2. Run it on a second corpus, ideally a design partner's redacted documents, and report recall at a fixed low false alarm rate.
3. Work on summaries: a summary-level embedding of each document, and a small reranker or local LLM judge only on borderline scores, so the fast path stays fast.
4. Test drag-and-drop end to end in both sites.
5. Fix VM latency by giving the backend its own memory or a lighter process, then re-measure p95 there.
6. Use the identity context. The match score and source name can be one more signal for Sidekick's reasoning: personal account plus strong match is a block that offers the approved workspace, while a corporate account plus a weak match is a nudge.
7. Scope the cases the extension cannot see (desktop apps, agentic browsers) as a separate feasibility question.

Sources: README.md, docs/OPTIMIZATION_LOG.md, eval/benchmarks.md, eval/results.md, CHANGELOG.md and paste-guard.toml in the repo. Market and competitor notes are from public vendor pages and documentation.