

## Assignment 0. Warmup exercises

Marks 15+5

Posted on 07.08.2025 @ 2:30 pm and due on 07.08.2025 @ 6:00 pm

---

1. Calculate the sum of first  $N = 20$  odd numbers and factorial of  $N = 8$  starting from 0. (using `do-while` or `for` loop). **[3+3]**
2. Calculate the sum of  $N = 15$  terms of a GP and HP series for common difference 1.5 and common ratio 0.5 starting from  $t_0 = 1.25$ . Use of analytical formulae not allowed. **[3+3]**
3. Consider the following matrices,

$$\mathbf{A} = \begin{pmatrix} 2 & -3 & 1.4 \\ 2.5 & 1 & -2 \\ -0.8 & 0 & 3.1 \end{pmatrix}, \quad \mathbf{B} = \begin{pmatrix} 0 & -1 & 1 \\ 1.5 & 0.5 & -2 \\ 3 & 0 & -2 \end{pmatrix}$$
$$\mathbf{C} = \begin{pmatrix} -2 \\ 0.5 \\ 1.5 \end{pmatrix}, \quad \mathbf{D} = \begin{pmatrix} 1 \\ 0 \\ -1 \end{pmatrix}$$

Find  $\mathbf{AB}$ ,  $\mathbf{D} \cdot \mathbf{C}$  and  $\mathbf{BC}$ . **[5]**

4. \*\* Define *MyComplex* class / structure and calculate the sum, difference, product and modulus of  $(1.3 - 2.2j)$  and  $(-0.8 + 1.7j)$ . **[5]**  
\*\* Extra 5 marks if you can do it.

Listing 1: Help with file reading

```
def read_matrix(filename):  
    with open(filename, 'r') as f:  
        matrix = []  
        for line in f:  
            # Split the line into numbers and convert to int/float  
            row = [float(num) for num in line.strip().split()]  
            matrix.append(row)  
    return matrix  
  
# Example usage  
matrix = read_matrix('matrix.txt')  
print(matrix)
```

Listing 2: Help with class complex : idragonlib.py

```
import numpy as np

class MyComplex():
    def __init__(self, real, imag=0.0):
        self.r=real
        self.i=imag
    def display_cmplx(self):
        print(self.r, ", ", self.i, "j", sep="")
    def add_cmplx(self, c1, c2):
        self.r=c1.r+c2.r
        self.i=c1.i+c2.i
        return MyComplex(self)
    def sub_cmplx(self, c1, c2):
        self.r=c1.r-c2.r
        self.i=c1.i-c2.i
        return MyComplex(self)
    def mul_cmplx(self, c1, c2):
        self.r=c1.r*c2.r - c1.i*c2.i
        self.i=c1.i*c2.r + c1.r*c2.i
        return MyComplex(self)
    def mod_cmplx(self):
        return np.sqrt(self.r**2+self.i**2)
```

Listing 3: Help with class complex : idragoncmplx.py

```
import numpy as np
# complex math : Name — Imagine Dragon, Roll — 007

import numpy as np
from idragonlib import *

c1=MyComplex(0.75,1.25)
c2=MyComplex(-1.5,-2.0)
c3=MyComplex(0.0,0.0)

print("\n_Two_complex")
c1.display_cmplx()
c2.display_cmplx()

print("\nAdding_two_complex")
c3.add_cmplx(c1,c2)
c3.display_cmplx()

print("\nSubtracting_two_complex")
c3.sub_cmplx(c1,c2)
c3.display_cmplx()

print("\nMultiplying_two_complex")
c3.mul_cmplx(c1,c2)
c3.display_cmplx()

print("\nModulus_of_two_complex")
mod=c1.mod_cmplx()
print(f" c1_mod={mod:.3f}")
mod=c2.mod_cmplx()
print(f" c2_mod={mod:.3f}")

Run as — python3 idragoncmplx.py
```

Listing 4: Help with structure complex : idragoncmplx.c

```
// Complex math : Name — Imagine Dragon, Roll — 007
// compile as : gcc idragoncmplx.c -lm
// run as : ./a.out

#include <stdio.h>
#include <math.h>

typedef struct{
    float re; float im;
} complex;

complex setcmplx(float a, float b)
{
    complex c;
    c.re=a; c.im=b;
    return(c);
}

complex prodcmplx(complex a, complex b)
{
    complex c;
    c.re=a.re*b.re - a.im*b.im;
    c.im=a.im*b.re + a.re*b.im;
    return(c);
}

int main(int argc, char *argv[])
{
    complex z1=setcmplx(2.4, -2.7);
    complex z2=setcmplx(-0.9, 1.25);
    printf("z1 = %.2f, %.2fj\n", z1.re, z1.im);
    printf("z2 = %.2f, %.2fj\n", z2.re, z2.im);

    complex z=prodcmplx(z1, z2);
    printf("z1*z2 = %.2f, %.2fj\n", z.re, z.im);
} // end of main
```