

Digitap.ai ITR Download API API Doc & Integration Guide

(Version 2.0, 09 Feb 2026)

A jumpstart guide to boosting your Business

Save Time, Save Cost

Table of Contents

1. Introduction	2
1.1 Description	2
1.2 How Does It Work?	3
2. API Structure	3
2.1 Authentication	3
2.2 API Request & Response Format	4
2.3 Response Properties	4
2.4 Response Structure	4
2.5 Error Responses	4
3. Generate URL API	5
3.1 URL	5
3.2 Accepted Method	5
3.3 Header	5
4. Status Check API	7
4.1 URL	7
4.2 Accepted Method	7
4.3 Header	8
4.7 Error Response	10
4.8 List of API Error Codes	10
5. Download Report API	11
5.1 URL	11
5.2 Accepted Method	11
5.3 Header	11
5.7 Error Response	16
5.8 List of API Error Codes	16
6. Appendix	16
A. Transaction Complete Callback URL	16
B - Return URL Integration	18

1. Introduction

1.1 Description

The Digitap ITR Download API Suite enables seamless retrieval of Income Tax Return (ITR) data directly from the Income Tax e-Filing portal through a secure, consent-driven process. This suite of APIs is designed to help financial institutions, NBFCs, and fintechs access

verified income data to power risk assessments, credit decisioning, and financial profiling, all while ensuring compliance and user privacy. ITR Download API aids clients to download ITR form, ITR V(Acknowledgement), Form 26AS, AIS, and TIS files of the customer directly from the portal using customer's consent.

The API suite automates the end-to-end ITR data extraction process:

- generating a secure, customer-facing URL for authentication,
- tracking the status of ongoing requests, and
- downloading structured ITR reports and documents upon completion.

By integrating Digitap's ITR Download API suite, clients can reduce manual verification effort, improve turnaround time, and download the authentic ITR documents directly from the portal.

This document provides details for the Digitap ITR Download APIs - the request, response, and error handling structures for each API.

1.2 How Does It Work?

The following steps describe the process flow for ITR data retrieval:

- **Step 1:**
Client initiates a request using the **Generate URL API**.
Digitap verifies client credentials and returns a URL which the client can share with the customer or embed in their app.
- **Step 2:**
The customer completes authentication on the ITR portal via the Digitap UI.
Upon completion, the customer is redirected to the client-specified return_url. If return_url is not provided, customer is redirected to Digitap website by default.
- **Step 3:**
Client invokes the **Status Check API** to track the progress of the ITR extraction.
The response indicates whether the report is being generated, completed, or failed.
- **Step 4:**
Once the report is ready, the client uses the **Download Report API** to fetch the generated ITR report(s).

Note: *Digitap.ai reserves the right to modify this API documentation from time-to-time. If you are a business using this Service, you will be notified well in advance, prior to any change being made.*

2. API Structure

2.1 Authentication

To use the API, one needs to register with Digitap and get a client id & client secret key. The client ID & secret key are different for the UAT & production environment.

We support JWT token based authentication, along with basic authentication.

2.2 API Request & Response Format

- Both the input request and response follow the JSON format.
- Authentication details need to be passed in the header as BASIC Auth.
- The API error is normally returned as standard HTTP Status/Response Codes and also mirrored in the body of the response.
- When the API request is accepted, HTTP status code 200 is returned and whether the request is successful or not, needs to be checked further based on the request status.
- For every request API call, an unique request-id would be returned, which can be used for easier debugging in the future. Clients are requested to provide this request-id when raising an issue or discussing the response.

All API requests use the following configuration:

- Content-Type: application/json
Authentication: **Basic Auth** (client_id:client_secret)

2.3 Response Properties

- Content-Type: application/json
- HTTP 200 → Successful call
- Non-200 → Error

2.4 Response Structure

```
{  
  "status": "Success",  
  ...  
}
```

or

```
{  
  "status": "Failure",  
  ...  
}
```

2.5 Error Responses

Example:

```

{
  ...
  "status": "Success",
  "transactions": [
    {
      "code": "InvalidCredentials",
      ...
    }
  ]
}

```

3. Generate URL API

The **Generate URL API** is the first step in the ITR download process. It creates a secure, time-bound URL that the client can share with the customer to authenticate and consent for ITR data retrieval.

3.1 URL

Following are the **URLs** for UAT & production Environment for Generate URL API.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/itr/generate_url
Production Env	https://svc.digitap.ai/validation/kyc/v1/itr/generate_url

3.2 Accepted Method

POST

3.3 Header

Key	M/O	Value
Content-Type	M	application/json
Authorization	M	Basic Auth (client_id:client_secret) OR BasicBase64encodedValueOf (client_id:client_secret)

3.4 Input JSON Structure

```
{
  "client_ref_num": "digitap-itr-test",
  "pan": "ABCDE1234F",
  "callback_url":
    "https://webhook.site/e8b4fce4-5c81-4e40-a8d0-7c8e51abde1f",
  "return_url": "https://www.digitap.ai?txn_id=%s&status=%s",
  "is_editable": 1,
  "txn_completed_cburl": "http://client-given-callback-url"
}
```

3.5 Payload Elements

Element	M/O	Data Type	Description
client_ref_num	M	String	Unique reference number assigned to client.
pan	M	String	PAN of the user whose ITR is to be fetched.
return_url	O	String	Redirect URL after completion. Supports placeholders (%s). If return_url is not provided, customer is redirected to Digitap website by default.
is_editable	O	Integer/Bool	1/true = Allow edit of PAN; 0/false = Lock PAN field. By default the value is 0
callback_url	O	String	Digitap will send an HTTP POST request to this URL once the transaction is complete. Please refer to the "Appendix A - CallBack URL" Section for more details.

3.6 Success Response

```
{
  "request_id": "0199e0b2-f0a1-8c74-8a37-0d042f7ebd6b",
  "url":
    "https://svcstage.digitap.work/itr/transact?gl=eyJhbGciOiJIUzI1NiIs...\"",
  "expires_on": "2025-10-15T08:40:47.964632+05:30"
}
```

Keys are explained below:

Key	Value
request_id	Unique request ID mapped to the generated URL
url	the Digitap ITR Download UI URL on which customer will do interactions
expires_on	denotes the expiry timestamp of the URL

3.7 Error Response

```
{
  "status": "Failure",
  "code": "InvalidPAN",
  "message": "Invalid PAN provided."
}
```

3.8 List of API Error Codes

Code	Description
InvalidPAN	PAN number is invalid.
ClientAuthenticationFailed	Invalid authorization credentials.
InternalError	Unexpected internal error.
InvalidClientRefNum	Client has sent an unsupported client reference number
MalformedJson	Malformed Json received in API request
InvalidRedirectUrl	Redirect URL is invalid or does not follow the regex
InvalidCallbackUrl	Callback URL is invalid or does not follow the regex

4. Status Check API

The Status Check API allows clients to track the real-time progress of an ITR extraction request.

4.1 URL

Following are the **URLs** for UAT & production Environment for Status Check API.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/itr/status
Production Env	https://svc.digitap.ai/validation/kyc/v1/itr/status

Note: DNS will be shared separately for UAT and PROD environments, senders just need to add the described path or parameter.

4.2 Accepted Method

POST

4.3 Header

Key	(Mandatory /OptionalM/O)	Value
Content-Type	M	application/json
Authorization	M	Basic Auth (client_id:client_secret) OR BasicBase64encodedValueOf (client_id:client_secret)

4.4 Input JSON Structure

```
{
  "request_id": "0199e0b2-f0a1-8c74-8a37-0d042f7ebd6b"
}
```

4.5 Payload Elements

Element	Description
request_id	Unique request ID returned from Generate URL API.

4.6 Success Response

Case 1: Generated URL status

```
{
  "request_id": "0199b8e0-f5fe-87dc-9d75-f3b1274c7648",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199b8e1-860d-8b5c-b859-0430bbf76dff",
      "code": "TxnInitiated",
      "status_last_updated_on": "2025-10-06T15:06:52.227181"
    }
  ]
}
```

Case 2: Start of the process

```
{
  "request_id": "0199b8e0-f5fe-87dc-9d75-f3b1274c7648",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199b8e1-860d-8b5c-b859-0430bbf76dff",
```



```
        "code": "TxnProcessing",
        "status_last_updated_on": "2025-10-06T15:06:52.227181"
    }
  ]
}
```

Case 3: Login Successful

```
{
  "request_id": "0199b8e0-f5fe-87dc-9d75-f3b1274c7648",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199b8e1-860d-8b5c-b859-0430bbf76dff",
      "code": "LoginSuccess",
      "status_last_updated_on": "2025-10-06T15:06:52.227181"
    }
  ]
}
```

Case 4: Website interaction completed

```
{
  "request_id": "0199b8e0-f5fe-87dc-9d75-f3b1274c7648",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199b8e1-860d-8b5c-b859-0430bbf76dff",
      "code": "UserInteractionCompleted",
      "status_last_updated_on": "2025-10-06T11:40:46.435745"
    }
  ]
}
```

Case 5: Report generated

```
{
  "request_id": "0199b8e0-f5fe-87dc-9d75-f3b1274c7648",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199b8e1-860d-8b5c-b859-0430bbf76dff",
      "code": "ReportGenerated",
      "status_last_updated_on": "2025-10-06T15:06:52.227181",
      "report_generated_on": "2025-11-04T10:42:45.133893"
    }
  ]
}
```

Case 5: Invalid credentials

```
{
  "request_id": "0199e0b2-f0a1-8c74-8a37-0d042f7ebd6b",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199e0b3-7d98-8767-ad82-03d2bdff0bf0",
      "code": "InvalidCredentials",
      "status_last_updated_on": "2025-10-14T14:11:50"
    }
  ]
}
```

Case 6: ITR was never filed for the input PAN

```
{
  "request_id": "0199e0b2-f0a1-8c74-8a37-0d042f7ebd6b",
  "status": "Success",
  "transactions": [
    {
      "txn_id": "0199e0b3-7d98-8767-ad82-03d2bdff0bf0",
      "code": "ITRNotFiled",
      "status_last_updated_on": "2025-10-14T14:11:50"
    }
  ]
}
```

Keys are explained below:

Key	Value
request_id	Inputted request ID
status	Status of the inputted request ID
transactions	List of transactions mapped to the inputted request ID
- txn_id	Transaction ID of respective transaction
- code	Error code in case of failure cases
status_last_updated_on	Timestamp of status last updated

NOTE: One request may have multiple transactions depending on the number of tries made with the same request until any transaction becomes successful.

4.7 Error Response

```
{
  "status": "Failure",
  "code": "ReqNotFound",
  "message": "Digitap request referred to by client not found."
}
```

4.8 List of API Error Codes

Code	Description
PANNotRegistered	PAN not registered with IT website
InvalidCredentials	User provided wrong password for ITR website
InvalidOtp	User provided invalid OTP(in case of 2FA)
OTPTimeout	OTP validation timeout
WebsiteDown	IT website is not fully functional
InternalError	Internal processing error.
MalformedJson	Malformed Json received in API request

5. Download Report API

The Download Report API provides the final step of the ITR data flow. Once the report is successfully generated, this API returns secure signed URLs for downloading ITR documents (PDFs and JSONs) for one or more assessment years.

5.1 URL

Following are the **URLs** for UAT & production Environment for Download Report API.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/itr/download
Production Env	https://svc.digitap.ai/validation/kyc/v1/itr/download

5.2 Accepted Method

POST

5.3 Header

Key	M/O	Value
Content-Type	M	application/json

Authorization	M	Basic Auth (client_id:client_secret) OR BasicBase64encodedValueOf (client_id:client_secret)
----------------------	---	--

5.4 Input JSON Structure

```
{
  "txn_id": "0199e0b3-7d98-8767-ad82-03d2bdff0bf0"
}
```

5.5 Payload Elements

Element	Description
txn_id	Transaction ID received from Status API

5.6 Success Response

Case 1: ITR is filed

```
{
  "status": "Success",
  "txn_id": "0199dea0-45d6-80fc-b648-e91007f9b6e5",
  "profile_data": {
    "pan": "ABCDE1234F",
    "pan_type": "Individual",
    "pan_status": "Active",
    "account_status": "Active",
    "first_name": "John",
    "middle_name": "",
    "last_name": "Doe",
    "full_name": "John Doe",
    "gender": "M",
    "dob": "22-01-1990",
    "aadhaar_number": "XXXXXXXXX9105",
    "aadhaar_linked": true,
    "address": {
      "building_name": "Sample Building",
      "street_name": "Main Street",
      "locality": "Sample Locality",
      "pincode": 400001,
      "city": "Mumbai",
      "state": "Maharashtra",
      "country": "India"
    }
  },
  "mobile": "9999999999",
  "email": "john.doe@example.com",
  "bank_details": [
    {

```

```

    "name": "John Doe",
    "account_number": "XXXXXXXXXXXX951",
    "account_type": "SAVING ACCOUNT",
    "account_holder_type": "PRIMARY",
    "bank_name": "HDFC BANK",
    "ifsc_code": "HDFC0000001",
    "branch_name": "Sample Branch",
    "remarks": "FAILURE IN NAME_MATCH",
    "message": "Refund can be credited only up to <50L> due to name mismatch between Bank account and PAN. Please update the name in PAN or with bank. EVC can be enabled for this bank account.",
    "nominated_for_refund": true
  }
],
},
"reports": {
  "itr": {
    "2025": [
      {
        "acknowledgement_number": "667733441122995",
        "form_type": "ITR-1",
        "status": "O",
        "filed_by": "SLF",
        "filed_on": "2023-05-11_18:33:00",
        "assessment_year": "2025",
        "pdf_report": "https://s3.amazonaws.com/.../itr-2025.pdf",
        "json_report": "https://s3.amazonaws.com/.../itr-2025.json"
      }
    ],
    "2023": [
      {
        "acknowledgement_number": "144644910110523",
        "form_type": "ITR-4",
        "status": "O",
        "filed_by": "SLF",
        "filed_on": "2023-05-11_18:33:00",
        "assessment_year": "2023",
        "pdf_report": "https://s3.amazonaws.com/.../itr-2023.pdf",
        "json_report": "https://s3.amazonaws.com/.../itr-2023.pdf"
      }
    ]
  },
  "2024": [
    {
      "message": "ITR filing information is not available for this PAN and year."
    }
  ]
},
"itr-v": {
  "2025": [
    {
      "acknowledgement_number": "667733441122995",
      "form_type": "ITR-1",
      "status": "O",

```

```

        "filed_by": "SLF",
        "filed_on": "2023-05-11_18:33:00",
        "assessment_year": "2025",
        "pdf_report": "https://s3.amazonaws.com/.../itr-v-2025.pdf",
        "json_report": ""
    }
],
"2023": [
    {
        "acknowledgement_number": "144644910110523",
        "form_type": "ITR-4",
        "status": "O",
        "filed_by": "SLF",
        "filed_on": "2023-05-11_18:33:00",
        "assessment_year": "2023",
        "pdf_report": "https://s3.amazonaws.com/.../itr-v-2023.pdf",
        "json_report": ""
    }
],
"2024": [
    {
        "message": "ITR filing information is not available for this PAN
and year."
    }
]
},
"form26as": {
    "2025": [
        {
            "acknowledgement_number": "667733441122995",
            "form_type": "ITR-1",
            "status": "O",
            "filed_by": "SLF",
            "filed_on": "2023-05-11_18:33:00",
            "assessment_year": "2025",
            "pdf_report": "https://s3.amazonaws.com/.../form26as-2025.pdf",
            "json_report": ""
        }
    ],
    "2023": [
        {
            "acknowledgement_number": "144644910110523",
            "form_type": "ITR-4",
            "status": "O",
            "filed_by": "SLF",
            "filed_on": "2023-05-11_18:33:00",
            "assessment_year": "2023",
            "pdf_report": "https://s3.amazonaws.com/.../form26as-2023.pdf",
            "json_report": ""
        }
    ],
    "2024": [
        {

```

```

        "message": "ITR filing information is not available for this PAN
and year."
    }
]
},
"ais": {
    "2025": [
        {
            "acknowledgement_number": "667733441122995",
            "form_type": "ITR-1",
            "status": "O",
            "filed_by": "SLF",
            "filed_on": "2023-05-11_18:33:00",
            "assessment_year": "2025",
            "pdf_report": "https://s3.amazonaws.com/.../ais-2025.pdf",
            "json_report": ""
        }
    ],
    "2023": [
        {
            "acknowledgement_number": "144644910110523",
            "form_type": "ITR-4",
            "status": "O",
            "filed_by": "SLF",
            "filed_on": "2023-05-11_18:33:00",
            "assessment_year": "2023",
            "pdf_report": "https://s3.amazonaws.com/.../ais-2023.pdf",
            "json_report": ""
        }
    ],
    "2024": [
        {
            "message": "ITR filing information is not available for this PAN
and year."
        }
    ]
},
"tis": {
    "2025": [
        {
            "acknowledgement_number": "667733441122995",
            "form_type": "ITR-1",
            "status": "O",
            "filed_by": "SLF",
            "filed_on": "2023-05-11_18:33:00",
            "assessment_year": "2025",
            "pdf_report": "https://s3.amazonaws.com/.../tis-2025.pdf",
            "json_report": ""
        }
    ],
    "2023": [

```

```

    {
      "acknowledgement_number": "144644910110523",
      "form_type": "ITR-4",
      "status": "O",
      "filed_by": "SLF",
      "filed_on": "2023-05-11_18:33:00",
      "assessment_year": "2023",
      "pdf_report": "https://s3.amazonaws.com/.../tis-2023.pdf",
      "json_report": ""
    }
  ],
  "2024": [
    {
      "message": "ITR filing information is not available for this PAN
and year."
    }
  ]
}

},
"link_expires_at": "2025-10-14T11:41:31+05:30"
}

```

Keys are explained below:

Key	Value
status	Status of the input transaction id. Possible values: Success, Failure
txn_id	Input transaction id
profile_data	All the personal details of the ITR account holder
 -pan	PAN number of the individual
 -pan_type	Type of PAN
 -pan_status	Status of the PAN
 -account_status	Status of the ITR account
 -first_name	First name of the individual
 -middle_name	Middle name of the individual
 -last_name	Last name of the individual
 -full_name	Full name of the individual
 -gender	Gender of the individual
 -dob	Date of birth
 -aadhaar_number	Masked Aadhaar number

 -aadhaar_linked	Linkage status of PAN and Aadhaar
 -address	Address details
 - -building_name	Building name
 - -street_name	Street name
 - -locality	locality
 - -pincode	pincode
 - -city	city
 - -state	state
 - -country	country
 -mobile	Mobile number of the individual
 -email	Email id of the individual
 -bank_details	Details of all linked bank accounts
 - -name	Name of individual
 - -account_number	Linked bank account number
 - -account_type	Linked bank account type
 - -account_holder_type	Linked bank account holder type
 - -bank_name	Linked bank name
 - -ifsc_code	Linked bank ifsc code
 - -branch_name	Linked bank branch name
 - -remarks	displayed case of any remark with the linked bank account
 - -message	Message displayed for this specific bank account, in case of any remarks
 - -nominated_for_refund	If the linked Bank account is nominated for refund or not
reports	Section to give details on report type and report links
 -itr	Type of report(ITR, ITR-V, form26as, AIS) and associated details
 - -2025	Assessment year
 - - -acknowledgement_number	Acknowledgement number of the ITR filing verification
 - - -form_type	ITR type
 - - -status	Original or Revised filing. Allowed values: O/R
 - - -filed_by	Person who filed the ITR
 - - -filed_on	Date of filing
 - - -assessment_year	Assessment year
 - - -pdf_report	Link to download ITR form PDF file

 -- --json_report	Link to download ITR form Json
 -- --message	This field is displayed in case ITR is unavailable/could not be extracted. Eg: "ITR filing information is not available for this PAN and year."
 --itr-v	Type of ITR(ITR, ITR-V, form26as, AIS, TIS) and associated details
 --2025	Assessment year
 -- --acknowledgement_number	Acknowledgement number of the ITR filing verification
 -- --form_type	ITR type(currently supporting ITR 1)
 -- --status	Original or Revised filing. Allowed values: O/R
 -- --filed_by	Person who filed the ITR
 -- --filed_on	Date of filing
 -- --assessment_year	Assessment year
 -- --pdf_report	Link to download ITR V PDF file
 -- --message	This field is displayed in case file is unavailable/could not be extracted. Eg: "ITR filing information is not available for this PAN and year."
 --form26as	Details of Form 26AS
 --2025	Assessment year
 -- --acknowledgement_number	Acknowledgement number of the ITR filing verification
 -- --form_type	ITR type
 -- --status	Original or Revised filing. Allowed values: O/R
 -- --filed_by	Person who filed the ITR
 -- --filed_on	Date of filing
 -- --assessment_year	Assessment year
 -- --pdf_report	Link to download Form26AS PDF file
 --ais	Details of AIS
 --2025	Assessment year
 -- --acknowledgement_number	Acknowledgement number of the ITR filing verification
 -- --form_type	ITR type
 -- --status	Original or Revised filing. Allowed values: O/R
 -- --filed_by	Person who filed the ITR
 -- --filed_on	Date of filing
 -- --assessment_year	Assessment year
 -- --pdf_report	Link to download AIS PDF file
 --tis	Details of TIS

 --2025	Assessment year
 --acknowledgement_number	Acknowledgement number of the ITR filing verification
 --form_type	ITR type
 --status	Original or Revised filing. Allowed values: O/R
 --filed_by	Person who filed the ITR
 --filed_on	Date of filing
 --assessment_year	Assessment year
 --pdf_report	Link to download TIS PDF file
link_expires_at	Time stamp of reports links expiry

5.7 Error Response

```
{
  "status": "Failure",
  "code": "TxnNotFound",
  "message": "Digitap request referred to by client not found."
}
```

5.8 List of API Error Codes

Code	Description
TxnNotFound	Digitap request referred to by client not found
ClientAuthenticationFailed	Invalid or missing authentication.
InternalError	Internal server error.
MalformedJson	Malformed Json received in API request

6. Appendix

A. Callback URL

The `callback_url` parameter given in the Generate URL API should be the RESTFUL API URL capable of receiving the callbacks. The same will be used to post the response by Digitap once the transaction is completed. The response will be posted in case of either successful or failure of the transaction. The success and failure of transaction is defined in the following points:

- Once data extraction completed & Report Generation Succeeded - in both cases whether status is `reportGenerated` or `reportNotGenerated(Success)`
- In all other cases, status will be failure, with a code and message to identify what is the next actionable step.

Digitap will attach the following header while posting on URL:

Header Name	Value	Description
x-digitap-callback-type	TRANSACTION_COMPLETE	Callback happened after transaction completed (successfully or otherwise)

Clients are advised to check the above header data and then process only the appropriate message, as the same URL would be used to give other types of callbacks in the future. The content type of the transaction complete callback would be “application/json” and below is the sample JSON structure:

```
{
  "client_ref_num": "",
  "request_id": "",
  "txn_id": "daf4292",
  "status": "Success",
  "code": "",
  "message": ""
}
```

Elements of the JSON are given below:

Elements	Description
client_ref_num	Client-specified identifier to uniquely identify this transaction, specified during the generate_url API call
request_id	Digitap provided unique request_id (returned during the Generate URL API response)
txn_id	Digitap generated unique transaction id
status	Possible values are Success, Failure. Success in case of status is reportGenerated or reportNotGenerated, Failure in all other cases
code	Code denoting the specific scenario. List is provided in each API section.
msg	Brief message description for either success or error response

Notes on the response posted by Digitap on callback URL.

- Digitap expects an HTTP 200 OK response from the URL on receipt of callback request
- If the first attempt fails, Digitap will try again two more times at regular intervals of 60 seconds.

- If a transaction concludes successfully, use the Download Report API to download the generated report(s).
- If a transaction does not conclude successfully, use the Status Check API to find out more details about why.

B - Return URL Integration

Digitap provide the facility to redirect to the client interface once transaction is complete and it can be done in following two ways:

1. Redirection to return url (Incase of web view in Android Application)
2. Redirection to the Application Interface (Incase of native Android application)

Redirection to return URL:

If the return url is specified and the client is using a web view, Digitap sends the End User to this URL after completing interaction with Digitap or after completing the user interaction. By default, request id, transaction id, status would be returned.

Placeholder for client ID can be inserted in the URL to get the client ID during the redirection. User will be redirected to the return URL once the transaction is complete or user interaction is complete, which will be one of the following cases:

- When User Clicked Cancel Button in the Home Page
- Once Data Extraction completed (Success)
- Once login is completed

If return_url is not provided, customer is redirected to Digitap website by default.

Redirection to the Application Interface:

If the return url is not specified and the client is using a native android application then the client can integrate with the below code snippet which Digitap will call after completing interaction with Digitap.

Digitap will pass the three parameters request_id, txn_id, and true/false indicating Transaction success/failure.

```
public class ClassName {

    @JavascriptInterface
    public void onFinish(String requestId, String txnId, String status) {

    }
}

webView.addJavascriptInterface(new ClassName(), "DigitapITR");
```

----- End of Document -----