

Digitap Mobile & UPI APIs Suite API Doc & Integration Guide

(Version 2.4, 5th March 2025)

A jumpstart guide to boosting your Business

Save Time, Save Cost

Table of Contents

1 Introduction	4
1.1 Validation API Suite Introduction	4
2 API Documentation	4
2.1 Introduction	4
2.2 Authentication	5
2.3 API URLs	5
2.4 API Request & Response Format	5
2.5 HTTP Status/Response Codes and its response body format	5
2.5.1 Error Messages	6
2.6 API Result	7
2.7 Additional Notes	8
3 MOBILE - Mobile Number Validation (MNV without OTP):	8
3.1 API Introduction	8
3.2 API Request	8
3.3 API Success Response	9
3.3.1 Successful Validation (result_code 101) Case	9
3.3.2 Unsuccessful Validation Case	17
3.4 API Error Response	17
4 Bank - UPI Validation - Basic	18
4.1 API Introduction	18
4.2 API Request	18
4.3 API Success Response	19
4.3.1 Successful Validation (result_code 101) Case	19
4.3.2 Unsuccessful Validation Case	20
4.4 API Error Response	20
5 Bank - UPI Validation - Advanced	21
5.1 API Introduction	21
5.2 API Request	21
5.3 API Success Response	21
5.3.1 Successful Validation (result_code 101) Case	21
5.3.2 Unsuccessful Validation Case	22
5.4 API Error Response	23
6 Bank - UPI Validation -Enhanced(Deprecated)	23
6.1 API Introduction	23
6.2 API Request	23
6.3 API Success Response	24
6.3.1 Successful Validation (result_code 101) Case	24
6.3.2 Unsuccessful Validation Case	27
6.4 API Error Response	27
7 Mobile to Name Lookup	28
7.1 API Introduction	28

7.2 API Request	28
7.3 API Success Response	29
7.3.1 Successful Validation (result_code 101) Case	29
7.3.2 Unsuccessful Validation Case	30
7.4 API Error Response	30
8 Mobile to UPI Lookup - Basic	30
8.1 API Introduction	30
8.2 API Request	31
8.3 API Success Response	31
8.3.1 Successful Validation (result_code 101) Case	31
8.3.2 Unsuccessful Validation Case	33
8.4 API Error Response	33
9 Mobile to UPI Lookup - Advanced	33
9.1 API Introduction	33
9.2 API Request	34
9.3 API Success Response	34
9.3.1 Successful Validation (result_code 101) Case	34
9.3.2 Unsuccessful Validation Case	37
9.4 API Error Response	37
10 Mobile to UPI Lookup - Enhanced	37
10.1 API Introduction	37
10.2 API Request	37
10.3 API Success Response	38
10.3.1 Successful Validation (result_code 101) Case	38
9.3.2 Unsuccessful Validation Case	42
10.4 API Error Response	42
11 Mobile to Multiple UPI Lookup - Basic- (Deprecated)	42
11.1 API Introduction	42
11.2 API Request	43
11.3 API Success Response	43
11.3.1 Successful Validation (result_code 101) Case	43
11.3.2 Unsuccessful Validation Case	46
11.4 API Failure Response	46
12 Mobile to Multiple UPI Lookup - Advanced-(Deprecated)	46
12.1 API Introduction	46
12.2 API Request	46
12.3 API Success Response	47
12.3.1 Successful Validation (result_code 101) Case	47
12.3.2 Unsuccessful Validation Case	50
12.4 API Error Response	50
13 Mobile to Multiple UPI Lookup - Enhanced (Deprecated)	50
13.1 API Introduction	50
13.2 API Request	51
13.3 API Success Response	51

13.3.1 Successful Validation (result_code 101) Case	51
13.3.2 Unsuccessful Validation Case	61
13.4 API Error Response	61

1 Introduction

This document is intended for our enterprise partners who can easily integrate the services they have chosen with Digitap.ai. Using this document they can jumpstart their business processes and start using the Digitap.ai services as early as possible and also align their own business processes seamlessly by integrating and making changes to their backend.

1.1 Validation API Suite Introduction

Digitap.ai Validation API Suite provides APIs to validate Mobile Number, Bank Account like UPI ID Validation and Other Misc Utilities:

- ❑ **Mobile Validation**
 - ❑ Mobile Number Validation (*MNV without OTP*)
- ❑ **Bank Validation**
 - ❑ UPI Validation - Basic
 - ❑ UPI Validation - Advanced
 - ❑ UPI Validation - Enhanced-(Deprecated)
- ❑ **Miscellaneous**
 - ❑ Mobile to Name Lookup
 - ❑ Mobile to UPI Lookup Basic
 - ❑ Mobile to UPI Lookup Advanced
 - ❑ Mobile to UPI Lookup Enhanced
 - ❑ Mobile to Multiple UPI Lookup Basic-(Deprecated)
 - ❑ Mobile to Multiple UPI Lookup Advanced-(Deprecated)
 - ❑ Mobile to Multiple UPI Lookup Enhanced-(Deprecated)

Note: *Digitap.ai reserves the right to modify this API documentation from time-to-time. If you are a business using this Service, you will be notified well in advance, prior to any impactful change being made.*

2 API Documentation

2.1 Introduction

Digitap.ai Validation Suite provides RESTful/standard HTTP Web APIs which help to validate a specific data point by providing the response synchronously in the same API Call. The API uses the standard HTTP status/response codes to indicate the success or API errors.

2.2 Authentication

To use API, one needs to register with Digitap and get a client id & client secret key. The client ID & secret key are different for the UAT & production environment.

2.3 API URLs

Following is the **base URL** for UAT & production Environment.

Production Env	https://svc.digitap.ai/validation/
UAT/DEMO Env	https://svcdemo.digitap.work/validation/

2.4 API Request & Response Format

- Both the input request and response follow the JSON format.
- In each APIs input, a client reference number is accepted to easily identify the given request from a client and the same is also mirrored in the output. The other parameters required in the input and their format are explained in specific APIs.
- The API error is normally returned as standard HTTP Status/Response Codes and also mirrored in the body of the response.
- When the API request is accepted, HTTP status code 200 is returned and whether the validation is successful or not is returned in the result_code. The various possible values of the validation is explained under the section “API Result”
- In all the responses, an unique request-id (unique UUID) would be returned, which can be used for easier debugging in the future. Clients are requested to provide this request-id when raising an issue or discussing the response.

2.5 HTTP Status/Response Codes and its response body format

The API Error Codes are returned as HTTP Status Codes. Following status codes would be returned by the APIs.

Code	Message	Description
200	OK	Request Successful <i>(Note: 200 does not mean that Validation is success, but indicates that the request is successful. result_code in the Response body indicates whether the validation is successful or not).</i>
400	One or more parameters format is wrong	Input parameter passed by the customer is missing or invalid

401	Client Authentication failed	Access to API is denied
500	Internal Error	Internal Server Error identified through its number
503	Website is in maintenance	The source for authentication is down for maintenance or inaccessible.
503	Source is down. Please try again	The source is not available for the moment. Please retry in this case
504	Endpoint request Timed out	The response latency from the source for authentication is >30sec.

Format of the response body for successful request case (http Status code 200) is like below:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",

  "result_code": nnn,

  // Optional items based on result_code
  "result": nnn,
  "message": "yyy",
}
```

Format of the response body for failure cases (http Status code other than 200) is like below:

```
{
  "http_response_code": nnn,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "xxxx"
}
```

2.5.1 Error Messages

Error messages for each of the failure cases is given below:

Code	Error Message
400	One or more parameters format is wrong or missing

401	Client Authentication Failed
500	Internal Error 1/2/3
503	Website is in maintenance
504	Endpoint request Timed out

Please see the respective APIs for any additional details.

2.6 API Result

When the API returns HTTP status code 200/OK, the API request is accepted, and result of the request is provided in the key called “**result_code**” in the response body:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": nnn,
}
```

Various possible values of **result_code** and is tabled below:

result_code	Description
101	Validation Successful
102	Invalid id number or combination of inputs
103	No record found for the given input
104	Source failed to respond with proper details
105	Unexpected Response from source
106	Multiple records exists
108	If the user's application is rejected

Please see the respective APIs for details of which result code occurs in the specific API.

2.7 Additional Notes

- API will be billable for any successful responses with http response code 200 irrespective of result code.

3 MOBILE - Mobile Number Validation (*MNV without OTP*):

3.1 API Introduction

This API allows clients to validate the mobile number and also obtain detailed information about the mobile number without any user consent or OTP. This API provides basic details about the mobile number like

- Valid Number or not
- Connection status
- Service provider information (Current, Original, and Roaming)
- Ported or not Details
- Prepaid or Postpaid Details

This API is useful for applications that require mobile number validation, customer profiling, network analysis, and related functionalities. This API can give additional information like customer details, last ported date, porting history and mobile vintage too.

*****Kindly reach out to our sales team for assistance in enabling one or all of the options.**

3.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/mobile/v1/mobile-lookup
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile_number	M	Mobile number which needs to be validated. It should be of type string and should be in a valid format (10 characters in length with only digits - starting digit should be from 6 to 9) without any spaces or special characters. Type: String
options	O	Include the options parameter as an array to specify additional information to be included in the response. If not given, it would consider the default options configured for the client. Options are available at additional commercials. Type: List/Array Options: 'customer_details', 'porting_history' and 'ported_date', "mobile_vintage"

3.3 API Success Response

3.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is a response format for the successful case when all the options - customer_details, porting_history, ported_date and mobile_vintage are requested during the input:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd_1233",
  "request_id": "78cbdc5b-bad7-44fc-9462-f686d76d75fa",
  "result_code": 101,
  "message": "Report Generated Successful",
  "result": {
    "customer_details": {
      "name": "Suxxxx xxxai",
      "alternate_number": "825021XXX"
    },
    "is_valid": true,
```

```

"subscriber_status": "CONNECTED",
"connection_status": {
  "status_code": "DELIVERED",
  "error_code_id": ""
},
"connection_type": "prepaid",
"msisdn": {
  "msisdn_country_code": "IN",
  "msisdn": "+91750127XXX",
  "type": "MOBILE",
  "mnc": "06",
  "imsi": "40445750127XXX",
  "mcc": "404",
  "mcc_mnc": "40406"
},
"current_service_provider": {
  "network_prefix": "98450",
  "network_name": "Airtel",
  "network_region": "Karnataka",
  "mcc": "404",
  "mnc": "06",
  "country_prefix": "+91",
  "country_code": "IN",
  "country_name": "India"
},
"original_service_provider": {
  "network_prefix": "75012",
  "network_name": "Airtel",
  "network_region": "West Bengal",
  "mcc": "",
  "mnc": "",
  "country_prefix": "+91",
  "country_code": "IN",
  "country_name": "India"
},
"is_ported": true,
"last_ported_date": "2019-07-16",
"porting_history": [
  {
    "porting_date": "2019-07-16T00:00:00",
    "porting_action": "Add",
    "ported_network": {
      "country_name": "India",
      "network_name": "Airtel",
      "network_region": "Karnataka",
      "mcc": "404",
      "mnc": "45"
    },
    "porting_number_type": "mobile"
  },
  {
    "porting_date": "2016-12-24T00:00:00",
    "porting_action": "Add",
    "ported_network": {
      "country_name": "India",
      "network_name": "IDEA",
      "network_region": "Karnataka",
      "mcc": "405",
      "mnc": "847"
    }
  }
]

```

```

    },
    "porting_number_type": "mobile"
  },
  {
    "porting_date": "2014-12-01T00:00:00",
    "porting_action": "Add",
    "ported_network": {
      "country_name": "India",
      "network_name": "IDEA",
      "network_region": "West Bengal",
      "mcc": "405",
      "mnc": "853"
    },
    "porting_number_type": "mobile"
  }
],
"mobile_vintage": {
  "phone_tenure": {
    "min": 48,
    "max": null
  },
  "last_deactivated": {
    "min": null,
    "max": null
  }
},
"is_roaming": false,
"roaming_service_provider": {
  "network_prefix": "",
  "network_name": "",
  "network_region": "",
  "mcc": "",
  "mnc": "",
  "country_prefix": "",
  "country_code": "",
  "country_name": ""
}
}
}

```

2. Following is a response format for successful cases when none of the options are requested.

```

{
  "http_response_code": 200,
  "client_ref_num": "abcd_1234",
  "request_id": "99237811-8f32-42d9-8cc9-359fc181179b",
  "result_code": 101,
  "message": "Report Generated Successful",
  "result": {
    "customer_details": {
      },
    "is_valid": true,
    "subscriber_status": "CONNECTED",
    "connection_status": {
      "status_code": "DELIVERED",
    }
  }
}

```

```

    "error_code_id":""
  },
  "connection_type":"prepaid",
  "msisdn":{
    "msisdn_country_code":"IN",
    "msisdn":"+917501277797",
    "type":"MOBILE",
    "mnc":"06",
    "imsi":"404457501277797",
    "mcc":"404",
    "mcc_mnc":"40406"
  },
  "current_service_provider":{
    "network_prefix":"98450",
    "network_name":"Airtel",
    "network_region":"Karnataka",
    "mcc":"404",
    "mnc":"06",
    "country_prefix":"+91",
    "country_code":"IN",
    "country_name":"India"
  },
  "original_service_provider":{
    "network_prefix":"75012",
    "network_name":"Airtel",
    "network_region":"West Bengal",
    "mcc":"",
    "mnc":"",
    "country_prefix":"+91",
    "country_code":"IN",
    "country_name":"India"
  },
  "is_roaming":false,
  "roaming_service_provider":{
    "network_prefix":"",
    "network_name":"",
    "network_region":"",
    "mcc":"",
    "mnc":"",
    "country_prefix":"",
    "country_code":"",
    "country_name":""
  },
  "is_ported":true,
  "Last_ported_date":"",
  "porting_history":[ ],
  "mobile_vintage":{ }
}

```

3. Following is a response format for successful cases when Mobile Vintage **configuration is enabled**

```

{
  "http_response_code":200,
  "client_ref_num":"new_29JUL2024_2330",
  "request_id":"00779ee6-20db-490b-9c6c-f288800503cb",
  "result_code":101,
  "message":"Report Generated Successful",
  "result":{
    "customer_details":{
      "name":"Thanikonda Kavya",
      "alternate_number":""
    },
    "is_valid":true,
    "subscriber_status":"CONNECTED",
    "connection_status":{
      "status_code":"DELIVERED",
      "error_code_id":""
    },
    "connection_type":"prepaid",
    "msisdn":{
      "msisdn_country_code":"IN",
      "msisdn":"+919916820606",
      "type":"MOBILE",
      "mnc":"86",
      "imsi":"404860511708729",
      "mcc":"404",
      "mcc_mnc":"40486"
    },
    "current_service_provider":{
      "network_prefix":"99168",
      "network_name":"Vodafone",
      "network_region":"Karnataka",
      "mcc":"404",
      "mnc":"86",
      "country_prefix":"+91",
      "country_code":"IN",
      "country_name":"India"
    },
    "original_service_provider":{
      "network_prefix":"99168",
      "network_name":"Vodafone",
      "network_region":"Karnataka",
      "mcc":"404",
      "mnc":"86",
      "country_prefix":"+91",
      "country_code":"IN",
      "country_name":"India"
    },
    "is_ported":false,
    "last_ported_date":"",
    "porting_history":[

  ],
  "mobile_vintage":{
    "mobile_tenure":{
      "min":48,
      "max":null
    },
    "last_deactivated":{
      "min":1491,

```

```

    "max":1521
  }
}
}
}

```

Keys of Result Object are explained below:

Key	Value
customer_details	Customer details associated with the mobile number. Type: Object NOTE: This data is available only if the “options” contain the customer_details. Also, this data comes at an additional cost.
name	Name of Customer. If Name is not provided, then this field value would have the value NULL. Type: String
alternate_number	Alternate Contact Number of the Customer of Mobile Number. If the alternate contact number is not provided, then this field value would have the value NULL. Type: String
is_valid	Indicates whether the mobile number is valid or not. Type: Boolean
subscriber_status	The status of the subscriber, such as "CONNECTED". Type: String Possible Values: 'CONNECTED' / 'UNDETERMINED'
connection_status	Information about the connection status, including the status code and error code, if applicable. 'error_code_id' can be an empty string. Type: Object
connection_type	The type of connection, such as "prepaid". Type: String Possible Values: 'postpaid', 'prepaid'
msisdn	Details about the MSISDN (Mobile Station International Subscriber Directory Number), including the country code, type, and more. Type: Object
current_service_provider	Information about the current service provider, including the network_prefix, network_name, network_region, mcc, mnc, country_prefix, country_code, country_name.

	Type: Object of Type Service Provider. Please see the below for more details.
original_service_provider	Information about the original service provider, including network_prefix, network_name, network_region, mcc, mnc, country_prefix, country_code, country_name. Type: Object of Type Service Provider. Please see the below for more details.
is_roaming	Indicates whether the mobile number is currently roaming or not. Type: Boolean
roaming_service_provider	Information about the roaming service provider, including the network_prefix, network_name, network_region, mcc, mnc, country_prefix, country_code, country_name. Type: Object of Type Service Provider. Please see the below for more details.
is_ported	Indicates whether the mobile number has been ported or not. Type: Boolean
last_ported_date	The date when the number was last ported. Example: "2014-12-01T00:00:00". Explained in - Type: String Format: yyyy-MM-ddTHH:mm:ss NOTE: This data is available only if the “options” contain the “ported_date”. Also, this data comes at additional cost.
porting_history	An array containing the porting history of the mobile number. Each entry includes the porting_date, porting_action, ported_network, porting_number_type. Explained in - Type: Array of objects of type “porting_history”. Please see the below for more details. NOTE: This data is available only if the “options” contain the “porting_history”. Also, this data comes at additional cost.
mobile_vintage	Mobile vintage associated with the mobile number. Type: Object NOTE: This data is available only if the “options” contain the mobile_vintage. Also, this data comes at an additional cost.
- mobile_tenure	mobile_tenure refers to the total duration in months that the mobile number has been active. Type: Object
min	This indicates the minimum month when a mobile number got active

	Type: Integer
max	This indicates the maximum month when the mobile number got active Note- <i>If the mobile number is more than 4 years old it will show only the minimum value from when the mobile number is activated</i> Type: Integer
l-last_deactivated	" last_deactivated " refers to the total number of days from today since the mobile number was deactivated Type: object
min	This indicates the minimum number of days since the mobile number was deactivated, counted from today Type: Integer
max	This indicates the maximum number of days since the mobile number was deactivated, counted from today. Type: Integer

Keys of "**Service Provider**" Object are explained below:

Key	Value
network_prefix	The network prefix associated with the service provider. Type: String
network_name	The name of the service provider. Type: String
network_region	The region where the service provider operates. Type: String
mcc	The Mobile Country Code (MCC) associated with the service provider. Type: String
mnc	The Mobile Network Code (MNC) associated with the service provider. Type: String
country_prefix	The country prefix associated with the service provider. Type: String
country_code	The country code associated with the service provider. Type: String

country_name	The name of the country where the service provider operates. Type: String
--------------	---

Keys of "Porting_History" Object are explained below:

Key	Value
porting_date	The date of the porting activity. Example - "2016-12-24T00:00:00" Type: String Format: yyyy-MM-ddTHH:mm:ss
porting_action	The action performed during the porting activity, such as "Add" or other applicable actions. Type: String
ported_network	Information about the network to which the number was ported, including country_name, network_name, network_region, mcc, mnc Type: Object
porting_number_type	The type of number that was ported, such as "mobile". Type: String

3.3.2 Unsuccessful Validation Case

1. If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "abbdj123",
  "request_id": "ebf2a4e9-2633-46b4-a3f8-0a2c813c1cf1",
  "result_code": 102,
  "error": "Invalid Mobile Number."
}
```

3.4 API Error Response

In case of Error, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned. Few of the API Error cases are:

1. If the provided number is invalid. Example : "7501299ABC"

```
{
  "http_response_code": 400,
  "client_ref_num": "abbdj123",
  "request_id": "8263e534-755d-4fc1-8d6b-7c9a4ae2672a",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

```
}
```

4 Bank - UPI Validation - Basic

4.1 API Introduction

This API allows you to verify the existence of a Virtual Payment Address (VPA) and perform a name matching check. The API verifies if the provided VPA exists and, optionally, matches the provided name with the account holder's name associated with the VPA.

4.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/bank/v1/upi-basic
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
vpa	M	The Virtual Payment Address to be verified. Type: String
name	O	The name to be matched with the account holder's name. This parameter is optional, but if provided, it will be used for name matching. Type: String

4.3 API Success Response

4.3.1 Successful Validation (result_code 101) Case

When the VPA is found, the message key will contain "VPA Found", http_response_code as 200, and result_code of 101 will be returned.

1. Following is the response format when the request does not contain input name.

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "cda8f14b-7e4e-4a97-a3ec-76dc229ce0dd",
  "result_code": 101,
  "message": "VPA Found",
  "result": {
    "vpa_details": {
      "vpa": "7501277797@paytm",
      "account_holder_name": "Shubhendu Dalai"
    }
  }
}
```

2. Following is the response format when the request contains the input name.

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "e01c8f7a-1dc1-4dd7-9cf2-ce575a80c9c6",
  "result_code": 101,
  "message": "VPA Found",
  "result": {
    "vpa_details": {
      "vpa": "7501277797@paytm",
      "account_holder_name": "Shubhendu Dalai"
    },
    "name_match": true,
    "name_match_score": 90.0
  }
}
```

Keys of Result Object are explained below:

Key	Value
vpa_details	Additional data related to the VPA verification such as vpa, account_holder_name. Explained below - Type: Object
vpa	The Virtual Payment Address that was queried Type: String
account_holder_name	Account Holder name of the UPI Linked Bank Account.

	Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float

4.3.2 Unsuccessful Validation Case

1. If there is no record found for the given VPA, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "a0e1f216-de8d-4750-8762-05133eab3643",
  "result_code": 103,
  "message": "VPA Not Found"
}
```

4.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned. Few common examples are given below.

1. If the provided VPA is invalid. Example : "testpaytm"

```
{
  "http_response_code": 400,
  "client_ref_num": "ref1234",
  "request_id": "95c3d669-bd8a-4654-bc94-7978022f98a3",
  "error": "UPI-ID (Virtual Payment Address) is not in valid format. Please try with valid UPI-ID"
}
```

5 Bank - UPI Validation - Advanced

5.1 API Introduction

This API allows you to perform an advanced verification of the existence of a Virtual Payment Address (VPA) and provides additional details. The API verifies if the provided VPA exists, returns the associated account holder's name and account details.

5.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/bank/v1/upi-advanced
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
vpa	M	The Virtual Payment Address to be verified. Type: String

5.3 API Success Response

5.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when there is a record found

```

{
  "http_response_code": 200,
  "client_ref_num": "en",
  "request_id": "a81c00cf-e857-40d9-842d-62184a327b01",
  "result_code": 101,
  "message": "VPA Found",
  "result": {
    "vpa_details": {
      "vpa": "suklasXX@ybl",
      "account_holder_name": "Ms SUKLAXX"
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "IDIB00XXXX"
    }
  }
}

```

Keys of Result Object are explained below

Key	Value
message	A message describing the result of the VPA verification. Type: String
vpa_details	Additional data related to the VPA verification such as vpa, account_holder_name. Explained below - Type: Object
vpa	The Virtual Payment Address that was queried Type: String
account_holder_name	Account Holder name of the UPI Linked Bank Account. Type: String
account_details	This section contains information about the bank account associated with the provided VPA. Type: Object
account_type	The type of the bank account, which is specified as "CURRENT". Type: String Possible Values: "CURRENT" or "SAVINGS"
account_ifsc	The IFSC of the bank where the account is held. Type: String

5.3.2 Unsuccessful Validation Case

1. If no record is found for the given VPA, then the below response will be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "f440112a-7740-4ffd-8d83-d6f61604dc08",
  "result_code": 103,
  "message": "VPA Not Found"
}
```

5.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided VPA is invalid. Example: "testpaytm"

```
{
  "http_response_code": 400,
  "client_ref_num": "ref1234",
  "request_id": "95c3d669-bd8a-4654-bc94-7978022f98a3",
  "error": "UPI-ID (Virtual Payment Address) is not in valid format. Please try with valid UPI-ID"
}
```

6 Bank - UPI Validation -Enhanced(Deprecated)

6.1 API Introduction

This API allows you to perform an advanced verification of the existence of a Virtual Payment Address (VPA) and provides additional details. The API verifies if the provided VPA exists, returns the associated account holder's name, merchant details, and account details.

6.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/bank/v1/upi-enhanced
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
vpa	M	The Virtual Payment Address to be verified. Type: String
name	O	The name to be matched with the account holder's name. This parameter is optional, but if provided, it will be used for name matching. Type: String

6.3 API Success Response

6.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name and if it belongs to an Individual

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "8a7e378d-e0d0-4eab-a1db-8b40f07f3502",
  "result_code": 101,
  "message": "VPA Found",
  "result": {
    "vpa_details": {
      "vpa": "7501277797@paytm",
      "account_holder_name": "Shubhendu Dalai",
      "entity_type": "Individual"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "PYTM0123456"
    }
  }
}
```


2. Following is the response format when the request does not contain input name and if it belongs to a Merchant

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "7c87151e-f3e7-4c01-b00b-acc7a0aa4691",
  "result_code": 101,
  "message": "VPA Found",
  "result": {
    "vpa_details": {
      "vpa": "q799338XXX@ybl",
      "account_holder_name": "XXXXXXXXXX",
      "entity_type": "Merchant"
    },
    "merchant_details": {
      "merchant_category": "RESTAURANTS OR EATING PLACES",
      "merchant_legal_name": "XXXXXXXXX",
      "merchant_size": "SMALL",
      "merchant_form": "PROPRIETARY",
      "merchant_type": "OFFLINE"
    },
    "account_details": {
      "account_type": "CURRENT",
      "account_ifsc": "YESB0YBLUPI"
    }
  }
}
```

3. Following is the response format when the request contains input name

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "1ea353ea-bd4a-4906-a421-3075732956c1",
  "result_code": 101,
  "message": "VPA Found",
  "result": {
    "vpa_details": {
      "vpa": "7501277797@paytm",
      "account_holder_name": "Shubhendu Dalai",
      "entity_type": "Individual"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "PYTM0123456"
    },
    "name_match": false,
    "name_match_score": 20.0
  }
}
```

```
}
}
```

Keys of Result Object are explained below

Key	Value
message	A message describing the result of the VPA verification. Type: String
vpa_details	Additional data related to the VPA verification such as vpa, account_holder_name. Explained below - Type: Object
-vpa	The Virtual Payment Address that was queried Type: String
-account_holder_name	Account Holder name of the UPI Linked Bank Account. Type: String
-entity_type	Indicates the type of entity associated with the VPA. Type: String Possible Values: "Merchant" or "Individual"
merchant_details	Indicates whether the provided name matches the account holder's name.Explained below - Type: Object
-merchant_category	The category of the merchant. Example - "RESTAURANTS OR EATING PLACES". Type: String
-merchant_legal_name	The legal name of the merchant. Type: String
-merchant_size	The size classification of the merchant. Example - 'SMALL' Type: String
-merchant_form	The form of the merchant. Example - 'PROPRIETARY' Type: String
-merchant_type	The type of the merchant. Example - "OFFLINE" Type: String

account_details	This section contains information about the bank account associated with the provided VPA. Explained below - Type: Object
account_type	The type of the bank account, which is specified as "CURRENT". Type: String Possible Values: "CURRENT" or "SAVINGS"
account_ifsc	The IFSC of the bank where the account is held. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float

6.3.2 Unsuccessful Validation Case

- If no record is found for the given VPA, then the below response will be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "f440112a-7740-4ffd-8d83-d6f61604dc08",
  "result_code": 103,
  "message": "VPA Not Found"
}
```

6.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

- If the provided VPA is invalid. Example: "testpaytm"

```
{
  "http_response_code": 400,
```

```
"client_ref_num": "ref1234",
"request_id": "95c3d669-bd8a-4654-bc94-7978022f98a3",
"error": "UPI-ID (Virtual Payment Address) is not in valid format. Please try with
valid UPI-ID"
}
```

7 Mobile to Name Lookup

7.1 API Introduction

This API allows you to obtain the linked name associated with a mobile number from various authentic sources. It is useful for verifying and retrieving the name registered to a given mobile number. This API is useful for applications that require user verification or customer information retrieval.

In addition, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

7.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-name-lookup
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name.

		Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

7.3 API Success Response

7.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name

```
{
  "http_response_code": 200,
  "client_ref_num": "req_12343",
  "request_id": "0fd4e8f4-9cf5-4809-9d3f-c9cfbba8b6bf",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Subhendu Dalai"
  }
}
```

2. Following is the response format when the request contains input name

```
{
  "http_response_code": 200,
  "client_ref_num": "req_12344",
  "request_id": "c2837129-bc1a-4c26-bb06-40ddb90ae256",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Subhendu Dalai",
    "name_match": true,
    "name_match_score": 100.0
  }
}
```

Keys of Result Object are explained below:

Key	Value
mobile_linked_name	The linked name associated with the provided mobile number. Type: String

name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float

7.3.2 Unsuccessful Validation Case

If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "req_12344",
  "request_id": "9696ed25-021d-4280-8bb8-4ff10299be00",
  "result_code": 103,
  "message": "No linked name found"
}
```

7.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

8 Mobile to UPI Lookup - Basic

8.1 API Introduction

This API allows you to obtain the linked name and VPA associated with a mobile number from various authentic sources. It is useful for verifying and retrieving the VPA and name registered to a given mobile number. This API is useful for applications that require user verification or customer information retrieval.

In addition, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

8.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-upi-lookup
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name. Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

8.3 API Success Response

8.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name

```
{
  "http_response_code": 200,
  "client_ref_num": "test123143123",
  "request_id": "ddb59384-9545-46ab-9f9d-bf3d9702eef1",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Shuxxxx",
    "vpa": "75012XXXXX@paytm"
  }
}
```

2. Following is the response format when the request contains input name

```
{
  "http_response_code": 200,
  "client_ref_num": "test123143123",
  "request_id": "0e4d2c91-d69d-4366-a88d-6dd467def6f8",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Shuxxxx",
    "vpa": "75012XXXXX@paytm",
    "name_match": true,
    "name_match_score": 97.0
  }
}
```

Keys of Result Object are explained below:

Key	Value
vpa	The Virtual Payment Address associated with the provided mobile number. Type: String
mobile_linked_name	The linked name associated with the provided mobile number. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.

name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float
partial_failure	Indicates whether the output is complete. Partial failure occurs when not all VPAs can be found due to a source being down. Type: Boolean true - Indicates all the VPAs couldn't be found false - Indicates all the VPAs are present

8.3.2 Unsuccessful Validation Case

1. If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-t1fky",
  "request_id": "b80c0014-7d9f-4c47-915f-324f272b31d7",
  "result_code": 103,
  "message": "VPA Not Found",
  "partial_failure": false
}
```

8.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

9 Mobile to UPI Lookup - Advanced

9.1 API Introduction

This API allows you to obtain the linked name, VPA, and account IFSC Code associated with a mobile number from various authentic sources. It is useful for verifying and retrieving the VPA, name, and IFSC Code registered to a given mobile number. This API is useful for applications that require user verification or customer information retrieval.

In addition, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

9.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-upi-lookup-advanced
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name. Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

9.3 API Success Response

9.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name and VPA is active

```
{
  "http_response_code": 200,
  "client_ref_num": "ref_123",
  "request_id": "d8b5bc75-4c32-4f96-996d-00a8a32dbbf6",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Shubxxxxxx",
    "vpa": "750XXXXXXXX@paytm",
    "account_ifsc": "PYTXXXXXX",
    "vpa_status": "active"
  }
}
```

2. Following is the response format when the request contains input name and VPA is active

```
{
  "http_response_code": 200,
  "client_ref_num": "test123143123",
  "request_id": "9ab51dda-fb99-4aaa-9760-591f8d7cedd3",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Shubxxx",
    "vpa": "75012XXXXX@paytm",
    "account_ifsc": "PYTM0123456",
    "vpa_status": "active",
    "name_match": true,
    "name_match_score": 97.0
  }
}
```

3. Following is the response format when the request does not contain input name and VPA is inactive

```
{
  "http_response_code": 200,
  "client_ref_num": "ref_123",
  "request_id": "1768b724-d643-4574-b818-8ebe1dfa8f95",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Subxxxxx",
    "vpa": "suvxxxx@okhdfcbank",
    "account_ifsc": "",
    "vpa_status": "inactive"
  }
}
```

4. Following is the response format when the request contains input name and VPA is inactive

```

{
  "http_response_code": 200,
  "client_ref_num": "ref_123",
  "request_id": "d7180fdf-e5fb-46ba-801c-9134464af93c",
  "result_code": 101,
  "result": {
    "mobile_linked_name": "Subxxxxx",
    "vpa": "suvxxxxx@okhdfcbank",
    "account_ifsc": "",
    "vpa_status": "inactive",
    "name_match": true,
    "name_match_score": 100.0
  }
}

```

Keys of Result Object are explained below:

Key	Value
vpa	The Virtual Payment Address associated with the provided mobile number. Type: String
mobile_linked_name	The linked name associated with the provided mobile number. Type: String
account_ifsc	The IFSC Code linked to the VPA associated with the provided mobile number. Type: String
vpa_status	Indicates the current status of the VPA, whether it is 'active' or 'inactive'. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float
partial_failure	Indicates whether the output is complete. Partial failure occurs when not all VPAs can be found due to a source being down.

	Type: Boolean true - Indicates all the VPAs couldn't be found false - Indicates all the VPAs are present
--	---

9.3.2 Unsuccessful Validation Case

1. If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-7iyzl",
  "request_id": "81a915d9-e803-482a-aa46-141f4cc509f8",
  "result_code": 103,
  "message": "No linked name found",
  "partial_failure": false
}
```

9.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

10 Mobile to UPI Lookup - Enhanced

10.1 API Introduction

This API allows you to obtain the linked name, VPA details, merchant details, and account details associated with a mobile number from various authentic sources. It is useful for verifying and retrieving the VPA, account holder name, account type, and merchant details registered to a given mobile number. This API is useful for applications that require user verification or customer information retrieval.

In addition, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

10.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-upi-lookup-enhanced

- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name. Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

10.3 API Success Response

10.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name and if it belongs to an Individual

```
{
  "http_response_code": 200,
  "client_ref_num": "ref_123",
  "request_id": "5f5bc99f-5e91-4d4b-a336-8ff3707c9540",
  "result_code": 101,
  "result": {
    "vpa_details": {
```

```

    "vpa": "955370XXXX@ybl",
    "vpa_status": "active",
    "account_holder_name": "CHEMBXXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "KKBK000XXXX"
  },
  "mcc_code": "0000"
},
"message": "VPA Found"
}

```

2. Following is the response format when the request does not contain input name and if it belongs to a Merchant

```

{
  "http_response_code": 200,
  "client_ref_num": "ref1234",
  "request_id": "aa0f117d-c2fb-4cd0-9432-a8dd7b17abb1",
  "result_code": 101,
  "result": {
    "vpa_details": {
      "vpa": "814099XXXX@okbizaxis",
      "vpa_status": "active",
      "account_holder_name": "Jay Jalaxxx Center",
      "entity_type": "MERCHANT"
    },
    "merchant_details": {
      "merchant_category": "RESTAURANTS OR EATING PLACES",
      "merchant_legal_name": "Axis",
      "merchant_size": "SMALL",
      "merchant_form": "PROPRIETARY",
      "merchant_type": "OFFLINE"
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "UTIB000XXXX"
    },
    "mcc_code": "5812"
  },
  "message": "VPA Found"
}

```

3. Following is the response format when the request contains input name

```

{
  "http_response_code": 200,
  "client_ref_num": "ref_123",
  "request_id": "d2b35c29-b770-43d5-8b86-033ef187fad4",
  "result_code": 101,
  "result": {
    "vpa_details": {
      "vpa": "955370XXXX@ybl",
      "vpa_status": "active",
      "account_holder_name": "CHEMXXXX",
      "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "KKBK000XXXX"
    },
    "mcc_code": "0000",
    "name_match": false,
    "name_match_score": 20.0
  },
  "message": "VPA Found"
}

```

Keys of Result Object are explained below:

Key	Value
vpa_details	Additional data related to the VPA verification such as vpa, account_holder_name. Explained below - Type: Object
vpa	The Virtual Payment Address associated with the provided mobile number. Type: String
account_holder_name	The linked name associated with the provided mobile number. Type: String
entity_type	Indicates the type of entity associated with the VPA. Type: String Possible Values: "Merchant" or "Individual"
merchant_details	Indicates whether the provided name matches the account holder's name.Explained below - Type: Object

merchant_category	The category of the merchant. Example - "RESTAURANTS OR EATING PLACES". Type: String
merchant_legal_name	The legal name of the merchant. Type: String
merchant_size	The size classification of the merchant. Example - 'SMALL' Type: String
merchant_form	The form of the merchant. Example - 'PROPRIETARY' Type: String
merchant_type	The type of the merchant. Example - "OFFLINE" Type: String
account_details	This section contains information about the bank account associated with the provided VPA. Explained below - Type: Object
account_type	The type of the bank account, which is specified as "CURRENT". Type: String Possible Values: "CURRENT" or "SAVINGS"
account_ifsc	The IFSC of the bank where the account is held. Type: String
mcc_code	A Merchant Category Code (MCC) is a four-digit number listed in ISO 18245 for retail financial services. An MCC is used to classify a business by the types of goods or services it provides. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float

vpa_status	Indicates the current status of the VPA, whether it is 'active' or 'inactive'. Type: String
partial_failure	Indicates whether the output is complete. Partial failure occurs when not all VPAs can be found due to a source being down. Type: Boolean true - Indicates all the VPAs couldn't be found false - Indicates all the VPAs are present

9.3.2 Unsuccessful Validation Case

1. If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-pyk5w",
  "request_id": "97a11251-0fdf-4642-8cc8-6771b3440225",
  "result_code": 103,
  "message": "VPA Not Found",
  "partial_failure": false
}
```

10.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

11 Mobile to Multiple UPI Lookup - Basic- (Deprecated)

11.1 API Introduction

This API expands upon the capabilities of the [Mobile to UPI Lookup - Basic](#) service, allowing you to retrieve all the VPAs and linked names associated with the mobile number. It serves as a valuable tool for applications that require batch verification or bulk retrieval of customer information.

Similar to its counterpart, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

11.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-multiple-upi-lookup-basic
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name. Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

11.3 API Success Response

11.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-b5r2o",
  "request_id": "19c726ff-ee40-42db-bfa6-1e41d3c63081",
  "result_code": 101,
  "partial_failure": false,
  "result": {
    "vpa_found_count": 3,
    "vpa": [
      {
        "vpa": "8877XXXXXX@ybl",
        "primary_vpa": false,
        "mobile_linked_name": "SukrXXX"
      },
      {
        "vpa": "8877XXXXXX@paytm",
        "primary_vpa": false,
        "mobile_linked_name": "SukXXX"
      },
      {
        "vpa": "sukritiXX@okaxis",
        "primary_vpa": true,
        "mobile_linked_name": "SukXXXi"
      }
    ]
  }
}
```

2. Following is the response format when the request contains input name

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-b5r2o",
  "request_id": "9ec524ad-c230-4337-b6aa-34e41110eaca",
  "result_code": 101,
  "partial_failure": false,
  "result": {
    "vpa_found_count": 3,
    "vpa": [
      {
        "vpa": "8877XXXXXX@ybl",
        "primary_vpa": false,
        "mobile_linked_name": "SukXXXi",
        "name_match": true,
        "name_match_score": 80
      },
      {
        "vpa": "8877XXXXXX@paytm",
        "primary_vpa": false,
        "mobile_linked_name": "SukXXX",
        "name_match": true,
        "name_match_score": 80
      }
    ]
  }
}
```

```
{
  "vpa": "sukritiXX@okaxis",
  "primary_vpa": true,
  "mobile_linked_name": "SukXXX",
  "name_match": true,
  "name_match_score": 80
}
```

Keys of Result Object are explained below:

Key	Value
vpa	The Virtual Payment Address associated with the provided mobile number. Type: String
mobile_linked_name	The linked name associated with the provided mobile number. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float
partial_failure	Indicates whether the output is complete. Partial failure occurs when not all VPAs can be found due to a source being down. Type: Boolean true - Indicates all the VPAs couldn't be found false - Indicates all the VPAs are present
primary_vpa	Indicates whether the VPA is the primary one. The primary VPA is the main address a user designates as their default for transactions. It is primarily used for receiving payments and sending payments. Type: Boolean true - Indicates the VPA is a primary VPA false - Indicates the VPA is not a primary VPA

11.3.2 Unsuccessful Validation Case

If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "ref_123",
  "request_id": "7aff0ded-3c28-4280-b1f4-ce3ad0e727ab",
  "result_code": 103,
  "message": "VPA Not Found"
}
```

11.4 API Failure Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

12 Mobile to Multiple UPI Lookup - Advanced-(Deprecated)

12.1 API Introduction

This API expands upon the capabilities of the [Mobile to UPI Lookup - Advanced](#) service, allows you to obtain the linked name, VPA, and account IFSC Code associated with a mobile number from various authentic sources. It is useful for verifying and retrieving the VPA, name, and IFSC Code registered to a given mobile number. This API is useful for applications that require user verification or customer information retrieval.

In addition, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

12.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-multiple-upi-lookup-advanced
- **Header:**

Key	Mandatory/Optional (M/O)	Value
-----	--------------------------	-------

content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name. Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

12.3 API Success Response

12.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101

1. Following is the response format when the request does not contain input name

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-eo2qx",
  "request_id": "961920be-9a43-4a27-bdad-0136d41e49f2",
  "result_code": 101,
  "partial_failure": false,
  "result": {
    "vpa_found_count": 3,
    "vpa": [
      {
        "vpa": "88773XXXXX@ybl",
        "primary_vpa": false,
        "vpa_status": "active",
        "mobile_linked_name": "SUKXX",

```

```

    "account_ifsc": "CNRBXXX"
  },
  {
    "vpa": "8877XXXX@paytm",
    "primary_vpa": false,
    "vpa_status": "active",
    "mobile_linked_name": "SukXX",
    "account_ifsc": "CNRBXXX"
  },
  {
    "vpa": "sukritiXX@okaxis",
    "primary_vpa": true,
    "vpa_status": "active",
    "mobile_linked_name": "SUKXX",
    "account_ifsc": "CNRBXXX"
  }
]
}
}

```

2. Following is the response format when request contains input name

```

{
  "http_response_code": 200,
  "client_ref_num": "testapis-eo2qx",
  "request_id": "ffa0a362-a3eb-40ab-ba44-a61e848459d7",
  "result_code": 101,
  "partial_failure": false,
  "result": {
    "vpa_found_count": 3,
    "vpa": [
      {
        "vpa": "8877XXX@ybl",
        "primary_vpa": false,
        "vpa_status": "active",
        "mobile_linked_name": "SUKXX",
        "account_ifsc": "CNRBXX",
        "name_match": true,
        "name_match_score": 80
      },
      {
        "vpa": "8877XXX@paytm",
        "primary_vpa": false,
        "vpa_status": "active",
        "mobile_linked_name": "SukXX",
        "account_ifsc": "CNRBXX",
        "name_match": true,
        "name_match_score": 80
      },
      {
        "vpa": "sukXXX@okaxis",

```



```

    "primary_vpa": true,
    "vpa_status": "active",
    "mobile_linked_name": "SUKXXX",
    "account_ifsc": "CNRBXXX",
    "name_match": true,
    "name_match_score": 80
  }
]
}
}

```

Keys of Result Object are explained below:

Key	Value
vpa	The Virtual Payment Address associated with the provided mobile number. Type: String
mobile_linked_name	The linked name associated with the provided mobile number. Type: String
account_ifsc	The IFSC Code linked to the VPA associated with the provided mobile number. Type: String
vpa_status	Indicates the current status of the VPA, whether it is 'active' or 'inactive'. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float
partial_failure	Indicates whether the output is complete. Partial failure occurs when not all VPAs can be found due to a source being down. Type: Boolean

	true - Indicates all the VPAs couldn't be found false - Indicates all the VPAs are present
primary_vpa	Indicates whether the VPA is the primary one. The primary VPA is the main address a user designates as their default for transactions. It is primarily used for receiving payments and sending payments. Type: Boolean true - Indicates the VPA is a primary VPA false - Indicates the VPA is not a primary VPA

12.3.2 Unsuccessful Validation Case

1. If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-gx6es",
  "request_id": "8267385c-3a56-43d4-b6a6-2ff13b0967f8",
  "result_code": 103,
  "message": "VPA Not Found",
  "partial_failure": false
}
```

12.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

13 Mobile to Multiple UPI Lookup - Enhanced (Deprecated)

13.1 API Introduction

This API expands upon the capabilities of the [Mobile to UPI Lookup - Enhanced](#) service, allows you to obtain the linked name, VPA details, merchant details, and account details associated with a mobile number from various authentic sources. It is useful for verifying and retrieving the VPA, account holder name, account type, and merchant details registered to a

given mobile number. This API is useful for applications that require user verification or customer information retrieval.

In addition, this API validates the provided name against the input and provides a matching score, enhancing the verification process.

13.2 API Request

- **Method:** POST
- **Endpoint:** {{baseurl}}/misc/v1/mobile-multiple-upi-lookup-enhanced
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	JSON/application
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side. Type: String Max Length: 50
mobile	M	The mobile number to retrieve the linked name. Type: String
name	O	To check if the provided name matches the registered name, along with the name matching score. Type: String Max_length: 100

13.3 API Success Response

13.3.1 Successful Validation (result_code 101) Case

When the data is found, the API gives the http_response_code as 200 and result_code as 101.

1. Following is the response format when the request does not contain input name and if it belongs to an Individual

```
{
  "vpa": "750127XXXX@apl",
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "SUBXXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "DBSS0IN0811"
  },
  "mcc_code": "0000"
},
{
  "vpa": "750127XXXX@upi",
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "SUBXXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "HDFC0001226"
  },
  "mcc_code": "0000"
}
]
```

2. Following is the response format when the request does not contain input name and if it belongs to a Merchant

```
{
  "http_response_code": 200,
  "client_ref_num": "ref1289",
  "request_id": "caeaacc6-50c9-4be6-8879-6810943bb1b0",
  "result_code": 101,
  "partial_failure": true,
  "result": {
    "vpa_found_count": 8,
    "vpa": [
```

```

{
  "vpa": "81099XX@upi",
  "primary_vpa": false,
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "MOXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "PUNXXX"
  },
  "mcc_code": "0000",
  "name_match": false,
  "name_match_score": 20.0
},
{
  "vpa": "8109XX@ibl",
  "primary_vpa": false,
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "MOXXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "KKBXXX"
  },
  "mcc_code": "0000",
  "name_match": false,
  "name_match_score": 20.0
},
{
  "vpa": "8109XXX@airtel",
  "primary_vpa": false,
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "MOXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",

```

```

    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "SBIXX"
  },
  "mcc_code": "0000",
  "name_match": false,
  "name_match_score": 20.0
},
{
  "vpa": "810XXX@amazonpay",
  "primary_vpa": false,
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "RiXXX",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "PPIXXX"
  },
  "mcc_code": "0000",
  "name_match": false,
  "name_match_score": 20.0
},
{
  "vpa": "8109XXX@idfcfirst",
  "primary_vpa": false,
  "vpa_status": "active",
  "vpa_details": {
    "account_holder_name": "Mr. X",
    "entity_type": "INDIVIDUAL"
  },
  "merchant_details": {
    "merchant_category": "",
    "merchant_legal_name": "",
    "merchant_size": "",
    "merchant_form": "",
    "merchant_type": ""
  },
  "account_details": {
    "account_type": "SAVINGS",
    "account_ifsc": "IDFBXX"
  },
  "mcc_code": "0000",
  "name_match": false,
  "name_match_score": 20.0
},
{
  "vpa": "8109XX@sbi",
  "primary_vpa": false,

```

```

    "vpa_status": "active",
    "vpa_details": {
      "account_holder_name": "Mr X",
      "entity_type": "MERCHANT"
    },
    "merchant_details": {
      "merchant_category": "P2PM CHANGES",
      "merchant_legal_name": "Mr. X ",
      "merchant_size": "SMALL",
      "merchant_form": "OTHERS",
      "merchant_type": "OTHERS"
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "SBIXX"
    },
    "mcc_code": "7407",
    "name_match": false,
    "name_match_score": 20.0
  },
  {
    "vpa": "81XX@yapl",
    "primary_vpa": false,
    "vpa_status": "active",
    "vpa_details": {
      "account_holder_name": "MXX",
      "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "KKBX"
    },
    "mcc_code": "0000",
    "name_match": false,
    "name_match_score": 20.0
  },
  {
    "vpa": "moX@okaxis",
    "primary_vpa": true,
    "vpa_status": "active",
    "vpa_details": {
      "account_holder_name": "MX",
      "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {

```

```

        "account_type": "SAVINGS",
        "account_ifsc": "INDB0000011"
    },
    "mcc_code": "0000",
    "name_match": false,
    "name_match_score": 20.0
}
]
}
}

```

3. Following is the response format when the request contains input name

```

{
  "http_response_code": 200,
  "client_ref_num": "ref1289",
  "request_id": "304b75c7-d241-4bc9-a512-03d81adbf756",
  "result_code": 101,
  "partial_failure": true,
  "result": {
    "vpa_found_count": 7,
    "vpa": [
      {
        "vpa": "7501XX@apl",
        "primary_vpa": false,
        "vpa_status": "active",
        "vpa_details": {
          "account_holder_name": "SUBXX",
          "entity_type": "INDIVIDUAL"
        },
        "merchant_details": {
          "merchant_category": "",
          "merchant_legal_name": "",
          "merchant_size": "",
          "merchant_form": "",
          "merchant_type": ""
        },
        "account_details": {
          "account_type": "SAVINGS",
          "account_ifsc": "DBXX"
        },
        "mcc_code": "0000",
        "name_match": true,
        "name_match_score": 80.0
      },
      {
        "vpa": "750XX@upi",
        "primary_vpa": false,
        "vpa_status": "active",
        "vpa_details": {
          "account_holder_name": "SUBXX",
          "entity_type": "INDIVIDUAL"
        },
        "merchant_details": {
          "merchant_category": "",
          "merchant_legal_name": "",

```



```

        "merchant_size": "",
        "merchant_form": "",
        "merchant_type": ""
    },
    "account_details": {
        "account_type": "SAVINGS",
        "account_ifsc": "HDFXXX"
    },
    "mcc_code": "0000",
    "name_match": true,
    "name_match_score": 80.0
},
{
    "vpa": "750XXXX@amazonpay",
    "primary_vpa": false,
    "vpa_status": "active",
    "vpa_details": {
        "account_holder_name": "SubXXXX",
        "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
        "merchant_category": "",
        "merchant_legal_name": "",
        "merchant_size": "",
        "merchant_form": "",
        "merchant_type": ""
    },
    "account_details": {
        "account_type": "SAVINGS",
        "account_ifsc": "PPIXXX"
    },
    "mcc_code": "0000",
    "name_match": true,
    "name_match_score": 80.0
},
{
    "vpa": "750XXXX@axisb",
    "primary_vpa": false,
    "vpa_status": "active",
    "vpa_details": {
        "account_holder_name": "SUBXXXX",
        "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
        "merchant_category": "",
        "merchant_legal_name": "",
        "merchant_size": "",
        "merchant_form": "",
        "merchant_type": ""
    },
    "account_details": {
        "account_type": "SAVINGS",
        "account_ifsc": "DBSXXXX"
    },
    "mcc_code": "0000",
    "name_match": true,
    "name_match_score": 80.0
},
{

```

```

    "vpa": "750XXX@hdfcbank",
    "primary_vpa": false,
    "vpa_status": "active",
    "vpa_details": {
      "account_holder_name": "SUBXXX",
      "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "HDFXXX"
    },
    "mcc_code": "0000",
    "name_match": true,
    "name_match_score": 80.0
  },
  {
    "vpa": "7501XXXX@idfcfirst",
    "primary_vpa": false,
    "vpa_status": "active",
    "vpa_details": {
      "account_holder_name": "Mr. SubhXXX",
      "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "IDFBXXX"
    },
    "mcc_code": "0000",
    "name_match": true,
    "name_match_score": 80.0
  },
  {
    "vpa": "suXX-2@okaxis",
    "primary_vpa": true,
    "vpa_status": "active",
    "vpa_details": {
      "account_holder_name": "SUBHXXX",
      "entity_type": "INDIVIDUAL"
    },
    "merchant_details": {
      "merchant_category": "",
      "merchant_legal_name": "",
      "merchant_size": "",
      "merchant_form": "",
      "merchant_type": ""
    }
  }

```

```

    },
    "account_details": {
      "account_type": "SAVINGS",
      "account_ifsc": "DBSSXXX"
    },
    "mcc_code": "0000",
    "name_match": true,
    "name_match_score": 80.0
  }
}
]
}
}

```

Keys of Result Object are explained below:

Key	Value
vpa_details	Additional data related to the VPA verification such as vpa, account_holder_name. Explained below - Type: Object
vpa	The Virtual Payment Address associated with the provided mobile number. Type: String
vpa_status	Indicates the current status of the VPA, whether it is 'active' or 'inactive'. Type: String
account_holder_name	The linked name associated with the provided mobile number. Type: String
entity_type	Indicates the type of entity associated with the VPA. Type: String Possible Values: "Merchant" or "Individual"
merchant_details	Indicates whether the provided name matches the account holder's name.Explained below - Type: Object
merchant_category	The category of the merchant. Example - "RESTAURANTS OR EATING PLACES". Type: String
merchant_legal_name	The legal name of the merchant. Type: String
merchant_size	The size classification of the merchant. Example - 'SMALL' Type: String

merchant_form	The form of the merchant. Example - 'PROPRIETARY' Type: String
merchant_type	The type of the merchant. Example - "OFFLINE" Type: String
account_details	This section contains information about the bank account associated with the provided VPA. Explained below - Type: Object
account_type	The type of the bank account, which is specified as "CURRENT". Type: String Possible Values: "CURRENT" or "SAVINGS"
account_ifsc	The IFSC of the bank where the account is held. Type: String
mcc_code	A Merchant Category Code (MCC) is a four-digit number listed in ISO 18245 for retail financial services. An MCC is used to classify a business by the types of goods or services it provides. Type: String
name_match	Indicates whether the provided name matches the account holder's name. Type: Boolean true - Indicates the name is matched false - Indicates the name is not matched Currently, name_match_score >=75 is used to determine the name_match true/false status. The name_match_score threshold would be adjusted in the future based on performance.
name_match_score	A score indicating the match strength between the provided name and the account holder's name. Type: Float
partial_failure	Indicates whether the output is complete. Partial failure occurs when not all VPAs can be found due to a source being down. Type: Boolean true - Indicates all the VPAs couldn't be found false - Indicates all the VPAs are present
primary_vpa	Indicates whether the VPA is the primary one. The primary VPA is the main address a user designates as their default for transactions. It is primarily used for receiving payments and sending payments. Type: Boolean

	true - Indicates the VPA is a primary VPA false - Indicates the VPA is not a primary VPA
--	---

13.3.2 Unsuccessful Validation Case

1. If there is no record found for the given mobile number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "testapis-vm1ex",
  "request_id": "1c0a3d45-a228-4192-928a-73a87dce8b9a",
  "result_code": 103,
  "message": "VPA Not Found",
  "partial_failure": false
}
```

13.4 API Error Response

In case of Failure, the response as explained in the [Section 2.5](#) and error messages as defined in the [Section 2.5.1 Error Messages](#) would be returned.

1. If the provided number is invalid. Example: "777ABCD444"

```
{
  "http_response_code": 400,
  "client_ref_num": "req_1344",
  "request_id": "6ef5164a-fd9a-403f-8960-71a4c736f739",
  "error": "One or more parameters is wrong or missing, Invalid mobile number"
}
```

----- End of Document -----