

Digitap.ai - Mobile to Prefill

API Doc

(Version 1.4, 17th April, 2026)

A jumpstart guide to boosting your Business

Save Time, Save Cost

Table of Contents

1.1 Introduction	3
1.2 Authentication	3
1.3 API URLs	3
1.4 Request API Input & Response Format	3
1.4.1 API Request	3
1.4.2 API Response	5
1.4.2.1 Successful response (result_code 101) Case	5
1.4.2.2 Successful response (result_code 102) Case - Record Not found	8
1.4.2.3 Successful response (result_code 103) Case - Name not found against mobile no	8
1.4.2.4 Failure response Case - Validation Error Cases	8
1.5 Error Messages	9
1.6 API Encryption	10
1.7 Additional Notes	13

1 API Documentation

1.1 Introduction

This document is intended for our enterprise partners who can easily integrate the services they have chosen with Digitap.ai. Using this document they can jumpstart their business processes and start using the Digitap.ai services as early as possible and also align their own business processes seamlessly by integrating and making changes to their backend. The **Mobile to Prefill API** is designed to fetch enriched user details based on a given mobile number. This API enhances customer verification and data enrichment by retrieving key attributes such as name, date of birth, gender, PAN, email, address, and score.

1.2 Authentication

To use the API, one needs to register with Digitap and get a client id & client secret key. The client ID & secret key are different for the UAT & production environment.

1.3 API URLs

Following is the **base URL** for UAT & production Environment.

Production Env	https://svc.digitap.ai/mobile_prefill/request
UAT/DEMO Env	https://svcdemo.digitap.work/mobile_prefill/request

1.4 Request API Input & Response Format

1.4.1 API Request

- **Endpoint:** <base_url>/mobile_prefill/request
- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- Request Body:

Key	Mandatory/Optional / Conditional Mandatory (M/O/CM)	Value
client_ref_num	M	Unique ID for this request from the Client side [<i>Max of 45 chars</i>] Regex <code>r'^[a-zA-Z0-9_-]*\$'</code>
mobile_no	M	String 10 numerical digits: Regex <code>r'(?:\+91\s?[0]?[6-9]\d{9})\$'</code>
name_lookup	M	Integer 1 - Utilize Name Lookup service 0 - Name Lookup service not needed Note – Name look-up is a service provided by Digitap which fetches name basis input mobile number
first_name	CM	String John Note - Do not pass this key if name look-up service is already enabled / name_lookup key value passed as 1
last_name	CM	String Doe Note - Do not pass this key if name look-up service is already enabled / name_lookup key value passed as 1
name_fallback	CM	Integer 1 - An additional flow with Name Lookup will be triggered if no record is found using the given name. 0 - Only the provided first_name and last_name will be considered.

		Note - name_fallback needs to be passed only if the name_lookup is passed as 0. If the key is not passed, the default value of name_fallback is considered as 0.
options	O	List Options: "alternate_mobile_numbers", "alternate_emails", "official_documents", "additional_details" Any of the additional options from above can be enabled at client ID level. Please discuss with your RM for details.

1.4.2 API Response

1.4.2.1 Successful response (result_code 101) Case

```
{
  "http_response_code": 200,
  "client_ref_num": "test_1",
  "request_id": "f7adfcbe-9287-4f5b-90b7-6d6ed10532c9",
  "result_code": 101,
  "message": "success",
  "result": {
    "name": "JOHN DOE",
    "dob": "19-09-2001",
    "age": "23",
    "gender": "Male",
    "pan": "CXXPD1234H",
    "email": "john.doe@gmail.com",
    "official_documents": [
      {
        "document": "PAN",
        "document_id": "CXXPD1234H"
      },
      {
        "document": "Voter_ID",
        "document_id": "XXXXXX8398"
      }
    ],
    "alternate_emails": [
      "john.doe@gmail.com",
      "john1909@digitap.ai"
    ],
    "alternate_mobile_numbers": [
      "9649112345",
      "9836412345",
      "9513312345"
    ],
    "address": [
      {
        "first_line_of_address": "301, SUNRISE TOWER, AIROLI",

```

```

    "second_line_of_address": "NAVI MUMBAI",
    "third_line_of_address": "AIROLI NAVI MUMBAI MAHARASHTRA",
    "city": null,
    "state": "MAHARASHTRA",
    "postal_code": "400708",
    "country_code": "IB",
    "reported_date": "15-04-2025"
  },
  {
    "first_line_of_address": "7, DOE STREET",
    "second_line_of_address": "MARATHAHALLI",
    "third_line_of_address": "BANGALORE",
    "city": null,
    "state": "KARNATAKA",
    "postal_code": "560048",
    "country_code": "IB",
    "reported_date": "30-03-2023"
  }
],
"score": "800",
"additional_details": {
  "employment_details": {
    "income_range": "4,00,001 - 6,00,000",
    "occupation": "SALARIED"
  },
  "alternate_emails": [
    {
      "email": "john.doe@gmail.com",
      "reported_date": "31-03-2026"
    },
    {
      "email": "john1909@digitap.ai",
      "reported_date": "31-03-2024"
    }
  ],
  "alternate_mobile_numbers": [
    {
      "mobile_number": "9649112345",
      "reported_date": "30-06-2025"
    },
    {
      "mobile_number": "9836412345",
      "reported_date": "10-01-2024"
    },
    {
      "mobile_number": "9513312345",
      "reported_date": "18-08-2024"
    }
  ]
}
}
}

```

Keys of “**Result**” objects are explained below:

Key	Value	Description
-----	-------	-------------

 -name	string	Name of the user
 -dob	string	Date of birth of the individual
 -age	string	Age of the individual
 -gender	string	Gender of the individual
 -pan	string	The Permanent Account Number (PAN) is a unique alphanumeric identifier issued by the Income Tax Department of India
 -email	string	Registered email of the individual
 -alternate_emails	list	List of all the alternate emails of the individual
 -alternate_mobile_numbers	list	List of all the alternate mobile numbers of the individual
 -official_documents	list	List of Dict of of officially valid documents of the individual
 - -document	string	Officially valid document - PAN, Passport, Voter ID, Driving License, Ration Card, Universal ID
 - -document_id	string	ID number of the document
 -address	list	List of Dict of address registered with the individual
 - -first_line_of_address	string	The first line of address of the Individual
 - -second_line_of_address	string	The second line of address of the individual
 - -third_line_of_address	string	The third line of address of the individual
 - -city	string	The city associated with the address
 - -state	string	The state associated with the address
 - -postal_code	string	The postal code of the address
 - -country_code	string	The country code
 - -reported_date	string	Date when the address was reported
 -score	string	Credit score of the individual
 -additional_details	dict	Contains employment, alternate contact details, and their reported dates.
 - -employment_details	dict	Contains the individual's employment details.

 -- income_range	string	Reported income range of the individual
 -- occupation	string	Occupation of the individual
 -- alternate_emails	list	List of emails along with their reported date
 -- email	string	Reported email
 -- reported_date	string	Reported date of the email
 -- alternate_mobile_numbers	list	List of mobile numbers with their reported date
 -- mobile_number	string	Reported mobile number
 -- reported_date	string	Reported date of the mobile number

1.4.2.2 Successful response (result_code 102) Case - Record Not found

```
{
  "http_response_code":200,
  "client_ref_num":"Test123",
  "request_id":"3897023c-85c4-455a-b620-2aaf957f73f0",
  "result_code":102,
  "message":"no record found",
  "result":null
}
```

1.4.2.3 Successful response (result_code 103) Case - Name not found against mobile no

```
{
  "http_response_code":200,
  "client_ref_num":"Test123",
  "request_id":"3897023c-85c4-455a-b620-2aaf957f73f0",
  "result_code":103,
  "message":"name not found",
  "result":null
}
```

1.4.2.4 Failure response Case - Validation Error Cases

- One or more parameter missing or wrong

```
{
  "http_response_code":400,
  "client_ref_num":"Test123",
  "request_id":"5c392766-ec6c-421f-9847-92c65d27074b",
  "result_code":null,
  "message":"one or more key format is wrong",
  "result":null
}
```

- Client authentication error


```
{
  "http_response_code":401,
  "client_ref_num":null,
  "request_id":null,
  "result_code":null,
  "message":"client authentication failed",
  "result":null
}
```

- **Client authentication error (Name look-up service is not enabled for the client)**

```
{
  "http_response_code":401,
  "client_ref_num":"test",
  "request_id":"39ca5622-8cc6-47bc-b5e6-d5e3b8822300",
  "result_code":null,
  "message":"name look-up service is not enabled",
  "result":null
}
```

- **Source error - This error comes when there is an issue from server's end (please do not retry in this scenario)**

```
{
  "http_response_code":503,
  "client_ref_num":"test",
  "request_id":"39ca5622-8cc6-47bc-b5e6-d5e3b8822300",
  "result_code":null,
  "message":"source error",
  "result":null
}
```

- **If any of the options ["alternate_mobile_numbers", "alternate_emails", "official_documents", "additional_details"] are not enabled in Digitap, but are included in the request, the following response will be returned.**

```
{
  "http_response_code": 403,
  "client_ref_num": "test",
  "request_id": "d2d4cf75-60b5-45cc-aa62-f3033146cb9d",
  "result_code": null,
  "message": "The following service(s) are not enabled for this client: alternate_mobile_numbers",
  "result": null
}
```

1.5 Error Messages

Error messages for each of the failure cases is given below:

HTTP Response Status Code	Error Message	description
400	one or more key format is wrong	One or more key format is wrong
401	client authentication failed	This error occurs when the client (such as an application or user) fails to prove its identity to the server.
401	name look-up service is not enabled	The name look-up service is not enabled
403	The following service(s) are not enabled for this client: alternate_mobile_numbers	If any of the options ["alternate_mobile_numbers", "alternate_emails", "official_documents"] are not enabled in Digitap, but are included in the request, the following response will be returned.
500	internal server error	The server encountered an unexpected condition that prevented it from fulfilling the request
503	source error	There is an issue with the source of the data being processed.

1.6 API Encryption

Digitap APIs offer an option to enable **JWE encryption**, allowing the request payload to be sent and the response to be received in an **encrypted format**.

Encryption:

Following is the method to encrypt the request payload for the API :

- Construct the request payload that needs to be sent to the server based on the specific API
- Stringify the JSON request payload.
- Create the JWE (*JSON Web Encryption*) Token for the above text using Digitap public key provided and one of the secure JWE Algorithm & Encryption methods (*we suggest to use "alg" as RSA-OAEP-256 and "enc" as A256GCM for speed*).
- Set the above JWE Token generated as the value for the **"encrypted_data"** and pass this payload to the API.

Sample Request Payload :

For the sample payload,

```
{
  "client_ref_num": "test",
  "mobile_no": "9168812345",
  "name_lookup": 0,
  "first_name": "Pranav",
  "last_name": "Chaudhari"
}
```

the following would be an encrypted payload.

```
{
  "encrypted_data":
  "eyJlbmMiOiJBMjU2R0NNIiwiaWYXnljoiUINBLU9BRVAtMjU2In0.ks48nUM
  JrUSFxxXH5ousovNmfUc8vFlukcQIVryKGwewoNc25jaEi0Aw-B6FDECeA
  1EZ0Mr6R16rQ13kbUifvPccTCQT5Sv2qhP3y0YfekvNdrzMIqBmPnU6G
  tzyPvXMGKvh0aWIdIW0BJgrDBIxRs-KWqHjoJUKCeSb_63P3hw.GfVGo
  6PLsWTN1hih.MlkihybDgCPo5U_6hOMSX6BBIRI-AWmmb4OF026fUOIG
  _7g6XMNzDk9oSShJwhbtbBuyhe1BdZBUX80rjTpHjZlnOcEgEnUAYyO3e
  53CUHiwKPxMcanIJjBOY06SdWGLRuE76GTq6HTidcTfvjCXUPWqRo5
  C9mdlf0SkeGSPZg.MPSzvZroJfPjcWiXMxgqYA"
}
```

Decryption:

Following is the method to decrypt the response payload received from the API :

- Get the data received in the “encrypted_data” field from the payload.
- Decrypt the above text using JWE method with your private key (*corresponding public key needs to be shared with the Digatap*)
- The decrypted data would be having the response in the format as given in the specified API.

Sample Response Payload :

For the sample response,

```
{
  "http_response_code": 200,
  "client_ref_num": "Test123",
  "request_id": "b18e7c0c-88f4-4a5c-bccc-efe907a5e76c",
  "result_code": 101,
  "message": "success",
}
```

```

"result": {
  "result_json": {
    .....
    .....
  }
}

```

the following would be an encrypted response given by the API.

```

{
  "encrypted_data":
  "eyJlbmMiOiJBMjU2R0NNIiwiaWVxnljoiUINBLU9BRVAtMjU2ln0.ks48nUM
  JrUSFxxXH5ousovNmfUc8vFlukcQIVryKGwewoNc25jaEi0Aw-B6FDECeA
  1EZ0Mr6R16rQ13kbUifvPccTCQT5Sv2qhP3y0YfekvNdrzMLqBmPnU6G
  tzyPvXMGKvh0aWIdlWoBJgrDBIxRs-KWqHjoJUKCeSb_63P3hw.GfVGo
  6PLsWTN1hih.MlkihybDgCPo5U_6hOMSX6BBIRI-AWmnb4OF026fUOIG
  _7g6XMNzDk9oSShJwhtbBuyhe1BdZBUX80rjTpHjZlnOcEgEnUAYyO3e
  53CUHwKPxMcanIJBOY06SdWGLRuE76GTq6HTidcTfjfcXUPWqRo5
  C9mdlf0SkeGSPZg.MPSzvZroJfPjcWiXMxgqYA"
}

```

Note :

- Clients need to generate the private-Public Key and provide the public key to Digitap. One can generate the public key using OpenSSH or a website like <https://cryptotools.net/rsagen>. We recommend using 1024 bits for speed of decryption. Clients can choose the bit length based on their infosec guidelines.
- Clients can get the Digitap Public Key by contacting the SM(Sales Manager).
- Only specific APIs support encryption and decryption. Please refer to the specific API to check whether encryption is supported in the specific API section. If you require Encryption in other APIs, please raise the request to the SM(Sales Manager).

Error Message related to Encryption:

When the encryption method is used for sending the data to the API, the response would be received in encrypted format including the error messages. However, some responses occurring at the infra level or initial validation would be in non-encrypted manner. Few cases where the response would be in non-encrypted manner are:

- Rate Limiting Error
- DNS or Load Balancer Errors

apart from the error messages provided in [Error code master](#) attached, following additional status code/errors may occur when encryption is being used.

Code	Error Message	Description
------	---------------	-------------

401	Invalid Encryption	JWE decryption failed at Digitap due to error in encrypted data
451	Misconfiguration	Encryption is not enabled for the client

1.7 Additional Notes

- API will be billable for any successful response with result_code 101