Terminal outputs

```
+                "/platform-admin",
+                cookies={SESSION_COOKIE: tokens[1]},
+                headers={"X-Role": "platform_admin"},
+            )
+            assert denied.status_code == 403
+            assert denied.json() == {"detail": "Permission denied"}
+    finally:
+        with connect() as conn, conn.cursor() as cur:
+            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id, user_id))
+
diff --git a/apps/api/tests/test_provision_user.py b/apps/api/tests/test_provision_user.py
index ad540b2..f6d78d8 100644
--- a/apps/api/tests/test_provision_user.py
+++ b/apps/api/tests/test_provision_user.py
@@ -30,6 +30,40 @@ def
test_provision_user_requires_email_and_display_arguments(monkeypatch, capsys
     assert "Usage:" in capsys.readouterr().err


+def test_provision_user_platform_admin_is_explicit_opt_in(monkeypatch, capsys):
+    monkeypatch.setattr(sys, "argv", ["provision_user", "admin@example.test", "Synthetic
Admin", "--platform-admin"])
+    values = iter(("synthetic-password", "synthetic-password"))
+    monkeypatch.setattr(provision_user.getpass, "getpass", lambda _prompt: next(values))
+
+    class Cursor:
+        statement = ""
+        parameters = None
+
+        def __enter__(self): return self
+        def __exit__(self, *_args): return None
+        def execute(self, statement, parameters):
+            self.statement, self.parameters = statement, parameters
+
+    cursor = Cursor()
+    class Connection:
+        def __enter__(self): return self
+        def __exit__(self, *_args): return None
+        def cursor(self): return cursor
```

```
+
+    monkeypatch.setattr(provision_user, "connect", Connection)
+    assert provision_user.main() == 0
+    assert "role_key = %s AND scope = 'platform'" in cursor.statement
+    assert cursor.parameters[-1] == "platform_admin"
+    output = capsys.readouterr()
+    assert "synthetic-password" not in output.out + output.err
+
+
+def test_provision_user_rejects_unknown_role_argument(monkeypatch, capsys):
+    monkeypatch.setattr(sys, "argv", ["provision_user", "analyst@example.test", "Synthetic
User", "--operator"])
+    assert provision_user.main() == 2
+    assert "Usage:" in capsys.readouterr().err
+
+
 @pytest.mark.parametrize(
     "email, display_name",
     [
@@ -99,8 +133,9 @@ def
test_provision_user_hashes_and_upserts_without_printing_password(monkeypatch
     assert "User provisioned" in output.out
     assert "synthetic-initial-password" not in output.out + output.err
     assert "ON CONFLICT ((lower(email))) DO UPDATE" in cursor.statement
-    normalized_email, password_hash, display_name = cursor.parameters
+    normalized_email, password_hash, display_name, role_key = cursor.parameters
     assert normalized_email == "analyst@example.com"
     assert display_name == "Synthetic Analyst"
+    assert role_key is None
     assert password_hash.startswith("argon2id")
     assert password_hash != "synthetic-initial-password"
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd apps/api
pytest -q tests/test_auth_unit.py tests/test_provision_user.py
==========================================================================
================ ERRORS
==========================================================================
==================
_____________________________________________________________________ ERROR
collecting apps/api/tests/test_auth_unit.py
_____________________________________________________________________
ImportError while importing test module
'/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI/apps/api/tests/test_auth_unit.py'.
```

```
Hint: make sure your test modules/packages have valid Python names.
Traceback:
/opt/anaconda3/lib/python3.14/importlib/__init__.py:88: in import_module
    return _bootstrap._gcd_import(name[level:], package, level)
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
tests/test_auth_unit.py:6: in <module>
    from fastapi import HTTPException
E   ModuleNotFoundError: No module named 'fastapi'
_____________________________________________________________________________ ERROR
collecting apps/api/tests/test_provision_user.py
_____________________________________________________________________________
ImportError while importing test module
'/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI/apps/api/tests/test_provision_use
r.py'.
Hint: make sure your test modules/packages have valid Python names.
Traceback:
/opt/anaconda3/lib/python3.14/importlib/__init__.py:88: in import_module
    return _bootstrap._gcd_import(name[level:], package, level)
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
tests/test_provision_user.py:9: in <module>
    import app.provision_user as provision_user
app/provision_user.py:9: in <module>
    from app.database import connect
app/database.py:8: in <module>
    import psycopg
E   ModuleNotFoundError: No module named 'psycopg'
=============================================================================
========= short test summary info
=============================================================================
=========
ERROR tests/test_auth_unit.py
ERROR tests/test_provision_user.py
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!! Interrupted: 2 errors during collection
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
2 errors in 66.77s (0:01:06)
(base) sandeeph@Sandeeps-MacBook-Pro api %
pwd
ls -la
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI/apps/api
total 0
drwxr-xr-x@ 9 sandeeph  staff  288 Oct 20 10:43 .
drwxr-xr-x@ 4 sandeeph  staff  128 Oct 20 10:43 ..
drwxr-xr-x@ 8 sandeeph  staff  256 Oct 20 10:43 app
drwxr-xr-x@ 4 sandeeph  staff  128 Oct 19 11:56 migrations
```

```
-rw-r--r--@ 1 sandeeph  staff  574 Oct 19 00:03 requirements-dev.lock
-rw-r--r--@ 1 sandeeph  staff   66 Oct 19 00:02 requirements-dev.txt
-rw-r--r--@ 1 sandeeph  staff  411 Oct 19 00:03 requirements.lock
-rw-r--r--@ 1 sandeeph  staff  138 Oct 19 00:02 requirements.txt
drwxr-xr-x@ 7 sandeeph  staff  224 Oct 19 13:47 tests
(base) sandeeph@Sandeeps-MacBook-Pro api %
ls -1 pyproject.toml requirements.txt requirements-dev.txt uv.lock poetry.lock 2>/dev/null
requirements-dev.txt
requirements.txt
(base) sandeeph@Sandeeps-MacBook-Pro api %
cat pyproject.toml
cat: pyproject.toml: No such file or directory
(base) sandeeph@Sandeeps-MacBook-Pro api %
cat requirements.txt
fastapi==0.133.0
starlette==1.3.1
uvicorn==0.40.0
argon2-cffi==25.1.0
psycopg[binary]==3.2.13
python-dotenv==1.2.2
email-validator==2.3.0
(base) sandeeph@Sandeeps-MacBook-Pro api %
python -m pip install -r requirements.txt
Collecting fastapi==0.133.0 (from -r requirements.txt (line 1))
  Using cached fastapi-0.133.0-py3-none-any.whl.metadata (30 kB)
Requirement already satisfied: starlette==1.3.1 in /opt/anaconda3/lib/python3.14/site-packages
(from -r requirements.txt (line 2)) (1.3.1)
Requirement already satisfied: uvicorn==0.40.0 in /opt/anaconda3/lib/python3.14/site-packages
(from -r requirements.txt (line 3)) (0.40.0)
Requirement already satisfied: argon2-cffi==25.1.0 in
/opt/anaconda3/lib/python3.14/site-packages (from -r requirements.txt (line 4)) (25.1.0)
Collecting psycopg==3.2.13 (from psycopg[binary]==3.2.13->-r requirements.txt (line 5))
  Using cached psycopg-3.2.13-py3-none-any.whl.metadata (4.5 kB)
Collecting python-dotenv==1.2.2 (from -r requirements.txt (line 6))
  Using cached python_dotenv-1.2.2-py3-none-any.whl.metadata (27 kB)
Collecting email-validator==2.3.0 (from -r requirements.txt (line 7))
  Using cached email_validator-2.3.0-py3-none-any.whl.metadata (26 kB)
Requirement already satisfied: pydantic>=2.7.0 in /opt/anaconda3/lib/python3.14/site-packages
(from fastapi==0.133.0->-r requirements.txt (line 1)) (2.13.4)
Requirement already satisfied: typing-extensions>=4.8.0 in
/opt/anaconda3/lib/python3.14/site-packages (from fastapi==0.133.0->-r requirements.txt (line
1)) (4.16.0)
```

Requirement already satisfied: typing-inspection>=0.4.2 in /opt/anaconda3/lib/python3.14/site-packages (from fastapi==0.133.0->-r requirements.txt (line 1)) (0.4.2)
Requirement already satisfied: annotated-doc>=0.0.2 in /opt/anaconda3/lib/python3.14/site-packages (from fastapi==0.133.0->-r requirements.txt (line 1)) (0.0.4)
Requirement already satisfied: anyio<5,>=3.6.2 in /opt/anaconda3/lib/python3.14/site-packages (from starlette==1.3.1->-r requirements.txt (line 2)) (4.12.1)
Requirement already satisfied: click>=7.0 in /opt/anaconda3/lib/python3.14/site-packages (from uvicorn==0.40.0->-r requirements.txt (line 3)) (8.4.1)
Requirement already satisfied: h11>=0.8 in /opt/anaconda3/lib/python3.14/site-packages (from uvicorn==0.40.0->-r requirements.txt (line 3)) (0.16.0)
Requirement already satisfied: argon2-cffi-bindings in /opt/anaconda3/lib/python3.14/site-packages (from argon2-cffi==25.1.0->-r requirements.txt (line 4)) (25.1.0)
Collecting dnspython>=2.0.0 (from email-validator==2.3.0->-r requirements.txt (line 7))
  Using cached dnspython-2.9.0-py3-none-any.whl.metadata (5.7 kB)
Requirement already satisfied: idna>=2.0.0 in /opt/anaconda3/lib/python3.14/site-packages (from email-validator==2.3.0->-r requirements.txt (line 7)) (3.18)
Collecting psycopg-binary==3.2.13 (from psycopg[binary]==3.2.13->-r requirements.txt (line 5))
  Using cached psycopg_binary-3.2.13-cp314-cp314-macosx_11_0_arm64.whl.metadata (2.9 kB)
Requirement already satisfied: annotated-types>=0.6.0 in /opt/anaconda3/lib/python3.14/site-packages (from pydantic>=2.7.0->fastapi==0.133.0->-r requirements.txt (line 1)) (0.7.0)
Requirement already satisfied: pydantic-core==2.46.4 in /opt/anaconda3/lib/python3.14/site-packages (from pydantic>=2.7.0->fastapi==0.133.0->-r requirements.txt (line 1)) (2.46.4)
Requirement already satisfied: cffi>=2.0.0b1 in /opt/anaconda3/lib/python3.14/site-packages (from argon2-cffi-bindings->argon2-cffi==25.1.0->-r requirements.txt (line 4)) (2.1.0)
Requirement already satisfied: pycparser in /opt/anaconda3/lib/python3.14/site-packages (from cffi>=2.0.0b1->argon2-cffi-bindings->argon2-cffi==25.1.0->-r requirements.txt (line 4)) (3.0)
Using cached fastapi-0.133.0-py3-none-any.whl (104 kB)
Using cached psycopg-3.2.13-py3-none-any.whl (206 kB)
Using cached python_dotenv-1.2.2-py3-none-any.whl (22 kB)
Using cached email_validator-2.3.0-py3-none-any.whl (35 kB)
Using cached psycopg_binary-3.2.13-cp314-cp314-macosx_11_0_arm64.whl (4.1 MB)
Using cached dnspython-2.9.0-py3-none-any.whl (354 kB)
Installing collected packages: python-dotenv, psycopg-binary, psycopg, dnspython, email-validator, fastapi
  Attempting uninstall: python-dotenv
    Found existing installation: python-dotenv 1.2.1
    Uninstalling python-dotenv-1.2.1:
      Successfully uninstalled python-dotenv-1.2.1

```
Successfully installed dnspython-2.9.0 email-validator-2.3.0 fastapi-0.133.0 psycopg-3.2.13
psycopg-binary-3.2.13 python-dotenv-1.2.2
(base) sandeeph@Sandeeps-MacBook-Pro api %
python -c "import fastapi, psycopg; print('FastAPI and psycopg imports OK')"
python -m pip check
FastAPI and psycopg imports OK
No broken requirements found.
(base) sandeeph@Sandeeps-MacBook-Pro api %
python -m pytest -q tests/test_auth_unit.py tests/test_provision_user.py
.....................................
[100%]
============================================================================
============ warnings summary
============================================================================
=============
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[get-/a
uth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[post-/
auth/logout-kwargs1]
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
43 passed, 3 warnings in 30.14s
(base) sandeeph@Sandeeps-MacBook-Pro api %
pytest -q tests/test_identity_constraints.py
FFF
[100%]
============================================================================
================ FAILURES
============================================================================
=================

_____________________________________________________________________
test_identity_schema_rejects_duplicate_email_and_cascades_sessions
_____________________________________________________________________

    def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
        email = f"constraint-{uuid4().hex}@example.com"
>       with connect() as conn, conn.cursor() as cur:
```

```
            ^^^^^^^^^
tests/test_identity_constraints.py:17:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
_____________________________________________________________________
test_platform_permission_is_resolved_from_database_role_and_session
_____________________________________________________________________
    def test_platform_permission_is_resolved_from_database_role_and_session():
        admin_email = f"platform-admin-{uuid4().hex}@example.test"
        user_email = f"unprivileged-{uuid4().hex}@example.test"
        tokens = []
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:50:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
_____________________________________________________________________
test_platform_role_assignment_rejects_workspace_scoped_roles
_____________________________________________________________________
    def test_platform_role_assignment_rejects_workspace_scoped_roles():
        email = f"wrong-scope-{uuid4().hex}@example.test"
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:93:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
```

```
========================================================================
============ warnings summary
========================================================================
=============
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
========================================================================
========= short test summary info
========================================================================
=========
FAILED
tests/test_identity_constraints.py::test_identity_schema_rejects_duplicate_email_and_cascades
_sessions - RuntimeError: DATABASE_URL is required
FAILED
tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_a
nd_session - RuntimeError: DATABASE_URL is required
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - RuntimeError: DATABASE_URL is required
3 failed, 1 warning in 8.92s
(base) sandeeph@Sandeeps-MacBook-Pro api %
cd ../..
# Find the database setup files
ls -la
find . -maxdepth 3
-name'compose.yaml' -o -name'compose.yml' -o -name'docker-compose.yml' -o -name'.env.
-print
# Inspect how the API connects to PostgreSQL
cat apps/api/app/database.py
# Inspect the API dependency and development instructions
cat apps/api/requirements-dev.txt
zsh: command not found: #
total 432
drwxr-xr-x@ 26 sandeeph  staff    832 Oct 20 10:57 .
drwxr-xr-x   5 sandeeph  staff    160 Oct 20 10:57 ..
-rw-r--r--@  1 sandeeph  staff   6148 Oct 18 16:21 .DS_Store
-rw-r--r--@  1 sandeeph  staff  53248 Oct 18 23:51 .coverage
-rw-r--r--@  1 sandeeph  staff    226 Oct 18 22:53 .env.example
drwxr-xr-x@ 13 sandeeph  staff    416 Oct 20 10:56 .git
drwxr-xr-x@  3 sandeeph  staff     96 Oct 19 10:40 .github
```

```
-rw-r--r--@  1 sandeeph  staff   1397 Oct 19 10:11 .gitignore
-rw-r--r--@  1 sandeeph  staff      3 Oct 18 21:39 .nvmrc
drwxr-xr-x@  6 sandeeph  staff    192 Oct 20 10:55 .pytest_cache
drwxr-xr-x@  7 sandeeph  staff    224 Oct 19 13:48 .venv
-rw-r--r--@  1 sandeeph  staff  29688 Oct 19 10:29 AGENTS.md
drwxr-xr-x  12 sandeeph  staff    384 Oct 18 10:19 Component_diagrams
drwxr-xr-x   6 sandeeph  staff    192 Oct 19 10:40 Database
drwxr-xr-x@ 10 sandeeph  staff    320 Oct 18 16:00 Dcos
-rw-r--r--@  1 sandeeph  staff  51885 Oct 19 11:14 IMPLEMENTATION_STATUS.txt
-rw-r--r--@  1 sandeeph  staff  11907 Oct 19 11:21 README.md
-rw-r--r--@  1 sandeeph  staff  18865 Oct 19 00:40 SPRINT_1_TEST_EXECUTION_STATUS.txt
drwxr-xr-x@  4 sandeeph  staff    128 Oct 20 10:57 apps
-rw-r--r--@  1 sandeeph  staff  30066 Oct 19 11:14 conversation.txt
-rw-r--r--@  1 sandeeph  staff   7574 Oct 18 23:51 coverage.xml
drwxr-xr-x@  5 sandeeph  staff    160 Oct 19 11:29 dist
drwxr-xr-x@  5 sandeeph  staff    160 Oct 19 11:43 docs
drwxr-xr-x@ 16 sandeeph  staff    512 Oct 19 11:57 htmlcov
-rw-r--r--@  1 sandeeph  staff     58 Oct 18 22:22 pytest.ini
drwxr-xr-x@  6 sandeeph  staff    192 Oct 19 10:41 scripts
./.env.example
./apps/web/.env.example
zsh: command not found: #
"""Small synchronous PostgreSQL boundary for the auth endpoints."""
from __future__ import annotations
import os
from pathlib import Path
import psycopg
from dotenv import load_dotenv
load_dotenv(Path(__file__).resolve().parents[3] / ".env")
def connect() -> psycopg.Connection:
    database_url = os.environ.get("DATABASE_URL")
    if not database_url:
        raise RuntimeError("DATABASE_URL is required")
    return psycopg.connect(database_url, connect_timeout=3)
zsh: command not found: #
-r requirements.txt
pytest==9.0.3
httpx==0.28.1
pytest-cov==6.2.1
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
.28.1
pytest-cov==6.2.1
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cat .env.example
```

Local development placeholders only. Replace DATABASE_URL locally; never commit it.
DATABASE_URL=postgresql://USER:PASSWORD@127.0.0.1:5432/finsight
WEB_ORIGIN=http://localhost:3000
SESSION_TTL_MINUTES=60
COOKIE_SECURE=false
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
grep -n -i -E 'postgres|database_url|migration|test database|docker' README.md
grep -n -i -E 'postgres|database_url|migration|test database' AGENTS.md
3:FinSight AI is an AI-powered financial research and analytics platform for market data, source-backed analysis, portfolio analytics, valuation, risk, and reporting. This repository is being built incrementally. It currently provides a Next.js sign-in page and a FastAPI authentication service with PostgreSQL-backed sessions.
9:- PostgreSQL 16 or newer for authentication and sessions.
12:Authentication uses a local PostgreSQL database. Ollama and market-data providers are not configured by this story. Do not put real credentials in the repository.
17:2. Copy `.env.example` to the repository root as `.env`. Set `DATABASE_URL` to a local PostgreSQL database accessible only to your development user and keep it in this ignored file. Copy `apps/web/.env.example` to `apps/web/.env.local`; `API_BASE_URL` configures the browser app's API target at runtime, and the frontend bundle can be promoted unchanged between environments.
18:3. Create a new development database, then apply only the FIN-13 identity migration:
23:   psql "$DATABASE_URL" -v ON_ERROR_STOP=1 -f apps/api/migrations/0001_auth_identity.sql
24:   psql "$DATABASE_URL" -v ON_ERROR_STOP=1 -f apps/api/migrations/0002_platform_authorization.sql
27:   These versioned migrations create the implemented subset of canonical identity and authorization tables. `0002` adds only `platform_admin` and the single explicit `platform.admin` permission; it does not seed workspace roles or grant product-module permissions. Never apply the supplied target schema wholesale to an existing database.
63:- `POST /auth/login` accepts an email and password, verifies the Argon2id password hash, and sets an opaque `HttpOnly`, `SameSite=Lax` session cookie. Only the SHA-256 digest of the random cookie value is stored in PostgreSQL.
65:- Backend routes requiring a capability use `require_permission(permission_key)`. Permissions are resolved from PostgreSQL through the user's platform role; absent roles and unknown permissions deny access with 403. The current migration grants only `platform.admin`; no current product/admin route consumes it. Workspace roles are not assigned globally. `/app/:path*` has a Next.js Proxy cookie-presence redirect for anonymous page requests; it is only a navigation aid, and every API still validates the server-side session and permission.
68:- Configure `DATABASE_URL` for a disposable development/test database before applying migrations or running integration tests. Install `apps/api/requirements-dev.lock` in the Python environment, then run the layers independently from the repository root:
69: - Backend line and branch coverage (unit tests need no database; integration tests require the identity migration): from the repository root, set `DATABASE_URL` to a disposable migrated PostgreSQL database and run `.venv/bin/python -m pytest -q --cov=app --cov-branch

--cov-report=term-missing --cov-report=xml:coverage.xml --cov-report=html:htmlcov apps/api/tests`. This writes a machine-readable `coverage.xml` and browsable `htmlcov/index.html`; reports are ignored local build output.
73: - Live browser smoke: with `DATABASE_URL` set to a disposable PostgreSQL database where migrations `0001_auth_identity.sql` and `0002_platform_authorization.sql` have been applied, run `python scripts/run_live_e2e.py` from the repository root. It starts local API/frontend processes, provisions one random synthetic account, tests failed/successful login and logout inChromium, then deletes the account. Set `FRONTEND_DIR` to a built Next.js standalone directory to exercise a production build; otherwise it runs the development server.
74:- The browser suite needs Playwright Chromium (`npx playwright install chromium`). PostgreSQL integration and live smoke require the disposable identity schema; tests do not apply migrations to a database automatically.
81: api/   FastAPI auth API, versioned migration, tests, requirements, and lock
106:- **Login returns a service-unavailable error:** confirm `DATABASE_URL` points to the migrated local database and that PostgreSQL is accepting connections.
111:The repository currently has no configured hosting target, deployment credentials, staging environment, or production environment. FIN-74 therefore produces a versioned downloadable build bundle; it does not deploy the application. The existing GitHub Actions workflow builds the standalone Next.js frontend, checks the FastAPI backend against its lock and disposable PostgreSQL tests, and packages both only after the CI jobs pass. CI bundles are named `finsight-<version>-<commit-prefix>.tar.gz` and include `RELEASE-METADATA.json` with version and full commit SHA. A sibling `.build-info.json` records the UTC packaging timestamp and archive checksum; `.sha256` independently verifies the exact archive. A local bundle without a source commit is named by version and records a null commit SHA. Pull-request/main builds use the package version; a `v<semver>` tag uses that tagged version. GitHub Actions retains the package artifact for 90 days.
113:The bundle contains a Node.js 22 standalone frontend and the FastAPI source, pinned backend runtime lockfile, and versioned migrations. The frontend reads `API_BASE_URL` from the frontend server's runtime environment through `/api/runtime-config`; the value must be an origin such as `https://api.example.com`, without credentials or a path. Backend runtime configuration uses `DATABASE_URL`, `WEB_ORIGIN`, `SESSION_TTL_MINUTES`, `COOKIE_SECURE`, and `APP_ENV`. Supply secrets through the chosen deployment platform's secret manager, never through the bundle or repository. Configure a least-privileged database runtime role separately from the migration role, TLS, backups, readiness/monitoring, and operator-owned RTO/RPO before production use.
30:2. **Core SQL schema and Database Schema/ERD Reference:** authoritative target relational entities, column types, PK/FK relationships, constraints, provenance, and domain model. Treatthe SQL files supplied as reference inputs, not disposable migration scripts.
46:- **Structured database:** PostgreSQL; structured relational records are the source of truth.
47:- **Vector retrieval:** pgvector in the PostgreSQL deployment for the initial RAG design; document/chunk IDs and permissions remain relationally authoritative.
98:### 5.2 PostgreSQL schema handling

101:- Inspect the current database, migrations, and code before proposing changes. Do not run the supplied full schema directly against an existing or non-disposable database without explicit approval and a verified backup/recovery plan.
102:- Create new, version-controlled migrations in the repository's established migration system. Never edit the source SQL/schema/reference PDFs to show implementation progress.
103:- Apply migrations only to a confirmed development/test database. Verify a clean install and, where supported, a forward migration from the previous schema version.
106:- Use PostgreSQL 16+ and pgvector as the design baseline unless the existing supported environment documents otherwise. Confirm required extensions are available before depending on them.
107:- Never drop tables, truncate user data, reset a database, rewrite migration history, or run destructive SQL without the user's explicit approval and a clear recovery plan.
120:Do not edit their contents, overwrite them with generated text, rename them, regenerate them, or alter their dates/claims. Use code, migrations, tests, configuration, ADRs, and new coordination/status files for implementation outputs. If an approved design change is needed, write a separate addendum/ADR rather than silently rewriting a source baseline.
194:3. **Plan:** identify the smallest vertical slice, dependencies, impacted files, migration impact, security concerns, test cases, and any user decision needed. Record concise intent in the status file.
239:- Run migrations against disposable test databases and verify constraints and FK behavior. Never use production credentials or real user data in tests.
241:- A failed security, access-isolation, data-integrity, migration, or Release 1 boundary test blocks acceptance until fixed or explicitly handled under an approved exception process.
252:- Do not deploy, publish images, provision paid infrastructure, run production migrations, or change provider entitlements unless explicitly approved.
263:- [ ] Database migrations are versioned and safely validated when database changes exist.
274:2. Inspect the project root, relevant subdirectories, Git branch/status/diff, package manifests, environment templates, migration setup, tests, and CI workflows. Do not reveal secretvalues while inspecting configuration.
282:**Final rule:** The source documents define what the system must be. This file governs how Codex works. New code, migrations, tests, and separate status/decision records may evolve; the original project artifacts remain read-only. Verify everything that can be verified, ask about consequential ambiguity, and never present an assumption as an observed fact.
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
pg_isready
/tmp:5432 - no response
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
ls -la apps/api/migrations
ls -la Database
total 0
drwxr-xr-x@ 4 sandeeph staff   128 Oct 20 10:57 .
drwxr-xr-x@ 9 sandeeph staff   288 Oct 20 10:57 ..
-rw-r--r--@ 1 sandeeph staff 1728 Oct 18 22:05 0001_auth_identity.sql
-rw-r--r--@ 1 sandeeph staff 2580 Oct 19 11:20 0002_platform_authorization.sql

```
total 592
drwxr-xr-x   6 sandeeph  staff     192 Oct 19 10:40 .
drwxr-xr-x@ 26 sandeeph  staff     832 Oct 20 10:57 ..
-rw-r--r--@  1 sandeeph  staff  151136 Oct 18 15:59
FinSight_AI_Jira_Backlog_72_Stories_Enhanced.pdf
-rw-r--r--@  1 sandeeph  staff  120188 Oct 18 16:19 schema (1).sql
-rw-r--r--@  1 sandeeph  staff   12778 Oct 18 16:20 schema_optional_trading.sql
-rw-r--r--@  1 sandeeph  staff    8988 Oct 18 16:20 seed_reference_data.sql
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
brew services start postgresql@16
pg_isready
Error: Formula `postgresql@16` is not installed.
/tmp:5432 - no response
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd apps/api
python -m pytest -q tests/test_identity_constraints.py
FFF
[100%]
================================================================================
================ FAILURES
================================================================================
=================

_____________________________________________________________
test_identity_schema_rejects_duplicate_email_and_cascades_sessions
_____________________________________________________________

    def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
        email = f"constraint-{uuid4().hex}@example.com"
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:17:

_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError

_____________________________________________________________
test_platform_permission_is_resolved_from_database_role_and_session
_____________________________________________________________

    def test_platform_permission_is_resolved_from_database_role_and_session():
```

```
        admin_email = f"platform-admin-{uuid4().hex}@example.test"
        user_email = f"unprivileged-{uuid4().hex}@example.test"
        tokens = []
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:50:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
_____________________________________________________________________
test_platform_role_assignment_rejects_workspace_scoped_roles
_____________________________________________________________________
    def test_platform_role_assignment_rejects_workspace_scoped_roles():
        email = f"wrong-scope-{uuid4().hex}@example.test"
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:93:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
=========================================================================
=========== warnings summary
=========================================================================
=============
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=========================================================================
========= short test summary info
=========================================================================
=========
```

```
FAILED
tests/test_identity_constraints.py::test_identity_schema_rejects_duplicate_email_and_cascades
_sessions - RuntimeError: DATABASE_URL is required
FAILED
tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_a
nd_session - RuntimeError: DATABASE_URL is required
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - RuntimeError: DATABASE_URL is required
3 failed, 1 warning in 29.77s
(base) sandeeph@Sandeeps-MacBook-Pro api %
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd apps/api
python -m pytest -q tests/test_identity_constraints.py
FFF
[100%]
================================================================================
================ FAILURES
================================================================================
_____________________________________________________________
test_identity_schema_rejects_duplicate_email_and_cascades_sessions
_____________________________________________________________
    def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
        email = f"constraint-{uuid4().hex}@example.com"
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:17:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
_____________________________________________________________
test_platform_permission_is_resolved_from_database_role_and_session
_____________________________________________________________
    def test_platform_permission_is_resolved_from_database_role_and_session():
        admin_email = f"platform-admin-{uuid4().hex}@example.test"
        user_email = f"unprivileged-{uuid4().hex}@example.test"
        tokens = []
>       with connect() as conn, conn.cursor() as cur:
```

```
            ^^^^^^^^^
tests/test_identity_constraints.py:50:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
_____________________________________________________________________
test_platform_role_assignment_rejects_workspace_scoped_roles
_____________________________________________________________________
    def test_platform_role_assignment_rejects_workspace_scoped_roles():
        email = f"wrong-scope-{uuid4().hex}@example.test"
>       with connect() as conn, conn.cursor() as cur:
            ^^^^^^^^^
tests/test_identity_constraints.py:93:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
    def connect() -> psycopg.Connection:
        database_url = os.environ.get("DATABASE_URL")
        if not database_url:
>           raise RuntimeError("DATABASE_URL is required")
E           RuntimeError: DATABASE_URL is required
app/database.py:17: RuntimeError
=============================================================================
============ warnings summary
=============================================================================
=============
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=============================================================================
========= short test summary info
=============================================================================
=========
FAILED
tests/test_identity_constraints.py::test_identity_schema_rejects_duplicate_email_and_cascades
_sessions - RuntimeError: DATABASE_URL is required
```

```
FAILED
tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_a
nd_session - RuntimeError: DATABASE_URL is required
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - RuntimeError: DATABASE_URL is required
3 failed, 1 warning in 29.77s
(base) sandeeph@Sandeeps-MacBook-Pro api % brew list --formula | grep -E
'^postgresql(@[0-9]+)?|$^{l}ibpq$'
brew services list
psql --version
which psql
postgresql@17
Name          Status  User     File
ollama        none    sandeeph
postgresql@17 none    sandeeph
redis         started sandeeph ~/Library/LaunchAgents/sh.brew.redis.plist
unbound       none
psql (PostgreSQL) 17.6 (Homebrew)
/opt/homebrew/opt/postgresql@17/bin/psql
(base) sandeeph@Sandeeps-MacBook-Pro api % brew services start postgresql@17
pg_isready
==> Successfully started `postgresql@17` (label: sh.brew.postgresql@17)
/tmp:5432 - no response
(base) sandeeph@Sandeeps-MacBook-Pro api % /tmp:5432 - accepting connections
zsh: no such file or directory: /tmp:5432
(base) sandeeph@Sandeeps-MacBook-Pro api % brew services list
tail -n 50 ~/Library/Logs/Homebrew/postgresql@17.log
Name          Status  User     File
ollama        none    sandeeph
postgresql@17 started sandeeph ~/Library/LaunchAgents/sh.brew.postgresql@17.plist
redis         started sandeeph ~/Library/LaunchAgents/sh.brew.redis.plist
unbound       none
tail: /Users/sandeeph/Library/Logs/Homebrew/postgresql@17.log: No such file or directory
(base) sandeeph@Sandeeps-MacBook-Pro api % psql -d postgres -c "SELECT current_user,
version();"
 current_user |                                                  version
--------------+-----------------------------------------------------------------------------------------------------------
--------------
 sandeeph     | PostgreSQL 17.6 (Homebrew) on aarch64-apple-darwin25.0.0, compiled by
Apple clang version 17.0.0 (clang-1700.3.19.1), 64-bit
(1 row)
(base) sandeeph@Sandeeps-MacBook-Pro api % psql -d postgres -c "\l"
psql -d postgres -tAc "SELECT 1 FROM pg_database WHERE datname = 'finsight_test';"
```

```
                                                List of databases
   Name    |  Owner   | Encoding | Locale Provider |   Collate   |    Ctype    | Locale | ICU Rules |
Access privileges
-----------+----------+----------+-----------------+-------------+-------------+--------+-----------+-------------------
---
 postgres  | sandeeph | UTF8     | libc            | en_US.UTF-8 | en_US.UTF-8 |        |           |
 template0 | sandeeph | UTF8     | libc            | en_US.UTF-8 | en_US.UTF-8 |        |           |
=c/sandeeph          +
           |          |          |                 |             |             |        |           | sandeeph=CTc/sandeeph
 template1 | sandeeph | UTF8     | libc            | en_US.UTF-8 | en_US.UTF-8 |        |           |
=c/sandeeph          +
           |          |          |                 |             |             |        |           | sandeeph=CTc/sandeeph
(3 rows)
(base) sandeeph@Sandeeps-MacBook-Pro api % createdb finsight_test
psql -d finsight_test -c "SELECT current_database(), current_user, version();"
createdb: error: database creation failed: ERROR:  could not extend file "base/16388/2692": No
space left on device
HINT:  Check free disk space.
psql: error: connection to server on socket "/tmp/.s.PGSQL.5432" failed: FATAL:  database
"finsight_test" does not exist
(base) sandeeph@Sandeeps-MacBook-Pro api %

 (base) sandeeph@Sandeeps-MacBook-Pro api % df -h /
df -h /System/Volumes/Data
du -sh ~/Library/Developer 2>/dev/null
du -sh ~/Library/Caches 2>/dev/null
du -sh ~/Documents 2>/dev/null
Filesystem        Size    Used   Avail Capacity iused ifree %iused  Mounted on
/dev/disk3s1s1   460Gi    12Gi   158Mi    99%    459k  1.6M   22%   /
Filesystem      Size    Used   Avail Capacity iused ifree %iused  Mounted on
/dev/disk3s5   460Gi   438Gi   158Mi   100%    2.0M  1.6M   56%   /System/Volumes/Data
 24G    /Users/sandeeph/Library/Caches
186G    /Users/sandeeph/Documents
(base) sandeeph@Sandeeps-MacBook-Pro api % brew --prefix postgresql@17
psql -d postgres -tAc "SHOW data_directory;"
/opt/homebrew/opt/postgresql@17
/opt/homebrew/var/postgresql@17
(base) sandeeph@Sandeeps-MacBook-Pro api %
(base) sandeeph@Sandeeps-MacBook-Pro api % clear
(base) sandeeph@Sandeeps-MacBook-Pro api % df -h /System/Volumes/Data
pg_isready
Filesystem      Size    Used   Avail Capacity iused ifree %iused  Mounted on
/dev/disk3s5   460Gi   417Gi    20Gi    96%    2.0M  214M    1%   /System/Volumes/Data
/tmp:5432 - accepting connections
```

```
(base) sandeeph@Sandeeps-MacBook-Pro api % createdb finsight_test
psql -d finsight_test -c "SELECT current_database(), current_user, version();"
 current_database | current_user |                                                 version
------------------+--------------+-----------------------------------------------------------------------------------------------------
---------------------------------
 finsight_test    | sandeeph     | PostgreSQL 17.6 (Homebrew) on aarch64-apple-darwin25.0.0,
compiled by Apple clang version 17.0.0 (clang-1700.3.19.1), 64-bit
(1 row)
(base) sandeeph@Sandeeps-MacBook-Pro api % psql -d finsight_test -v ON_ERROR_STOP=1
-f apps/api/migrations/0001_auth_identity.sql
psql -d finsight_test -v ON_ERROR_STOP=1 -f
apps/api/migrations/0002_platform_authorization.sql
psql: error: apps/api/migrations/0001_auth_identity.sql: No such file or directory
psql: error: apps/api/migrations/0002_platform_authorization.sql: No such file or directory
(base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % psql -d finsight_test -v
ON_ERROR_STOP=1 -f apps/api/migrations/0001_auth_identity.sql
psql -d finsight_test -v ON_ERROR_STOP=1 -f
apps/api/migrations/0002_platform_authorization.sql
BEGIN
CREATE TABLE
CREATE TABLE
CREATE INDEX
CREATE TABLE
CREATE INDEX
COMMIT
BEGIN
CREATE TABLE
CREATE TABLE
INSERT 0 1
DO
INSERT 0 1
INSERT 0 1
CREATE FUNCTION
CREATE TRIGGER
CREATE FUNCTION
CREATE TRIGGER
COMMIT
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
..F
[100%]
```

```
=========================================================================
======== FAILURES
=========================================================================
========

_____________________________________________________________
test_platform_role_assignment_rejects_workspace_scoped_roles
_____________________________________________________________
    def test_platform_role_assignment_rejects_workspace_scoped_roles():
        email = f"wrong-scope-{uuid4().hex}@example.test"
        with connect() as conn, conn.cursor() as cur:
>           cur.execute(
                "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s, 'workspace')
RETURNING role_id",
                (f"synthetic-workspace-{uuid4().hex}", "Synthetic Workspace Role"),
            )
tests/test_identity_constraints.py:94:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
self = <psycopg.Cursor [closed] [BAD] at 0x11ce647d0>, query = "INSERT INTO roles
(role_key, display_name, scope) VALUES (%s, %s, 'workspace') RETURNING role_id"
params = ('synthetic-workspace-47234ef256b54a6f894c6a716489fd5e', 'Synthetic Workspace
Role')
    def execute(
        self,
        query: Query,
        params: Params | None = None,
        *,
        prepare: bool | None = None,
        binary: bool | None = None,
    ) -> Self:
        """
        Execute a query or command to the database.
        """
        try:
            with self._conn.lock:
                self._conn.wait(
                    self._execute_gen(query, params, prepare=prepare, binary=binary)
                )
        except e._NO_TRACEBACK as ex:
>           raise ex.with_traceback(None)
E           psycopg.errors.StringDataRightTruncation: value too long for type character varying(50)
/opt/anaconda3/lib/python3.14/site-packages/psycopg/cursor.py:97: StringDataRightTruncation
=========================================================================
==== warnings summary
```

```
=============================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=============================================================================
short test summary info
=============================================================================
=
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - psycopg.errors.StringDataRightTruncation: value too long for type character varying(50)
1 failed, 2 passed, 3 warnings in 26.85s
(base) sandeeph@Sandeeps-MacBook-Pro api %
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % psql -d finsight_test -v
ON_ERROR_STOP=1 -f apps/api/migrations/0001_auth_identity.sql
psql -d finsight_test -v ON_ERROR_STOP=1 -f
apps/api/migrations/0002_platform_authorization.sql
BEGIN
CREATE TABLE
CREATE TABLE
CREATE INDEX
CREATE TABLE
CREATE INDEX
COMMIT
BEGIN
CREATE TABLE
CREATE TABLE
INSERT 0 1
DO
INSERT 0 1
INSERT 0 1
CREATE FUNCTION
```

```
CREATE TRIGGER
CREATE FUNCTION
CREATE TRIGGER
COMMIT
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
..F
[100%]
================================================================================
======== FAILURES
================================================================================
========

_____________________________________________________________
test_platform_role_assignment_rejects_workspace_scoped_roles
_____________________________________________________________
    def test_platform_role_assignment_rejects_workspace_scoped_roles():
        email = f"wrong-scope-{uuid4().hex}@example.test"
        with connect() as conn, conn.cursor() as cur:
>           cur.execute(
              "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s, 'workspace')
RETURNING role_id",
              (f"synthetic-workspace-{uuid4().hex}", "Synthetic Workspace Role"),
            )
tests/test_identity_constraints.py:94:
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
self = <psycopg.Cursor [closed] [BAD] at 0x11ce647d0>, query = "INSERT INTO roles
(role_key, display_name, scope) VALUES (%s, %s, 'workspace') RETURNING role_id"
params = ('synthetic-workspace-47234ef256b54a6f894c6a716489fd5e', 'Synthetic Workspace
Role')
    def execute(
        self,
        query: Query,
        params: Params | None = None,
        *,
        prepare: bool | None = None,
        binary: bool | None = None,
    ) -> Self:
        """
        Execute a query or command to the database.
        """
        try:
            with self._conn.lock:
```

```
                self._conn.wait(
                    self._execute_gen(query, params, prepare=prepare, binary=binary)
                )
        except e._NO_TRACEBACK as ex:
>           raise ex.with_traceback(None)
E           psycopg.errors.StringDataRightTruncation: value too long for type character varying(50)
/opt/anaconda3/lib/python3.14/site-packages/psycopg/cursor.py:97: StringDataRightTruncation
=============================================================================
==== warnings summary
=============================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=============================================================================
short test summary info
=============================================================================
=
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - psycopg.errors.StringDataRightTruncation: value too long for type character varying(50)
1 failed, 2 passed, 3 warnings in 26.85s
(base) sandeeph@Sandeeps-MacBook-Pro api % DATABASE_URL="postgresql:///finsight_test"
python -m pytest -q
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles
F
[100%]
=============================================================================
======== FAILURES
=============================================================================
========
```

```
_____ test_platform_role_assignment_rejects_workspace_scoped_roles _____
    def test_platform_role_assignment_rejects_workspace_scoped_roles():
        email = f"wrong-scope-{uuid4().hex}@example.test"
        with connect() as conn, conn.cursor() as cur:
>           cur.execute(
                "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s, 'workspace') RETURNING role_id",
                (f"synthetic-workspace-{uuid4().hex}", "Synthetic Workspace Role"),
            )
tests/test_identity_constraints.py:94:
_ _ _ _
```

```
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=========================================================================
short test summary info
=========================================================================
=
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - psycopg.errors.StringDataRightTruncation: value too long for type character varying(50)
1 failed, 1 warning in 41.39s
(base) sandeeph@Sandeeps-MacBook-Pro api %
    from starlette.testclient import TestClient as TestClient  # noqa
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=========================================================================
short test summary info
=========================================================================
=
FAILED
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles - psycopg.errors.StringDataRightTruncation: value too long for type character varying(50)
1 failed, 1 warning in 41.39s
(base) sandeeph@Sandeeps-MacBook-Pro api % DATABASE_URL="postgresql:///finsight_test"
python -m pytest -q
tests/test_identity_constraints.py::test_platform_role_assignment_rejects_workspace_scoped_r
oles
.
[100%]
=========================================================================
==== warnings summary
=========================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
1 passed, 1 warning in 11.42s
(base) sandeeph@Sandeeps-MacBook-Pro api % DATABASE_URL="postgresql:///finsight_test"
python -m pytest -q tests/test_identity_constraints.py
```

```
...
[100%]
=============================================================================
==== warnings summary
=============================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
3 passed, 3 warnings in 0.26s
(base) sandeeph@Sandeeps-MacBook-Pro api % DATABASE_URL="postgresql:///finsight_test"
python -m pytest -q
.....................................................
[100%]
=============================================================================
==== warnings summary
=============================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[get-/a
uth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[post-/
auth/logout-kwargs1]
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
```

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
55 passed, 9 warnings in 9.52s
(base) sandeeph@Sandeeps-MacBook-Pro api %
55 passed, 9 warnings in 9.52s
(base) sandeeph@Sandeeps-MacBook-Pro api % grep -R -n "require_permission" app tests
grep -n -E "@app\\.(get|post|put|patch|delete)|require_permission|/auth/" app/main.py
Binary file app/__pycache__/main.cpython-312.pyc matches
Binary file app/__pycache__/main.cpython-314.pyc matches
app/main.py:109:def require_permission(permission_key: str):
tests/test_identity_constraints.py:12:from app.main import SESSION_COOKIE, require_permission
tests/test_identity_constraints.py:74:   lambda _authorized=Depends(require_permission("platform.admin")): {"allowed": True},
Binary file tests/__pycache__/test_auth_unit.cpython-312-pytest-9.0.3.pyc matches
Binary file tests/__pycache__/test_identity_constraints.cpython-314-pytest-9.0.3.pyc matches
Binary file tests/__pycache__/test_auth_unit.cpython-314-pytest-9.0.3.pyc matches
tests/test_auth_unit.py:109:   lambda _authorized=Depends(main.require_permission("platform.admin")): {"allowed": True},
tests/test_auth_unit.py:128:   lambda _authorized=Depends(main.require_permission("platform.admin")): {"allowed": True},
109:def require_permission(permission_key: str):
119:@app.post("/auth/login", response_model=UserView)
160:@app.post("/auth/logout", status_code=204)
179:@app.get("/auth/me", response_model=UserView)
(base) sandeeph@Sandeeps-MacBook-Pro api %
apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[get-/auth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[post-/auth/logout-kwargs1]
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session

```
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
55 passed, 9 warnings in 9.52s
(base) sandeeph@Sandeeps-MacBook-Pro api % grep -R -n "require_permission" app tests
grep -n -E "@app\\.(get|post|put|patch|delete)|require_permission|/auth/" app/main.py
Binary file app/__pycache__/main.cpython-312.pyc matches
Binary file app/__pycache__/main.cpython-314.pyc matches
app/main.py:109:def require_permission(permission_key: str):
tests/test_identity_constraints.py:12:from app.main import SESSION_COOKIE,
require_permission
tests/test_identity_constraints.py:74:        lambda
_authorized=Depends(require_permission("platform.admin")): {"allowed": True},
Binary file tests/__pycache__/test_auth_unit.cpython-312-pytest-9.0.3.pyc matches
Binary file tests/__pycache__/test_identity_constraints.cpython-314-pytest-9.0.3.pyc matches
Binary file tests/__pycache__/test_auth_unit.cpython-314-pytest-9.0.3.pyc matches
tests/test_auth_unit.py:109:        lambda
_authorized=Depends(main.require_permission("platform.admin")): {"allowed": True},
tests/test_auth_unit.py:128:        lambda
_authorized=Depends(main.require_permission("platform.admin")): {"allowed": True},
109:def require_permission(permission_key: str):
119:@app.post("/auth/login", response_model=UserView)
160:@app.post("/auth/logout", status_code=204)
179:@app.get("/auth/me", response_model=UserView)
(base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
git status --short
git diff --check
git diff --stat
Refresh index: 100% (71/71), done.
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? apps/api/migrations/0002_platform_authorization.sql
```

```
?? apps/web/proxy.js
 .github/workflows/ci.yml                  |  4 ++++
 IMPLEMENTATION_STATUS.txt                 |  7 +++++++
 README.md                                 |  8 ++++++--
 apps/api/app/main.py                      | 20 ++++++++++++++++++--
 apps/api/app/provision_user.py            | 16 ++++++++++------
 apps/api/tests/test_auth_unit.py          | 40
++++++++++++++++++++++++++++++++++++++++
 apps/api/tests/test_identity_constraints.py | 71
+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
 apps/api/tests/test_provision_user.py     | 37 +++++++++++++++++++++++++++++++++++-
 apps/web/tests/ui/auth.spec.js            | 10 ++++++++++
 conversation.txt                          |  8 ++++++++
 docs/architecture/README.md               |  4 ++--
 scripts/package_release.py                |  2 +-
 12 files changed, 213 insertions(+), 14 deletions(-)
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cat >>
IMPLEMENTATION_STATUS.txt <<'EOF'
FIN-15 verification update — 2026-10-20
- PostgreSQL 17.6 is running locally.
- Created and used the dedicated finsight_test database.
- Applied apps/api/migrations/0001_auth_identity.sql successfully.
- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API test suite: 55 passed, 0 failed, 9 warnings.
- git diff --check: no errors reported.
- Warning: Starlette/httpx deprecation warnings remain.
- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual
application route was found using it in the current route inspection.
- FIN-15 is not yet marked complete pending route-level authorization verification and remaining
acceptance checks.
EOF
cat >> SPRINT_1_TEST_EXECUTION_STATUS.txt <<'EOF'
Additional test evidence — 2026-10-20
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
- Result: 3 passed, 0 failed, 3 warnings.
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
- Result: 55 passed, 0 failed, 9 warnings in 9.52s.
- Environment: local PostgreSQL 17.6; dedicated finsight_test database.
- Migrations applied successfully before test execution: 0001_auth_identity.sql and
0002_platform_authorization.sql.
- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
```

- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
EOF
cat >> conversation.txt <<'EOF'
2026-10-20 — FIN-15 verification checkpoint
- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.
EOF
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % tail -n 18
IMPLEMENTATION_STATUS.txt
tail -n 18 SPRINT_1_TEST_EXECUTION_STATUS.txt
tail -n 18 conversation.txt
git diff --check
git status --short
FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)
Status: BLOCKED pending role-scope decision; implementation not started.
Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorizeminimal canonical workspace membership model.
Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.
Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be

completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.

FIN-15 verification update — 2026-10-20

- PostgreSQL 17.6 is running locally.
- Created and used the dedicated finsight_test database.
- Applied apps/api/migrations/0001_auth_identity.sql successfully.
- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API test suite: 55 passed, 0 failed, 9 warnings.
- git diff --check: no errors reported.
- Warning: Starlette/httpx deprecation warnings remain.
- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.

TC_EXEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_EXEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_EXEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_DASH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_DASH_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_INT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_BOUNDARY_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

Additional test evidence — 2026-10-20

- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q tests/test_identity_constraints.py
- Result: 3 passed, 0 failed, 3 warnings.
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
- Result: 55 passed, 0 failed, 9 warnings in 9.52s.
- Environment: local PostgreSQL 17.6; dedicated finsight_test database.
- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.

- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
FIN-79 / FS-11-08 — SRS addendum and requirement traceability (2026-10-19)
Status: PARTIAL. Added `docs/requirements/traceability-matrix.md`, 409-row `traceability-requirements.csv`, 72-row `traceability-stories.csv`, and `srs-addendum.md`; added `scripts/validate_traceability.py` and README links. All source requirements and aliases are represented; Jira keys and test statuses remain separately identified. 328requirement rows map to story aliases via Jira text or explicit test-plan traceability; 81 remain unmapped. Of 23 Sprint 1 stories, 22 carry explicit SRS IDs; FS-11-09/FIN-80 is a management/process story without a direct SRS ID. All 54 supplied test cases map to a catalog story. 104 requirement rows have supplied linked tests; 305 do not. Test-plan requirement ranges were expanded across all IDs in each interval. Q-009/Q-010 request disposition of unmapped requirements and FIN-84–FIN-87. TC_TRACE_001 isPASS; no other test status was changed. Validation command: `python3 scripts/validate_traceability.py` (PASS; 409 requirements, 72 aliases, 54 tests; records the two source tests missing explicit execution rows as NOT RUN). `python3 -m py_compile scripts/validate_traceability.py` and local Markdown relative-link checks passed. Source PDFs, SQL, diagrams, and original test plan remain read-only. No Jira or Git action was taken.
FIN-73 targeted CI repair — run 39203215763 (2026-10-19)
Status: local fixes verified; remote confirmation pending. Corrected frontend artifact packaging in `.github/workflows/ci.yml` to archive from `.next` under working directory `apps/web`, with explicit hard-failing checks for `.next/standalone` and `.next/static`. Existing E2E and release-package extract/restore paths continue to use archive-root `standalone/` and `static/`. Normalized `docs/requirements/traceability-stories.csv` CRLF to LF; CSV parsing against HEAD proved all 73 rows and field values identical. No trailing whitespace remains. Removed one extra blank EOF line in `scripts/validate_traceability.py`, retaining the final newline. No repository CSV generator exists; validator is read-only.
Local checks: PyYAML workflow parse/target assertions PASS; `NEXT_TELEMETRY_DISABLED=1 npm run build` PASS (exit 0; Next 16.4.2); `.next/standalone` and `.next/static` exist; exact tar packaging command succeeded and archive inspection confirmed only `standalone/` and `static/` roots, 1,466 entries, SHA-256 `651f28563199baf95574f9c23fc78e2b8d6a10a88bf4a114c3fc033b744c3513`; `python3 scripts/validate_traceability.py` PASS; Python compilation PASS; CSV whitespace scan 0 rows; `git diff --check` PASS. No backend/security/Playwright suites were rerun.
Caveat: `git show --check --format= HEAD` on the existing root commit exits 2 with 1,323 historical whitespace diagnostics including immutable PDFs and other existing files. These were not changed. Current incremental worktree diff passes. A new incremental commit/push and GitHub Actions run are required to confirm the corrected workflow; no commit, push, Jira update, or rerun was performed.
Final validation note: after updating the coordination records, bounded `git diff --check` timed out at 8 seconds. Earlier targeted `git diff --check` completed with exit 0, and direct whitespace scans of all affected text files found zero trailing-whitespace lines and valid final newlines. Treat final full Git diff hygiene as incompletedue intermittent Git responsiveness; the incremental GitHub Actions run remains required.
2026-10-20 — FIN-15 verification checkpoint

- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.

```
warning: Not a git repository. Use --no-index to compare two paths outside a working tree
usage: git diff --no-index [<options>] <path> <path> [<pathspec>...]
Diff output format options
    -p, --patch           generate patch
    -s, --no-patch        suppress diff output
    -u                    generate patch
    -U, --unified[=<n>]   generate diffs with <n> lines context
    -W, --[no-]function-context
                          generate diffs with <n> lines context
    --raw                 generate the diff in raw format
    --patch-with-raw      synonym for '-p --raw'
    --patch-with-stat     synonym for '-p --stat'
    --numstat             machine friendly --stat
    --shortstat           output only the last line of --stat
    -X, --dirstat[=<param1>,<param2>...]
                          output the distribution of relative amount of changes for each sub-directory
    --cumulative          synonym for --dirstat=cumulative
    --dirstat-by-file[=<param1>,<param2>...]
                          synonym for --dirstat=files,<param1>,<param2>...
    --check               warn if changes introduce conflict markers or whitespace errors
    --summary             condensed summary such as creations, renames and mode changes
    --name-only           show only names of changed files
    --name-status         show only names and status of changed files
    --stat[=<width>[,<name-width>[,<count>]]]
                          generate diffstat
    --stat-width <width>  generate diffstat with a given width
    --stat-name-width <width>
                          generate diffstat with a given name width
    --stat-graph-width <width>
                          generate diffstat with a given graph width
    --stat-count <count>  generate diffstat with limited lines
    --[no-]compact-summary
                          generate compact summary in diffstat
    --binary              output a binary diff that can be applied
    --[no-]full-index     show full pre- and post-image object names on the "index" lines
```

```
    --[no-]color[=<when>] show colored diff
    --ws-error-highlight <kind>
                          highlight whitespace errors in the 'context', 'old' or 'new' lines in the diff
    -z                    do not munge pathnames and use NULs as output field terminators in --raw or
--numstat
    --[no-]abbrev[=<n>]   use <n> digits to display object names
    --src-prefix <prefix> show the given source prefix instead of "a/"
    --dst-prefix <prefix> show the given destination prefix instead of "b/"
    --line-prefix <prefix>
                          prepend an additional prefix to every line of output
    --no-prefix           do not show any source or destination prefix
    --default-prefix      use default prefixes a/ and b/
    --inter-hunk-context <n>
                          show context between diff hunks up to the specified number of lines
    --output-indicator-new <char>
                          specify the character to indicate a new line instead of '+'
    --output-indicator-old <char>
                          specify the character to indicate an old line instead of '-'
    --output-indicator-context <char>
                          specify the character to indicate a context instead of ' '
Diff rename options
    -B, --break-rewrites[=<n>[/<m>]]
                          break complete rewrite changes into pairs of delete and create
    -M, --find-renames[=<n>]
                          detect renames
    -D, --irreversible-delete
                          omit the preimage for deletes
    -C, --find-copies[=<n>]
                          detect copies
    --[no-]find-copies-harder
                          use unmodified files as source to find copies
    --no-renames          disable rename detection
    --[no-]rename-empty   use empty blobs as rename source
    --[no-]follow         continue listing the history of a file beyond renames
    -l <n>                prevent rename/copy detection if the number of rename/copy targets exceeds
given limit
Diff algorithm options
    --minimal             produce the smallest possible diff
    -w, --ignore-all-space
                          ignore whitespace when comparing lines
    -b, --ignore-space-change
                          ignore changes in amount of whitespace
    --ignore-space-at-eol ignore changes in whitespace at EOL
    --ignore-cr-at-eol    ignore carrier-return at the end of line
```

```
    --ignore-blank-lines  ignore changes whose lines are all blank
    -I, --[no-]ignore-matching-lines <regex>
                          ignore changes whose all lines match <regex>
    --[no-]indent-heuristic
                          heuristic to shift diff hunk boundaries for easy reading
    --patience            generate diff using the "patience diff" algorithm
    --histogram           generate diff using the "histogram diff" algorithm
    --diff-algorithm <algorithm>
                          choose a diff algorithm
    --anchored <text>     generate diff using the "anchored diff" algorithm
    --word-diff[=<mode>]  show word diff, using <mode> to delimit changed words
    --word-diff-regex <regex>
                          use <regex> to decide what a word is
    --color-words[=<regex>]
                          equivalent to --word-diff=color --word-diff-regex=<regex>
    --[no-]color-moved[=<mode>]
                          moved lines of code are colored differently
    --[no-]color-moved-ws <mode>
                          how white spaces are ignored in --color-moved
Other diff options
    --[no-]relative[=<prefix>]
                          when run from subdir, exclude changes outside and show relative paths
    -a, --[no-]text       treat all files as text
    -R                    swap two inputs, reverse the diff
    --[no-]exit-code      exit with 1 if there were differences, 0 otherwise
    --[no-]quiet          disable all output of the program
    --[no-]ext-diff       allow an external diff helper to be executed
    --[no-]textconv       run external text conversion filters when comparing binary files
    --ignore-submodules[=<when>]
                          ignore changes to submodules in the diff generation
    --submodule[=<format>]
                          specify how differences in submodules are shown
    --ita-invisible-in-index
                          hide 'git add -N' entries from the index
    --ita-visible-in-index
                          treat 'git add -N' entries as real in the index
    -S <string>           look for differences that change the number of occurrences of the specified
string
    -G <regex>            look for differences that change the number of occurrences of the
specified regex
    --pickaxe-all         show all changes in the changeset with -S or -G
    --pickaxe-regex       treat <string> in -S as extended POSIX regular expression
    -O <file>             control the order in which files appear in the output
    --rotate-to <path>    show the change in the specified path first
```

```
   --skip-to <path>      skip the output to the specified path
   --find-object <object-id>
                         look for differences that change the number of occurrences of the specified
object
   --diff-filter [(A|C|D|M|R|T|U|X|B)...[*]]
                         select files by diff type
   --max-depth <depth>   maximum tree depth to recurse
   --output <file>       output to a specific file
fatal: not a git repository (or any of the parent directories): .git
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % pwd
ls -la .git
git status --short
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI
total 16
drwxr-xr-x@  13 sandeeph  staff   416 Oct 20 12:19 .
drwxr-xr-x@  26 sandeeph  staff   832 Oct 20 12:19 ..
-rw-r--r--@   1 sandeeph  staff    29 Oct 19 10:58 COMMIT_EDITMSG
-rw-r--r--@   1 sandeeph  staff    21 Oct 18 10:15 HEAD
-rw-r--r--@   1 sandeeph  staff   351 Oct 19 10:59 config
-rw-r--r--@   1 sandeeph  staff    73 Oct 18 10:15 description
drwxr-xr-x@  16 sandeeph  staff   512 Oct 18 10:16 hooks
-rw-r--r--@   1 sandeeph  staff  8146 Oct 20 12:02 index
drwxr-xr-x@   3 sandeeph  staff    96 Oct 18 10:16 info
drwxr-xr-x@   4 sandeeph  staff   128 Oct 19 11:24 logs
drwxr-xr-x@ 107 sandeeph  staff  3424 Oct 20 12:19 objects
-rw-r--r--@   1 sandeeph  staff   112 Oct 18 10:15 packed-refs
drwxr-xr-x@   6 sandeeph  staff   192 Oct 19 11:05 refs
fatal: not a git repository (or any of the parent directories): .git
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % tail -n 20
IMPLEMENTATION_STATUS.txt
tail -n 20 SPRINT_1_TEST_EXECUTION_STATUS.txt
tail -n 20 conversation.txt
```

Final review note (2026-10-19): `git diff --check` exited 0 for the targeted workflow/CSV/script changes before coordination records were appended. A later full `git diff --check` attempt timed out after 8 seconds (intermittent Git responsiveness); direct trailing-whitespace scans of `.github/workflows/ci.yml`, `docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both updated coordination files found zero whitespace errors and all had final newlines. The historical root-commit check result above remains distinct from the current worktree check.

FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)

Status: BLOCKED pending role-scope decision; implementation not started.

Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST

`/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorizeminimal canonical workspace membership model.
Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.
Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
FIN-15 verification update — 2026-10-20
- PostgreSQL 17.6 is running locally.
- Created and used the dedicated finsight_test database.
- Applied apps/api/migrations/0001_auth_identity.sql successfully.
- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API test suite: 55 passed, 0 failed, 9 warnings.
- git diff --check: no errors reported.
- Warning: Starlette/httpx deprecation warnings remain.
- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
TC_PRIV_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_EXEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_EXEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_EXEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_DASH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_DASH_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_INT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_BOUNDARY_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
Additional test evidence — 2026-10-20
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q tests/test_identity_constraints.py
- Result: 3 passed, 0 failed, 3 warnings.
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
- Result: 55 passed, 0 failed, 9 warnings in 9.52s.
- Environment: local PostgreSQL 17.6; dedicated finsight_test database.
- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
Recommended decision: Confirm whether the four issues are supplemental Jira work outside the source catalog, or provide an approved source alias/document reference for each. Keep them separate until confirmed.
Exact next action: Reply with `FIN-84–FIN-87 are supplemental` or provide the approved alias and source document reference for each issue. No Jira changes are pending/authorized.
FIN-79 / FS-11-08 — SRS addendum and requirement traceability (2026-10-19)
Status: PARTIAL. Added `docs/requirements/traceability-matrix.md`, 409-row `traceability-requirements.csv`, 72-row `traceability-stories.csv`, and `srs-addendum.md`; added `scripts/validate_traceability.py` and README links. All source requirements and aliases are represented; Jira keys and test statuses remain separately identified. 328requirement rows map to story aliases via Jira text or explicit test-plan traceability; 81 remain unmapped. Of 23 Sprint 1 stories, 22 carry explicit SRS IDs; FS-11-09/FIN-80 is a management/process story without a direct SRS ID. All 54 supplied test cases map to a catalog story. 104 requirement rows have supplied linked tests; 305 do not. Test-plan requirement ranges were expanded across all IDs in each interval. Q-009/Q-010 request disposition of unmapped requirements and FIN-84–FIN-87. TC_TRACE_001 isPASS; no other test status was changed. Validation command: `python3 scripts/validate_traceability.py` (PASS; 409 requirements, 72 aliases, 54 tests; records the two source tests missing explicit execution rows as NOT RUN). `python3 -m py_compile scripts/validate_traceability.py` and local Markdown relative-link checks passed. Source PDFs, SQL, diagrams, and original test plan remain read-only. No Jira or Git action was taken.

FIN-73 targeted CI repair — run 39203215763 (2026-10-19)
Status: local fixes verified; remote confirmation pending. Corrected frontend artifact packaging in `.github/workflows/ci.yml` to archive from `.next` under working directory `apps/web`, with explicit hard-failing checks for `.next/standalone` and `.next/static`. Existing E2E and release-package extract/restore paths continue to use archive-root `standalone/` and `static/`. Normalized `docs/requirements/traceability-stories.csv` CRLF to LF; CSV parsing against HEAD proved all 73 rows and field values identical. No trailing whitespace remains. Removed one extra blank EOF line in `scripts/validate_traceability.py`, retaining the final newline. No repository CSV generator exists; validator is read-only.
Local checks: PyYAML workflow parse/target assertions PASS; `NEXT_TELEMETRY_DISABLED=1 npm run build` PASS (exit 0; Next 16.4.2); `.next/standalone` and `.next/static` exist; exact tar packaging command succeeded and archive inspection confirmed only `standalone/` and `static/` roots, 1,466 entries, SHA-256 `651f28563199baf95574f9c23fc78e2b8d6a10a88bf4a114c3fc033b744c3513`; `python3 scripts/validate_traceability.py` PASS; Python compilation PASS; CSV whitespace scan 0 rows; `git diff --check` PASS. No backend/security/Playwright suites were rerun.
Caveat: `git show --check --format= HEAD` on the existing root commit exits 2 with 1,323 historical whitespace diagnostics including immutable PDFs and other existing files. These were not changed. Current incremental worktree diff passes. A new incremental commit/push and GitHub Actions run are required to confirm the corrected workflow; no commit, push, Jira update, or rerun was performed.
Final validation note: after updating the coordination records, bounded `git diff --check` timed out at 8 seconds. Earlier targeted `git diff --check` completed with exit 0, and direct whitespace scans of all affected text files found zero trailing-whitespace lines and valid final newlines. Treat final full Git diff hygiene as incompletedue intermittent Git responsiveness; the incremental GitHub Actions run remains required.
2026-10-20 — FIN-15 verification checkpoint
- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
d `scripts/validate_traceability.py` and README links. All source requirements and aliases are represented; Jira keys and test statuses remain separately identified. 328requirement rows map to story aliases via Jira text or explicit test-plan traceability; 81 remain unmapped. Of 23 Sprint 1 stories, 22 carry explicit SRS IDs; FS-11-09/FIN-80 is a management/process story without a direct SRS ID. All 54 supplied test cases map to a catalog story. 104 requirement rows have supplied linked tests; 305 do not. Test-plan requirement ranges were expanded across all IDs in each interval. Q-009/Q-010 request disposition of unmapped requirements and FIN-84–FIN-87.

TC_TRACE_001 isPASS; no other test status was changed. Validation command: `python3 scripts/validate_traceability.py` (PASS; 409 requirements, 72 aliases, 54 tests; records the two source tests missing explicit execution rows as NOT RUN). `python3 -m py_compile scripts/validate_traceability.py` and local Markdown relative-link checks passed. Source PDFs, SQL, diagrams, and original test plan remain read-only. No Jira or Git action was taken.
FIN-73 targeted CI repair — run 39203215763 (2026-10-19)
Status: local fixes verified; remote confirmation pending. Corrected frontend artifact packaging in `.github/workflows/ci.yml` to archive from `.next` under working directory `apps/web`, with explicit hard-failing checks for `.next/standalone` and `.next/static`. Existing E2E and release-package extract/restore paths continue to use archive-root `standalone/` and `static/`. Normalized `docs/requirements/traceability-stories.csv` CRLF to LF; CSV parsing against HEAD proved all 73 rows and field values identical. No trailing whitespace remains. Removed one extra blank EOF line in `scripts/validate_traceability.py`, retaining the final newline. No repository CSV generator exists; validator is read-only.
Local checks: PyYAML workflow parse/target assertions PASS; `NEXT_TELEMETRY_DISABLED=1 npm run build` PASS (exit 0; Next 16.4.2); `.next/standalone` and `.next/static` exist; exact tar packaging command succeeded and archive inspection confirmed only `standalone/` and `static/` roots, 1,466 entries, SHA-256 `651f28563199baf95574f9c23fc78e2b8d6a10a88bf4a114c3fc033b744c3513`; `python3 scripts/validate_traceability.py` PASS; Python compilation PASS; CSV whitespace scan 0 rows; `git diff --check` PASS. No backend/security/Playwright suites were rerun.
Caveat: `git show --check --format= HEAD` on the existing root commit exits 2 with 1,323 historical whitespace diagnostics including immutable PDFs and other existing files. These were not changed. Current incremental worktree diff passes. A new incremental commit/push and GitHub Actions run are required to confirm the corrected workflow; no commit, push, Jira update, or rerun was performed.
Final validation note: after updating the coordination records, bounded `git diff --check` timed out at 8 seconds. Earlier targeted `git diff --check` completed with exit 0, and direct whitespace scans of all affected text files found zero trailing-whitespace lines and valid final newlines. Treat final full Git diff hygiene as incompletedue intermittent Git responsiveness; the incremental GitHub Actions run remains required.
2026-10-20 — FIN-15 verification checkpoint
- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % pwd
git --version
env | grep '^GIT_'

ls -ld .git
cat .git/HEAD
git rev-parse --show-toplevel
git -C "$PWD" rev-parse --git-dir
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI
git version 2.54.0 (Apple Git-157)
GIT_ASKPASS=/Applications/Visual Studio
Code.app/Contents/Resources/app/extensions/git/dist/askpass.sh
drwxr-xr-x@ 13 sandeeph staff 416 Oct 20 12:19 .git
cat: .git/HEAD: Operation timed out
fatal: not a git repository (or any of the parent directories): .git
fatal: not a git repository (or any of the parent directories): .git
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % pwd
git --version
env | grep '^GIT_'
ls -ld .git
cat .git/HEAD
git rev-parse --show-toplevel
git -C "$PWD" rev-parse --git-dir
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI
git version 2.54.0 (Apple Git-157)
GIT_ASKPASS=/Applications/Visual Studio
Code.app/Contents/Resources/app/extensions/git/dist/askpass.sh
drwxr-xr-x@ 13 sandeeph staff 416 Oct 20 12:19 .git
cat: .git/HEAD: Operation timed out
fatal: not a git repository (or any of the parent directories): .git
fatal: not a git repository (or any of the parent directories): .git
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
zsh: parse error near `sandeeph@Sandeeps-Ma...'
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % ls -l .git/HEAD
stat .git/HEAD
cat .git/config
cat .git/HEAD
-rw-r--r--@ 1 sandeeph staff 21 Oct 18 10:15 .git/HEAD
16777230 91699237 -rw-r--r-- 1 sandeeph staff 0 21 "Oct 18 11:36:11 2026" "Oct 18 10:15:55 2026" "Oct 20 12:19:09 2026" "Oct 18 10:15:55 2026" 4096 0 0x40008060 .git/HEAD

```
cat: .git/config: Operation timed out
cat: .git/HEAD: Operation timed out
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % ls -la .git
ls -la .git/refs/heads
ls -la .git/logs
total 16
drwxr-xr-x@  13 sandeeph  staff   416 Oct 20 12:19 .
drwxr-xr-x@  26 sandeeph  staff   832 Oct 20 12:19 ..
-rw-r--r--@   1 sandeeph  staff    29 Oct 19 10:58 COMMIT_EDITMSG
-rw-r--r--@   1 sandeeph  staff    21 Oct 18 10:15 HEAD
-rw-r--r--@   1 sandeeph  staff   351 Oct 19 10:59 config
-rw-r--r--@   1 sandeeph  staff    73 Oct 18 10:15 description
drwxr-xr-x@  16 sandeeph  staff   512 Oct 18 10:16 hooks
-rw-r--r--@   1 sandeeph  staff  8146 Oct 20 12:02 index
drwxr-xr-x@   3 sandeeph  staff    96 Oct 18 10:16 info
drwxr-xr-x@   4 sandeeph  staff   128 Oct 19 11:24 logs
drwxr-xr-x@ 107 sandeeph  staff  3424 Oct 20 12:19 objects
-rw-r--r--@   1 sandeeph  staff   112 Oct 18 10:15 packed-refs
drwxr-xr-x@   6 sandeeph  staff   192 Oct 19 11:05 refs
total 0
drwxr-xr-x@ 4 sandeeph  staff  128 Oct 19 11:05 .
drwxr-xr-x@ 6 sandeeph  staff  192 Oct 19 11:05 ..
-rw-r--r--@ 1 sandeeph  staff   41 Oct 19 10:58 main
-rw-------  1 sandeeph  staff   41 Oct 18 10:15 main 2
total 0
drwxr-xr-x@  4 sandeeph  staff  128 Oct 19 11:24 .
drwxr-xr-x@ 13 sandeeph  staff  416 Oct 20 12:19 ..
-rw-r--r--@  1 sandeeph  staff  603 Oct 19 10:58 HEAD
drwxr-xr-x@  4 sandeeph  staff  128 Oct 19 11:24 refs
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % ls -l IMPLEMENTATION_STATUS.txt
conversation.txt
tail -n 8 IMPLEMENTATION_STATUS.txt
tail -n 8 conversation.txt
-rw-r--r--@ 1 sandeeph  staff  52635 Oct 20 12:14 IMPLEMENTATION_STATUS.txt
-rw-r--r--@ 1 sandeeph  staff  30708 Oct 20 12:14 conversation.txt
- Applied apps/api/migrations/0001_auth_identity.sql successfully.
- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API test suite: 55 passed, 0 failed, 9 warnings.
- git diff --check: no errors reported.
- Warning: Starlette/httpx deprecation warnings remain.
- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual
application route was found using it in the current route inspection.
```

- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
2026-10-20 — FIN-15 verification checkpoint
- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % git status
fatal: not a git repository (or any of the parent directories): .git
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % file .git/HEAD .git/config
.git/HEAD: ERROR: cannot read `.git/HEAD' (Operation timed out)
.git/config: ERROR: cannot read `.git/config' (Operation timed out)
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % xattr -l .git/HEAD
com.apple.provenance:
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % dd if=.git/HEAD
of=/tmp/finsight-head-check bs=1 count=21
dd: /tmp/finsight-head-check: No space left on device
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % df -h .
mount | grep -E ' /System/Volumes/Data |/Volumes/'
Filesystem   Size   Used   Avail Capacity iused ifree %iused Mounted on
/dev/disk3s5   460Gi   438Gi   116Mi   100%   2.0M 1.2M   62%   /System/Volumes/Data
/dev/disk3s6 on /System/Volumes/VM (apfs, local, noexec, journaled, noatime, nobrowse)
/dev/disk3s2 on /System/Volumes/Preboot (apfs, local, journaled, nobrowse)
/dev/disk3s4 on /System/Volumes/Update (apfs, local, journaled, nobrowse)
/dev/disk1s2 on /System/Volumes/xarts (apfs, local, noexec, journaled, noatime, nobrowse)
/dev/disk1s1 on /System/Volumes/iSCPreboot (apfs, local, journaled, nobrowse)
/dev/disk1s3 on /System/Volumes/Hardware (apfs, local, journaled, nobrowse)
/dev/disk3s5 on /System/Volumes/Data (apfs, local, journaled, nobrowse, protect, root data)
map auto_home on /System/Volumes/Data/home (autofs, automounted, nobrowse)
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
/proxy.js
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cat
apps/api/migrations/0002_platform_authorization.sql
cat apps/web/proxy.js
-- FIN-15: only the platform-scoped administrator permission is implemented.

```
-- Workspace roles and workspace permissions remain unavailable until workspace
membership exists.
BEGIN;
CREATE TABLE permissions (
   permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
   permission_key VARCHAR(120) NOT NULL UNIQUE,
   description TEXT NOT NULL
);
CREATE TABLE role_permissions (
   role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
   permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON DELETE
CASCADE,
   PRIMARY KEY (role_id, permission_id)
);
INSERT INTO roles (role_key, display_name, scope, description)
VALUES ('platform_admin', 'Platform Administrator', 'platform',
       'Administrator privileges for currently implemented platform operations only.')
ON CONFLICT (role_key) DO NOTHING;
DO $$
BEGIN
   IF NOT EXISTS (SELECT 1 FROM roles WHERE role_key = 'platform_admin' AND scope =
'platform') THEN
       RAISE EXCEPTION 'Existing platform_admin role has non-platform scope';
   END IF;
END
$$;
INSERT INTO permissions (permission_key, description)
VALUES ('platform.admin', 'Access operations explicitly assigned platform administrator
permission.')
ON CONFLICT (permission_key) DO NOTHING;
INSERT INTO role_permissions (role_id, permission_id)
SELECT r.role_id, p.permission_id
FROM roles r CROSS JOIN permissions p
WHERE r.role_key = 'platform_admin' AND r.scope = 'platform'
  AND p.permission_key = 'platform.admin'
ON CONFLICT DO NOTHING;
CREATE FUNCTION enforce_platform_role_scope() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
   IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
      SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope = 'platform'
   ) THEN
      RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
         USING ERRCODE = '23514';
```

```
    END IF;
    RETURN NEW;
END
$$;
CREATE TRIGGER users_platform_role_scope_check
BEFORE INSERT OR UPDATE OF platform_role_id ON users
FOR EACH ROW EXECUTE FUNCTION enforce_platform_role_scope();
CREATE FUNCTION prevent_platform_role_scope_drift() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
    IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
        SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
    ) THEN
        RAISE EXCEPTION 'Cannot change scope of an assigned platform role';
    END IF;
    RETURN NEW;
END
$$;
CREATE TRIGGER roles_prevent_scope_drift
BEFORE UPDATE OF scope ON roles
FOR EACH ROW EXECUTE FUNCTION prevent_platform_role_scope_drift();
COMMIT;
import { NextResponse } from "next/server";
// This is an optimistic page redirect only. Protected APIs must validate the
// opaque session and permissions server-side; cookie presence grants no access.
export function proxy(request) {
  if (!request.cookies.has("finsight_session")) {
    const signIn = new URL("/", request.url);
    signIn.searchParams.set("next", request.nextUrl.pathname);
    return NextResponse.redirect(signIn);
  }
  return NextResponse.next();
}
export const config = { matcher: ["/app/:path*"] };
] };
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
echo "===== CHECK MIGRATION CONTENT ====="
grep -n -i "go through all the socuce" apps/api/migrations/0002_platform_authorization.sql
nl -ba apps/api/migrations/0002_platform_authorization.sql | sed -n '1,120p'
echo "===== CHECK EXISTING MIGRATION STATUS ====="
psql -d finsight_test -c "\dt"
psql -d finsight_test -c "\df *platform*"
echo "===== CHECK CURRENT API IMPLEMENTATION ====="
sed -n '1,260p' apps/api/app/main.py
```

```
echo "===== CHECK AUTHORIZATION TESTS ====="
sed -n '1,240p' apps/api/tests/test_auth_unit.py
sed -n '1,180p' apps/api/tests/test_identity_constraints.py
echo "===== CHECK PROVISIONING ====="
sed -n '1,240p' apps/api/app/provision_user.py
sed -n '1,220p' apps/api/tests/test_provision_user.py
echo "===== CHECK EXISTING TRACEABILITY FILES ====="
find . -maxdepth 3 -name 'FUNCTION_TEST_TRACEABILITY.txt' -o -name '*traceability*.txt'
echo "===== CHECK CURRENT CHANGES ====="
git status --short --branch
git diff --check
git diff --stat
===== CHECK MIGRATION CONTENT =====
     1  -- FIN-15: only the platform-scoped administrator permission is implemented.
     2  -- Workspace roles and workspace permissions remain unavailable until workspace
membership exists.
     3  BEGIN;
     4
     5  CREATE TABLE permissions (
     6      permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
     7      permission_key VARCHAR(120) NOT NULL UNIQUE,
     8      description TEXT NOT NULL
     9  );
    10
    11  CREATE TABLE role_permissions (
    12      role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
    13      permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON
DELETE CASCADE,
    14      PRIMARY KEY (role_id, permission_id)
    15  );
    16
    17  INSERT INTO roles (role_key, display_name, scope, description)
    18  VALUES ('platform_admin', 'Platform Administrator', 'platform',
    19          'Administrator privileges for currently implemented platform operations only.')
    20  ON CONFLICT (role_key) DO NOTHING;
    21
    22  DO $$
    23  BEGIN
    24      IF NOT EXISTS (SELECT 1 FROM roles WHERE role_key = 'platform_admin' AND
scope = 'platform') THEN
    25          RAISE EXCEPTION 'Existing platform_admin role has non-platform scope';
    26      END IF;
    27  END
    28  $$;
```

```
29
30  INSERT INTO permissions (permission_key, description)
31  VALUES ('platform.admin', 'Access operations explicitly assigned platform administrator
permission.')
32  ON CONFLICT (permission_key) DO NOTHING;
33
34  INSERT INTO role_permissions (role_id, permission_id)
35  SELECT r.role_id, p.permission_id
36  FROM roles r CROSS JOIN permissions p
37  WHERE r.role_key = 'platform_admin' AND r.scope = 'platform'
38    AND p.permission_key = 'platform.admin'
39  ON CONFLICT DO NOTHING;
40
41  CREATE FUNCTION enforce_platform_role_scope() RETURNS trigger
42  LANGUAGE plpgsql AS $$
43  BEGIN
44      IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
45          SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope =
'platform'
46      ) THEN
47          RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
48              USING ERRCODE = '23514';
49      END IF;
50      RETURN NEW;
51  END
52  $$;
53
54  CREATE TRIGGER users_platform_role_scope_check
55  BEFORE INSERT OR UPDATE OF platform_role_id ON users
56  FOR EACH ROW EXECUTE FUNCTION enforce_platform_role_scope();
57
58  CREATE FUNCTION prevent_platform_role_scope_drift() RETURNS trigger
59  LANGUAGE plpgsql AS $$
60  BEGIN
61      IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
62          SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
63      ) THEN
64          RAISE EXCEPTION 'Cannot change scope of an assigned platform role';
65      END IF;
66      RETURN NEW;
67  END
68  $$;
69
70  CREATE TRIGGER roles_prevent_scope_drift
```

```
    71  BEFORE UPDATE OF scope ON roles
    72  FOR EACH ROW EXECUTE FUNCTION prevent_platform_role_scope_drift();
    73
    74  COMMIT;
===== CHECK EXISTING MIGRATION STATUS =====
             List of relations
 Schema |       Name       | Type  |  Owner
--------+------------------+-------+----------
 public | auth_sessions    | table | sandeeph
 public | permissions      | table | sandeeph
 public | role_permissions | table | sandeeph
 public | roles            | table | sandeeph
 public | users            | table | sandeeph
(5 rows)
                                 List of functions
 Schema |               Name                | Result data type | Argument data types | Type
--------+-----------------------------------+------------------+---------------------+------
 public | enforce_platform_role_scope       | trigger          |                     | func
 public | prevent_platform_role_scope_drift | trigger          |                     | func
(2 rows)
===== CHECK CURRENT API IMPLEMENTATION =====
"""FinSight AI API with PostgreSQL-backed browser sessions."""
from __future__ import annotations
import os
import secrets
from datetime import UTC, datetime
from pathlib import Path
from typing import Annotated, Any
from uuid import UUID
import psycopg
from dotenv import load_dotenv
from fastapi import Cookie, Depends, FastAPI, HTTPException, Request, Response, status
from fastapi.middleware.cors import CORSMiddleware
from pydantic import BaseModel, EmailStr, Field
from psycopg.rows import dict_row
from app.auth import hash_password, new_session_token, session_expiry, token_digest,
verify_password
from app.database import connect
load_dotenv(Path(__file__).resolve().parents[3] / ".env")
app = FastAPI(title="FinSight AI API", version="0.2.0")
web_origin = os.environ.get("WEB_ORIGIN", "http://localhost:3000")
app.add_middleware(
    CORSMiddleware,
    allow_origins=[web_origin],
```

```
    allow_credentials=True,
    allow_methods=["GET", "POST"],
    allow_headers=["Content-Type"],
)
SESSION_COOKIE = "finsight_session"
GENERIC_LOGIN_ERROR = "Email or password is incorrect."
DUMMY_PASSWORD_HASH = hash_password(secrets.token_urlsafe(32))
class LoginRequest(BaseModel):
    email: EmailStr
    password: str = Field(min_length=1, max_length=1024)
class UserView(BaseModel):
    user_id: UUID
    email: str
    display_name: str
def _ttl_minutes() -> int:
    try:
        value = int(os.environ.get("SESSION_TTL_MINUTES", "60"))
        session_expiry(value)
        return value
    except ValueError as exc:
        raise HTTPException(status_code=500, detail="Session configuration is invalid") from exc
def _secure_cookie() -> bool:
    configured = os.environ.get("COOKIE_SECURE")
    if configured is not None:
        return configured.lower() in {"1", "true", "yes"}
    return os.environ.get("APP_ENV", "development").lower() == "production"
def _check_origin(request: Request) -> None:
    origin = request.headers.get("origin")
    if origin and origin != web_origin:
        raise HTTPException(status_code=403, detail="Request origin is not allowed")
def get_current_user(
    session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] = None,
) -> dict[str, Any]:
    if not session_token:
        raise HTTPException(status_code=status.HTTP_401_UNAUTHORIZED,
detail="Authentication required")
    try:
        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
            cur.execute(
                """SELECT u.user_id, u.email, u.display_name, r.role_key,
                        COALESCE(array_agg(DISTINCT p.permission_key)
                            FILTER (WHERE p.permission_key IS NOT NULL), ARRAY[]::varchar[])
AS permissions
                    FROM auth_sessions s JOIN users u ON u.user_id = s.user_id
```

```
                LEFT JOIN roles r ON r.role_id = u.platform_role_id AND r.scope = 'platform'
                LEFT JOIN role_permissions rp ON rp.role_id = r.role_id
                LEFT JOIN permissions p ON p.permission_id = rp.permission_id
                WHERE s.refresh_token_hash = %s AND s.revoked_at IS NULL
                  AND s.expires_at > %s AND u.account_status = 'active'
                  AND s.last_seen_at > %s - make_interval(mins => %s)
                  AND u.deleted_at IS NULL
                GROUP BY u.user_id, u.email, u.display_name, r.role_key""",
              (token_digest(session_token), datetime.now(UTC), datetime.now(UTC),
_ttl_minutes()),
            )
            user = cur.fetchone()
            if not user:
                raise HTTPException(status_code=401, detail="Authentication required")
            cur.execute(
                "UPDATE auth_sessions SET last_seen_at = %s WHERE refresh_token_hash = %s",
                (datetime.now(UTC), token_digest(session_token)),
            )
            return user
    except psycopg.Error as exc:
        raise HTTPException(status_code=503, detail="Authentication service unavailable") from
exc
CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]
def require_permission(permission_key: str):
    """Build a deny-by-default backend permission dependency."""
    def dependency(user: CurrentUser) -> dict[str, Any]:
        if permission_key not in user.get("permissions", []):
            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN, detail="Permission
denied")
        return user
    return dependency
@app.post("/auth/login", response_model=UserView)
def login(payload: LoginRequest, request: Request, response: Response) -> UserView:
    _check_origin(request)
    email = payload.email.strip().lower()
    try:
        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
            cur.execute(
                """SELECT user_id, email, display_name, password_hash
                  FROM users WHERE lower(email) = %s AND account_status = 'active'
                    AND deleted_at IS NULL""",
                (email,),
            )
            user = cur.fetchone()
```

```
            if not user or not user["password_hash"]:
                verify_password(DUMMY_PASSWORD_HASH, payload.password)
                raise HTTPException(status_code=401, detail=GENERIC_LOGIN_ERROR)
            if not verify_password(user["password_hash"], payload.password):
                raise HTTPException(status_code=401, detail=GENERIC_LOGIN_ERROR)
            token, digest = new_session_token()
            expires_at = session_expiry(_ttl_minutes())
            cur.execute(
                """INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
                   VALUES (%s, %s, %s)""",
                (user["user_id"], digest, expires_at),
            )
            cur.execute("UPDATE users SET last_login_at = %s, updated_at = %s WHERE user_id
= %s",
                        (datetime.now(UTC), datetime.now(UTC), user["user_id"]))
        response.set_cookie(
            SESSION_COOKIE,
            token,
            httponly=True,
            secure=_secure_cookie(),
            samesite="lax",
            max_age=_ttl_minutes() * 60,
            path="/",
        )
        return UserView(user_id=user["user_id"], email=user["email"],
display_name=user["display_name"])
    except psycopg.Error as exc:
        raise HTTPException(status_code=503, detail="Authentication service unavailable") from
exc
@app.post("/auth/logout", status_code=204)
def logout(request: Request, response: Response,
           session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] = None) ->
Response:
    _check_origin(request)
    if session_token:
        try:
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    """UPDATE auth_sessions SET revoked_at = %s, revoke_reason = 'logout'
                       WHERE refresh_token_hash = %s AND revoked_at IS NULL""",
                    (datetime.now(UTC), token_digest(session_token)),
                )
        except psycopg.Error as exc:
```

```
        raise HTTPException(status_code=503, detail="Authentication service unavailable")
from exc
    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
    response.status_code = status.HTTP_204_NO_CONTENT
    return response
@app.get("/auth/me", response_model=UserView)
def who_am_i(user: CurrentUser) -> UserView:
    return UserView(**user)
===== CHECK AUTHORIZATION TESTS =====
from __future__ import annotations
from datetime import UTC, datetime, timedelta
import pytest
from fastapi import HTTPException
from fastapi.testclient import TestClient
from app.auth import hash_password, new_session_token, session_expiry, token_digest,
verify_password
from app.main import _secure_cookie, _ttl_minutes, app
def test_password_helpers_accept_only_the_original_password():
    encoded = hash_password("synthetic-password")
    assert encoded.startswith("argon2id")
    assert verify_password(encoded, "synthetic-password")
    assert not verify_password(encoded, "different-password")
    assert not verify_password("not-an-argon2-hash", "synthetic-password")
    assert not verify_password(None, "synthetic-password")
def test_session_expiry_uses_utc_and_requested_ttl():
    now = datetime(2026, 1, 1, tzinfo=UTC)
    assert session_expiry(15, now) == now + timedelta(minutes=15)
@pytest.mark.parametrize("ttl", [0, -1, 10081])
def test_session_expiry_rejects_out_of_range_ttl(ttl: int):
    with pytest.raises(ValueError, match="SESSION_TTL_MINUTES"):
        session_expiry(ttl)
@pytest.mark.parametrize("configured, expected", [("60", 60), ("1", 1), ("10080", 10080)])
def test_ttl_configuration_accepts_only_supported_values(monkeypatch, configured: str,
expected: int):
    monkeypatch.setenv("SESSION_TTL_MINUTES", configured)
    assert _ttl_minutes() == expected
@pytest.mark.parametrize("configured", ["0", "10081", "not-a-number"])
def test_ttl_configuration_fails_closed(monkeypatch, configured: str):
    monkeypatch.setenv("SESSION_TTL_MINUTES", configured)
    with pytest.raises(HTTPException) as error:
        _ttl_minutes()
    assert error.value.status_code == 500
    assert error.value.detail == "Session configuration is invalid"
```

```
def test_session_tokens_are_opaque_and_only_digest_is_stable():
    token, digest = new_session_token()
    another_token, another_digest = new_session_token()
    assert token != another_token
    assert digest == token_digest(token)
    assert digest != token
    assert digest != another_digest
def test_login_maps_database_outage_to_controlled_error(monkeypatch):
    import app.main as main
    def unavailable_database():
        import psycopg
        raise psycopg.OperationalError("synthetic database detail")
    monkeypatch.setattr(main, "connect", unavailable_database)
    response = TestClient(app).post(
        "/auth/login",
        json={"email": "synthetic@example.com", "password": "synthetic-password"},
    )
    assert response.status_code == 503
    assert response.json() == {"detail": "Authentication service unavailable"}
    assert "synthetic database detail" not in response.text
def test_protected_route_rejects_missing_session_before_database_access(monkeypatch):
    import app.main as main
    def unexpected_database_access():
        raise AssertionError("database must not be accessed without a session cookie")
    monkeypatch.setattr(main, "connect", unexpected_database_access)
    response = TestClient(app).get("/auth/me")
    assert response.status_code == 401
    assert response.json() == {"detail": "Authentication required"}
@pytest.mark.parametrize(
    ("user", "expected_status"),
    [({"permissions": ["platform.admin"]}, 200), ({"permissions": []}, 403), ({}, 403)],
)
def test_permission_dependency_allows_only_explicit_permission(user, expected_status):
    from fastapi import Depends, FastAPI
    from fastapi.testclient import TestClient
    import app.main as main
    protected_app = FastAPI()
    protected_app.dependency_overrides[main.get_current_user] = lambda: user
    protected_app.add_api_route(
        "/platform-admin",
        lambda _authorized=Depends(main.require_permission("platform.admin")): {"allowed":
True},
    )
    response = TestClient(protected_app).get("/platform-admin")
```

```
    assert response.status_code == expected_status
    if expected_status == 403:
        assert response.json() == {"detail": "Permission denied"}
def test_permission_dependency_ignores_client_supplied_role_header():
    from fastapi import Depends, FastAPI
    from fastapi.testclient import TestClient
    import app.main as main
    protected_app = FastAPI()
    protected_app.dependency_overrides[main.get_current_user] = lambda: {"permissions": []}
    protected_app.add_api_route(
        "/platform-admin",
        lambda _authorized=Depends(main.require_permission("platform.admin")): {"allowed":
True},
    )
    response = TestClient(protected_app).get("/platform-admin", headers={"X-Role":
"platform_admin"})
    assert response.status_code == 403
@pytest.mark.parametrize(
    ("method", "path", "kwargs"),
    [
        ("get", "/auth/me", {"cookies": {"finsight_session": "synthetic-token"}}),
        ("post", "/auth/logout", {"cookies": {"finsight_session": "synthetic-token"}}),
    ],
)
def test_session_database_outages_return_controlled_error(monkeypatch, method, path,
kwargs):
    import app.main as main
    import psycopg
    def unavailable_database():
        raise psycopg.OperationalError("synthetic database detail")
    monkeypatch.setattr(main, "connect", unavailable_database)
    response = getattr(TestClient(app), method)(path, **kwargs)
    assert response.status_code == 503
    assert response.json() == {"detail": "Authentication service unavailable"}
    assert "synthetic database detail" not in response.text
def test_database_configuration_is_required(monkeypatch):
    import app.database as database
    monkeypatch.delenv("DATABASE_URL", raising=False)
    with pytest.raises(RuntimeError, match="DATABASE_URL is required"):
        database.connect()
def test_login_rejects_invalid_input_before_database_access():
    response = TestClient(app).post(
        "/auth/login",
        json={"email": "not-an-email", "password": ""},
```

```
    )
    assert response.status_code == 422
    assert "synthetic database detail" not in response.text
@pytest.mark.parametrize("configured", ["1", "true", "yes"])
def test_secure_cookie_accepts_explicit_secure_values(monkeypatch, configured: str):
    monkeypatch.setenv("COOKIE_SECURE", configured)
    assert _secure_cookie()
@pytest.mark.parametrize("configured", ["0", "false", "no", "invalid"])
def test_secure_cookie_treats_other_explicit_values_as_insecure(monkeypatch, configured:
str):
    monkeypatch.setenv("COOKIE_SECURE", configured)
    assert not _secure_cookie()
@pytest.mark.parametrize(("app_env", "expected"), [("production", True), ("development",
False), ("test", False)])
def test_secure_cookie_defaults_by_environment(monkeypatch, app_env: str, expected: bool):
    monkeypatch.delenv("COOKIE_SECURE", raising=False)
    monkeypatch.setenv("APP_ENV", app_env)
    assert _secure_cookie() is expected
from __future__ import annotations
from uuid import uuid4
import psycopg
import pytest
from fastapi import Depends, FastAPI
from fastapi.testclient import TestClient
from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, require_permission
def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s, %s)
RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )
```

```
        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) VALUES
(%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s", (user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin' AND
scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s, %s)
RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) VALUES
(%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )
    protected_app = FastAPI()
    protected_app.add_api_route(
        "/platform-admin",
        lambda _authorized=Depends(require_permission("platform.admin")): {"allowed": True},
```

```
    )
    try:
        with TestClient(protected_app) as client:
            assert client.get("/platform-admin", cookies={SESSION_COOKIE:
tokens[0]}).status_code == 200
            denied = client.get(
                "/platform-admin",
                cookies={SESSION_COOKIE: tokens[1]},
                headers={"X-Role": "platform_admin"},
            )
            assert denied.status_code == 403
            assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id, user_id))
def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s, 'workspace')
RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope User')
RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id = %s",
(workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s", (workspace_role_id,))
===== CHECK PROVISIONING =====
"""Create or update a user from a trusted local administrator shell."""
from __future__ import annotations
import getpass
import sys
```

```
from app.auth import hash_password
from app.database import connect
def main() -> int:
    if len(sys.argv) not in {3, 4} or (len(sys.argv) == 4 and sys.argv[3] != "--platform-admin"):
        print("Usage: python -m app.provision_user EMAIL DISPLAY_NAME [--platform-admin]",
file=sys.stderr)
        return 2
    email, display_name = sys.argv[1].strip().lower(), sys.argv[2].strip()
    if not email or len(email) > 320 or not display_name or len(display_name) > 160:
        print("Email and display name are required and must fit the identity schema.",
file=sys.stderr)
        return 2
    password = getpass.getpass("Initial password (hidden): ")
    confirmation = getpass.getpass("Confirm password (hidden): ")
    if password != confirmation or not password:
        print("Passwords did not match or were empty.", file=sys.stderr)
        return 2
    password_hash = hash_password(password)
    role_key = "platform_admin" if len(sys.argv) == 4 else None
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            """INSERT INTO users (email, password_hash, display_name, account_status,
platform_role_id)
               VALUES (%s, %s, %s, 'active',
                       (SELECT role_id FROM roles WHERE role_key = %s AND scope = 'platform'))
               ON CONFLICT ((lower(email))) DO UPDATE SET
                  password_hash = EXCLUDED.password_hash,
                  display_name = EXCLUDED.display_name,
                  platform_role_id = COALESCE(EXCLUDED.platform_role_id,
users.platform_role_id),
                  account_status = 'active', updated_at = now(), deleted_at = NULL""",
            (email, password_hash, display_name, role_key),
        )
    label = " with platform administrator permission" if role_key else " without platform
permissions"
    print(f"User provisioned{label}. No password value was displayed.")
    return 0
if __name__ == "__main__":
    raise SystemExit(main())
from __future__ import annotations
import sys
import subprocess
from pathlib import Path
import pytest
```

```
import app.provision_user as provision_user
def test_provision_user_module_exits_with_usage_error_without_database_access():
    result = subprocess.run(
        [sys.executable, "-m", "app.provision_user"],
        cwd=Path(__file__).resolve().parents[1],
        capture_output=True,
        text=True,
        check=False,
    )
    assert result.returncode == 2
    assert "Usage:" in result.stderr
    assert "DATABASE_URL" not in result.stderr
def test_provision_user_requires_email_and_display_arguments(monkeypatch, capsys):
    monkeypatch.setattr(sys, "argv", ["provision_user"])
    assert provision_user.main() == 2
    assert "Usage:" in capsys.readouterr().err
def test_provision_user_platform_admin_is_explicit_opt_in(monkeypatch, capsys):
    monkeypatch.setattr(sys, "argv", ["provision_user", "admin@example.test", "Synthetic
Admin", "--platform-admin"])
    values = iter(("synthetic-password", "synthetic-password"))
    monkeypatch.setattr(provision_user.getpass, "getpass", lambda _prompt: next(values))
    class Cursor:
        statement = ""
        parameters = None
        def __enter__(self): return self
        def __exit__(self, *_args): return None
        def execute(self, statement, parameters):
            self.statement, self.parameters = statement, parameters
    cursor = Cursor()
    class Connection:
        def __enter__(self): return self
        def __exit__(self, *_args): return None
        def cursor(self): return cursor
    monkeypatch.setattr(provision_user, "connect", Connection)
    assert provision_user.main() == 0
    assert "role_key = %s AND scope = 'platform'" in cursor.statement
    assert cursor.parameters[-1] == "platform_admin"
    output = capsys.readouterr()
    assert "synthetic-password" not in output.out + output.err
def test_provision_user_rejects_unknown_role_argument(monkeypatch, capsys):
    monkeypatch.setattr(sys, "argv", ["provision_user", "analyst@example.test", "Synthetic User",
"--operator"])
    assert provision_user.main() == 2
    assert "Usage:" in capsys.readouterr().err
```

```
@pytest.mark.parametrize(
    "email, display_name",
    [
        (" ", "Synthetic Analyst"),
        ("a" * 321, "Synthetic Analyst"),
        ("analyst@example.com", " "),
        ("analyst@example.com", "A" * 161),
    ],
)
def test_provision_user_rejects_invalid_identity_fields(monkeypatch, capsys, email,
display_name):
    monkeypatch.setattr(sys, "argv", ["provision_user", email, display_name])
    monkeypatch.setattr(provision_user, "connect", lambda: pytest.fail("database must not be
opened"))
    monkeypatch.setattr(provision_user.getpass, "getpass", lambda _prompt:
pytest.fail("password must not be requested"))
    assert provision_user.main() == 2
    assert "must fit the identity schema" in capsys.readouterr().err
@pytest.mark.parametrize("passwords", [("", ""), ("synthetic-one", "synthetic-two")])
def test_provision_user_rejects_empty_or_mismatched_passwords(monkeypatch, capsys,
passwords):
    monkeypatch.setattr(sys, "argv", ["provision_user", "analyst@example.com", "Synthetic
Analyst"])
    values = iter(passwords)
    monkeypatch.setattr(provision_user.getpass, "getpass", lambda _prompt: next(values))
    monkeypatch.setattr(provision_user, "connect", lambda: pytest.fail("invalid password must not
change the database"))
    assert provision_user.main() == 2
    output = capsys.readouterr()
    assert "Passwords did not match or were empty." in output.err
    assert all(password not in output.out + output.err for password in passwords if password)
def test_provision_user_hashes_and_upserts_without_printing_password(monkeypatch,
capsys):
    monkeypatch.setattr(sys, "argv", ["provision_user", " Analyst@Example.com ", " Synthetic
Analyst "])
    values = iter(("synthetic-initial-password", "synthetic-initial-password"))
    monkeypatch.setattr(provision_user.getpass, "getpass", lambda _prompt: next(values))
    class Cursor:
        statement = ""
        parameters = None
        def __enter__(self):
            return self
        def __exit__(self, *_args):
            return None
```

```
        def execute(self, statement, parameters):
            self.statement = statement
            self.parameters = parameters
    cursor = Cursor()
    class Connection:
        def __enter__(self):
            return self
        def __exit__(self, *_args):
            return None
        def cursor(self):
            return cursor
    monkeypatch.setattr(provision_user, "connect", Connection)
    assert provision_user.main() == 0
    output = capsys.readouterr()
    assert "User provisioned" in output.out
    assert "synthetic-initial-password" not in output.out + output.err
    assert "ON CONFLICT ((lower(email))) DO UPDATE" in cursor.statement
    normalized_email, password_hash, display_name, role_key = cursor.parameters
    assert normalized_email == "analyst@example.com"
    assert display_name == "Synthetic Analyst"
    assert role_key is None
    assert password_hash.startswith("argon2id")
    assert password_hash != "synthetic-initial-password"
===== CHECK EXISTING TRACEABILITY FILES =====
===== CHECK CURRENT CHANGES =====
## main...origin/main
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
 .github/workflows/ci.yml                 |  4 ++++
 IMPLEMENTATION_STATUS.txt                | 19 ++++++++++++++++++
 README.md                                |  8 ++++++--
```

```
 SPRINT_1_TEST_EXECUTION_STATUS.txt         | 10 ++++++++++
 apps/api/app/main.py                       | 20 ++++++++++++++++++--
 apps/api/app/provision_user.py             | 16 ++++++++++------
 apps/api/tests/test_auth_unit.py           | 40
++++++++++++++++++++++++++++++++++++++++
 apps/api/tests/test_identity_constraints.py | 71
+++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
 apps/api/tests/test_provision_user.py      | 37 +++++++++++++++++++++++++++++++++++++-
 apps/web/tests/ui/auth.spec.js             | 10 ++++++++++
 conversation.txt                           | 17 ++++++++++++++++
 docs/architecture/README.md                |  4 ++--
 scripts/package_release.py                 |  2 +-
 13 files changed, 244 insertions(+), 14 deletions(-)
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % pwd
python3 ~/Downloads/fin15_apply_local_patch.py
git diff --check
git status --short
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI
Updated: apps/api/app/main.py
Updated: apps/api/tests/test_identity_constraints.py
Updated/created: FUNCTION_TEST_TRACEABILITY.txt
Updated: IMPLEMENTATION_STATUS.txt, conversation.txt,
SPRINT_1_TEST_EXECUTION_STATUS.txt
No tests were run by this script. No migrations, commits, or pushes were performed.
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
```

```
...
[100%]
=============================================================================
==== warnings summary
=============================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
3 passed, 3 warnings in 6.04s
(base) sandeeph@Sandeeps-MacBook-Pro api % DATABASE_URL="postgresql:///finsight_test"
python -m pytest -q
.....................................................
[100%]
=============================================================================
==== warnings summary
=============================================================================
====
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install
`httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa
apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[get-/a
uth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[post-/
auth/logout-kwargs1]
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
```

```
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454: DeprecationWarning:
Setting per-request cookies=<...> is being deprecated, because the expected behaviour on
cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(
-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
55 passed, 9 warnings in 2.55s
(base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
git diff --check
git status --short
git diff --stat
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
 .github/workflows/ci.yml                  |  4 ++++
 IMPLEMENTATION_STATUS.txt                 | 27 ++++++++++++++++++++++++++
 README.md                                 |  8 ++++++--
 SPRINT_1_TEST_EXECUTION_STATUS.txt        | 15 +++++++++++++++
 apps/api/app/main.py                      | 28 ++++++++++++++++++++++++++--
 apps/api/app/provision_user.py            | 16 ++++++++++------
 apps/api/tests/test_auth_unit.py          | 40
++++++++++++++++++++++++++++++++++++++++
 apps/api/tests/test_identity_constraints.py | 75
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+++
 apps/api/tests/test_provision_user.py     | 37 ++++++++++++++++++++++++++++++++++-
 apps/web/tests/ui/auth.spec.js            | 10 ++++++++++
 conversation.txt                          | 25 +++++++++++++++++++++++++
 docs/architecture/README.md               |  4 ++--
 scripts/package_release.py                |  2 +-
```

```
 13 files changed, 277 insertions(+), 14 deletions(-)
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
git diff --check
git status --short
git diff --stat
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
 .github/workflows/ci.yml                  |  4 ++++
 IMPLEMENTATION_STATUS.txt                 | 27 ++++++++++++++++++++++++++
 README.md                                 |  8 ++++++--
 SPRINT_1_TEST_EXECUTION_STATUS.txt        | 15 +++++++++++++++
 apps/api/app/main.py                      | 28 ++++++++++++++++++++++++++--
 apps/api/app/provision_user.py            | 16 ++++++++++------
 apps/api/tests/test_auth_unit.py          | 40
++++++++++++++++++++++++++++++++++++++++
 apps/api/tests/test_identity_constraints.py | 75
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+++
 apps/api/tests/test_provision_user.py     | 37 ++++++++++++++++++++++++++++++++++-
 apps/web/tests/ui/auth.spec.js            | 10 ++++++++++
 conversation.txt                          | 25 +++++++++++++++++++++++++
 docs/architecture/README.md               |  4 ++--
 scripts/package_release.py                |  2 +-
 13 files changed, 277 insertions(+), 14 deletions(-)
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % echo "===== REAL API ROUTES
====="
grep -n -E "@app\\.(get|post|put|patch|delete)|require_permission|platform/admin/capability"
apps/api/app/main.py
echo "===== REAL-ROUTE AUTHORIZATION TESTS ====="
```

```
grep -n -E "platform/admin/capability|platform_admin|status_code|403|401"
apps/api/tests/test_identity_constraints.py
echo "===== FUNCTION TEST TRACEABILITY ====="
cat FUNCTION_TEST_TRACEABILITY.txt
echo "===== PATCH SUMMARY ====="
git diff --check
git status --short
===== REAL API ROUTES =====
109:def require_permission(permission_key: str):
119:@app.post("/auth/login", response_model=UserView)
160:@app.post("/auth/logout", status_code=204)
179:@app.get("/auth/me", response_model=UserView)
184:@app.get("/platform/admin/capability")
186:    _authorized: Annotated[dict[str, Any], Depends(require_permission("platform.admin"))],
===== REAL-ROUTE AUTHORIZATION TESTS =====
50:        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin' AND
scope = 'platform'")
72:            anonymous = client.get("/platform/admin/capability")
73:            assert anonymous.status_code == 401
77:                "/platform/admin/capability",
80:            assert allowed.status_code == 200
84:                "/platform/admin/capability",
86:                headers={"X-Role": "platform_admin"},
88:            assert denied.status_code == 403
===== FUNCTION TEST TRACEABILITY =====
FinSight AI — Function/Test Traceability
FIN-15 / FS-01-02 — platform authorization capability endpoint
Function: GET /platform/admin/capability
Authorization rule: requires a valid active session and database-resolved `platform.admin`
permission; deny by default.
Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002
(permission matrix: platform admin allowed, standard user denied; client-supplied X-Role
ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session
dependency).
Evidence note: route integration assertions were added to
apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the
mapped tests and confirming the expected behavior.
===== PATCH SUMMARY =====
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
```

```
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
N-15/20261020_135513_full_api_suite.log
test-results/FIN-15/20261020_135513_identity_authorization.log
test-results/FIN-15/run_20261020_135513_summary.txt
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd "$(git rev-parse --show-toplevel)"
echo "===== Verify FIN-15 evidence ====="
ls -lh test-results/FIN-15/
echo
echo "===== Check patch formatting ====="
git diff --check
echo
echo "===== Review changed and new files ====="
git status --short
===== Verify FIN-15 evidence =====
total 32
-rw-r--r--@ 1 sandeeph  staff   1.6K Oct 20 13:55 20261020_135513_auth_regression.log
-rw-r--r--@ 1 sandeeph  staff   1.7K Oct 20 13:55 20261020_135513_full_api_suite.log
-rw-r--r--@ 1 sandeeph  staff   1.3K Oct 20 13:55 20261020_135513_identity_authorization.log
-rw-r--r--@ 1 sandeeph  staff   296B Oct 20 13:55 run_20261020_135513_summary.txt
===== Check patch formatting =====
===== Review changed and new files =====
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
```

```
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % echo "===== 1. Authorization route
====="
grep -n -A35 -B12 "platform/admin/capability\|require_permission" apps/api/app/main.py
echo
echo "===== 2. Actual authorization tests ====="
grep -n -A35 -B12 "platform/admin/capability\|X-Role\|platform_admin"
apps/api/tests/test_identity_constraints.py
echo
echo "===== 3. FIN-15 migration ====="
sed -n '1,240p' apps/api/migrations/0002_platform_authorization.sql
echo
echo "===== 4. Source test definitions ====="
grep -n -A28 -B3 -E
'^TC_AUTHZ_001|^TC_AUTHZ_002|^TC_AUTHZ_003|^TC_PRIV_002|^TC_SYS_001'
SPRINT_1_TEST_EXECUTION_STATUS.txt
echo
echo "===== 5. FIN-15 status records ====="
grep -n -i -A8 -B4 'FIN-15\|FS-01-02\|TC_AUTHZ' IMPLEMENTATION_STATUS.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt FUNCTION_TEST_TRACEABILITY.txt
===== 1. Authorization route =====
97-            cur.execute(
98-                "UPDATE auth_sessions SET last_seen_at = %s WHERE refresh_token_hash =
%s",
99-                (datetime.now(UTC), token_digest(session_token)),
100-            )
101-            return user
102-    except psycopg.Error as exc:
103-        raise HTTPException(status_code=503, detail="Authentication service unavailable")
from exc
104-
105-
106-CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]
107-
108-
109:def require_permission(permission_key: str):
110-    """Build a deny-by-default backend permission dependency."""
111-    def dependency(user: CurrentUser) -> dict[str, Any]:
112-        if permission_key not in user.get("permissions", []):
```

```
113-            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN,
detail="Permission denied")
114-        return user
115-
116-    return dependency
117-
118-
119-@app.post("/auth/login", response_model=UserView)
120-def login(payload: LoginRequest, request: Request, response: Response) -> UserView:
121-    _check_origin(request)
122-    email = payload.email.strip().lower()
123-    try:
124-        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
125-            cur.execute(
126-                """SELECT user_id, email, display_name, password_hash
127-                   FROM users WHERE lower(email) = %s AND account_status = 'active'
128-                     AND deleted_at IS NULL""",
129-                (email,),
130-            )
131-            user = cur.fetchone()
132-            if not user or not user["password_hash"]:
133-                verify_password(DUMMY_PASSWORD_HASH, payload.password)
134-                raise HTTPException(status_code=401, detail=GENERIC_LOGIN_ERROR)
135-            if not verify_password(user["password_hash"], payload.password):
136-                raise HTTPException(status_code=401, detail=GENERIC_LOGIN_ERROR)
137-            token, digest = new_session_token()
138-            expires_at = session_expiry(_ttl_minutes())
139-            cur.execute(
140-                """INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
141-                   VALUES (%s, %s, %s)""",
142-                (user["user_id"], digest, expires_at),
143-            )
144-            cur.execute("UPDATE users SET last_login_at = %s, updated_at = %s WHERE
user_id = %s",
--
172-        except psycopg.Error as exc:
173-            raise HTTPException(status_code=503, detail="Authentication service unavailable")
from exc
174-    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
175-    response.status_code = status.HTTP_204_NO_CONTENT
176-    return response
177-
178-
```

```
179-@app.get("/auth/me", response_model=UserView)
180-def who_am_i(user: CurrentUser) -> UserView:
181-    return UserView(**user)
182-
183-
184:@app.get("/platform/admin/capability")
185-def platform_admin_capability(
186:    _authorized: Annotated[dict[str, Any], Depends(require_permission("platform.admin"))],
187-) -> dict[str, str | bool]:
188-    """Minimal capability endpoint proving platform-admin authorization at the API boundary."""
189-    return {"permission": "platform.admin", "allowed": True}
===== 2. Actual authorization tests =====
38-            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s", (user_id,))
39-            assert cur.fetchone()[0] == 0
40-    finally:
41-        with connect() as conn, conn.cursor() as cur:
42-            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
43-
44-
45-def test_platform_permission_is_resolved_from_database_role_and_session():
46-    admin_email = f"platform-admin-{uuid4().hex}@example.test"
47-    user_email = f"unprivileged-{uuid4().hex}@example.test"
48-    tokens = []
49-    with connect() as conn, conn.cursor() as cur:
50:        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin' AND scope = 'platform'")
51-        admin_role_id = cur.fetchone()[0]
52-        cur.execute(
53-            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s, %s) RETURNING user_id",
54-            (admin_email, "Synthetic Platform Admin", admin_role_id),
55-        )
56-        admin_id = cur.fetchone()[0]
57-        cur.execute(
58-            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING user_id",
59-            (user_email, "Synthetic Standard User"),
60-        )
61-        user_id = cur.fetchone()[0]
62-        for owner_id in (admin_id, user_id):
63-            token, digest = new_session_token()
64-            tokens.append(token)
```

```
65-            cur.execute(
66-                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) VALUES
(%s, %s, %s)",
67-                (owner_id, digest, session_expiry(5)),
68-            )
69-
70-    try:
71-        with TestClient(app) as client:
72:            anonymous = client.get("/platform/admin/capability")
73-            assert anonymous.status_code == 401
74-            assert anonymous.json() == {"detail": "Authentication required"}
75-
76-            allowed = client.get(
77:                "/platform/admin/capability",
78-                cookies={SESSION_COOKIE: tokens[0]},
79-            )
80-            assert allowed.status_code == 200
81-            assert allowed.json() == {"permission": "platform.admin", "allowed": True}
82-
83-            denied = client.get(
84:                "/platform/admin/capability",
85-                cookies={SESSION_COOKIE: tokens[1]},
86:                headers={"X-Role": "platform_admin"},
87-            )
88-            assert denied.status_code == 403
89-            assert denied.json() == {"detail": "Permission denied"}
90-    finally:
91-        with connect() as conn, conn.cursor() as cur:
92-            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))
93-
94-
95-def test_platform_role_assignment_rejects_workspace_scoped_roles():
96-    email = f"wrong-scope-{uuid4().hex}@example.test"
97-    with connect() as conn, conn.cursor() as cur:
98-        cur.execute(
99-            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
100-            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
101-        )
102-        workspace_role_id = cur.fetchone()[0]
103-        cur.execute(
104-            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope User')
RETURNING user_id",
```

```
105-            (email,),
106-        )
107-        user_id = cur.fetchone()[0]
108-    try:
109-        with pytest.raises(psycopg.errors.CheckViolation):
110-            with connect() as conn, conn.cursor() as cur:
111-                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id = %s",
(workspace_role_id, user_id))
112-    finally:
113-        with connect() as conn, conn.cursor() as cur:
114-            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
115-            cur.execute("DELETE FROM roles WHERE role_id = %s", (workspace_role_id,))
===== 3. FIN-15 migration =====
-- FIN-15: only the platform-scoped administrator permission is implemented.
-- Workspace roles and workspace permissions remain unavailable until workspace
membership exists.
BEGIN;
CREATE TABLE permissions (
   permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
   permission_key VARCHAR(120) NOT NULL UNIQUE,
   description TEXT NOT NULL
);
CREATE TABLE role_permissions (
   role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
   permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON DELETE
CASCADE,
   PRIMARY KEY (role_id, permission_id)
);
INSERT INTO roles (role_key, display_name, scope, description)
VALUES ('platform_admin', 'Platform Administrator', 'platform',
       'Administrator privileges for currently implemented platform operations only.')
ON CONFLICT (role_key) DO NOTHING;
DO $$
BEGIN
   IF NOT EXISTS (SELECT 1 FROM roles WHERE role_key = 'platform_admin' AND scope =
'platform') THEN
       RAISE EXCEPTION 'Existing platform_admin role has non-platform scope';
   END IF;
END
$$;
INSERT INTO permissions (permission_key, description)
VALUES ('platform.admin', 'Access operations explicitly assigned platform administrator
permission.')
ON CONFLICT (permission_key) DO NOTHING;
```

```
INSERT INTO role_permissions (role_id, permission_id)
SELECT r.role_id, p.permission_id
FROM roles r CROSS JOIN permissions p
WHERE r.role_key = 'platform_admin' AND r.scope = 'platform'
  AND p.permission_key = 'platform.admin'
ON CONFLICT DO NOTHING;
CREATE FUNCTION enforce_platform_role_scope() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
    IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
        SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope = 'platform'
    ) THEN
        RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
            USING ERRCODE = '23514';
    END IF;
    RETURN NEW;
END
$$;
CREATE TRIGGER users_platform_role_scope_check
BEFORE INSERT OR UPDATE OF platform_role_id ON users
FOR EACH ROW EXECUTE FUNCTION enforce_platform_role_scope();
CREATE FUNCTION prevent_platform_role_scope_drift() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
    IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
        SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
    ) THEN
        RAISE EXCEPTION 'Cannot change scope of an assigned platform role';
    END IF;
    RETURN NEW;
END
$$;
CREATE TRIGGER roles_prevent_scope_drift
BEFORE UPDATE OF scope ON roles
FOR EACH ROW EXECUTE FUNCTION prevent_platform_role_scope_drift();
COMMIT;
===== 4. Source test definitions =====
48-Evidence: test `test_public_registration_is_not_available`; `apps/api/app/provision_user.py`.
49-Remaining: implement/verify the approved administrator-controlled onboarding workflow in
its authorized scope.
50-
51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
52-Status: PASS (session-expiry behavior exercised as a FIN-13 acceptance check; Jira scope
remains unchanged)
```

Actual result: A session with stale `last_seen_at` was rejected by the protected endpoint. TTL bounds are validated and expiry uses `SESSION_TTL_MINUTES`.
Evidence: test `test_expired_session_is_rejected` in the command above.

TC_AUTHN_006 — Verify passwords are not stored in plaintext
Status: PASS
Execution date: 2026-10-18
Actual result: A synthetic random password and session token were inserted into the disposable PostgreSQL database; the generated `pg_dump` contained their password/session digests and neither plaintext value. The login test also verified response and captured log/stdout/stderr privacy. The synthetic user was deleted and dump removed.
Evidence: `test_password_hash_is_argon2_and_never_plaintext`, `test_login_creates_protected_hashed_expiring_session`, and the disposable scan command/result summarized in `IMPLEMENTATION_STATUS.txt`.

TC_AUTHN_007 — Verify HTTPS transport and secure cookie handling in deployed configuration
Status: BLOCKED
Actual result: The cookie was verified HttpOnly and SameSite=Lax in local HTTP tests; `COOKIE_SECURE=true` sets Secure. No deployed HTTPS endpoint was available to verify transport enforcement.
Evidence: `test_secure_cookie_can_be_required_by_deployment`.

Other cases remain NOT RUN unless listed below. Password recovery is required by SRS FR-P1-03 while password authentication is enabled, and is BLOCKED pending the decision in conversation.txt Q-005. Broader RBAC/security cases, deployment checks, and manual browser accessibility were not executed.

Full Sprint 1 inventory status index (source register contains 54 cases):
TC_CI_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Workflow YAML parsed locally; GitHub Actions pull-request run not available without publishing changes | Tester/owner: Codex | Evidence: .github/workflows/ci.yml; workflow validation command in IMPLEMENTATION_STATUS.txt | Linked defect: GitHub run required
TC_CI_002 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Local checks pass, but GitHub required-check/failing-job enforcement not verified on an actual PR | Tester/owner: Codex | Evidence: .github/workflows/ci.yml; conversation.txt Q-006 | Linked defect: GitHub rules/run required
TC_BUILD_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Versioned local package built with runtime API configuration and verified checksum/repeatable packaging; no full source commit SHA was available because implementation changes are uncommitted | Tester/owner: Codex| Evidence: dist/finsight-0.1.0-local.tar.gz; adjacent build-info/checksum; IMPLEMENTATION_STATUS.txt | Linked defect: committed candidate SHA required
TC_BUILD_002 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Deployment/rollback runbook recorded and extracted package smoke-tested locally; no hosting

target or previous known-good release exists to execute a deployment rollback | Tester/owner: Codex | Evidence: docs/release/RELEASE_README.md; local extracted bundle smoke result in IMPLEMENTATION_STATUS.txt | Linked defect: target and prior release required
74-TC_TEST_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: Backend unit and PostgreSQL integration suites passed; frontend interaction tests passed; live browser smoke passed twice against fresh synthetic accounts and once against production standalone output; exit codes and JUnit reports reviewed | Tester/owner: Codex | Evidence: apps/api/tests/test_auth_unit.py; apps/api/tests/test_auth.py; apps/api/tests/test_identity_constraints.py; apps/web/test-results/ui/results.xml; apps/web/test-results/e2e/results.xml; coverage.xml; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: —
75-TC_DB_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Existing identity migration applied to a fresh disposable PostgreSQL database; case-insensitive email uniqueness and session cascade verified. Full case remains blocked because only identity/session schema exists; api_credentials, audit_events, execution_runs, service_health_checks and migration-runner repeatability are not implemented | Tester/owner: Codex | Evidence: apps/api/migrations/0001_auth_identity.sql; apps/api/tests/test_identity_constraints.py; IMPLEMENTATION_STATUS.txt | Linked defect: Missing broader Sprint 1 schemas and migration runner
76-TC_COV_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: CI-equivalent unit (37) and PostgreSQL integration (10) suites passed; cumulative backend line coverage 156/156 (100%) and branch coverage 28/28 (100%). Provisioning CLI, configuration and authentication/session database failure paths were tested. Frontend source coverage is not supported by current Playwright instrumentation; remote artifact retention remains unverified. | Tester/owner: Codex | Evidence: coverage.xml (ignored local report); htmlcov/index.html (ignored local report); /tmp/finsight-coverage.json; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py; apps/api/tests/test_provision_user.py; IMPLEMENTATION_STATUS.txt | Linked defect: GitHub artifact confirmation / frontend source instrumentation decision
77-TC_INT_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Authentication/session persistence tested against PostgreSQL; configuration versioning, audit persistence, and authorized/denied configuration update flows are absent from the current implementation | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py; apps/api/tests/test_identity_constraints.py; IMPLEMENTATION_STATUS.txt | Linked defect: FIN-08/FIN-09 capabilities not implemented
78:TC_SYS_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Browser smoke verified current sign-in/session/logout path against live frontend, FastAPI, and PostgreSQL. Full planned dashboard/settings, dependency health, Ollama available/unavailable, and correlation-log workflow cannot run because those components are not implemented | Tester/owner: Codex | Evidence: apps/web/tests/e2e/auth.spec.js; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: Current application implements auth starter only
79-TC_SEC_001 | Status: BLOCKED | Execution date: 2026-10-19 | Actual result: Local dependency audits and Bandit ran. Before remediation npm auditfound 3 vulnerable

dependency nodes (1 critical, 2 high); pip-audit found 14 advisory records across 3 packages. After targeted updates npm audit and pip-audit reported zero known vulnerabilities. Security job added to CI and release-package depends on it; workflow parsed locally but no GitHub runner execution was available. | Tester/owner: Codex | Evidence: /tmp/finsight-npm-audit-before.json; /tmp/finsight-npm-audit-after.json; /tmp/finsight-pip-audit.json; /tmp/finsight-pip-audit-after.json; .github/workflows/ci.yml; IMPLEMENTATION_STATUS.txt | Linked defect: GitHub Actions runrequired
80-TC_SEC_002 | Status: BLOCKED | Execution date: 2026-10-19 | Actual result: Secret-pattern scan of application/configuration paths reported no matches. Upload validation and prompt-injection tests could not be exercised because file upload and RAG/context construction are not implemented inthis repository; no related feature or tests were added. | Tester/owner: Codex | Evidence: local source/config credential-pattern scan; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt | Linked defect: Upload/RAG implementation required in authorized later stories
81-TC_DOC_001 | Status: PASS | Execution date: 2026-10-19 | Actual result: Reviewed documented current endpoints and schemas against generated FastAPI OpenAPI; representative invalid login returned 422 with `detail`, and unauthenticated `/auth/me` returned 401 with the documented generic detail. Architecture and compatibility notes distinguish current implementation from target features. | Tester/owner: Codex | Evidence: docs/architecture/README.md; docs/architecture/adr/; command output recorded in IMPLEMENTATION_STATUS.txt | Linked defect: —
82-TC_TRACE_001 | Status: PASS | Execution date: 2026-10-19 | Actual result: All 23 Sprint 1 plan aliases have verified Jira mappings; 22 have explicit SRS requirement IDs and FS-11-09/FIN-80 is explicitly recorded as a process story with no direct SRS ID; all 54 source test cases map to a Sprint 1 story; Release 2 labels remain intact; unmapped requirements and catalog extras are reported explicitly. | Tester/owner: Codex | Evidence: docs/requirements/traceability-matrix.md; docs/requirements/traceability-requirements.csv; docs/requirements/traceability-stories.csv; scripts/validate_traceability.py | Linked defect: —
83-TC_MGMT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
84-TC_REL_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
85-TC_ETH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
86-TC_OPS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
87-TC_OPS_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
88-TC_OPS_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
89-TC_AUTHN_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: Login/session/persistence/protected request verified | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —

90-TC_AUTHN_002 | Status: PASS | Execution date: 2026-10-18 | Actual result: Generic failure responses verified | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
91-TC_AUTHN_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Logout revocation and replay rejection verified | Tester/owner: Codex| Evidence: apps/api/tests/test_auth.py | Linked defect: —
92-TC_AUTHN_004 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Password recovery is required while password authentication is enabled; implementation and delivery approach await user decision | Tester/owner: Codex | Evidence: conversation.txt Q-005; SRS FR-P1-03 | Linked defect: —
93-TC_AUTHN_005 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Public registration is absent, but admin onboarding workflow is incomplete | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
94:TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
95:TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
97-TC_AUTHSEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
98-TC_AUTHSEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
99-TC_AUTHSEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
100-TC_AUTHSEC_004 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
101-TC_AUTHN_006 | Status: PASS | Execution date: 2026-10-18 | Actual result: Disposable synthetic database dump contained password/session digests; plaintext password/token absent; API test checked captured logs/stdout/stderr and response | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py; disposable scan summarized in IMPLEMENTATION_STATUS.txt (dump removed) | Linked defect: —
102-TC_AUTHN_007 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Local cookie flags checked; deployed HTTPS verification unavailable | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
103-TC_AUTHN_008 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
104-TC_AUTHN_009 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
105-TC_LLM_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
106-TC_LLM_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

107-TC_LLM_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
108-TC_CFG_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
109-TC_CFG_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
110-TC_CFG_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
111-TC_CFG_004 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
112-TC_CRED_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
113-TC_CRED_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
114-TC_PRIV_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
115:TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
116-TC_EXEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
117-TC_EXEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
118-TC_EXEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
119-TC_DASH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
120-TC_DASH_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
121-TC_INT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
122:TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
123-TC_BOUNDARY_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
124-
125-Additional test evidence — 2026-10-20
126-- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q tests/test_identity_constraints.py
127-- Result: 3 passed, 0 failed, 3 warnings.
128-- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
129-- Result: 55 passed, 0 failed, 9 warnings in 9.52s.
130-- Environment: local PostgreSQL 17.6; dedicated finsight_test database.
131-- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.

132-- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
134-
135-FIN-15 route-level authorization test update — 2026-10-20
136-- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
===== 5. FIN-15 status records =====
IMPLEMENTATION_STATUS.txt-55-
IMPLEMENTATION_STATUS.txt-56-FIN-13 / FS-01-01 — Authenticate and manage sessions
IMPLEMENTATION_STATUS.txt-57-Status: PARTIAL
IMPLEMENTATION_STATUS.txt-58-Jira: FIN-13 (Sprint 1 — Foundation; no Jira changes made)
IMPLEMENTATION_STATUS.txt:59:Reviewed requirements: SRS FR-P1-01..04, FR-P1-06, FR-P1-08 and NFR-P1-01..03/05; canonical identity DDL `Database/schema (1).sql` (`roles`, `users`, `auth_sessions`); backlog FS-01-01 page 2; test-plan management cases TC_AUTHN_001..005 and TC_AUTHZ_003.
IMPLEMENTATION_STATUS.txt-60-
IMPLEMENTATION_STATUS.txt-61-Implementation summary:
IMPLEMENTATION_STATUS.txt-62-- Added FastAPI login, logout, and protected `/auth/me` endpoints; generic errors; Argon2id password verification including a dummy hash check for unknown accounts; opaque random session cookie with only its SHA-256 digest persisted; revocation and configurable expiry/inactivity checks; strict configured CORS origin and Origin checks on mutations.
IMPLEMENTATION_STATUS.txt-63-- Added a minimal, versioned PostgreSQL migration for only canonical `roles`, `users`, and `auth_sessions` identity records. It was applied only to a disposable PostgreSQL cluster.
IMPLEMENTATION_STATUS.txt-64-- Added a local administrator/DB-access-controlled account provisioning CLI; there is no public registration endpoint.
IMPLEMENTATION_STATUS.txt-65-- Integrated the Next.js login/logout/session display using credentialed API requests and accessible labels/focus/error status.
IMPLEMENTATION_STATUS.txt-66-- Updated the safe environment template and README with auth flow, migration, provisioning, local test setup, and production cookie guidance.
IMPLEMENTATION_STATUS.txt-67-
--
IMPLEMENTATION_STATUS.txt-88-- 2026-10-18 TC_AUTHN_006: synthetic random credentials/session token inserted in disposable PostgreSQL, `pg_dump` scanned in memory; plaintext password and token absent, stored password/session digests present. Synthetic user

deleted and temporary dump removed. Login test also checks captured logs/stdout/stderr and response for sensitive values. PASS for these exercised checks.
IMPLEMENTATION_STATUS.txt-89-- 2026-10-18 TC_AUTHN_007 remains BLOCKED: no deployed HTTPS endpoint was available. Local test proves only that `COOKIE_SECURE=true` sets the Secure cookie attribute, not deployment transport enforcement.
IMPLEMENTATION_STATUS.txt-90-- Re-read SRS FR-P1-03/04: because password authentication is enabled, password recovery is required by the SRS and is not implemented; administrator-controlled invitation workflow is likewise not implemented. See Q-004 and Q-005; no acceptance claim is made pending user decisions.
IMPLEMENTATION_STATUS.txt-91-
IMPLEMENTATION_STATUS.txt:92:Test execution: detailed statuses and evidence are recorded in `SPRINT_1_TEST_EXECUTION_STATUS.txt`. TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, and the shared session-expiry behavior in TC_AUTHZ_003 passed against disposable PostgreSQL. TC_AUTHN_005 is BLOCKED because the full administrator invitation lifecycle is not implemented. TC_AUTHN_006 passed the disposable database dump/log/API privacy checks recorded below; TC_AUTHN_007 is BLOCKED pending deployed HTTPS verification. TC_AUTHN_004 is BLOCKED pending the SRS-required password recovery scope/delivery decision.
IMPLEMENTATION_STATUS.txt-93-
IMPLEMENTATION_STATUS.txt-94-Remaining acceptance criteria / blockers:
IMPLEMENTATION_STATUS.txt-95-- Decide whether trusted local database-operator provisioning satisfies onboarding or authorize application-admin invitations; separately decide whether to implement password recovery and approve its delivery approach. See Q-004 and Q-005 in `conversation.txt`.
IMPLEMENTATION_STATUS.txt-96-- Deployed HTTPS verification is blocked pending an HTTPS deployment/endpoint; local secure-cookie behavior alone is insufficient. Role/permission administration, authentication event/audit recording, MFA, rate limiting, and broader auth cases remain unverified against SRS-wide requirements.
IMPLEMENTATION_STATUS.txt-97-- Run the true clean-clone verification and final Git status/diff review when Git metadata responds and the authorized revision is cloneable. Record exact immutable-path diff evidence.
IMPLEMENTATION_STATUS.txt-98-- CI, independent code review, deployed configuration, and final Definition of Done have not been completed. Do not mark FIN-13 VERIFIED COMPLETE or Done.
IMPLEMENTATION_STATUS.txt-99-
IMPLEMENTATION_STATUS.txt-100-FIN-73 / FS-11-02 — Run CI quality gates on every pull request
--
IMPLEMENTATION_STATUS.txt-315-- CSV trailing-whitespace scan: 0 rows. `git diff --check`: PASS, exit 0.
IMPLEMENTATION_STATUS.txt-316-GitHub-side limitation: `git show --check --format= HEAD` against the existing root commit exits 2 with 1,323 diagnostics, including immutable source PDFs and other pre-existing root-commit files. No source PDF/SQL/diagram/test plan was edited. The targeted working diff passes `git diff --check`; an incremental commit/push is needed

so the next GitHub run checks only the corrective diff. No commit, push, Jira update, or remote rerun was made. A new GitHub Actions result is required before claiming the repair passed remotely; FIN-73/74/79 status is unchanged.
IMPLEMENTATION_STATUS.txt-317-Final review note (2026-10-19): `git diff --check` exited 0 for the targeted workflow/CSV/script changes before coordination records were appended. A later full `git diff --check` attempt timed out after 8 seconds (intermittent Git responsiveness); direct trailing-whitespace scans of `.github/workflows/ci.yml`, `docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both updated coordination files found zero whitespace errors and all had final newlines. The historical root-commit check result above remains distinct from the current worktree check.
IMPLEMENTATION_STATUS.txt-318-
IMPLEMENTATION_STATUS.txt:319:FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)
IMPLEMENTATION_STATUS.txt-320-Status: BLOCKED pending role-scope decision; implementation not started.
IMPLEMENTATION_STATUS.txt:321:Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
IMPLEMENTATION_STATUS.txt-322-Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorize minimal canonical workspace membership model.
IMPLEMENTATION_STATUS.txt-323-Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence.No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchangedpending decision and executable verification.
IMPLEMENTATION_STATUS.txt:324:Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
IMPLEMENTATION_STATUS.txt-325-

IMPLEMENTATION_STATUS.txt:326:FIN-15 verification update — 2026-10-20
IMPLEMENTATION_STATUS.txt-327-- PostgreSQL 17.6 is running locally.
IMPLEMENTATION_STATUS.txt-328-- Created and used the dedicated finsight_test database.
IMPLEMENTATION_STATUS.txt-329-- Applied apps/api/migrations/0001_auth_identity.sql successfully.
IMPLEMENTATION_STATUS.txt-330-- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
IMPLEMENTATION_STATUS.txt-331-- Database integration tests: 3 passed.
IMPLEMENTATION_STATUS.txt-332-- Full API test suite: 55 passed, 0 failed, 9 warnings.
IMPLEMENTATION_STATUS.txt-333-- git diff --check: no errors reported.
IMPLEMENTATION_STATUS.txt-334-- Warning: Starlette/httpx deprecation warnings remain.
IMPLEMENTATION_STATUS.txt-335-- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
IMPLEMENTATION_STATUS.txt:336:- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
IMPLEMENTATION_STATUS.txt-337-
IMPLEMENTATION_STATUS.txt:338:FIN-15 implementation update — 2026-10-20
IMPLEMENTATION_STATUS.txt-339-- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
IMPLEMENTATION_STATUS.txt-340-- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
IMPLEMENTATION_STATUS.txt-341-- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
IMPLEMENTATION_STATUS.txt:342:- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
IMPLEMENTATION_STATUS.txt:343:- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are checked.
IMPLEMENTATION_STATUS.txt-344-- No migrations, commits, pushes, or workspace schema changes performed by this patch script.
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-47-Actual result: The test confirmed `/auth/register` is not exposed (404). A local provisioning command existsand requires database access, but the administrator onboarding workflow and invitation lifecycle are not implemented or verified.
SPRINT_1_TEST_EXECUTION_STATUS.txt-48-Evidence: test `test_public_registration_is_not_available`; `apps/api/app/provision_user.py`.
SPRINT_1_TEST_EXECUTION_STATUS.txt-49-Remaining: implement/verify the approved administrator-controlled onboarding workflow in its authorized scope.
SPRINT_1_TEST_EXECUTION_STATUS.txt-50-

SPRINT_1_TEST_EXECUTION_STATUS.txt:51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
SPRINT_1_TEST_EXECUTION_STATUS.txt-52-Status: PASS (session-expiry behavior exercised as a FIN-13 acceptance check; Jira scope remains unchanged)
SPRINT_1_TEST_EXECUTION_STATUS.txt-53-Actual result: A session with stale `last_seen_at` was rejected by the protected endpoint. TTL bounds are validated and expiry uses `SESSION_TTL_MINUTES`.
SPRINT_1_TEST_EXECUTION_STATUS.txt-54-Evidence: test `test_expired_session_is_rejected` in the command above.
SPRINT_1_TEST_EXECUTION_STATUS.txt-55-
SPRINT_1_TEST_EXECUTION_STATUS.txt-56-TC_AUTHN_006 — Verify passwords are not stored in plaintext
SPRINT_1_TEST_EXECUTION_STATUS.txt-57-Status: PASS
SPRINT_1_TEST_EXECUTION_STATUS.txt-58-Execution date: 2026-10-18
SPRINT_1_TEST_EXECUTION_STATUS.txt-59-Actual result: A synthetic random password and session token were inserted into the disposable PostgreSQL database; the generated `pg_dump` contained their password/session digests and neither plaintext value. The login test also verified response and captured log/stdout/stderr privacy. The synthetic user was deleted and dump removed.
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-90-TC_AUTHN_002 | Status: PASS | Execution date: 2026-10-18 | Actual result: Generic failure responses verified| Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-91-TC_AUTHN_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Logout revocation and replay rejection verified | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-92-TC_AUTHN_004 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Password recovery is required while password authentication is enabled; implementation and delivery approach await user decision | Tester/owner: Codex | Evidence: conversation.txt Q-005; SRS FR-P1-03 | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-93-TC_AUTHN_005 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Public registration is absent, but admin onboarding workflow is incomplete | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:94:TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:95:TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-97-TC_AUTHSEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

SPRINT_1_TEST_EXECUTION_STATUS.txt-98-TC_AUTHSEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-99-TC_AUTHSEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-100-TC_AUTHSEC_004 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-101-TC_AUTHN_006 | Status: PASS | Execution date: 2026-10-18 | Actual result: Disposable synthetic database dump contained password/session digests; plaintext password/token absent; API test checked captured logs/stdout/stderr and response | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py; disposable scan summarized in IMPLEMENTATION_STATUS.txt (dump removed) | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-102-TC_AUTHN_007 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Local cookie flags checked; deployed HTTPS verification unavailable | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-103-TC_AUTHN_008 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-104-TC_AUTHN_009 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-131-- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
SPRINT_1_TEST_EXECUTION_STATUS.txt-132-- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
SPRINT_1_TEST_EXECUTION_STATUS.txt-133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS withoutverifying their mapping to the test inventory.
SPRINT_1_TEST_EXECUTION_STATUS.txt-134-
SPRINT_1_TEST_EXECUTION_STATUS.txt:135:FIN-15 route-level authorization test update — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt:136:- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
SPRINT_1_TEST_EXECUTION_STATUS.txt-137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
SPRINT_1_TEST_EXECUTION_STATUS.txt-138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
--
FUNCTION_TEST_TRACEABILITY.txt-1-FinSight AI — Function/Test Traceability
FUNCTION_TEST_TRACEABILITY.txt-2-
FUNCTION_TEST_TRACEABILITY.txt:3:FIN-15 / FS-01-02 — platform authorization capability endpoint

FUNCTION_TEST_TRACEABILITY.txt-4-Function: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-5-Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
FUNCTION_TEST_TRACEABILITY.txt-6-Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
FUNCTION_TEST_TRACEABILITY.txt:7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt-8-Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mapped tests and confirming the expected behavior.
(base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % source /Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % >....
Traceability status:
- TC_AUTHZ_001: the executed integration test covers anonymous denial. Record invalid session denial as PASS only if the current test code explicitly asserts that case. Review any other acceptance criteria for this case separately.
- TC_AUTHZ_002: PASS for the tested platform-admin allow / standard-user deny behavior, including the tested client-supplied X-Role header not granting permission. This does not prove that unimplemented model/provider administration operations exist.
- TC_AUTHZ_003: existing session-expiry/revocation regression tests passed in a prior recorded run. They were not separately rerun in run 20261020_141030.
- TC_PRIV_002: BLOCKED / deferred; workspace membership and resource-level authorization are outside the approved platform-only scope.
- TC_SYS_001: do not mark PASS based only on the API test suite; broader system-level acceptance remains to be verified.
Evidence paths:
- test-results/FIN-15/20261020_141030_identity_authorization.log
- test-results/FIN-15/20261020_141030_full_api_suite.log
- test-results/FIN-15/run_20261020_141030_summary.txt
Only mark a case PASS when its mapped assertions have actually run and the expected behavior is confirmed. This addendum supplements rather than deletes historical entries.
EOF
echo
echo "=== Check whitespace and patch formatting ==="
git diff --check || exit 1
echo
echo "=== Confirm documentation changes ==="
git status --short
git diff --stat -- IMPLEMENTATION_STATUS.txt SPRINT_1_TEST_EXECUTION_STATUS.txt FUNCTION_TEST_TRACEABILITY.txt

```
echo
echo "Documentation addenda appended. No commit or push performed."
zsh: command not found: #
zsh: command not found: #
zsh: command not found: #
=== Check whitespace and patch formatting ===
=== Confirm documentation changes ===
?? .DS_Store
?? .localized
?? 43Days/
?? Comptative_guide.zip
?? Comptative_guide/
?? DaVinci_Resolve/
?? Data/
?? Duke_Cloud_computing/
?? FUNCTION_TEST_TRACEABILITY.txt
?? IMPLEMENTATION_STATUS.txt
?? Images/
?? ML_deploy/
?? NVDIA_Play_Book/
?? Resume.pdf
?? SE_github/
?? SE_mini_project/
?? SPRINT_1_TEST_EXECUTION_STATUS.txt
?? "Sandeep H_portflio.pdf"
?? "Screenshot 2026-10-19 at 9.52.10\342\200\257AM.png"
?? "Screenshot 2026-10-20 at 10.29.39\342\200\257AM.png"
?? "Screenshot 2026-10-20 at 9.50.23\342\200\257AM.png"
?? System_design/
?? test-results/
?? ubuntu-24.04.3-live-server-arm64.iso
Documentation addenda appended. No commit or push performed.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro Documents % git diff --check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro Documents % >....
echo "=== Confirm project root ==="
pwd
git rev-parse --show-toplevel
echo
echo "=== Confirm documentation files ==="
for FILE in \
  IMPLEMENTATION_STATUS.txt \
  SPRINT_1_TEST_EXECUTION_STATUS.txt \
  FUNCTION_TEST_TRACEABILITY.txt
do
```

```
  if [ -f "$FILE" ]; then
    echo "FOUND: $FILE"
    tail -n 8 "$FILE"
    echo
  else
    echo "MISSING: $FILE"
  fi
done
echo "=== Confirm test evidence ==="
ls -lh \
  test-results/FIN-15/20261020_141030_identity_authorization.log \
  test-results/FIN-15/20261020_141030_full_api_suite.log \
  test-results/FIN-15/run_20261020_141030_summary.txt
echo
echo "=== Check whitespace ==="
git diff --check
echo
echo "=== Project Git status ==="
git status --short
=== Confirm project root ===
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI
/Users/sandeeph/Documents/NVDIA_Play_Book/FinSight_AI
=== Confirm documentation files ===
FOUND: IMPLEMENTATION_STATUS.txt
FIN-15 implementation update — 2026-10-20
- Approved scope: platform-level authorization only; workspace roles, membership, and
workspace tables deferred.
- Added GET /platform/admin/capability to the real FastAPI application, protected by the
database-backed platform.admin permission dependency. This endpoint is a minimal
authorization capability check and does not mutate data.
- Updated the database integration test to exercise the real application route for anonymous,
platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to
verify client headers do not grant permission.
- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001,
TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do
not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are
checked.
- No migrations, commits, pushes, or workspace schema changes performed by this patch
script.
FOUND: SPRINT_1_TEST_EXECUTION_STATUS.txt
- Migrations applied successfully before test execution: 0001_auth_identity.sql and
0002_platform_authorization.sql.
- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
```

- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
FIN-15 route-level authorization test update — 2026-10-20
- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
FOUND: FUNCTION_TEST_TRACEABILITY.txt
FinSight AI — Function/Test Traceability
FIN-15 / FS-01-02 — platform authorization capability endpoint
Function: GET /platform/admin/capability
Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-suppliedX-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mapped tests and confirming the expected behavior.
=== Confirm test evidence ===
-rw-r--r--@ 1 sandeeph staff   1.7K Oct 20 14:10 test-results/FIN-15/20261020_141030_full_api_suite.log
-rw-r--r--@ 1 sandeeph staff   1.2K Oct 20 14:10 test-results/FIN-15/20261020_141030_identity_authorization.log
-rw-r--r--@ 1 sandeeph staff   365B Oct 20 14:10 test-results/FIN-15/run_20261020_141030_summary.txt
=== Check whitespace ===
apps/api/tests/test_identity_constraints.py:81: trailing whitespace.
+
=== Project Git status ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py

```
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....
- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
  integration test; this does not imply missing model/provider operations exist.
- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
  it was not separately rerun under run ID 20261020_141030.
- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
  authorization are outside the approved platform-only scope.
- TC_SYS_001: not established by the API suite alone; broader system acceptance remains
  to be verified.
Do not infer full story completion from a green test suite. Historical entries are
retained, and this addendum records the latest observed execution.
EOF
echo
echo "=== Verify evidence files ==="
ls -lh \
  test-results/FIN-15/20261020_141030_identity_authorization.log \
  test-results/FIN-15/20261020_141030_full_api_suite.log \
  test-results/FIN-15/run_20261020_141030_summary.txt || exit 1
echo
echo "=== Check whitespace ==="
git diff --check || exit 1
echo
echo "=== Documentation change summary ==="
git diff --stat -- IMPLEMENTATION_STATUS.txt SPRINT_1_TEST_EXECUTION_STATUS.txt
FUNCTION_TEST_TRACEABILITY.txt apps/api/tests/test_identity_constraints.py
echo
echo "=== Git status ==="
git status --short
echo
echo "Finished. No files staged; no commit or push performed."
Removed trailing whitespace from line 81 only.
=== Verify evidence files ===
-rw-r--r--@ 1 sandeeph  staff   1.7K Oct 20 14:10
test-results/FIN-15/20261020_141030_full_api_suite.log
-rw-r--r--@ 1 sandeeph  staff   1.2K Oct 20 14:10
test-results/FIN-15/20261020_141030_identity_authorization.log
```

```
-rw-r--r--@ 1 sandeeph  staff   365B Oct 20 14:10
test-results/FIN-15/run_20261020_141030_summary.txt
=== Check whitespace ===
=== Documentation change summary ===
 IMPLEMENTATION_STATUS.txt                  | 50
++++++++++++++++++++++++++++++++++++++++++++++++++
 SPRINT_1_TEST_EXECUTION_STATUS.txt         | 33
+++++++++++++++++++++++++++++++++
 apps/api/tests/test_identity_constraints.py | 81
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
+++++++++
 3 files changed, 164 insertions(+)
=== Git status ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
Finished. No files staged; no commit or push performed.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % git diff --check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %




(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....

mkdir -p test-results/FIN-15
AUDIT="test-results/FIN-15/$(date '+%Y%m%d_%H%M%S')_acceptance_review.txt"

{
  echo "FIN-15 Acceptance Criteria Review"
```

```
  date
  echo

  echo "=== FIN-15 references in project documents ==="
  grep -n -i -C 4 'FIN-15' \
    IMPLEMENTATION_STATUS.txt \
    SPRINT_1_TEST_EXECUTION_STATUS.txt \
    FUNCTION_TEST_TRACEABILITY.txt \
    README.md 2>/dev/null || true

  echo
  echo "=== Authorization and permission test references ==="
  grep -R -n -E
'TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_001|FR-P1-05|FR
-P1-06|FR-P1-07' \
    docs apps/api/tests FUNCTION_TEST_TRACEABILITY.txt \
    2>/dev/null || true

  echo
  echo "=== FIN-15 test implementation ==="
  sed -n '1,180p' apps/api/tests/test_identity_constraints.py

  echo
  echo "=== Authorization endpoint and dependency ==="
  grep -n -B 8 -A 24 -E 'require_permission|platform/admin/capability' \
    apps/api/app/main.py
} | tee "$AUDIT"

echo
echo "Review saved to: $AUDIT"

FIN-15 Acceptance Criteria Review
Tue Oct 20 14:16:30 IST 2026

=== FIN-15 references in project documents ===
IMPLEMENTATION_STATUS.txt-315-- CSV trailing-whitespace scan: 0 rows. `git diff --check`:
PASS, exit 0.
IMPLEMENTATION_STATUS.txt-316-GitHub-side limitation: `git show --check --format= HEAD`
against the existing root commit exits 2 with 1,323 diagnostics, including immutable source
PDFs and other pre-existing root-commit files. No source PDF/SQL/diagram/test plan was
edited. The targeted working diff passes `git diff --check`;an incremental commit/push is needed
so the next GitHub run checks only the corrective diff. No commit, push, Jira update, or remote
rerun was made. A new GitHub Actions result is required before claiming the repair passed
remotely; FIN-73/74/79 status is unchanged.
```

IMPLEMENTATION_STATUS.txt-317-Final review note (2026-10-19): `git diff --check` exited 0 for the targeted workflow/CSV/script changes before coordination records were appended. A later full `git diff --check` attempt timed out after 8 seconds (intermittent Git responsiveness); direct trailing-whitespace scans of `.github/workflows/ci.yml`, `docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both updated coordination files found zero whitespace errors and all had final newlines. The historical root-commit check result above remains distinct from the current worktree check.
IMPLEMENTATION_STATUS.txt-318-
IMPLEMENTATION_STATUS.txt:319:FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)
IMPLEMENTATION_STATUS.txt-320-Status: BLOCKED pending role-scope decision; implementation not started.
IMPLEMENTATION_STATUS.txt-321-Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
IMPLEMENTATION_STATUS.txt-322-Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorize minimal canonical workspace membership model.
IMPLEMENTATION_STATUS.txt-323-Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.
IMPLEMENTATION_STATUS.txt:324:Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected routeapplication, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
IMPLEMENTATION_STATUS.txt-325-
IMPLEMENTATION_STATUS.txt:326:FIN-15 verification update — 2026-10-20
IMPLEMENTATION_STATUS.txt-327-- PostgreSQL 17.6 is running locally.
IMPLEMENTATION_STATUS.txt-328-- Created and used the dedicated finsight_test database.

IMPLEMENTATION_STATUS.txt-329-- Applied apps/api/migrations/0001_auth_identity.sql successfully.
IMPLEMENTATION_STATUS.txt-330-- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
--
IMPLEMENTATION_STATUS.txt-332-- Full API test suite: 55 passed, 0 failed, 9 warnings.
IMPLEMENTATION_STATUS.txt-333-- git diff --check: no errors reported.
IMPLEMENTATION_STATUS.txt-334-- Warning: Starlette/httpx deprecation warnings remain.
IMPLEMENTATION_STATUS.txt-335-- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
IMPLEMENTATION_STATUS.txt:336:- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
IMPLEMENTATION_STATUS.txt-337-
IMPLEMENTATION_STATUS.txt:338:FIN-15 implementation update — 2026-10-20
IMPLEMENTATION_STATUS.txt-339-- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
IMPLEMENTATION_STATUS.txt-340-- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
IMPLEMENTATION_STATUS.txt-341-- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
IMPLEMENTATION_STATUS.txt-342-- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
IMPLEMENTATION_STATUS.txt:343:- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are checked.
IMPLEMENTATION_STATUS.txt-344-- No migrations, commits, pushes, or workspace schema changes performed by this patch script.
IMPLEMENTATION_STATUS.txt-345-
IMPLEMENTATION_STATUS.txt:346:FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
IMPLEMENTATION_STATUS.txt-347-Latest run: 20261020_141030
IMPLEMENTATION_STATUS.txt-348-Recorded revision: 64f2637
IMPLEMENTATION_STATUS.txt-349-Python: 3.14.6
IMPLEMENTATION_STATUS.txt-350-Database: finsight_test
--
IMPLEMENTATION_STATUS.txt-355-- Both pytest commands exited with code 0.
IMPLEMENTATION_STATUS.txt-356-- The test-run summary records Overall result: PASS.
IMPLEMENTATION_STATUS.txt-357-
IMPLEMENTATION_STATUS.txt-358-Evidence:

IMPLEMENTATION_STATUS.txt:359:-
test-results/FIN-15/20261020_141030_identity_authorization.log
IMPLEMENTATION_STATUS.txt:360:- test-results/FIN-15/20261020_141030_full_api_suite.log
IMPLEMENTATION_STATUS.txt:361:- test-results/FIN-15/run_20261020_141030_summary.txt
IMPLEMENTATION_STATUS.txt-362-
IMPLEMENTATION_STATUS.txt-363-The warnings were Starlette/httpx deprecations. The passing test suites establish
IMPLEMENTATION_STATUS.txt:364:the behavior exercised by those tests, not automatic completion of every FIN-15
IMPLEMENTATION_STATUS.txt-365-acceptance criterion. Workspace membership and resource-level authorization remain
IMPLEMENTATION_STATUS.txt-366-deferred under the approved platform-only scope. Earlier entries are retained as
IMPLEMENTATION_STATUS.txt-367-historical records; this addendum records the later successful run.
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-131-- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
SPRINT_1_TEST_EXECUTION_STATUS.txt-132-- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
SPRINT_1_TEST_EXECUTION_STATUS.txt-133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
SPRINT_1_TEST_EXECUTION_STATUS.txt-134-
SPRINT_1_TEST_EXECUTION_STATUS.txt:135:FIN-15 route-level authorization test update — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt-136-- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
SPRINT_1_TEST_EXECUTION_STATUS.txt-137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
SPRINT_1_TEST_EXECUTION_STATUS.txt-138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
SPRINT_1_TEST_EXECUTION_STATUS.txt-139-
SPRINT_1_TEST_EXECUTION_STATUS.txt:140:FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)
SPRINT_1_TEST_EXECUTION_STATUS.txt-141-Run ID: 20261020_141030
SPRINT_1_TEST_EXECUTION_STATUS.txt-142-Python: 3.14.6
SPRINT_1_TEST_EXECUTION_STATUS.txt-143-Database: finsight_test
SPRINT_1_TEST_EXECUTION_STATUS.txt-144-Recorded Git revision: 64f2637
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-146-Results:

SPRINT_1_TEST_EXECUTION_STATUS.txt-147-- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-148-- Full API suite: 55 passed, 10 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-149-- Evidence files:
SPRINT_1_TEST_EXECUTION_STATUS.txt:150:
test-results/FIN-15/20261020_141030_identity_authorization.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:151:
test-results/FIN-15/20261020_141030_full_api_suite.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:152:
test-results/FIN-15/run_20261020_141030_summary.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt-153-
SPRINT_1_TEST_EXECUTION_STATUS.txt-154-These results supersede earlier NOT RUN notes for the test execution performed
SPRINT_1_TEST_EXECUTION_STATUS.txt-155-in this run. They do not establish that every mapped test-plan case or the entire
SPRINT_1_TEST_EXECUTION_STATUS.txt:156:FIN-15 story is complete. Workspace-level authorization remains deferred.
--
FUNCTION_TEST_TRACEABILITY.txt-1-FinSight AI — Function/Test Traceability
FUNCTION_TEST_TRACEABILITY.txt-2-
FUNCTION_TEST_TRACEABILITY.txt:3:FIN-15 / FS-01-02 — platform authorization capability endpoint
FUNCTION_TEST_TRACEABILITY.txt-4-Function: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-5-Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
FUNCTION_TEST_TRACEABILITY.txt-6-Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
FUNCTION_TEST_TRACEABILITY.txt-7-Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt-8-Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mapped tests and confirming the expected behavior.
FUNCTION_TEST_TRACEABILITY.txt-9-
FUNCTION_TEST_TRACEABILITY.txt:10:FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
FUNCTION_TEST_TRACEABILITY.txt-11-Run ID: 20261020_141030
FUNCTION_TEST_TRACEABILITY.txt-12-Endpoint: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-13-
FUNCTION_TEST_TRACEABILITY.txt-14-Observed execution:
FUNCTION_TEST_TRACEABILITY.txt-15-- tests/test_identity_constraints.py: 3 passed, 4 warnings.

FUNCTION_TEST_TRACEABILITY.txt-16-- Full API suite: 55 passed, 10 warnings.
FUNCTION_TEST_TRACEABILITY.txt-17-- Both pytest commands exited with code 0.
FUNCTION_TEST_TRACEABILITY.txt-18-- Evidence:
FUNCTION_TEST_TRACEABILITY.txt:19:
test-results/FIN-15/20261020_141030_identity_authorization.log
FUNCTION_TEST_TRACEABILITY.txt:20:
test-results/FIN-15/20261020_141030_full_api_suite.log
FUNCTION_TEST_TRACEABILITY.txt:21:
test-results/FIN-15/run_20261020_141030_summary.txt
FUNCTION_TEST_TRACEABILITY.txt-22-
FUNCTION_TEST_TRACEABILITY.txt-23-Case-status guidance:
FUNCTION_TEST_TRACEABILITY.txt-24-- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt-25- test suite passed, but broader acceptance criteria must also be checked.

=== Authorization and permission test references ===
docs/requirements/traceability-stories.csv:2:FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35;NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:4:FS-01-03,FIN-14,LIVE JIRA VERIFIED 2026-10-19,Protect accounts and audit authentication,Sprint 1,Release 1 per Jira

issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-10; FR-P1-11; FR-P1-12; FR-P9-13; NFR-G-08; NFR-G-11; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P9-02,Security events are auditable; repeated failures are throttled; MFA/session features are enabled only when configured. detected and limited.,TC_AUTHSEC_001; TC_AUTHSEC_002; TC_AUTHSEC_003; TC_INT_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_002=NOT RUN; TC_AUTHSEC_003=NOT RUN; TC_INT_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:6:FS-01-05,FIN-17,LIVE JIRA VERIFIED 2026-10-19,Meet identity security and accessibility requirements,Sprint 1,Release 1per Jira issue,FR-P1-01; NFR-G-03; NFR-G-18; NFR-G-19; NFR-G-20; NFR-G-21; NFR-P1-01; NFR-P1-02; NFR-P1-03; NFR-P1-04; NFR-P1-05; NFR-P1-06,"No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002;TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:14:FS-02-08,FIN-25,LIVE JIRA VERIFIED 2026-10-19,"Keep dashboard responsive, isolated and freshness-aware",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-01; NFR-P2-02; NFR-P2-03; NFR-P2-04; NFR-P2-05; NFR-P8-04,Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:45:FS-08-01,FIN-57,LIVE JIRA VERIFIED 2026-10-19,"Configure Ollama, model selection and inference parameters",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-01; FR-P8-02; FR-P8-03; FR-P8-04; FR-P8-05; FR-P8-12; FR-P8-14; FR-P8-16; NFR-G-08; NFR-G-13; NFR-G-22;

NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02,Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:49:FS-08-05,FIN-61,LIVE JIRA VERIFIED 2026-10-19,Secure and validate configuration changes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-14; FR-P8-16; NFR-G-03; NFR-G-07; NFR-G-08; NFR-G-14; NFR-G-22;NFR-G-26; NFR-P8-01; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02; NFR-P9-03,Secrets are referenced securely; config changes are audited; validation precedes activation; retrieval/index compatibility is checked. production unexpectedly.,TC_CFG_001; TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_INT_001; TC_TRACE_001,TC_CFG_001=NOT RUN; TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_INT_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:65:FS-11-04,FIN-75,LIVE JIRA VERIFIED 2026-10-19,Apply TDD and maintain unit/integration/E2E suites,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-07; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-27; NFR-G-30; NFR-G-31;

NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-04; NFR-P8-02; NFR-P9-02,"Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably. implementation where practical so that behavior is verified continuously.",TC_CI_001; TC_COV_001; TC_DB_001; TC_INT_001; TC_OPS_003;TC_SEC_002; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_COV_001=PASS; TC_DB_001=BLOCKED; TC_INT_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,IMPLEMENTATION_STATUS.txt; issue-specific paths in prior records,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:72:FS-11-11,FIN-82,LIVE JIRA VERIFIED 2026-10-19,"Document usability, AI use, licenses and data rights",Sprint 1,Release1 per Jira issue,NFR-G-18; NFR-G-19; NFR-G-20; NFR-G-21; NFR-G-27; NFR-P1-06,AI-generated code is reviewed and tested; license/data rights are recorded; usability checks include accessibility and understandable failures. compliant.,TC_AUTHN_009; TC_ETH_001,TC_AUTHN_009=NOT RUN; TC_ETH_001=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:73:FS-11-12,FIN-83,LIVE JIRA VERIFIED 2026-10-19,"Add health checks, structured logs, retry and recovery runbook",Sprint1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-06; NFR-G-07; NFR-G-08; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-02; NFR-P7-04; NFR-P7-05; NFR-P8-04; NFR-P9-03,Health endpoints work; logs include run IDs and redact secrets; retries are bounded/idempotent; outage drill has recorded outcome. are diagnosable.,TC_BUILD_002; TC_DASH_002; TC_DB_001; TC_EXEC_001; TC_EXEC_002; TC_OPS_001; TC_OPS_002; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TRACE_001,TC_BUILD_002=BLOCKED; TC_DASH_002=NOT RUN; TC_DB_001=BLOCKED; TC_EXEC_001=NOT RUN; TC_EXEC_002=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-matrix.md:31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN,

TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23,NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt |Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:33:| FS-01-03 | [FIN-14](https://sandeephgowda8618.atlassian.net/browse/FIN-14) | Protect accounts and audit authentication | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-10, FR-P1-11, FR-P1-12, FR-P9-13, NFR-G-08, NFR-G-11, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P9-02 | Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED| — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:35:| FS-01-05 | [FIN-17](https://sandeephgowda8618.atlassian.net/browse/FIN-17) | Meet identity security and accessibilityrequirements | Sprint 1 | Release 1 per Jira issue | FR-P1-01, NFR-G-03, NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-P1-01, NFR-P1-02, NFR-P1-03, NFR-P1-04, NFR-P1-05, NFR-P1-06 | No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007,

TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:43:| FS-02-08 |
[FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:74:| FS-08-01 |
[FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05, FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:78:| FS-08-05 |
[FIN-61](https://sandeephgowda8618.atlassian.net/browse/FIN-61) | Secure and validate configuration changes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-14, FR-P8-16, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-22, NFR-G-26, NFR-P8-01, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02, NFR-P9-03 | Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js,

IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe account administration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecyclefollows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001,TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:101:| FS-11-11 | [FIN-82](https://sandeephgowda8618.atlassian.net/browse/FIN-82) | Document usability, AI use, licenses and data rights | Sprint 1 | Release 1 per Jira issue | NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-G-27, NFR-P1-06 | AI-generated code is reviewed and tested, license/data rights are recorded, usability checks include accessibility and understandable failures. compliant. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue | FR-P1-01,

FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create asession, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED,

TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
docs/requirements/traceability-matrix.md:122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN,

TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-executionpath, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2|
docs/requirements/traceability-matrix.md:132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state,model and parameters are traceable.

configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | LiveJira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped

foundation scope is absent from thecurrent implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state,model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
docs/requirements/traceability-matrix.md:377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
docs/requirements/traceability-matrix.md:378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |

docs/requirements/traceability-matrix.md:416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping isneeded. | Unmapped to source story |
docs/requirements/traceability-matrix.md:428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02,FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
docs/requirements/traceability-matrix.md:449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOTASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED |— | No direct

source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02,FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target andcommitted-SHA evidence are absent. | Unmapped to source story |
docs/requirements/traceability-matrix.md:458:| NFR-P1-05 | Information Disclosure | PDF p.5, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05 | FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_004, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:459:| NFR-P1-06 | Accessibility | PDF p.5, SRS P1 requirements | Identity and access | FS-01-05, FS-11-11 | FIN-17, FIN-82| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/web/app/page.js, apps/web/tests/ui/auth.spec.js | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25| Live Jira JQL

verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001| TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layoutswork on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | LiveJira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOTRUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |

docs/requirements/traceability-matrix.md:510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05,FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action

checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOTRUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 |FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |

docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN;TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local operator CLI

only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label
docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOTRUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05;FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py;

apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional trading DDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL

verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so thatAI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOTRUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live JiraJQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02;FS-02-08;

FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04;FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership;shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001;

TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03; FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74; FIN-75; FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,scripts/package_release.py;

docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
docs/requirements/traceability-requirements.csv:352:NFR-P1-05,Information Disclosure,PDF p.5; SRS P1 requirements,Identity and access,FS-01-01; FS-01-05,FIN-13; FIN-17,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_004; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:353:NFR-P1-06,Accessibility,PDF p.5; SRS P1 requirements,Identity and access,FS-01-05; FS-11-11,FIN-17; FIN-82,LiveJira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/web/app/page.js; apps/web/tests/ui/auth.spec.js,Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,LiveJira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25:

Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current imple

nt proving platform-admin authorization at the API boundary."""
189-   return {"permission": "platform.admin", "allowed": True}

Review saved to: test-results/FIN-15/20261020_141630_acceptance_review.txt
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd "$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

grep -R -n -E \
  'TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_001' \
  docs apps/api/tests \
  --exclude='*.pyc' 2>/dev/null
docs/requirements/traceability-stories.csv:2:FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35;NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin

policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:14:FS-02-08,FIN-25,LIVE JIRA VERIFIED 2026-10-19,"Keep dashboard responsive, isolated and freshness-aware",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-01; NFR-P2-02; NFR-P2-03; NFR-P2-04; NFR-P2-05; NFR-P8-04,Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN;

TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:45:FS-08-01,FIN-57,LIVE JIRA VERIFIED 2026-10-19,"Configure Ollama, model selection and inference parameters",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-01; FR-P8-02; FR-P8-03; FR-P8-04; FR-P8-05; FR-P8-12; FR-P8-14; FR-P8-16; NFR-G-08; NFR-G-13; NFR-G-22; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02,Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:65:FS-11-04,FIN-75,LIVE JIRA VERIFIED 2026-10-19,Apply TDD and maintain unit/integration/E2E suites,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-07; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-27; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37;

NFR-G-38; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-04; NFR-P8-02; NFR-P9-02,"Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably. implementation where practical so that behavior is verified continuously.",TC_CI_001; TC_COV_001; TC_DB_001; TC_INT_001; TC_OPS_003;TC_SEC_002; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_COV_001=PASS; TC_DB_001=BLOCKED; TC_INT_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,IMPLEMENTATION_STATUS.txt; issue-specific paths in prior records,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:73:FS-11-12,FIN-83,LIVE JIRA VERIFIED 2026-10-19,"Add health checks, structured logs, retry and recovery runbook",Sprint1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-06; NFR-G-07; NFR-G-08; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-02; NFR-P7-04; NFR-P7-05; NFR-P8-04; NFR-P9-03,Health endpoints work; logs include run IDs and redact secrets; retries are bounded/idempotent; outage drill has recorded outcome. are diagnosable.,TC_BUILD_002; TC_DASH_002; TC_DB_001; TC_EXEC_001; TC_EXEC_002; TC_OPS_001; TC_OPS_002; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TRACE_001,TC_BUILD_002=BLOCKED; TC_DASH_002=NOT RUN; TC_DB_001=BLOCKED; TC_EXEC_001=NOT RUN; TC_EXEC_002=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-matrix.md:31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL

| apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23,NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt |Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED| — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama,

model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05, FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | docs/requirements/traceability-matrix.md:83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe account administration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecyclefollows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001,TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | docs/requirements/traceability-matrix.md:94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where

practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue |
FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |

docs/requirements/traceability-matrix.md:119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create asession, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
docs/requirements/traceability-matrix.md:122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61,

FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN,

TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-executionpath, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2|
docs/requirements/traceability-matrix.md:132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state,model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN,

TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | LiveJira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN,

TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from thecurrent implementation. | Preserve source story release label | docs/requirements/traceability-matrix.md:344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state,model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label | docs/requirements/traceability-matrix.md:351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story | docs/requirements/traceability-matrix.md:376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label | docs/requirements/traceability-matrix.md:377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label | docs/requirements/traceability-matrix.md:378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04,

FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
docs/requirements/traceability-matrix.md:416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping isneeded. | Unmapped to source story |
docs/requirements/traceability-matrix.md:428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02,FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
docs/requirements/traceability-matrix.md:449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |

docs/requirements/traceability-matrix.md:450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOTASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED |— | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02,FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target andcommitted-SHA evidence are absent. | Unmapped to source story |
docs/requirements/traceability-matrix.md:460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary

content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001| TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layoutswork on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | LiveJira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002,

TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOTRUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05,FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001,

TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOTRUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain

protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 |FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004;

TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py;
apps/api/tests/test_auth.py,Evidence supports the current scoped behavior
only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF
p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05;
FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified
2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session;
logout invalidates it; invalid credentials reveal no account existence; onboarding follows
admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004;
TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT
IMPLEMENTED,—,Mapped foundation scope is absent from the current
implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF
p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05;
FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified
2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session;
logout invalidates it; invalid credentials reveal no account existence; onboarding follows
admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004;
TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN;TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local
operator CLI only),Local provisioning exists; administrator invitation/onboarding
workflow is absent.,Preserve source story release label
docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access
Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02;
FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16;
FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source
refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is
tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001;
TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002;
TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN;

TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOTRUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05;FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label

docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional trading DDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT

IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so thatAI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOTRUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live JiraJQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped

foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02;FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04;FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is

scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership;shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story

criterion; do not infer.,TC_DASH_002; TC_OPS_001;
TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF
p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02;
FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;
FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan
source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002;
TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational
Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;
FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;
FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source
refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003;
TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful
Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;
FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;
FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source
refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003;
TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment
Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and
operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03;
FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74;
FIN-75; FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No
mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001;
TC_OPS_001; TC_OPS_003; TC_REL_001;
TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED;
TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN;
TC_REL_001=NOT RUN; TC_SYS_001=NOT
RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no

deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,LiveJira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN;

TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive Changes,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65; FIN-75,Live Jira JQL verified2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002;TC_CFG_003; TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from thecurrent implementation.,Preserve source story release label

docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05; FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001; TC_CFG_003; TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT

IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

./docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;

TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py;
apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped
behavior only.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session
Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03;
FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL
verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a
session; logout invalidates it; invalid credentials reveal no account existence;
onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003;
TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py;
apps/api/tests/test_auth.py,Evidence supports the current scoped behavior
only.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password
Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03;
FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL
verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a
session; logout invalidates it; invalid credentials reveal no account existence;
onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003;
TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT
IMPLEMENTED,—,Mapped foundation scope is absent from the current
implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF
p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05;
FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified
2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session;
logout invalidates it; invalid credentials reveal no account existence; onboarding follows
admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004;
TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local

operator CLI only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this source requirement.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL

verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
./docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional trading DDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
./docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
./docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source

refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail

before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label

./docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS;

TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN;
TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests;
scripts/run_live_e2e.py,Current code covers only part of this source
requirement.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF
p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02;
FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75;
FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story
criterion; do not infer.,TC_DASH_002; TC_OPS_001;
TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF
p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02;
FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;
FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan
source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002;
TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational
Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;
FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;
FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source
refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003;
TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful
Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;
FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;
FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source
refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003;
TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN;
TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72
catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment
Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and
operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03;
FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74;

FIN-75; FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
./docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label

./docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive Changes,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain

protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05; FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001; TC_CFG_003; TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege

changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:22:FS-11-04: TC_TEST_001, TC_DB_001, TC_COV_001, TC_INT_001, TC_SYS_001
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:30:FS-11-12: TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_DB_001, TC_EXEC_001, TC_DASH_002, TC_SYS_001

./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:32:FS-01-02:
TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:36:FS-08-01: TC_LLM_001,
TC_LLM_002, TC_LLM_003, TC_CFG_004, TC_OPS_001, TC_SYS_001
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:39:FS-09-05:
TC_AUTHZ_002, TC_AUTHSEC_001, TC_AUTHSEC_004, TC_CFG_003,
TC_PRIV_001, TC_PRIV_002, TC_EXEC_002
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:41:FS-02-08: TC_OPS_001,
TC_DASH_001, TC_DASH_002, TC_SYS_001
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:594:TEST CASE ID:
TC_AUTHZ_001
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:615:TEST CASE ID:
TC_AUTHZ_002
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:637:TEST CASE ID:
TC_AUTHZ_003
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:1057:TEST CASE ID:
TC_PRIV_002
./Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt:1212:TEST CASE ID:
TC_SYS_001
./test-results/FIN-15/20261020_141630_acceptance_review.txt:11:IMPLEMENTATION_
STATUS.txt-321-Inspected relevant SRS access-control requirements, canonical
schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping,
architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and
relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected
GET `/auth/me`; no product/admin operation or protected frontend page currently exists.
Existing session dependency already rejects absent, revoked, and expired sessions;
prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:14:IMPLEMENTATION_
STATUS.txt:324:Remaining acceptance criteria: role/permission matrix, 403 behavior,
trusted role resolution/provisioning assignment, protected route application, and
frontend guard cannot be completed safely until scope decision and a concrete
capability/resource mapping are established. TC_AUTHZ_001 also requires a protected
frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin
operation that does not exist; TC_PRIV_002 requires workspace membership/resources
not implemented. FIN-15 is not ready for acceptance.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:32:IMPLEMENTATION_
STATUS.txt-342-- Function/test traceability added in
FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and
related existing session coverage TC_AUTHZ_003.

./test-results/FIN-15/20261020_141630_acceptance_review.txt:61:SPRINT_1_TEST_EXECUTION_STATUS.txt-136-- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
./test-results/FIN-15/20261020_141630_acceptance_review.txt:89:FUNCTION_TEST_TRACEABILITY.txt-7-Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
./test-results/FIN-15/20261020_141630_acceptance_review.txt:106:FUNCTION_TEST_TRACEABILITY.txt-24-- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
./test-results/FIN-15/20261020_141630_acceptance_review.txt:110:docs/requirements/traceability-stories.csv:2:FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:111:docs/requirements/traceability-stories.csv:3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.

./test-results/FIN-15/20261020_141630_acceptance_review.txt:113:docs/requirements/traceability-stories.csv:5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:115:docs/requirements/traceability-stories.csv:14:FS-02-08,FIN-25,LIVE JIRA VERIFIED 2026-10-19,"Keep dashboard responsive, isolated and freshness-aware",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-01; NFR-P2-02; NFR-P2-03; NFR-P2-04; NFR-P2-05; NFR-P8-04,Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:116:docs/requirements/traceability-stories.csv:45:FS-08-01,FIN-57,LIVE JIRA VERIFIED 2026-10-19,"Configure Ollama, model selection and inference parameters",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-01; FR-P8-02; FR-P8-03; FR-P8-04; FR-P8-05; FR-P8-12; FR-P8-14; FR-P8-16; NFR-G-08; NFR-G-13; NFR-G-22; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02,Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:118:docs/requirements/traceability-stories.csv:54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce

privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:119:docs/requirements/traceability-stories.csv:65:FS-11-04,FIN-75,LIVE JIRA VERIFIED 2026-10-19,Apply TDD and maintain unit/integration/E2E suites,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-07; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-27; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-04; NFR-P8-02; NFR-P9-02,"Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably. implementation where practical so that behavior is verified continuously.",TC_CI_001; TC_COV_001; TC_DB_001; TC_INT_001; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_COV_001=PASS; TC_DB_001=BLOCKED; TC_INT_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,IMPLEMENTATION_STATUS.txt; issue-specific paths in prior records,Acceptance remains incomplete or externally unverified; see implementation record.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:121:docs/requirements/traceability-stories.csv:73:FS-11-12,FIN-83,LIVE JIRA VERIFIED 2026-10-19,"Add health checks, structured logs, retry and recovery runbook",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-06; NFR-G-07; NFR-G-08; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-02;

NFR-P7-04; NFR-P7-05; NFR-P8-04; NFR-P9-03,Health endpoints work; logs include run IDs and redact secrets; retries are bounded/idempotent; outage drill has recorded outcome. are diagnosable.,TC_BUILD_002; TC_DASH_002; TC_DB_001; TC_EXEC_001; TC_EXEC_002; TC_OPS_001; TC_OPS_002; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TRACE_001,TC_BUILD_002=BLOCKED; TC_DASH_002=NOT RUN; TC_DB_001=BLOCKED; TC_EXEC_001=NOT RUN; TC_EXEC_002=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
./test-results/FIN-15/20261020_141630_acceptance_review.txt:122:docs/requirements/traceability-matrix.md:31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:123:docs/requirements/traceability-matrix.md:32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |

./test-results/FIN-15/20261020_141630_acceptance_review.txt:125:docs/requirements/traceability-matrix.md:34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:127:docs/requirements/traceability-matrix.md:43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:128:docs/requirements/traceability-matrix.md:74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05, FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN,

TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | ./test-results/FIN-15/20261020_141630_acceptance_review.txt:130:docs/requirements/traceability-matrix.md:83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe account administration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | ./test-results/FIN-15/20261020_141630_acceptance_review.txt:131:docs/requirements/traceability-matrix.md:94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. | ./test-results/FIN-15/20261020_141630_acceptance_review.txt:133:docs/requirements/traceability-matrix.md:102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks,

structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:134:docs/requirements/traceability-matrix.md:118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:135:docs/requirements/traceability-matrix.md:119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN,

TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:136:docs/requirements/traceability-matrix.md:120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:137:docs/requirements/traceability-matrix.md:121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:138:docs/requirements/traceability-matrix.md:122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL |

apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:139:docs/requirements/traceability-matrix.md:123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers only part of this source requirement. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:140:docs/requirements/traceability-matrix.md:124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:141:docs/requirements/traceability-matrix.md:125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |

./test-results/FIN-15/20261020_141630_acceptance_review.txt:142:docs/requirements/traceability-matrix.md:130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:143:docs/requirements/traceability-matrix.md:131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2 |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:144:docs/requirements/traceability-matrix.md:132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:145:docs/requirements/traceability-matrix.md:340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 |

TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:146:docs/requirements/traceability-matrix.md:341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:147:docs/requirements/traceability-matrix.md:342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:148:docs/requirements/traceability-matrix.md:343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT

RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:149:docs/requirements/traceability-matrix.md:344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:150:docs/requirements/traceability-matrix.md:351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:151:docs/requirements/traceability-matrix.md:376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:152:docs/requirements/traceability-matrix.md:377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan

source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:153:docs/requirements/traceability-matrix.md:378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:154:docs/requirements/traceability-matrix.md:416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:155:docs/requirements/traceability-matrix.md:428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:156:docs/requirements/traceability-matrix.md:438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests,

apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:157:docs/requirements/traceability-matrix.md:449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:158:docs/requirements/traceability-matrix.md:450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:159:docs/requirements/traceability-matrix.md:451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:160:docs/requirements/traceability-matrix.md:452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:161:docs/requirements/traceability-matrix.md:453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS

global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target and committed-SHA evidence are absent. | Unmapped to source story |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:164:docs/requirements/traceability-matrix.md:460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:165:docs/requirements/traceability-matrix.md:461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:166:docs/requirements/traceability-matrix.md:462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN,

TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:167:docs/requirements/traceability-matrix.md:463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:168:docs/requirements/traceability-matrix.md:464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:169:docs/requirements/traceability-matrix.md:510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:170:docs/requirements/traceability-matrix.md:511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01, FS-01-02, FS-01-03,

FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:171:docs/requirements/traceability-matrix.md:512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05, FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:172:docs/requirements/traceability-matrix.md:513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT

IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:173:docs/requirements/traceability-matrix.md:514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:174:docs/requirements/traceability-matrix.md:515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
./test-results/FIN-15/20261020_141630_acceptance_review.txt:175:docs/requirements/traceability-matrix.md:516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN,

TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label | ./test-results/FIN-15/20261020_141630_acceptance_review.txt:176:docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label ./test-results/FIN-15/20261020_141630_acceptance_review.txt:177:docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label ./test-results/FIN-15/20261020_141630_acceptance_review.txt:178:docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;

TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:179:docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local operator CLI only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:180:docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:181:docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN;

TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this source requirement.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:182:docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:183:docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:184:docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
./test-results/FIN-15/20261020_141630_acceptance_review.txt:185:docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16;

FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional trading DDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
./test-results/FIN-15/20261020_141630_acceptance_review.txt:186:docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
./test-results/FIN-15/20261020_141630_acceptance_review.txt:187:docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:188:docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is

controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:189:docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:190:docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:191:docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before

activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:192:docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:193:docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:194:docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:195:docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02;

FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:196:docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:197:docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:198:docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:199:docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN;

TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:200:docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:201:docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:202:docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:203:docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03; FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74; FIN-75; FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT

RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
./test-results/FIN-15/20261020_141630_acceptance_review.txt:206:docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:207:docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:208:docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:209:docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are

shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:210:docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:211:docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:212:docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive Changes,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;

TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:213:docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05; FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001; TC_CFG_003; TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:214:docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:215:docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain

protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:216:docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:217:docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
./test-results/FIN-15/20261020_141630_acceptance_review.txt:218:FUNCTION_TEST_TRACEABILITY.txt:7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).

./test-results/FIN-15/20261020_141630_acceptance_review.txt:219:FUNCTION_TEST_TRACEABILITY.txt:24:- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
./test-results/FIN-15/20261020_141630_acceptance_review.txt:220:FUNCTION_TEST_TRACEABILITY.txt:26:- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
./test-results/FIN-15/20261020_141630_acceptance_review.txt:221:FUNCTION_TEST_TRACEABILITY.txt:28:- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
./test-results/FIN-15/20261020_141630_acceptance_review.txt:222:FUNCTION_TEST_TRACEABILITY.txt:30:- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
./test-results/FIN-15/20261020_141630_acceptance_review.txt:223:FUNCTION_TEST_TRACEABILITY.txt:32:- TC_SYS_001: not established by the API suite alone; broader system acceptance remains
./IMPLEMENTATION_STATUS.txt:59:Reviewed requirements: SRS FR-P1-01..04, FR-P1-06, FR-P1-08 and NFR-P1-01..03/05; canonical identity DDL `Database/schema (1).sql` (`roles`, `users`, `auth_sessions`); backlog FS-01-01 page 2; test-plan management cases TC_AUTHN_001..005 and TC_AUTHZ_003.
./IMPLEMENTATION_STATUS.txt:92:Test execution: detailed statuses and evidence are recorded in `SPRINT_1_TEST_EXECUTION_STATUS.txt`. TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, and the shared session-expiry behavior in TC_AUTHZ_003 passed against disposable PostgreSQL. TC_AUTHN_005 is BLOCKED because the full administrator invitation lifecycle is not implemented. TC_AUTHN_006 passed the disposable database dump/log/API privacy checks recorded below; TC_AUTHN_007 is BLOCKED pending deployed HTTPS verification. TC_AUTHN_004 is BLOCKED pending the SRS-required password recovery scope/delivery decision.
./IMPLEMENTATION_STATUS.txt:214:- `TC_INT_001` remains BLOCKED for configuration-version/audit persistence and allowed/denied configuration flows (not implemented). `TC_SYS_001` remains BLOCKED for dashboard/settings, health and Ollama flows (not implemented). Password recovery, admin invitations and deployed HTTPS remain the previously recorded FIN-13 gaps and are untouched.
./IMPLEMENTATION_STATUS.txt:321:Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects

absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
./IMPLEMENTATION_STATUS.txt:324:Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
./IMPLEMENTATION_STATUS.txt:342:- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
./SPRINT_1_TEST_EXECUTION_STATUS.txt:51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
./SPRINT_1_TEST_EXECUTION_STATUS.txt:78:TC_SYS_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Browser smoke verified current sign-in/session/logout path against live frontend, FastAPI, and PostgreSQL. Full planned dashboard/settings, dependency health, Ollama available/unavailable, and correlation-log workflow cannot run because those components are not implemented | Tester/owner: Codex | Evidence: apps/web/tests/e2e/auth.spec.js; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: Current application implements auth starter only
./SPRINT_1_TEST_EXECUTION_STATUS.txt:94:TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
./SPRINT_1_TEST_EXECUTION_STATUS.txt:95:TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
./SPRINT_1_TEST_EXECUTION_STATUS.txt:96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
./SPRINT_1_TEST_EXECUTION_STATUS.txt:115:TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
./SPRINT_1_TEST_EXECUTION_STATUS.txt:122:TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
./SPRINT_1_TEST_EXECUTION_STATUS.txt:136:- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
./conversation.txt:10:FIN-15 inspection note (2026-10-19): reviewed the FIN-15 pasted request, SRS FR-P1-05..08 and relevant access-control statements, canonical identity DDL and reference role seeds, FS-01-02 backlog acceptance/dependency, Sprint 1 TC_AUTHZ_001/002/003 and TC_PRIV_002, current architecture docs, auth route/dependency, migration 0001, provisioning CLI, and existing auth tests. Source

PDFs, SQL, diagrams, and original test plan remain read-only. Existing evidence: `/auth/me` uses the existing session validation and rejects anonymous/expired/revoked sessions; there is no RBAC layer, permission persistence, admin operation, workspace membership, or protected frontend page. `TC_AUTHZ_003` remains previously recorded PASS for session expiry only; no new result is claimed. Attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; process produced no output within the bounded polling window and was interrupted, so no test result is claimed. No Git, Jira, or source-artifact changes were made.
./conversation.txt:61:Implemented test infrastructure: unit coverage for password/session/config helpers and controlled API errors; a PostgreSQL email-uniqueness/session-cascade integration test; deterministic Playwright tests for login error/success/logout and service-unavailable UI; and a live browser smoke runner that uses synthetic accounts and cleans them up. CI now runs frontend browser checks, backend unit/integration suites with coverage evidence, and live browser authentication against disposable PostgreSQL. Source traceability consulted: detailed backlog FS-11-04 (five critical validators/authorization/idempotency/API errors plus repeatable smoke), and Sprint 1 plan TC_TEST_001, TC_DB_001, TC_COV_001, TC_INT_001, TC_SYS_001. Original PDFs and source test plan were not modified.
./conversation.txt:63:Known gaps: TC_DB_001 is BLOCKED for non-identity Sprint 1 schemas and migration-runner repeatability; TC_INT_001 is BLOCKED for configuration/audit persistence flows; TC_SYS_001 is BLOCKED for dashboard/settings, health, and Ollama paths that do not exist. Coverage leaves `apps/api/app/provision_user.py` at 0%, explicitly recorded. Existing npm install output summarized 3 advisories (2 high, 1 critical); they were not triaged in this test-only change. CI syntax and commands were validated locally, but no GitHub Actions run or branch protection check exists. Existing FIN-13 password-recovery, application-admin onboarding, and deployed-HTTPS gaps remain unchanged. No feature code, source references, Git history, or Jira state was changed.
./conversation.txt:125:- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

```
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== Working tree (preserve all changes) ==="
git status --short

echo "=== Current FastAPI routes and authorization ==="
grep -n -E \

'@app\.(get|post|put|patch|delete)|require_permission|platform/admin/capability|authoriz
ation/capabilities' \
  apps/api/app/main.py

echo "=== FIN-15 endpoint in OpenAPI contract ==="
grep -n -A35 -B8 \
  '/api/v1/admin/authorization/capabilities' \
  FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml \
  2>/dev/null || true

echo "=== FIN-15 story and test status ==="
grep -n -E
'FIN-15|TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_00
1' \
  docs/requirements/traceability-stories.csv \
  docs/requirements/traceability-requirements.csv \
  SPRINT_1_TEST_EXECUTION_STATUS.txt \
  FUNCTION_TEST_TRACEABILITY.txt
=== Working tree (preserve all changes) ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
```

```
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
=== Current FastAPI routes and authorization ===
109:def require_permission(permission_key: str):
119:@app.post("/auth/login", response_model=UserView)
160:@app.post("/auth/logout", status_code=204)
179:@app.get("/auth/me", response_model=UserView)
184:@app.get("/platform/admin/capability")
186:    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
=== FIN-15 endpoint in OpenAPI contract ===
=== FIN-15 story and test status ===
docs/requirements/traceability-stories.csv:2:FS-01-01,FIN-13,LIVE JIRA VERIFIED
2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira
issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07;
FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23;
NFR-G-26; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03;
NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout
invalidates it; invalidcredentials reveal no account existence; onboarding follows admin
policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004;
TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py;
apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains
incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:3:FS-01-02,FIN-15,LIVE JIRA VERIFIED
2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira
issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12;
FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34;
NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02;
NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested
server-side; inactive sessions expire per configuration.,TC_AUTHZ_001;
TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002;
TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN;
TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT
```

RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:14:FS-02-08,FIN-25,LIVE JIRA VERIFIED 2026-10-19,"Keep dashboard responsive, isolated and freshness-aware",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02;FR-P8-12; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-01; NFR-P2-02; NFR-P2-03; NFR-P2-04; NFR-P2-05; NFR-P8-04,Primary content meets agreed performance target; layouts work on supported screens; onlyauthorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:45:FS-08-01,FIN-57,LIVE JIRA VERIFIED 2026-10-19,"Configure Ollama, model selection and inference parameters",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-01; FR-P8-02; FR-P8-03; FR-P8-04; FR-P8-05; FR-P8-12; FR-P8-14; FR-P8-16; NFR-G-08; NFR-G-13; NFR-G-22; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02,Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.

docs/requirements/traceability-stories.csv:54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06;FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:65:FS-11-04,FIN-75,LIVE JIRA VERIFIED 2026-10-19,Apply TDD and maintain unit/integration/E2E suites,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-07; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-27; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-04; NFR-P8-02; NFR-P9-02,"Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably. implementationwhere practical so that behavior is verified continuously.",TC_CI_001; TC_COV_001; TC_DB_001; TC_INT_001; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_COV_001=PASS; TC_DB_001=BLOCKED; TC_INT_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,IMPLEMENTATION_STATUS.txt; issue-specific paths in prior records,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:73:FS-11-12,FIN-83,LIVE JIRA VERIFIED 2026-10-19,"Add health checks, structured logs, retry and recovery runbook",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-06; NFR-G-07; NFR-G-08; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06;

NFR-P7-01; NFR-P7-02; NFR-P7-04; NFR-P7-05; NFR-P8-04; NFR-P9-03,Health endpoints work; logs include run IDs and redact secrets; retries are bounded/idempotent; outage drill has recorded outcome. are diagnosable.,TC_BUILD_002; TC_DASH_002; TC_DB_001; TC_EXEC_001; TC_EXEC_002; TC_OPS_001; TC_OPS_002; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TRACE_001,TC_BUILD_002=BLOCKED; TC_DASH_002=NOT RUN; TC_DB_001=BLOCKED; TC_EXEC_001=NOT RUN; TC_EXEC_002=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified

2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local operator CLI only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label
docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per

configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19;

test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional trading DDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN;TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inferencewith versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN;

TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN;

TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:304:NFR-FIN-15,Data Licensing,"PDF p.46; SRS Section 11, financial NFR",Financial correctness and safety,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOTRUN,NOT

ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15;FIN-25; FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan

source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03; FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74; FIN-75; FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN;

TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001;TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primarycontent meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT

IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive Changes,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05; FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65;FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and cleardestructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001; TC_CFG_003; TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN;

TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace dataremain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002;

TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002;
TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
SPRINT_1_TEST_EXECUTION_STATUS.txt:51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
SPRINT_1_TEST_EXECUTION_STATUS.txt:78:TC_SYS_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Browser smoke verified current sign-in/session/logout path against live frontend, FastAPI, and PostgreSQL. Full planned dashboard/settings, dependency health, Ollama available/unavailable, and correlation-log workflow cannot run because those components are not implemented | Tester/owner: Codex | Evidence: apps/web/tests/e2e/auth.spec.js; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: Current application implements auth starter only
SPRINT_1_TEST_EXECUTION_STATUS.txt:94:TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:95:TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:115:TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:122:TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

SPRINT_1_TEST_EXECUTION_STATUS.txt:135:FIN-15 route-level authorization test update — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt:136:- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
SPRINT_1_TEST_EXECUTION_STATUS.txt:140:FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)
SPRINT_1_TEST_EXECUTION_STATUS.txt:150: test-results/FIN-15/20261020_141030_identity_authorization.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:151: test-results/FIN-15/20261020_141030_full_api_suite.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:152: test-results/FIN-15/run_20261020_141030_summary.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt:156:FIN-15 story is complete. Workspace-level authorization remains deferred.
FUNCTION_TEST_TRACEABILITY.txt:3:FIN-15 / FS-01-02 — platform authorization capability endpoint
FUNCTION_TEST_TRACEABILITY.txt:7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt:10:FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
FUNCTION_TEST_TRACEABILITY.txt:19: test-results/FIN-15/20261020_141030_identity_authorization.log
FUNCTION_TEST_TRACEABILITY.txt:20: test-results/FIN-15/20261020_141030_full_api_suite.log
FUNCTION_TEST_TRACEABILITY.txt:21: test-results/FIN-15/run_20261020_141030_summary.txt
FUNCTION_TEST_TRACEABILITY.txt:24:- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt:26:- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
FUNCTION_TEST_TRACEABILITY.txt:28:- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
FUNCTION_TEST_TRACEABILITY.txt:30:- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
FUNCTION_TEST_TRACEABILITY.txt:32:- TC_SYS_001: not established by the API suite alone; broader system acceptance remains
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

```
run_20261020_141030_summary.txt
FUNCTION_TEST_TRACEABILITY.txt:24:- TC_AUTHZ_001: verify its exact assertions
before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt:26:- TC_AUTHZ_002: PASS for the platform
permission behavior explicitly asserted by the
FUNCTION_TEST_TRACEABILITY.txt:28:- TC_AUTHZ_003: existing expiry/revocation
regression passed in an earlier recorded run;
FUNCTION_TEST_TRACEABILITY.txt:30:- TC_PRIV_002: BLOCKED / deferred
because workspace membership and resource-level
FUNCTION_TEST_TRACEABILITY.txt:32:- TC_SYS_001: not established by the API
suite alone; broader system acceptance remains
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== API pack files ==="
find FinSight_AI_API_Design_Pack -maxdepth 3 -type f -print

echo "=== OpenAPI paths and authorization references ==="
grep -R -n -E \

'platform/admin/capability|authorization/capabilities|platform\.admin|securitySchemes|/a
uth/me' \
  FinSight_AI_API_Design_Pack

echo "=== Current session expiry tests ==="
grep -n -A55 -B10 -E \
  'expiry|expired|last_seen_at|revok|TTL|stale session' \
  apps/api/tests/test_auth.py \
  apps/api/tests/test_auth_unit.py \
  apps/api/tests/test_identity_constraints.py

echo "=== Current proxy and protected frontend routes ==="
find apps/web/app -maxdepth 3 -type f -print
sed -n '1,180p' apps/web/proxy.js

echo "=== Existing FIN-15 completion claims ==="
grep -n -A8 -B8 'FIN-15 story is complete' \
  SPRINT_1_TEST_EXECUTION_STATUS.txt IMPLEMENTATION_STATUS.txt
=== API pack files ===
```

FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md
FinSight_AI_API_Design_Pack/FinSight_AI_API_Requirement_Traceability.csv
FinSight_AI_API_Design_Pack/README.md
FinSight_AI_API_Design_Pack/FinSight_AI_API_Endpoint_Catalog.csv
FinSight_AI_API_Design_Pack/FinSight_AI_API_Story_Coverage.csv
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.docx
=== OpenAPI paths and authorization references ===
FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml:309: /auth/me:
FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml:1199: /admin/authorization/capabilities:
FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml:1205:   description: 'Decision A: narrowly scoped real-app route protected by require_permission("platform.admin"); no user
FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml:1208:   x-required-permission: platform.admin
FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml:18750: securitySchemes:
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:11:**Decision A is recommended and incorporated.** Implement one minimal platform-admin-only authorization/capability endpoint in the actual FastAPIapp: `GET /api/v1/admin/authorization/capabilities`, protected by the real `require_permission("platform.admin")` dependency. It must return only the caller's effective permission/capability summary and policy version, not platform user lists or unrelated business resources. The route is a direct test seam for SRS backend RBAC (FR-P1-05/06/07) and Sprint 1 story FS-01-02 / Jira FIN-15; it is not a substitute for implementing authorization across all protected endpoints.
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:111:| platform.admin | Inspect platform-level capabilities | Keep the minimal Sprint 1 route read-only. Grant only through explicit role_permissionsmapping. |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:124:**GET `/api/v1/admin/authorization/capabilities`** | Required permission: `platform.admin` | Release: Sprint 1 authorization foundation | Must be wired through the real FastAPI dependency chain, not a test-only helper.
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:136:   "platform.admin",
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:155:| Admin success | Real persisted admin user + active database-backed

session + explicit `platform.admin` grant; GET endpoint. | 200; only caller’s effective permission/capability summary; request ID; no secret fields. | Any role-name-only bypass or response containing unrelated user/workspace data. |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:156:| Authenticated denied user | Real active session; lacks `platform.admin`; GET endpoint. | 403 `permission_denied`; no capabilities or policy details leaked. | 200, 404 workaround, or permission derived from caller-supplied JSON. |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:200:@admin_router.get("/authorization/capabilities", response_model=CapabilitiesResponse)
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:202:   principal = Depends(require_permission("platform.admin")),
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:230:| GET | `/api/v1/auth/me` | Get the current user and effective access summary | Authenticated + resource ACL | — | EXISTING BEHAVIOR EVIDENCED; PATH TO VERIFY |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:240:| GET | `/api/v1/admin/authorization/capabilities` | Inspect authorized platform capabilities | platform.admin | — | SPRINT 1 PROPOSED — DECISION A |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:580:| 4. Decision A endpoint | Add `GET /api/v1/admin/authorization/capabilities` via actual router and dependency; return small DTO only. | Admin 200, non-admin 403, anonymous/expired/revoked 401, DB/RBAC unavailable 503; permission revocation and no secret leakage. |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:581:| 5. Regression + security | Verify current `/auth/login`, `/auth/me`, `/auth/logout` behavior and frontend integration; cookie/CSRF tests as applicable; lint/type/test/secret scanning. | Run actual test commands and record outcomes; don’t alter planned test register statuses without evidence. |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contract.md:598:| RBAC bootstrap and platform.admin grants | Approve a least-privilege bootstrap mechanism; no default public admin, no implicit promotion by display name. |
FinSight_AI_API_Design_Pack/FinSight_AI_API_Requirement_Traceability.csv:17:FR-P1-06,Protected Routes,"PDF p.3, SRS P1 requirements",Identity and access,"FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12","FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83","Live Jira JQL verified 2026-10-19, test-plan source refs","FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration.","TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001","TC_AUTHZ_001=NOT

RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN",PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this source requirement.,Preserve source story release label,Identity & access; workspace; privacy; platform/health as linked by story,Proposed mapping only; source implementation/test statuses preserved verbatim.
FinSight_AI_API_Design_Pack/README.md:17:2. Decision A is included: add a narrow platform-admin-only capability endpoint using `require_permission("platform.admin")`, tested against real database-backed sessions.
FinSight_AI_API_Design_Pack/FinSight_AI_API_Endpoint_Catalog.csv:6:GET,/api/v1/auth/me,Identity & access,Get the current user and effective access summary,Authenticated + resource ACL,Authenticated session; resource-level permission required,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-01-05,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-10; FR-P1-11; FR-P1-12; FR-P1-13; FR-P1-14; FR-P1-15; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-13; NFR-P1-01; NFR-P1-02; NFR-P1-03; NFR-P1-04; NFR-P1-05; NFR-P1-06; NFR-P9-01; NFR-P9-02; NFR-P9-06,Release 1 target,false,false,EXISTING BEHAVIOR EVIDENCED; PATH TO VERIFY,Return identity/session state only; no raw session token.
FinSight_AI_API_Design_Pack/FinSight_AI_API_Endpoint_Catalog.csv:16:GET,/api/v1/admin/authorization/capabilities,Identity & access,Inspect authorized platform capabilities,platform.admin,Authenticated; require permission `platform.admin`,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-01-05; FS-09-01; FS-09-02; FS-09-03; FS-09-04; FS-09-05,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-10; FR-P1-11; FR-P1-12; FR-P1-13; FR-P1-14; FR-P1-15; FR-P9-01; FR-P9-02; FR-P9-03; FR-P9-04; FR-P9-05; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-09; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-15; FR-P9-16; FR-P9-17; FR-P9-18; FR-P9-19; FR-P9-20; FR-P9-21; FR-P9-22; FR-P9-25; NFR-P1-01; NFR-P1-02; NFR-P1-03; NFR-P1-04; NFR-P1-05; NFR-P1-06; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Release 1 target,false,false,SPRINT 1 PROPOSED — DECISION A,"Decision A: narrowly scoped real-app route protected by require_permission(""platform.admin""); no user listing or unrelated business operations."
=== Current session expiry tests ===
apps/api/tests/test_auth.py-26-   user_id = cur.fetchone()[0]
apps/api/tests/test_auth.py-27-   try:
apps/api/tests/test_auth.py-28-   yield user_id, email, encoded
apps/api/tests/test_auth.py-29-   finally:
apps/api/tests/test_auth.py-30-   with connect() as conn, conn.cursor() as cur:

```
apps/api/tests/test_auth.py-31-            cur.execute("DELETE FROM users WHERE
user_id = %s", (user_id,))
apps/api/tests/test_auth.py-32-
apps/api/tests/test_auth.py-33-
apps/api/tests/test_auth.py-34-@pytest.fixture
apps/api/tests/test_auth.py-35-def client(monkeypatch):
apps/api/tests/test_auth.py:36:    monkeypatch.setenv("SESSION_TTL_MINUTES",
"60")
apps/api/tests/test_auth.py-37-    monkeypatch.setenv("COOKIE_SECURE", "false")
apps/api/tests/test_auth.py-38-    monkeypatch.setenv("WEB_ORIGIN",
"http://localhost:3000")
apps/api/tests/test_auth.py-39-    with TestClient(app) as test_client:
apps/api/tests/test_auth.py-40-        yield test_client
apps/api/tests/test_auth.py-41-
apps/api/tests/test_auth.py-42-
apps/api/tests/test_auth.py-43-def
test_password_hash_is_argon2_and_never_plaintext():
apps/api/tests/test_auth.py-44-    encoded = hash_password(TEST_PASSWORD)
apps/api/tests/test_auth.py-45-    assert encoded.startswith("argon2id")
apps/api/tests/test_auth.py-46-    assert encoded != TEST_PASSWORD
apps/api/tests/test_auth.py-47-    assert verify_password(encoded, TEST_PASSWORD)
apps/api/tests/test_auth.py-48-    assert not verify_password(encoded, "wrong")
apps/api/tests/test_auth.py-49-
apps/api/tests/test_auth.py-50-
apps/api/tests/test_auth.py-51-def
test_login_creates_protected_hashed_expiring_session(client, identity, caplog, capsys):
apps/api/tests/test_auth.py-52-    user_id, email, encoded = identity
apps/api/tests/test_auth.py-53-    response = client.post("/auth/login", json={"email":
email, "password": TEST_PASSWORD})
apps/api/tests/test_auth.py-54-    assert response.status_code == 200
apps/api/tests/test_auth.py-55-    assert response.json() == {"user_id": str(user_id),
"email": email, "display_name": "Synthetic Analyst"}
apps/api/tests/test_auth.py-56-    assert TEST_PASSWORD not in response.text and
encoded not in response.text
apps/api/tests/test_auth.py-57-    cookie = response.cookies.get(SESSION_COOKIE)
apps/api/tests/test_auth.py-58-    assert cookie
apps/api/tests/test_auth.py-59-    set_cookie = response.headers["set-cookie"].lower()
apps/api/tests/test_auth.py-60-    assert "httponly" in set_cookie and "samesite=lax" in
set_cookie and "path=/" in set_cookie
```

```
apps/api/tests/test_auth.py-61-    with connect() as conn,
conn.cursor(row_factory=dict_row) as cur:
apps/api/tests/test_auth.py:62:        cur.execute("SELECT refresh_token_hash,
expires_at, revoked_at FROM auth_sessions WHERE user_id = %s", (user_id,))
apps/api/tests/test_auth.py-63-        stored = cur.fetchone()
apps/api/tests/test_auth.py-64-    assert stored["refresh_token_hash"] ==
token_digest(cookie)
apps/api/tests/test_auth.py-65-    assert stored["refresh_token_hash"] != cookie
apps/api/tests/test_auth.py:66:    assert stored["expires_at"] is not None and
stored["revoked_at"] is None
apps/api/tests/test_auth.py-67-    protected = client.get("/auth/me",
cookies={SESSION_COOKIE: cookie})
apps/api/tests/test_auth.py-68-    assert protected.status_code == 200 and
protected.json()["user_id"] == str(user_id)
apps/api/tests/test_auth.py-69-    captured = capsys.readouterr()
apps/api/tests/test_auth.py-70-    assert TEST_PASSWORD not in caplog.text +
captured.out + captured.err
apps/api/tests/test_auth.py-71-    assert cookie not in caplog.text + captured.out +
captured.err
apps/api/tests/test_auth.py-72-
apps/api/tests/test_auth.py-73-
apps/api/tests/test_auth.py-74-def
test_invalid_credentials_have_same_generic_response(client, identity):
apps/api/tests/test_auth.py-75-    _, email, _ = identity
apps/api/tests/test_auth.py-76-    known = client.post("/auth/login", json={"email": email,
"password": "wrong-password"})
apps/api/tests/test_auth.py-77-    absent = client.post("/auth/login", json={"email":
"absent@example.com", "password": "wrong-password"})
apps/api/tests/test_auth.py-78-    assert (known.status_code, known.json()) ==
(absent.status_code, absent.json())
apps/api/tests/test_auth.py-79-    assert known.status_code == 401 and known.json()
== {"detail": "Email or password is incorrect."}
apps/api/tests/test_auth.py-80-    assert SESSION_COOKIE not in known.cookies and
SESSION_COOKIE not in absent.cookies
apps/api/tests/test_auth.py-81-
apps/api/tests/test_auth.py-82-
apps/api/tests/test_auth.py:83:def test_logout_revokes_session_and_replay_fails(client,
identity):
apps/api/tests/test_auth.py-84-    _, email, _ = identity
```

```
apps/api/tests/test_auth.py-85-    login = client.post("/auth/login", json={"email": email,
"password": TEST_PASSWORD})
apps/api/tests/test_auth.py-86-    cookie = login.cookies.get(SESSION_COOKIE)
apps/api/tests/test_auth.py-87-    assert cookie
apps/api/tests/test_auth.py-88-    logout = client.post("/auth/logout",
cookies={SESSION_COOKIE: cookie})
apps/api/tests/test_auth.py-89-    assert logout.status_code == 204
apps/api/tests/test_auth.py-90-    replay = client.get("/auth/me",
cookies={SESSION_COOKIE: cookie})
apps/api/tests/test_auth.py-91-    assert replay.status_code == 401
apps/api/tests/test_auth.py-92-    with connect() as conn, conn.cursor() as cur:
apps/api/tests/test_auth.py:93:        cur.execute("SELECT revoked_at FROM
auth_sessions WHERE refresh_token_hash = %s", (token_digest(cookie),))
apps/api/tests/test_auth.py-94-        assert cur.fetchone()[0] is not None
apps/api/tests/test_auth.py-95-
apps/api/tests/test_auth.py-96-
apps/api/tests/test_auth.py-97-def test_logout_without_session_is_idempotent(client):
apps/api/tests/test_auth.py-98-    response = client.post("/auth/logout")
apps/api/tests/test_auth.py-99-
apps/api/tests/test_auth.py-100-    assert response.status_code == 204
apps/api/tests/test_auth.py-101-    assert
response.headers["set-cookie"].startswith(f"{SESSION_COOKIE}=")
apps/api/tests/test_auth.py-102-
apps/api/tests/test_auth.py-103-
apps/api/tests/test_auth.py:104:def test_expired_session_is_rejected(client, identity):
apps/api/tests/test_auth.py-105-    user_id, email, _ = identity
apps/api/tests/test_auth.py-106-    login = client.post("/auth/login", json={"email": email,
"password": TEST_PASSWORD})
apps/api/tests/test_auth.py-107-    cookie = login.cookies.get(SESSION_COOKIE)
apps/api/tests/test_auth.py-108-    assert cookie
apps/api/tests/test_auth.py-109-    with connect() as conn, conn.cursor() as cur:
apps/api/tests/test_auth.py:110:        cur.execute("UPDATE auth_sessions SET
last_seen_at = now() - interval '61 minutes' WHERE user_id = %s", (user_id,))
apps/api/tests/test_auth.py-111-    assert client.get("/auth/me",
cookies={SESSION_COOKIE: cookie}).status_code == 401
apps/api/tests/test_auth.py-112-
apps/api/tests/test_auth.py-113-
apps/api/tests/test_auth.py-114-def test_public_registration_is_not_available(client):
apps/api/tests/test_auth.py-115-    response = client.post("/auth/register", json={"email":
"public@example.com", "password": TEST_PASSWORD})
```

```
apps/api/tests/test_auth.py-116-    assert response.status_code == 404
apps/api/tests/test_auth.py-117-
apps/api/tests/test_auth.py-118-
apps/api/tests/test_auth.py-119-def test_auth_mutation_rejects_foreign_origin(client):
apps/api/tests/test_auth.py-120-    response = client.post(
apps/api/tests/test_auth.py-121-        "/auth/logout", headers={"Origin":
"https://attacker.invalid"},
apps/api/tests/test_auth.py-122-    )
apps/api/tests/test_auth.py-123-    assert response.status_code == 403
apps/api/tests/test_auth.py-124-
apps/api/tests/test_auth.py-125-
apps/api/tests/test_auth.py-126-def
test_secure_cookie_can_be_required_by_deployment(client, identity, monkeypatch):
apps/api/tests/test_auth.py-127-    _, email, _ = identity
apps/api/tests/test_auth.py-128-    monkeypatch.setenv("COOKIE_SECURE", "true")
apps/api/tests/test_auth.py-129-    response = client.post("/auth/login", json={"email":
email, "password": TEST_PASSWORD})
apps/api/tests/test_auth.py-130-    assert response.status_code == 200
apps/api/tests/test_auth.py-131-    assert "secure" in
response.headers["set-cookie"].lower()
--
apps/api/tests/test_auth_unit.py-1-from __future__ import annotations
apps/api/tests/test_auth_unit.py-2-
apps/api/tests/test_auth_unit.py-3-from datetime import UTC, datetime, timedelta
apps/api/tests/test_auth_unit.py-4-
apps/api/tests/test_auth_unit.py-5-import pytest
apps/api/tests/test_auth_unit.py-6-from fastapi import HTTPException
apps/api/tests/test_auth_unit.py-7-from fastapi.testclient import TestClient
apps/api/tests/test_auth_unit.py-8-
apps/api/tests/test_auth_unit.py:9:from app.auth import hash_password,
new_session_token, session_expiry, token_digest, verify_password
apps/api/tests/test_auth_unit.py-10-from app.main import _secure_cookie, _ttl_minutes,
app
apps/api/tests/test_auth_unit.py-11-
apps/api/tests/test_auth_unit.py-12-
apps/api/tests/test_auth_unit.py-13-def
test_password_helpers_accept_only_the_original_password():
apps/api/tests/test_auth_unit.py-14-    encoded = hash_password("synthetic-password")
apps/api/tests/test_auth_unit.py-15-
apps/api/tests/test_auth_unit.py-16-    assert encoded.startswith("argon2id")
```

```
apps/api/tests/test_auth_unit.py-17-    assert verify_password(encoded,
"synthetic-password")
apps/api/tests/test_auth_unit.py-18-    assert not verify_password(encoded,
"different-password")
apps/api/tests/test_auth_unit.py-19-    assert not verify_password("not-an-argon2-hash",
"synthetic-password")
apps/api/tests/test_auth_unit.py-20-    assert not verify_password(None,
"synthetic-password")
apps/api/tests/test_auth_unit.py-21-
apps/api/tests/test_auth_unit.py-22-
apps/api/tests/test_auth_unit.py:23:def
test_session_expiry_uses_utc_and_requested_ttl():
apps/api/tests/test_auth_unit.py-24-    now = datetime(2026, 1, 1, tzinfo=UTC)
apps/api/tests/test_auth_unit.py-25-
apps/api/tests/test_auth_unit.py:26:    assert session_expiry(15, now) == now +
timedelta(minutes=15)
apps/api/tests/test_auth_unit.py-27-
apps/api/tests/test_auth_unit.py-28-
apps/api/tests/test_auth_unit.py-29-@pytest.mark.parametrize("ttl", [0, -1, 10081])
apps/api/tests/test_auth_unit.py:30:def test_session_expiry_rejects_out_of_range_ttl(ttl:
int):
apps/api/tests/test_auth_unit.py:31:    with pytest.raises(ValueError,
match="SESSION_TTL_MINUTES"):
apps/api/tests/test_auth_unit.py:32:        session_expiry(ttl)
apps/api/tests/test_auth_unit.py-33-
apps/api/tests/test_auth_unit.py-34-
apps/api/tests/test_auth_unit.py-35-@pytest.mark.parametrize("configured, expected",
[("60", 60), ("1", 1), ("10080", 10080)])
apps/api/tests/test_auth_unit.py-36-def
test_ttl_configuration_accepts_only_supported_values(monkeypatch, configured: str,
expected: int):
apps/api/tests/test_auth_unit.py:37:
monkeypatch.setenv("SESSION_TTL_MINUTES", configured)
apps/api/tests/test_auth_unit.py-38-
apps/api/tests/test_auth_unit.py-39-    assert _ttl_minutes() == expected
apps/api/tests/test_auth_unit.py-40-
apps/api/tests/test_auth_unit.py-41-
apps/api/tests/test_auth_unit.py-42-@pytest.mark.parametrize("configured", ["0",
"10081", "not-a-number"])
```

```
apps/api/tests/test_auth_unit.py-43-def
test_ttl_configuration_fails_closed(monkeypatch, configured: str):
apps/api/tests/test_auth_unit.py:44:
monkeypatch.setenv("SESSION_TTL_MINUTES", configured)
apps/api/tests/test_auth_unit.py-45-
apps/api/tests/test_auth_unit.py-46-    with pytest.raises(HTTPException) as error:
apps/api/tests/test_auth_unit.py-47-        _ttl_minutes()
apps/api/tests/test_auth_unit.py-48-
apps/api/tests/test_auth_unit.py-49-    assert error.value.status_code == 500
apps/api/tests/test_auth_unit.py-50-    assert error.value.detail == "Session configuration
is invalid"
apps/api/tests/test_auth_unit.py-51-
apps/api/tests/test_auth_unit.py-52-
apps/api/tests/test_auth_unit.py-53-def
test_session_tokens_are_opaque_and_only_digest_is_stable():
apps/api/tests/test_auth_unit.py-54-    token, digest = new_session_token()
apps/api/tests/test_auth_unit.py-55-    another_token, another_digest =
new_session_token()
apps/api/tests/test_auth_unit.py-56-
apps/api/tests/test_auth_unit.py-57-    assert token != another_token
apps/api/tests/test_auth_unit.py-58-    assert digest == token_digest(token)
apps/api/tests/test_auth_unit.py-59-    assert digest != token
apps/api/tests/test_auth_unit.py-60-    assert digest != another_digest
apps/api/tests/test_auth_unit.py-61-
apps/api/tests/test_auth_unit.py-62-
apps/api/tests/test_auth_unit.py-63-def
test_login_maps_database_outage_to_controlled_error(monkeypatch):
apps/api/tests/test_auth_unit.py-64-    import app.main as main
apps/api/tests/test_auth_unit.py-65-
apps/api/tests/test_auth_unit.py-66-    def unavailable_database():
apps/api/tests/test_auth_unit.py-67-        import psycopg
apps/api/tests/test_auth_unit.py-68-
apps/api/tests/test_auth_unit.py-69-        raise psycopg.OperationalError("synthetic
database detail")
apps/api/tests/test_auth_unit.py-70-
apps/api/tests/test_auth_unit.py-71-    monkeypatch.setattr(main, "connect",
unavailable_database)
apps/api/tests/test_auth_unit.py-72-    response = TestClient(app).post(
apps/api/tests/test_auth_unit.py-73-        "/auth/login",
```

```
apps/api/tests/test_auth_unit.py-74-        json={"email": "synthetic@example.com",
"password": "synthetic-password"},
apps/api/tests/test_auth_unit.py-75-    )
apps/api/tests/test_auth_unit.py-76-
apps/api/tests/test_auth_unit.py-77-    assert response.status_code == 503
apps/api/tests/test_auth_unit.py-78-    assert response.json() == {"detail":
"Authentication service unavailable"}
apps/api/tests/test_auth_unit.py-79-    assert "synthetic database detail" not in
response.text
apps/api/tests/test_auth_unit.py-80-
apps/api/tests/test_auth_unit.py-81-
apps/api/tests/test_auth_unit.py-82-def
test_protected_route_rejects_missing_session_before_database_access(monkeypatch)
:
apps/api/tests/test_auth_unit.py-83-    import app.main as main
apps/api/tests/test_auth_unit.py-84-
apps/api/tests/test_auth_unit.py-85-    def unexpected_database_access():
apps/api/tests/test_auth_unit.py-86-        raise AssertionError("database must not be
accessed without a session cookie")
apps/api/tests/test_auth_unit.py-87-
apps/api/tests/test_auth_unit.py-88-    monkeypatch.setattr(main, "connect",
unexpected_database_access)
apps/api/tests/test_auth_unit.py-89-    response = TestClient(app).get("/auth/me")
apps/api/tests/test_auth_unit.py-90-
apps/api/tests/test_auth_unit.py-91-    assert response.status_code == 401
apps/api/tests/test_auth_unit.py-92-    assert response.json() == {"detail":
"Authentication required"}
apps/api/tests/test_auth_unit.py-93-
apps/api/tests/test_auth_unit.py-94-
apps/api/tests/test_auth_unit.py-95-@pytest.mark.parametrize(
apps/api/tests/test_auth_unit.py-96-    ("user", "expected_status"),
apps/api/tests/test_auth_unit.py-97-    [({"permissions": ["platform.admin"]}, 200),
({"permissions": []}, 403), ({}, 403)],
apps/api/tests/test_auth_unit.py-98-)
apps/api/tests/test_auth_unit.py-99-def
test_permission_dependency_allows_only_explicit_permission(user, expected_status):
--
apps/api/tests/test_identity_constraints.py-1-from __future__ import annotations
apps/api/tests/test_identity_constraints.py-2-
apps/api/tests/test_identity_constraints.py-3-from uuid import uuid4
```

```
apps/api/tests/test_identity_constraints.py-4-
apps/api/tests/test_identity_constraints.py-5-import psycopg
apps/api/tests/test_identity_constraints.py-6-import pytest
apps/api/tests/test_identity_constraints.py-7-from fastapi.testclient import TestClient
apps/api/tests/test_identity_constraints.py-8-
apps/api/tests/test_identity_constraints.py:9:from app.auth import new_session_token,
session_expiry
apps/api/tests/test_identity_constraints.py-10-from app.database import connect
apps/api/tests/test_identity_constraints.py-11-from app.main import
SESSION_COOKIE, app, require_permission
apps/api/tests/test_identity_constraints.py-12-
apps/api/tests/test_identity_constraints.py-13-
apps/api/tests/test_identity_constraints.py-14-def
test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
apps/api/tests/test_identity_constraints.py-15-    email =
f"constraint-{uuid4().hex}@example.com"
apps/api/tests/test_identity_constraints.py-16-    with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-17-        cur.execute(
apps/api/tests/test_identity_constraints.py-18-            "INSERT INTO users (email,
password_hash, display_name) VALUES (%s, %s, %s) RETURNING user_id",
apps/api/tests/test_identity_constraints.py-19-            (email, "synthetic-hash",
"Synthetic Constraint Test"),
apps/api/tests/test_identity_constraints.py-20-        )
apps/api/tests/test_identity_constraints.py-21-        user_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-22-
apps/api/tests/test_identity_constraints.py-23-    try:
apps/api/tests/test_identity_constraints.py-24-        with
pytest.raises(psycopg.errors.UniqueViolation):
apps/api/tests/test_identity_constraints.py-25-            with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-26-                cur.execute(
apps/api/tests/test_identity_constraints.py-27-                    "INSERT INTO users (email,
password_hash, display_name) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py-28-                    (email.upper(),
"synthetic-hash", "Duplicate Synthetic Test"),
apps/api/tests/test_identity_constraints.py-29-                )
apps/api/tests/test_identity_constraints.py-30-
apps/api/tests/test_identity_constraints.py-31-        _, digest = new_session_token()
```

```
apps/api/tests/test_identity_constraints.py-32-        with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-33-            cur.execute(
apps/api/tests/test_identity_constraints.py-34-                "INSERT INTO auth_sessions
(user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py:35:                (user_id, digest,
session_expiry(5)),
apps/api/tests/test_identity_constraints.py-36-            )
apps/api/tests/test_identity_constraints.py-37-            cur.execute("DELETE FROM
users WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-38-            cur.execute("SELECT count(*)
FROM auth_sessions WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-39-            assert cur.fetchone()[0] == 0
apps/api/tests/test_identity_constraints.py-40-    finally:
apps/api/tests/test_identity_constraints.py-41-        with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-42-            cur.execute("DELETE FROM
users WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-43-
apps/api/tests/test_identity_constraints.py-44-
apps/api/tests/test_identity_constraints.py-45-def
test_platform_permission_is_resolved_from_database_role_and_session():
apps/api/tests/test_identity_constraints.py-46-    admin_email =
f"platform-admin-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py-47-    user_email =
f"unprivileged-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py-48-    tokens = []
apps/api/tests/test_identity_constraints.py-49-    with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-50-        cur.execute("SELECT role_id FROM
roles WHERE role_key = 'platform_admin' AND scope = 'platform'")
apps/api/tests/test_identity_constraints.py-51-        admin_role_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-52-        cur.execute(
apps/api/tests/test_identity_constraints.py-53-            "INSERT INTO users (email,
display_name, platform_role_id) VALUES (%s, %s, %s) RETURNING user_id",
apps/api/tests/test_identity_constraints.py-54-            (admin_email, "Synthetic Platform
Admin", admin_role_id),
apps/api/tests/test_identity_constraints.py-55-        )
apps/api/tests/test_identity_constraints.py-56-        admin_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-57-        cur.execute(
```

```
apps/api/tests/test_identity_constraints.py-58-            "INSERT INTO users (email,
display_name) VALUES (%s, %s) RETURNING user_id",
apps/api/tests/test_identity_constraints.py-59-            (user_email, "Synthetic Standard
User"),
apps/api/tests/test_identity_constraints.py-60-        )
apps/api/tests/test_identity_constraints.py-61-        user_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-62-        for owner_id in (admin_id, user_id):
apps/api/tests/test_identity_constraints.py-63-            token, digest =
new_session_token()
apps/api/tests/test_identity_constraints.py-64-            tokens.append(token)
apps/api/tests/test_identity_constraints.py-65-            cur.execute(
apps/api/tests/test_identity_constraints.py-66-                "INSERT INTO auth_sessions
(user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py:67:                (owner_id, digest,
session_expiry(5)),
apps/api/tests/test_identity_constraints.py-68-            )
apps/api/tests/test_identity_constraints.py-69-
apps/api/tests/test_identity_constraints.py-70-    try:
apps/api/tests/test_identity_constraints.py-71-        with TestClient(app) as client:
apps/api/tests/test_identity_constraints.py-72-            anonymous =
client.get("/platform/admin/capability")
apps/api/tests/test_identity_constraints.py-73-            assert anonymous.status_code ==
401
apps/api/tests/test_identity_constraints.py-74-            assert anonymous.json() ==
{"detail": "Authentication required"}
apps/api/tests/test_identity_constraints.py-75-
apps/api/tests/test_identity_constraints.py-76-            invalid_session = client.get(
apps/api/tests/test_identity_constraints.py-77-                "/platform/admin/capability",
apps/api/tests/test_identity_constraints.py-78-                cookies={SESSION_COOKIE:
"invalid-session-token"},
apps/api/tests/test_identity_constraints.py-79-            )
apps/api/tests/test_identity_constraints.py-80-            assert
invalid_session.status_code == 401
apps/api/tests/test_identity_constraints.py-81-
apps/api/tests/test_identity_constraints.py-82-            allowed = client.get(
apps/api/tests/test_identity_constraints.py-83-                "/platform/admin/capability",
apps/api/tests/test_identity_constraints.py-84-                cookies={SESSION_COOKIE:
tokens[0]},
apps/api/tests/test_identity_constraints.py-85-            )
```

```
apps/api/tests/test_identity_constraints.py-86-        assert allowed.status_code ==
200
apps/api/tests/test_identity_constraints.py-87-        assert allowed.json() ==
{"permission": "platform.admin", "allowed": True}
apps/api/tests/test_identity_constraints.py-88-
apps/api/tests/test_identity_constraints.py-89-        denied = client.get(
apps/api/tests/test_identity_constraints.py-90-            "/platform/admin/capability",
apps/api/tests/test_identity_constraints.py-91-            cookies={SESSION_COOKIE:
tokens[1]},
apps/api/tests/test_identity_constraints.py-92-            headers={"X-Role":
"platform_admin"},
apps/api/tests/test_identity_constraints.py-93-        )
apps/api/tests/test_identity_constraints.py-94-        assert denied.status_code == 403
apps/api/tests/test_identity_constraints.py-95-        assert denied.json() == {"detail":
"Permission denied"}
apps/api/tests/test_identity_constraints.py-96-    finally:
apps/api/tests/test_identity_constraints.py-97-        with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-98-            cur.execute("DELETE FROM
users WHERE user_id IN (%s, %s)", (admin_id, user_id))
apps/api/tests/test_identity_constraints.py-99-
apps/api/tests/test_identity_constraints.py-100-
apps/api/tests/test_identity_constraints.py-101-def
test_platform_role_assignment_rejects_workspace_scoped_roles():
apps/api/tests/test_identity_constraints.py-102-    email =
f"wrong-scope-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py-103-    with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-104-        cur.execute(
apps/api/tests/test_identity_constraints.py-105-            "INSERT INTO roles (role_key,
display_name, scope) VALUES (%s, %s, 'workspace') RETURNING role_id",
apps/api/tests/test_identity_constraints.py-106-            (f"ws-{uuid4().hex[:12]}",
"Synthetic Workspace Role"),
apps/api/tests/test_identity_constraints.py-107-        )
apps/api/tests/test_identity_constraints.py-108-        workspace_role_id =
cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-109-        cur.execute(
apps/api/tests/test_identity_constraints.py-110-            "INSERT INTO users (email,
display_name) VALUES (%s, 'Synthetic Scope User') RETURNING user_id",
apps/api/tests/test_identity_constraints.py-111-            (email,),
```

```
apps/api/tests/test_identity_constraints.py-112-        )
apps/api/tests/test_identity_constraints.py-113-        user_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-114-    try:
apps/api/tests/test_identity_constraints.py-115-        with
pytest.raises(psycopg.errors.CheckViolation):
apps/api/tests/test_identity_constraints.py-116-            with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-117-                cur.execute("UPDATE users
SET platform_role_id = %s WHERE user_id = %s", (workspace_role_id, user_id))
apps/api/tests/test_identity_constraints.py-118-    finally:
apps/api/tests/test_identity_constraints.py-119-        with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-120-            cur.execute("DELETE FROM
users WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-121-            cur.execute("DELETE FROM
roles WHERE role_id = %s", (workspace_role_id,))
=== Current proxy and protected frontend routes ===
apps/web/app/layout.js
apps/web/app/page.js
apps/web/app/api/runtime-config/route.js
import { NextResponse } from "next/server";

// This is an optimistic page redirect only. Protected APIs must validate the
// opaque session and permissions server-side; cookie presence grants no access.
export function proxy(request) {
  if (!request.cookies.has("finsight_session")) {
    const signIn = new URL("/", request.url);
    signIn.searchParams.set("next", request.nextUrl.pathname);
    return NextResponse.redirect(signIn);
  }
  return NextResponse.next();
}

export const config = { matcher: ["/app/:path*"] };
=== Existing FIN-15 completion claims ===
SPRINT_1_TEST_EXECUTION_STATUS.txt-148-- Full API suite: 55 passed, 10
warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-149-- Evidence files:
SPRINT_1_TEST_EXECUTION_STATUS.txt-150-
test-results/FIN-15/20261020_141030_identity_authorization.log
```

```
SPRINT_1_TEST_EXECUTION_STATUS.txt-151-
test-results/FIN-15/20261020_141030_full_api_suite.log
SPRINT_1_TEST_EXECUTION_STATUS.txt-152-
test-results/FIN-15/run_20261020_141030_summary.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt-153-
SPRINT_1_TEST_EXECUTION_STATUS.txt-154-These results supersede earlier NOT
RUN notes for the test execution performed
SPRINT_1_TEST_EXECUTION_STATUS.txt-155-in this run. They do not establish that
every mapped test-plan case or the entire
SPRINT_1_TEST_EXECUTION_STATUS.txt:156:FIN-15 story is complete.
Workspace-level authorization remains deferred.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book %  source
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd
FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== FastAPI app configuration and route definitions ==="
grep -n -E
'FastAPI\(|root_path|include_router|APIRouter|prefix=|platform/admin/capability|authoriz
ation/capabilities|openapi_url' \
  apps/api/app/main.py apps/api/app/*.py

echo "=== OpenAPI contract endpoint definition ==="
sed -n '1185,1245p' FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml

echo "=== Contract response and security details ==="
sed -n '120,170p'
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contrac
t.md

echo "=== Current working tree (preserve every change) ==="
git status --short
git diff --check
=== FastAPI app configuration and route definitions ===
apps/api/app/main.py:24:app = FastAPI(title="FinSight AI API", version="0.2.0")
apps/api/app/main.py:184:@app.get("/platform/admin/capability")
apps/api/app/main.py:24:app = FastAPI(title="FinSight AI API", version="0.2.0")
```

apps/api/app/main.py:184:@app.get("/platform/admin/capability")
=== OpenAPI contract endpoint definition ===
        content:
          application/json:
            schema:
              type: object
              properties:
                display_name:
                  type: string
                  example: Analyst
                  description: Illustrative only; final constraints are defined by the
operation-specific Pydantic model.
              additionalProperties: false
              description: Illustrative request schema. Validate exact fields, enums and
constraints against the SRS before
                implementing.
            example:
              display_name: Analyst
  /admin/authorization/capabilities:
    get:
      operationId: get_admin_authorization_capabilities
      tags:
      - Identity & access
      summary: Inspect authorized platform capabilities
      description: 'Decision A: narrowly scoped real-app route protected by
require_permission("platform.admin"); no user
        listing or unrelated business operations.'
      x-contract-status: SPRINT 1 PROPOSED — DECISION A
      x-required-permission: platform.admin
      x-source-stories:
      - FS-01-01
      - FS-01-02
      - FS-01-03
      - FS-01-04
      - FS-01-05
      - FS-09-01
      - FS-09-02
      - FS-09-03
      - FS-09-04
      - FS-09-05

x-source-requirement-ids:
- FR-P1-01
- FR-P1-02
- FR-P1-03
- FR-P1-04
- FR-P1-05
- FR-P1-06
- FR-P1-07
- FR-P1-08
- FR-P1-09
- FR-P1-10
- FR-P1-11
- FR-P1-12
- FR-P1-13
- FR-P1-14
- FR-P1-15
- FR-P9-01
- FR-P9-02
- FR-P9-03
- FR-P9-04
- FR-P9-05
- FR-P9-06
- FR-P9-07
- FR-P9-08
- FR-P9-09
- FR-P9-10

=== Contract response and security details ===

Minimal capability endpoint — approved design

GET `/api/v1/admin/authorization/capabilities` | Required permission: `platform.admin` | Release: Sprint 1 authorization foundation | Must be wired through the real FastAPI dependency chain, not a test-only helper.

Success contract (example):

```json
{
  "data": {
```

```
    "subject": {
      "user_id": "<uuid>",
      "platform_role_code": "platform_admin"
    },
    "effective_permissions": [
      "platform.admin",
      "platform.roles.read"
    ],
    "capabilities": [
      "inspect_authorization_policy"
    ],
    "policy_version": "<policy-version>"
  },
  "request_id": "req_01J..."
}
```

Do not include user directories, workspace data, secrets, session identifiers, password state, or mutation capabilities not actually available. `effective_permissions` must come from persisted roles/permissions and role-permission relationships, not a hard-coded `if role == "admin"` branch. If canonical permission tables are missing in the current migration set, add a new forward-only migration for `permissions`, `role_permissions` (and any necessary constraints/indexes); inspect migration history first, and do not edit an applied migration or the reference SQL package.

Required database-backed test matrix

Case	Setup/request	Expected result	Failure condition
Admin success	Real persisted admin user + active database-backed session + explicit `platform.admin` grant; GET endpoint.	200; only caller’s effective permission/capability summary; request ID; no secret fields.	Any role-name-only bypass or response containing unrelated user/workspace data.
Authenticated denied user	Real active session; lacks `platform.admin`; GET endpoint.	403 `permission_denied`; no capabilities or policy details leaked.	200, 404 workaround, or permission derived from caller-supplied JSON.
Anonymous	No cookie/token.	401 `unauthorized`.	Any response with admin capabilities.

Expired/revoked session	Session persisted then expired/revoked; GET endpoint.	401; server-side revocation and expiry checked for each request.	A previously valid cookie remains trusted after revocation.
Database/RBAC failure	Inject session or permission query failure.	503 `authorization_unavailable`; fail closed; structured redacted log.	Fallback-to-admin, unprotected 200, or leak of SQL/stack trace.
Cross-role spoofing	Non-admin attempts to provide a fake role/user/workspace claim.	403; server trusts authenticated principal and persisted policy only.	Any client field changes authorization.
Permission revoked after session	Create session, remove permission mapping, repeat request.	Denied on next authorization check within defined cache policy (default no positive cache in Sprint 1).	Stale grant remains valid without documented bounded cache invalidation.
CSRF/cookie posture	Browser-origin mutating request without required CSRF protection (where cookie auth used).	Rejected according to selected CSRF policy.	Cookie-authenticated mutation succeeds with missing/invalid CSRF proof.

Never mark FIN-15 complete from the capability endpoint alone: it is a minimal authorization proof route. The role/permission matrix, access checks for all implemented protected APIs, test evidence, route ownership checks and outstanding source acceptance criteria still have to pass.

FastAPI implementation pattern

The example below is a design sketch, not a drop-in replacement for the current auth/session modules. It must use the repository's real principal, database session dependency, role/permission tables and error conventions. The dependency should be shared and applied to route groups; domain services must still check resource ownership/workspace grants.

=== Current working tree (preserve every change) ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py

```
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
```

Never mark FIN-15 complete from the capability endpoint alone: it is a minimal authorization proof route. The role/permission matrix, access checks for all implemented protected APIs, test evidence, route ownership checks and outstanding source acceptance criteria still have to pass.

FastAPI implementation pattern

The example below is a design sketch, not a drop-in replacement for the current auth/session modules. It must use the repository's real principal, database session dependency, role/permission tables and error conventions. The dependency should be shared and applied to route groups; domain services must still check resource ownership/workspace grants.

```
=== Current working tree (preserve every change) ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
```

```
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== Current FastAPI auth and capability route ==="
sed -n '1,230p' apps/api/app/main.py

echo "=== Authorization migration ==="
sed -n '1,260p' apps/api/migrations/0002_platform_authorization.sql

echo "=== Earlier migration and database schema references ==="
find apps/api/migrations -maxdepth 1 -type f -print | sort
grep -n -E 'CREATE
TABLE.*(users|roles|permissions|role_permissions|auth_sessions)|platform_role_id|role
_permissions|permissions' \
  apps/api/migrations/*.sql

echo "=== Request ID and error conventions ==="
grep -R -n -E
'request_id|correlation|authorization_unavailable|permission_denied|Authentication
service unavailable' \
  apps/api/app apps/api/tests

echo "=== OpenAPI response schema for capability endpoint ==="
grep -n -A120 '^  /admin/authorization/capabilities:' \
  FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml

echo "=== Current permission test and helpers ==="
sed -n '245,310p' apps/api/tests/test_auth_unit.py
sed -n '310,405p' apps/api/tests/test_identity_constraints.py
=== Current FastAPI auth and capability route ===
"""FinSight AI API with PostgreSQL-backed browser sessions."""

from __future__ import annotations

import os
import secrets
from datetime import UTC, datetime
```

```
from pathlib import Path
from typing import Annotated, Any
from uuid import UUID

import psycopg
from dotenv import load_dotenv
from fastapi import Cookie, Depends, FastAPI, HTTPException, Request, Response,
status
from fastapi.middleware.cors import CORSMiddleware
from pydantic import BaseModel, EmailStr, Field
from psycopg.rows import dict_row

from app.auth import hash_password, new_session_token, session_expiry,
token_digest, verify_password
from app.database import connect

load_dotenv(Path(__file__).resolve().parents[3] / ".env")

app = FastAPI(title="FinSight AI API", version="0.2.0")
web_origin = os.environ.get("WEB_ORIGIN", "http://localhost:3000")
app.add_middleware(
    CORSMiddleware,
    allow_origins=[web_origin],
    allow_credentials=True,
    allow_methods=["GET", "POST"],
    allow_headers=["Content-Type"],
)

SESSION_COOKIE = "finsight_session"
GENERIC_LOGIN_ERROR = "Email or password is incorrect."
DUMMY_PASSWORD_HASH = hash_password(secrets.token_urlsafe(32))


class LoginRequest(BaseModel):
    email: EmailStr
    password: str = Field(min_length=1, max_length=1024)


class UserView(BaseModel):
    user_id: UUID
```

```
    email: str
    display_name: str


def _ttl_minutes() -> int:
    try:
        value = int(os.environ.get("SESSION_TTL_MINUTES", "60"))
        session_expiry(value)
        return value
    except ValueError as exc:
        raise HTTPException(status_code=500, detail="Session configuration is invalid")
from exc


def _secure_cookie() -> bool:
    configured = os.environ.get("COOKIE_SECURE")
    if configured is not None:
        return configured.lower() in {"1", "true", "yes"}
    return os.environ.get("APP_ENV", "development").lower() == "production"


def _check_origin(request: Request) -> None:
    origin = request.headers.get("origin")
    if origin and origin != web_origin:
        raise HTTPException(status_code=403, detail="Request origin is not allowed")


def get_current_user(
    session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] = None,
) -> dict[str, Any]:
    if not session_token:
        raise HTTPException(status_code=status.HTTP_401_UNAUTHORIZED,
detail="Authentication required")
    try:
        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
            cur.execute(
                """SELECT u.user_id, u.email, u.display_name, r.role_key,
                        COALESCE(array_agg(DISTINCT p.permission_key)
                                FILTER (WHERE p.permission_key IS NOT NULL),
ARRAY[]::varchar[]) AS permissions
```

```
                FROM auth_sessions s JOIN users u ON u.user_id = s.user_id
                LEFT JOIN roles r ON r.role_id = u.platform_role_id AND r.scope =
'platform'
                LEFT JOIN role_permissions rp ON rp.role_id = r.role_id
                LEFT JOIN permissions p ON p.permission_id = rp.permission_id
                WHERE s.refresh_token_hash = %s AND s.revoked_at IS NULL
                  AND s.expires_at > %s AND u.account_status = 'active'
                  AND s.last_seen_at > %s - make_interval(mins => %s)
                  AND u.deleted_at IS NULL
                GROUP BY u.user_id, u.email, u.display_name, r.role_key""",
              (token_digest(session_token), datetime.now(UTC), datetime.now(UTC),
_ttl_minutes()),
            )
            user = cur.fetchone()
            if not user:
                raise HTTPException(status_code=401, detail="Authentication required")
            cur.execute(
                "UPDATE auth_sessions SET last_seen_at = %s WHERE
refresh_token_hash = %s",
                (datetime.now(UTC), token_digest(session_token)),
            )
            return user
    except psycopg.Error as exc:
        raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc


CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]


def require_permission(permission_key: str):
    """Build a deny-by-default backend permission dependency."""
    def dependency(user: CurrentUser) -> dict[str, Any]:
        if permission_key not in user.get("permissions", []):
            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN,
detail="Permission denied")
        return user

    return dependency
```

```
@app.post("/auth/login", response_model=UserView)
def login(payload: LoginRequest, request: Request, response: Response) -> UserView:
    _check_origin(request)
    email = payload.email.strip().lower()
    try:
        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
            cur.execute(
                """SELECT user_id, email, display_name, password_hash
                   FROM users WHERE lower(email) = %s AND account_status = 'active'
                     AND deleted_at IS NULL""",
                (email,),
            )
            user = cur.fetchone()
            if not user or not user["password_hash"]:
                verify_password(DUMMY_PASSWORD_HASH, payload.password)
                raise HTTPException(status_code=401, detail=GENERIC_LOGIN_ERROR)
            if not verify_password(user["password_hash"], payload.password):
                raise HTTPException(status_code=401, detail=GENERIC_LOGIN_ERROR)
            token, digest = new_session_token()
            expires_at = session_expiry(_ttl_minutes())
            cur.execute(
                """INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
                   VALUES (%s, %s, %s)""",
                (user["user_id"], digest, expires_at),
            )
            cur.execute("UPDATE users SET last_login_at = %s, updated_at = %s WHERE
user_id = %s",
                        (datetime.now(UTC), datetime.now(UTC), user["user_id"]))
        response.set_cookie(
            SESSION_COOKIE,
            token,
            httponly=True,
            secure=_secure_cookie(),
            samesite="lax",
            max_age=_ttl_minutes() * 60,
            path="/",
        )
        return UserView(user_id=user["user_id"], email=user["email"],
display_name=user["display_name"])
```

```
    except psycopg.Error as exc:
        raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc


@app.post("/auth/logout", status_code=204)
def logout(request: Request, response: Response,
           session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] =
None) -> Response:
    _check_origin(request)
    if session_token:
        try:
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    """UPDATE auth_sessions SET revoked_at = %s, revoke_reason = 'logout'
                       WHERE refresh_token_hash = %s AND revoked_at IS NULL""",
                    (datetime.now(UTC), token_digest(session_token)),
                )
        except psycopg.Error as exc:
            raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
    response.status_code = status.HTTP_204_NO_CONTENT
    return response


@app.get("/auth/me", response_model=UserView)
def who_am_i(user: CurrentUser) -> UserView:
    return UserView(**user)


@app.get("/platform/admin/capability")
def platform_admin_capability(
    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
) -> dict[str, str | bool]:
    """Minimal capability endpoint proving platform-admin authorization at the API
boundary."""
    return {"permission": "platform.admin", "allowed": True}
```

```
=== Authorization migration ===
-- FIN-15: only the platform-scoped administrator permission is implemented.
-- Workspace roles and workspace permissions remain unavailable until workspace
membership exists.
BEGIN;

CREATE TABLE permissions (
    permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    permission_key VARCHAR(120) NOT NULL UNIQUE,
    description TEXT NOT NULL
);

CREATE TABLE role_permissions (
    role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
    permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON
DELETE CASCADE,
    PRIMARY KEY (role_id, permission_id)
);

INSERT INTO roles (role_key, display_name, scope, description)
VALUES ('platform_admin', 'Platform Administrator', 'platform',
        'Administrator privileges for currently implemented platform operations only.')
ON CONFLICT (role_key) DO NOTHING;

DO $$
BEGIN
    IF NOT EXISTS (SELECT 1 FROM roles WHERE role_key = 'platform_admin' AND
scope = 'platform') THEN
        RAISE EXCEPTION 'Existing platform_admin role has non-platform scope';
    END IF;
END
$$;

INSERT INTO permissions (permission_key, description)
VALUES ('platform.admin', 'Access operations explicitly assigned platform administrator
permission.')
ON CONFLICT (permission_key) DO NOTHING;

INSERT INTO role_permissions (role_id, permission_id)
SELECT r.role_id, p.permission_id
```

```
FROM roles r CROSS JOIN permissions p
WHERE r.role_key = 'platform_admin' AND r.scope = 'platform'
  AND p.permission_key = 'platform.admin'
ON CONFLICT DO NOTHING;

CREATE FUNCTION enforce_platform_role_scope() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
   IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
      SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope =
'platform'
   ) THEN
      RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
         USING ERRCODE = '23514';
   END IF;
   RETURN NEW;
END
$$;

CREATE TRIGGER users_platform_role_scope_check
BEFORE INSERT OR UPDATE OF platform_role_id ON users
FOR EACH ROW EXECUTE FUNCTION enforce_platform_role_scope();

CREATE FUNCTION prevent_platform_role_scope_drift() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
   IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
      SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
   ) THEN
      RAISE EXCEPTION 'Cannot change scope of an assigned platform role';
   END IF;
   RETURN NEW;
END
$$;

CREATE TRIGGER roles_prevent_scope_drift
BEFORE UPDATE OF scope ON roles
FOR EACH ROW EXECUTE FUNCTION prevent_platform_role_scope_drift();

COMMIT;
```

=== Earlier migration and database schema references ===
apps/api/migrations/0001_auth_identity.sql
apps/api/migrations/0002_platform_authorization.sql
apps/api/migrations/0001_auth_identity.sql:5:CREATE TABLE roles (
apps/api/migrations/0001_auth_identity.sql:14:CREATE TABLE users (
apps/api/migrations/0001_auth_identity.sql:21:   platform_role_id UUID REFERENCES roles(role_id) ON DELETE SET NULL,
apps/api/migrations/0001_auth_identity.sql:31:CREATE TABLE auth_sessions (
apps/api/migrations/0002_platform_authorization.sql:2:-- Workspace roles and workspace permissions remain unavailable until workspace membership exists.
apps/api/migrations/0002_platform_authorization.sql:5:CREATE TABLE permissions (
apps/api/migrations/0002_platform_authorization.sql:11:CREATE TABLE role_permissions (
apps/api/migrations/0002_platform_authorization.sql:13:   permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON DELETE CASCADE,
apps/api/migrations/0002_platform_authorization.sql:30:INSERT INTO permissions (permission_key, description)
apps/api/migrations/0002_platform_authorization.sql:34:INSERT INTO role_permissions (role_id, permission_id)
apps/api/migrations/0002_platform_authorization.sql:36:FROM roles r CROSS JOIN permissions p
apps/api/migrations/0002_platform_authorization.sql:44:   IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
apps/api/migrations/0002_platform_authorization.sql:45:   SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope = 'platform'
apps/api/migrations/0002_platform_authorization.sql:47:   RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
apps/api/migrations/0002_platform_authorization.sql:55:BEFORE INSERT OR UPDATE OF platform_role_id ON users
apps/api/migrations/0002_platform_authorization.sql:62:   SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
=== Request ID and error conventions ===
Binary file apps/api/app/__pycache__/main.cpython-312.pyc matches
Binary file apps/api/app/__pycache__/main.cpython-314.pyc matches
apps/api/app/main.py:103:   raise HTTPException(status_code=503, detail="Authentication service unavailable") from exc
apps/api/app/main.py:157:   raise HTTPException(status_code=503, detail="Authentication service unavailable") from exc
apps/api/app/main.py:173:   raise HTTPException(status_code=503, detail="Authentication service unavailable") from exc

Binary file apps/api/tests/__pycache__/test_auth_unit.cpython-312-pytest-9.0.3.pyc matches
Binary file apps/api/tests/__pycache__/test_auth_unit.cpython-314.pyc matches
Binary file apps/api/tests/__pycache__/test_auth_unit.cpython-314-pytest-8.4.2.pyc matches
Binary file apps/api/tests/__pycache__/test_auth_unit.cpython-314-pytest-9.0.3.pyc matches
apps/api/tests/test_auth_unit.py:78:   assert response.json() == {"detail": "Authentication service unavailable"}
apps/api/tests/test_auth_unit.py:153:   assert response.json() == {"detail": "Authentication service unavailable"}
=== OpenAPI response schema for capability endpoint ===
1199: /admin/authorization/capabilities:
1200-   get:
1201-   operationId: get_admin_authorization_capabilities
1202-   tags:
1203-   - Identity & access
1204-   summary: Inspect authorized platform capabilities
1205-   description: 'Decision A: narrowly scoped real-app route protected by require_permission("platform.admin"); no user
1206-   listing or unrelated business operations.'
1207-   x-contract-status: SPRINT 1 PROPOSED — DECISION A
1208-   x-required-permission: platform.admin
1209-   x-source-stories:
1210-   - FS-01-01
1211-   - FS-01-02
1212-   - FS-01-03
1213-   - FS-01-04
1214-   - FS-01-05
1215-   - FS-09-01
1216-   - FS-09-02
1217-   - FS-09-03
1218-   - FS-09-04
1219-   - FS-09-05
1220-   x-source-requirement-ids:
1221-   - FR-P1-01
1222-   - FR-P1-02
1223-   - FR-P1-03
1224-   - FR-P1-04
1225-   - FR-P1-05

1226- - FR-P1-06
1227- - FR-P1-07
1228- - FR-P1-08
1229- - FR-P1-09
1230- - FR-P1-10
1231- - FR-P1-11
1232- - FR-P1-12
1233- - FR-P1-13
1234- - FR-P1-14
1235- - FR-P1-15
1236- - FR-P9-01
1237- - FR-P9-02
1238- - FR-P9-03
1239- - FR-P9-04
1240- - FR-P9-05
1241- - FR-P9-06
1242- - FR-P9-07
1243- - FR-P9-08
1244- - FR-P9-09
1245- - FR-P9-10
1246- - FR-P9-11
1247- - FR-P9-12
1248- - FR-P9-13
1249- - FR-P9-14
1250- - FR-P9-15
1251- - FR-P9-16
1252- - FR-P9-17
1253- - FR-P9-18
1254- - FR-P9-19
1255- - FR-P9-20
1256- - FR-P9-21
1257- - FR-P9-22
1258- - FR-P9-25
1259- - NFR-P1-01
1260- - NFR-P1-02
1261- - NFR-P1-03
1262- - NFR-P1-04
1263- - NFR-P1-05
1264- - NFR-P1-06
1265- - NFR-P9-01

```
1266-      - NFR-P9-02
1267-      - NFR-P9-03
1268-      - NFR-P9-04
1269-      - NFR-P9-05
1270-      - NFR-P9-06
1271-      - NFR-P9-07
1272-      x-release-scope: Release 1 target
1273-      responses:
1274-        '200':
1275-          description: Successful response; operation-specific schema must be
finalized from its Pydantic DTO
1276-          content:
1277-            application/json:
1278-              schema:
1279-                $ref: '#/components/schemas/SuccessEnvelope'
1280-        '400':
1281-          $ref: '#/components/responses/BadRequest'
1282-        '401':
1283-          $ref: '#/components/responses/Unauthorized'
1284-        '403':
1285-          $ref: '#/components/responses/Forbidden'
1286-        '404':
1287-          $ref: '#/components/responses/NotFound'
1288-        '409':
1289-          $ref: '#/components/responses/Conflict'
1290-        '422':
1291-          $ref: '#/components/responses/ValidationError'
1292-        '429':
1293-          $ref: '#/components/responses/RateLimited'
1294-        '500':
1295-          $ref: '#/components/responses/InternalError'
1296-        '503':
1297-          $ref: '#/components/responses/DependencyUnavailable'
1298-      security:
1299-      - cookieSession: []
1300-      - bearerAuth: []
1301-      parameters:
1302-      - name: request_id
1303-        in: header
1304-        required: false
```

```
1305-        schema:
1306-          type: string
1307-          maxLength: 128
1308-        description: Optional caller correlation ID; server validates and returns
canonical request_id.
1309-  /admin/roles:
1310-    get:
1311-      operationId: get_admin_roles
1312-      tags:
1313-      - Identity & access
1314-      summary: List platform roles
1315-      description: Not part of the minimal capability endpoint; implement only with
explicit RBAC and tests.
1316-      x-contract-status: PROPOSED TARGET CONTRACT
1317-      x-required-permission: platform.roles.read
1318-      x-source-stories:
1319-      - FS-01-01
=== Current permission test and helpers ===
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
== Current permission test and helpers ===
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== Remaining permission tests ==="
sed -n '250,330p' apps/api/tests/test_auth_unit.py
sed -n '310,405p' apps/api/tests/test_identity_constraints.py

echo "=== API dependency and test configuration ==="
sed -n '1,180p' apps/api/pyproject.toml 2>/dev/null
sed -n '1,180p' apps/api/pytest.ini 2>/dev/null
sed -n '1,120p' apps/api/app/database.py

echo "=== Request ID middleware or handlers, if any ==="
grep -R -n --exclude='*.pyc' -E 'request_id|X-Request-ID|middleware\(' apps/api/app
=== Remaining permission tests ===
=== API dependency and test configuration ===
"""Small synchronous PostgreSQL boundary for the auth endpoints."""

from __future__ import annotations
```

```
import os
from pathlib import Path

import psycopg
from dotenv import load_dotenv

load_dotenv(Path(__file__).resolve().parents[3] / ".env")


def connect() -> psycopg.Connection:
    database_url = os.environ.get("DATABASE_URL")
    if not database_url:
        raise RuntimeError("DATABASE_URL is required")
    return psycopg.connect(database_url, connect_timeout=3)
=== Request ID middleware or handlers, if any ===
apps/api/app/main.py:26:app.add_middleware(
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

import psycopg
from dotenv import load_dotenv

load_dotenv(Path(__file__).resolve().parents[3] / ".env")


def connect() -> psycopg.Connection:
    database_url = os.environ.get("DATABASE_URL")
    if not database_url:
        raise RuntimeError("DATABASE_URL is required")
    return psycopg.connect(database_url, connect_timeout=3)
=== Request ID middleware or handlers, if any ===
apps/api/app/main.py:26:app.add_middleware(
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

mkdir -p /tmp/finsight-fin15-backup
cp apps/api/app/main.py /tmp/finsight-fin15-backup/main.py
cp apps/api/tests/test_identity_constraints.py \
  /tmp/finsight-fin15-backup/test_identity_constraints.py

echo "Backup created:"
```

```
ls -l /tmp/finsight-fin15-backup
Backup created:
total 32
-rw-r--r--@ 1 sandeeph  wheel  7780 Oct 20 14:40 main.py
-rw-r--r--@ 1 sandeeph  wheel  5227 Oct 20 14:40 test_identity_constraints.py
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

Backup created:
total 32
-rw-r--r--@ 1 sandeeph  wheel  7780 Oct 20 14:40 main.py
-rw-r--r--@ 1 sandeeph  wheel  5227 Oct 20 14:40 test_identity_constraints.py
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== Success envelope schema ==="
grep -n -A55 '^    SuccessEnvelope:' \
  FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml

echo "=== Permission test definitions ==="
grep -n '^def test_' apps/api/tests/test_auth_unit.py
grep -n '^def test_' apps/api/tests/test_identity_constraints.py

echo "=== Backup integrity ==="
cmp apps/api/app/main.py /tmp/finsight-fin15-backup/main.py
cmp apps/api/tests/test_identity_constraints.py \
  /tmp/finsight-fin15-backup/test_identity_constraints.py
echo "Backup comparison exit code: $?"
=== Success envelope schema ===
18763:    SuccessEnvelope:
18764-      type: object
18765-      required:
18766-      - data
18767-      - request_id
18768-      properties:
18769-        data:
18770-          type: object
18771-          additionalProperties: true
18772-        request_id:
18773-          type: string
18774-        correlation_id:
```

```
18775-        type: string
18776-    ErrorResponse:
18777-      type: object
18778-      required:
18779-      - error
18780-      - request_id
18781-      properties:
18782-        error:
18783-          type: object
18784-          required:
18785-          - code
18786-          - message
18787-          properties:
18788-            code:
18789-              type: string
18790-            message:
18791-              type: string
18792-            field_errors:
18793-              type: array
18794-              items:
18795-                type: object
18796-                properties:
18797-                  field:
18798-                    type: string
18799-                  code:
18800-                    type: string
18801-                  message:
18802-                    type: string
18803-          details:
18804-            type: object
18805-            additionalProperties: true
18806-        request_id:
18807-          type: string
18808-        correlation_id:
18809-          type: string
18810-    PageInfo:
18811-      type: object
18812-      properties:
18813-        next_cursor:
18814-          type:
```

```
18815-          - string
18816-          - 'null'
18817-        has_more:
18818-          type: boolean
=== Permission test definitions ===
13:def test_password_helpers_accept_only_the_original_password():
23:def test_session_expiry_uses_utc_and_requested_ttl():
30:def test_session_expiry_rejects_out_of_range_ttl(ttl: int):
36:def test_ttl_configuration_accepts_only_supported_values(monkeypatch, configured:
str, expected: int):
43:def test_ttl_configuration_fails_closed(monkeypatch, configured: str):
53:def test_session_tokens_are_opaque_and_only_digest_is_stable():
63:def test_login_maps_database_outage_to_controlled_error(monkeypatch):
82:def
test_protected_route_rejects_missing_session_before_database_access(monkeypatch)
:
99:def test_permission_dependency_allows_only_explicit_permission(user,
expected_status):
118:def test_permission_dependency_ignores_client_supplied_role_header():
142:def test_session_database_outages_return_controlled_error(monkeypatch,
method, path, kwargs):
157:def test_database_configuration_is_required(monkeypatch):
166:def test_login_rejects_invalid_input_before_database_access():
177:def test_secure_cookie_accepts_explicit_secure_values(monkeypatch, configured:
str):
184:def test_secure_cookie_treats_other_explicit_values_as_insecure(monkeypatch,
configured: str):
191:def test_secure_cookie_defaults_by_environment(monkeypatch, app_env: str,
expected: bool):
14:def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
45:def test_platform_permission_is_resolved_from_database_role_and_session():
101:def test_platform_role_assignment_rejects_workspace_scoped_roles():
=== Backup integrity ===
Backup comparison exit code: 0
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book %  source
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd
FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....
```

```
        "request_id": request_id,
        "correlation_id": request_id,
    }
'''

if old_route not in main:
    raise SystemExit("ABORT: expected original capability route was not found; no files changed.")

old_test_route = '"/platform/admin/capability"'
new_test_route = '"/api/v1/admin/authorization/capabilities"'

test = test_path.read_text()
if old_test_route not in test:
    raise SystemExit("ABORT: expected old route in integration test was not found; no files changed.")

# Update response assertions only for the known existing success assertion.
old_success = '''            assert allowed.status_code == 200
            assert allowed.json() == {"permission": "platform.admin", "allowed": True}
'''
new_success = '''            assert allowed.status_code == 200
            body = allowed.json()
            assert body["data"]["subject"]["user_id"] == str(admin_id)
            assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
            assert body["data"]["effective_permissions"] == ["platform.admin"]
            assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
            assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
            assert body["request_id"].startswith("req_")
            assert body["correlation_id"] == body["request_id"]
'''
if old_success not in test:
    raise SystemExit("ABORT: expected success assertion was not found; no files changed.")

# Complete all validation before writing either file.
main_path.write_text(main.replace(old_route, new_route, 1))
test = test.replace(old_test_route, new_test_route)
test_path.write_text(test.replace(old_success, new_success, 1))
```

```
print("Updated capability endpoint and its existing integration test.")
PY
Updated capability endpoint and its existing integration test.
o update, run: pip install --upgrade pip
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd ..
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro apps % cd ..
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

cd apps/api || exit 1

DATABASE_URL="postgresql:///finsight_test" \
  python -m pytest -q \
  tests/test_identity_constraints.py \
  tests/test_auth_unit.py \
  tests/test_auth.py
.....................................
[100%]
========================================================================
=============================== warnings summary
========================================================================
================================
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
```

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[get-/auth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_error[post-/auth/logout-kwargs1]
apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour oncookie persistence is ambiguous. Set cookies directly on the client instance instead.
  return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
44 passed, 11 warnings in 13.68s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %

.....
[100%]
========== warnings summary ==========
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fastapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install `httpx2` instead.
  from starlette.testclient import TestClient as TestClient # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is deprecated, use anyio.from_thread.BlockingPortal instead.
  _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

```
apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_err
or[get-/auth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_err
or[post-/auth/logout-kwargs1]
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour oncookie persistence is ambiguous. Set
cookies directly on the client instance instead.
  return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
55 passed, 11 warnings in 1.11s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "=== FIN-15 implementation diff ==="
git diff -- apps/api/app/main.py apps/api/tests/test_identity_constraints.py

echo "=== Working tree status ==="
git status --short
=== FIN-15 implementation diff ===
diff --git a/apps/api/app/main.py b/apps/api/app/main.py
index b91a470..4fd17ab 100644
--- a/apps/api/app/main.py
+++ b/apps/api/app/main.py
@@ -77,12 +77,18 @@ def get_current_user(
    try:
        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
```

```
            cur.execute(
-               """SELECT u.user_id, u.email, u.display_name
+               """SELECT u.user_id, u.email, u.display_name, r.role_key,
+                      COALESCE(array_agg(DISTINCT p.permission_key)
+                               FILTER (WHERE p.permission_key IS NOT NULL),
ARRAY[]::varchar[]) AS permissions
                   FROM auth_sessions s JOIN users u ON u.user_id = s.user_id
+                   LEFT JOIN roles r ON r.role_id = u.platform_role_id AND r.scope =
'platform'
+                   LEFT JOIN role_permissions rp ON rp.role_id = r.role_id
+                   LEFT JOIN permissions p ON p.permission_id = rp.permission_id
                   WHERE s.refresh_token_hash = %s AND s.revoked_at IS NULL
                    AND s.expires_at > %s AND u.account_status = 'active'
                    AND s.last_seen_at > %s - make_interval(mins => %s)
-                   AND u.deleted_at IS NULL""",
+                    AND u.deleted_at IS NULL
+                  GROUP BY u.user_id, u.email, u.display_name, r.role_key""",
                (token_digest(session_token), datetime.now(UTC), datetime.now(UTC),
_ttl_minutes()),
            )
            user = cur.fetchone()
@@ -100,6 +106,16 @@ def get_current_user(
 CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]


+def require_permission(permission_key: str):
+    """Build a deny-by-default backend permission dependency."""
+    def dependency(user: CurrentUser) -> dict[str, Any]:
+        if permission_key not in user.get("permissions", []):
+            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN,
detail="Permission denied")
+        return user
+
+    return dependency
+
+
=== Working tree status ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
```

```
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

+    return dependency
+
+
=== Working tree status ===
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1
```

```
echo "=== Capability routes currently registered in source ==="
grep -n -A28 -B5 -E \
  'platform_admin_capabilit|authorization/capabilities|platform/admin/capability' \
  apps/api/app/main.py

echo "=== Capability route tests ==="
grep -n -A70 -B5 -E \
  'platform_permission_is_resolved|authorization/capabilities|platform/admin/capability' \
  apps/api/tests/test_identity_constraints.py

echo "=== Confirm OpenAPI route in the running application ==="
cd apps/api || exit 1
DATABASE_URL="postgresql:///finsight_test" python - <<'PY'
from app.main import app

for route in app.routes:
    path = getattr(route, "path", "")
    if "capability" in path or "authorization" in path:
        print(path, sorted(getattr(route, "methods", set())))
PY
=== Capability routes currently registered in source ===
179-@app.get("/auth/me", response_model=UserView)
180-def who_am_i(user: CurrentUser) -> UserView:
181-    return UserView(**user)
182-
183-
184:@app.get("/api/v1/admin/authorization/capabilities")
185:def platform_admin_capabilities(
186-    request: Request,
187-    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
188-) -> dict[str, Any]:
189-    """Return the authenticated caller's database-backed platform capabilities."""
190-    supplied_request_id = request.headers.get("request_id", "").strip()
191-    if supplied_request_id and (
192-        len(supplied_request_id) > 128
193-        or any(ord(char) < 32 or ord(char) == 127 for char in supplied_request_id)
194-    ):
195-        raise HTTPException(status_code=400, detail="Invalid request_id")
196-
```

```
197-    request_id = supplied_request_id or f"req_{secrets.token_urlsafe(12)}"
198-    permissions = sorted(set(_authorized.get("permissions", [])))
199-    capabilities = (
200-        ["inspect_authorization_policy"]
201-        if "platform.admin" in permissions
202-        else []
203-    )
204-
205-    return {
206-        "data": {
207-            "subject": {
208-                "user_id": str(_authorized["user_id"]),
209-                "platform_role_code": _authorized.get("role_key"),
210-            },
211-            "effective_permissions": permissions,
212-            "capabilities": capabilities,
213-            "policy_version": "sprint-1-platform-rbac-v1",
=== Capability route tests ===
40-    finally:
41-        with connect() as conn, conn.cursor() as cur:
42-            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
43-
44-
45:def test_platform_permission_is_resolved_from_database_role_and_session():
46-    admin_email = f"platform-admin-{uuid4().hex}@example.test"
47-    user_email = f"unprivileged-{uuid4().hex}@example.test"
48-    tokens = []
49-    with connect() as conn, conn.cursor() as cur:
50-        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
51-        admin_role_id = cur.fetchone()[0]
52-        cur.execute(
53-            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s,
%s, %s) RETURNING user_id",
54-            (admin_email, "Synthetic Platform Admin", admin_role_id),
55-        )
56-        admin_id = cur.fetchone()[0]
57-        cur.execute(
58-            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
```

```
59-            (user_email, "Synthetic Standard User"),
60-        )
61-        user_id = cur.fetchone()[0]
62-        for owner_id in (admin_id, user_id):
63-            token, digest = new_session_token()
64-            tokens.append(token)
65-            cur.execute(
66-                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
67-                (owner_id, digest, session_expiry(5)),
68-            )
69-
70-    try:
71-        with TestClient(app) as client:
72:            anonymous = client.get("/api/v1/admin/authorization/capabilities")
73-            assert anonymous.status_code == 401
74-            assert anonymous.json() == {"detail": "Authentication required"}
75-
76-            invalid_session = client.get(
77:                "/api/v1/admin/authorization/capabilities",
78-                cookies={SESSION_COOKIE: "invalid-session-token"},
79-            )
80-            assert invalid_session.status_code == 401
81-
82-            allowed = client.get(
83:                "/api/v1/admin/authorization/capabilities",
84-                cookies={SESSION_COOKIE: tokens[0]},
85-            )
86-            assert allowed.status_code == 200
87-            body = allowed.json()
88-            assert body["data"]["subject"]["user_id"] == str(admin_id)
89-            assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
90-            assert body["data"]["effective_permissions"] == ["platform.admin"]
91-            assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
92-            assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
93-            assert body["request_id"].startswith("req_")
94-            assert body["correlation_id"] == body["request_id"]
95-
96-            denied = client.get(
97:                "/api/v1/admin/authorization/capabilities",
```

```
98-              cookies={SESSION_COOKIE: tokens[1]},
99-              headers={"X-Role": "platform_admin"},
100-          )
101-          assert denied.status_code == 403
102-          assert denied.json() == {"detail": "Permission denied"}
103-    finally:
104-        with connect() as conn, conn.cursor() as cur:
105-            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)",
(admin_id, user_id))
106-
107-
108-def test_platform_role_assignment_rejects_workspace_scoped_roles():
109-    email = f"wrong-scope-{uuid4().hex}@example.test"
110-    with connect() as conn, conn.cursor() as cur:
111-        cur.execute(
112-            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
113-            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
114-        )
115-        workspace_role_id = cur.fetchone()[0]
116-        cur.execute(
117-            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
118-            (email,),
119-        )
120-        user_id = cur.fetchone()[0]
121-    try:
122-        with pytest.raises(psycopg.errors.CheckViolation):
123-            with connect() as conn, conn.cursor() as cur:
124-                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id
= %s", (workspace_role_id, user_id))
125-    finally:
126-        with connect() as conn, conn.cursor() as cur:
127-            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
128-            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))
=== Confirm OpenAPI route in the running application ===
/api/v1/admin/authorization/capabilities ['GET']
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
```

```
git diff --check || exit 1

cd apps/api || exit 1
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
.....................................................
[100%]
=============================================================================
================================== warnings summary
=============================================================================
==================================
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_err
or[get-/auth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_err
or[post-/auth/logout-kwargs1]
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
```

```
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour oncookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
55 passed, 11 warnings in 1.06s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
/admin/authorization/capabilities ['GET']
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

git diff --check || exit 1

cd apps/api || exit 1
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
.....................................................
[100%]
=============================================================================
=============================== warnings summary
=============================================================================
================================
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fastapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py::test_login_creates_protected_hashed_expiring_session
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
```

```
apps/api/tests/test_auth.py::test_logout_revokes_session_and_replay_fails
apps/api/tests/test_auth.py::test_expired_session_is_rejected
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_err
or[get-/auth/me-kwargs0]
apps/api/tests/test_auth_unit.py::test_session_database_outages_return_controlled_err
or[post-/auth/logout-kwargs1]
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour oncookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
55 passed, 11 warnings in 1.06s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "===== 1. WORKING TREE ====="
git status --short

echo "\n===== 2. AUTHORIZATION ENDPOINT ====="
grep -n -A55 -B12 'platform_admin_capabilities|authorization/capabilities|def
require_permission' apps/api/app/main.py

echo "\n===== 3. EXISTING AUTHORIZATION TESTS ====="
grep -n -A90 -B10
'test_platform_permission_is_resolved_from_database_role_and_session|database_out
ages_return_controlled_error|permission' apps/api/tests/test_identity_constraints.py
apps/api/tests/test_auth_unit.py

echo "\n===== 4. TRACEABILITY STATUS ====="
```

```
grep -n -A5 -B3
'FIN-15|TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_00
1' FUNCTION_TEST_TRACEABILITY.txt SPRINT_1_TEST_EXECUTION_STATUS.txt

echo "\n===== 5. CHECK PATCH FORMATTING ====="
git diff --check
===== 1. WORKING TREE =====
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js

===== 2. AUTHORIZATION ENDPOINT =====

===== 3. EXISTING AUTHORIZATION TESTS =====

===== 4. TRACEABILITY STATUS =====

===== 5. CHECK PATCH FORMATTING =====
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

echo "\n===== 3. EXISTING AUTHORIZATION TESTS ====="
grep -n -A90 -B10
'test_platform_permission_is_resolved_from_database_role_and_session|database_out
ages_return_controlled_error|permission' apps/api/tests/test_identity_constraints.py
apps/api/tests/test_auth_unit.py
```

```
echo "\n===== 4. TRACEABILITY STATUS ====="
grep -n -A5 -B3
'FIN-15|TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_00
1' FUNCTION_TEST_TRACEABILITY.txt SPRINT_1_TEST_EXECUTION_STATUS.txt

echo "\n===== 5. CHECK PATCH FORMATTING ====="
git diff --check
===== 1. WORKING TREE =====
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js

===== 2. AUTHORIZATION ENDPOINT =====

===== 3. EXISTING AUTHORIZATION TESTS =====

===== 4. TRACEABILITY STATUS =====

===== 5. CHECK PATCH FORMATTING =====
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

echo "===== 1. AUTHORIZATION IMPLEMENTATION ====="
grep -n -E -A55 -B12 'platform_admin_capabilities|authorization/capabilities|def
require_permission' apps/api/app/main.py
```

```
echo "\n===== 2. AUTHORIZATION TESTS ====="
grep -n -E -A70 -B8
'test_platform_permission_is_resolved_from_database_role_and_session|database_out
ages_return_controlled_error|permission' apps/api/tests/test_identity_constraints.py
apps/api/tests/test_auth_unit.py

echo "\n===== 3. FIN-15 TRACEABILITY ====="
grep -n -E -A5 -B3
'FIN-15|TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_00
1' FUNCTION_TEST_TRACEABILITY.txt SPRINT_1_TEST_EXECUTION_STATUS.txt

echo "\n===== 4. API DESIGN CONTRACT ====="
grep -n -E -A12 -B5 'authorization/capabilities|authorization_unavailable|canonical
request_id|permission revoked'
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contrac
t.md

echo "\n===== 5. PATCH VALIDATION ====="
git diff --check
===== 1. AUTHORIZATION IMPLEMENTATION =====
97-            cur.execute(
98-                "UPDATE auth_sessions SET last_seen_at = %s WHERE
refresh_token_hash = %s",
99-                (datetime.now(UTC), token_digest(session_token)),
100-            )
101-            return user
102-    except psycopg.Error as exc:
103-        raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
104-
105-
106-CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]
107-
108-
109:def require_permission(permission_key: str):
110-    """Build a deny-by-default backend permission dependency."""
111-    def dependency(user: CurrentUser) -> dict[str, Any]:
112-        if permission_key not in user.get("permissions", []):
113-            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN,
detail="Permission denied")
```

```
114-        return user
115-
116-    return dependency
117-
118-
119-@app.post("/auth/login", response_model=UserView)
120-def login(payload: LoginRequest, request: Request, response: Response) ->
UserView:
121-    _check_origin(request)
122-    email = payload.email.strip().lower()
123-    try:
124-        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
125-            cur.execute(
126-                """SELECT user_id, email, display_name, password_hash
127-                   FROM users WHERE lower(email) = %s AND account_status = 'active'
128-                     AND deleted_at IS NULL""",
129-                (email,),
130-            )
131-            user = cur.fetchone()
132-            if not user or not user["password_hash"]:
133-                verify_password(DUMMY_PASSWORD_HASH, payload.password)
134-                raise HTTPException(status_code=401,
detail=GENERIC_LOGIN_ERROR)
135-            if not verify_password(user["password_hash"], payload.password):
136-                raise HTTPException(status_code=401,
detail=GENERIC_LOGIN_ERROR)
137-            token, digest = new_session_token()
138-            expires_at = session_expiry(_ttl_minutes())
139-            cur.execute(
140-                """INSERT INTO auth_sessions (user_id, refresh_token_hash,
expires_at)
141-                   VALUES (%s, %s, %s)""",
142-                (user["user_id"], digest, expires_at),
143-            )
144-            cur.execute("UPDATE users SET last_login_at = %s, updated_at = %s
WHERE user_id = %s",
145-                        (datetime.now(UTC), datetime.now(UTC), user["user_id"]))
146-        response.set_cookie(
147-            SESSION_COOKIE,
148-            token,
```

```
149-            httponly=True,
150-            secure=_secure_cookie(),
151-            samesite="lax",
152-            max_age=_ttl_minutes() * 60,
153-            path="/",
154-        )
155-        return UserView(user_id=user["user_id"], email=user["email"],
display_name=user["display_name"])
156-    except psycopg.Error as exc:
157-        raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
158-
159-
160-@app.post("/auth/logout", status_code=204)
161-def logout(request: Request, response: Response,
162-           session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] =
None) -> Response:
163-    _check_origin(request)
164-    if session_token:
--
172-        except psycopg.Error as exc:
173-            raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
174-    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
175-    response.status_code = status.HTTP_204_NO_CONTENT
176-    return response
177-
178-
179-@app.get("/auth/me", response_model=UserView)
180-def who_am_i(user: CurrentUser) -> UserView:
181-    return UserView(**user)
182-
183-
184:@app.get("/api/v1/admin/authorization/capabilities")
185:def platform_admin_capabilities(
186-    request: Request,
187-    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
188-) -> dict[str, Any]:
```

```
189-    """Return the authenticated caller's database-backed platform capabilities."""
190-    supplied_request_id = request.headers.get("request_id", "").strip()
191-    if supplied_request_id and (
192-        len(supplied_request_id) > 128
193-        or any(ord(char) < 32 or ord(char) == 127 for char in supplied_request_id)
194-    ):
195-        raise HTTPException(status_code=400, detail="Invalid request_id")
196-
197-    request_id = supplied_request_id or f"req_{secrets.token_urlsafe(12)}"
198-    permissions = sorted(set(_authorized.get("permissions", [])))
199-    capabilities = (
200-        ["inspect_authorization_policy"]
201-        if "platform.admin" in permissions
202-        else []
203-    )
204-
205-    return {
206-        "data": {
207-            "subject": {
208-                "user_id": str(_authorized["user_id"]),
209-                "platform_role_code": _authorized.get("role_key"),
210-            },
211-            "effective_permissions": permissions,
212-            "capabilities": capabilities,
213-            "policy_version": "sprint-1-platform-rbac-v1",
214-        },
215-        "request_id": request_id,
216-        "correlation_id": request_id,
217-    }

===== 2. AUTHORIZATION TESTS =====
apps/api/tests/test_identity_constraints.py-3-from uuid import uuid4
apps/api/tests/test_identity_constraints.py-4-
apps/api/tests/test_identity_constraints.py-5-import psycopg
apps/api/tests/test_identity_constraints.py-6-import pytest
apps/api/tests/test_identity_constraints.py-7-from fastapi.testclient import TestClient
apps/api/tests/test_identity_constraints.py-8-
apps/api/tests/test_identity_constraints.py-9-from app.auth import new_session_token,
session_expiry
apps/api/tests/test_identity_constraints.py-10-from app.database import connect
```

```
apps/api/tests/test_identity_constraints.py:11:from app.main import SESSION_COOKIE,
app, require_permission
apps/api/tests/test_identity_constraints.py-12-
apps/api/tests/test_identity_constraints.py-13-
apps/api/tests/test_identity_constraints.py-14-def
test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
apps/api/tests/test_identity_constraints.py-15-    email =
f"constraint-{uuid4().hex}@example.com"
apps/api/tests/test_identity_constraints.py-16-    with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-17-        cur.execute(
apps/api/tests/test_identity_constraints.py-18-            "INSERT INTO users (email,
password_hash, display_name) VALUES (%s, %s, %s) RETURNING user_id",
apps/api/tests/test_identity_constraints.py-19-            (email, "synthetic-hash",
"Synthetic Constraint Test"),
apps/api/tests/test_identity_constraints.py-20-        )
apps/api/tests/test_identity_constraints.py-21-        user_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-22-
apps/api/tests/test_identity_constraints.py-23-    try:
apps/api/tests/test_identity_constraints.py-24-        with
pytest.raises(psycopg.errors.UniqueViolation):
apps/api/tests/test_identity_constraints.py-25-            with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-26-                cur.execute(
apps/api/tests/test_identity_constraints.py-27-                    "INSERT INTO users (email,
password_hash, display_name) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py-28-                    (email.upper(),
"synthetic-hash", "Duplicate Synthetic Test"),
apps/api/tests/test_identity_constraints.py-29-                )
apps/api/tests/test_identity_constraints.py-30-
apps/api/tests/test_identity_constraints.py-31-        _, digest = new_session_token()
apps/api/tests/test_identity_constraints.py-32-        with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-33-            cur.execute(
apps/api/tests/test_identity_constraints.py-34-                "INSERT INTO auth_sessions
(user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py-35-                (user_id, digest,
session_expiry(5)),
apps/api/tests/test_identity_constraints.py-36-            )
```

```
apps/api/tests/test_identity_constraints.py-37-            cur.execute("DELETE FROM
users WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-38-            cur.execute("SELECT count(*)
FROM auth_sessions WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-39-            assert cur.fetchone()[0] == 0
apps/api/tests/test_identity_constraints.py-40-    finally:
apps/api/tests/test_identity_constraints.py-41-        with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-42-            cur.execute("DELETE FROM
users WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-43-
apps/api/tests/test_identity_constraints.py-44-
apps/api/tests/test_identity_constraints.py:45:def
test_platform_permission_is_resolved_from_database_role_and_session():
apps/api/tests/test_identity_constraints.py-46-    admin_email =
f"platform-admin-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py-47-    user_email =
f"unprivileged-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py-48-    tokens = []
apps/api/tests/test_identity_constraints.py-49-    with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-50-        cur.execute("SELECT role_id FROM
roles WHERE role_key = 'platform_admin' AND scope = 'platform'")
apps/api/tests/test_identity_constraints.py-51-        admin_role_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-52-        cur.execute(
apps/api/tests/test_identity_constraints.py-53-            "INSERT INTO users (email,
display_name, platform_role_id) VALUES (%s, %s, %s) RETURNING user_id",
apps/api/tests/test_identity_constraints.py-54-            (admin_email, "Synthetic Platform
Admin", admin_role_id),
apps/api/tests/test_identity_constraints.py-55-        )
apps/api/tests/test_identity_constraints.py-56-        admin_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-57-        cur.execute(
apps/api/tests/test_identity_constraints.py-58-            "INSERT INTO users (email,
display_name) VALUES (%s, %s) RETURNING user_id",
apps/api/tests/test_identity_constraints.py-59-            (user_email, "Synthetic Standard
User"),
apps/api/tests/test_identity_constraints.py-60-        )
apps/api/tests/test_identity_constraints.py-61-        user_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-62-        for owner_id in (admin_id, user_id):
```

```
apps/api/tests/test_identity_constraints.py-63-            token, digest =
new_session_token()
apps/api/tests/test_identity_constraints.py-64-            tokens.append(token)
apps/api/tests/test_identity_constraints.py-65-            cur.execute(
apps/api/tests/test_identity_constraints.py-66-                "INSERT INTO auth_sessions
(user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py-67-                (owner_id, digest,
session_expiry(5)),
apps/api/tests/test_identity_constraints.py-68-            )
apps/api/tests/test_identity_constraints.py-69-
apps/api/tests/test_identity_constraints.py-70-    try:
apps/api/tests/test_identity_constraints.py-71-        with TestClient(app) as client:
apps/api/tests/test_identity_constraints.py-72-            anonymous =
client.get("/api/v1/admin/authorization/capabilities")
apps/api/tests/test_identity_constraints.py-73-            assert anonymous.status_code ==
401
apps/api/tests/test_identity_constraints.py-74-            assert anonymous.json() ==
{"detail": "Authentication required"}
apps/api/tests/test_identity_constraints.py-75-
apps/api/tests/test_identity_constraints.py-76-            invalid_session = client.get(
apps/api/tests/test_identity_constraints.py-77-
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py-78-                cookies={SESSION_COOKIE:
"invalid-session-token"},
apps/api/tests/test_identity_constraints.py-79-            )
apps/api/tests/test_identity_constraints.py-80-            assert
invalid_session.status_code == 401
apps/api/tests/test_identity_constraints.py-81-
apps/api/tests/test_identity_constraints.py-82-            allowed = client.get(
apps/api/tests/test_identity_constraints.py-83-
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py-84-                cookies={SESSION_COOKIE:
tokens[0]},
apps/api/tests/test_identity_constraints.py-85-            )
apps/api/tests/test_identity_constraints.py-86-            assert allowed.status_code ==
200
apps/api/tests/test_identity_constraints.py-87-            body = allowed.json()
apps/api/tests/test_identity_constraints.py-88-            assert
body["data"]["subject"]["user_id"] == str(admin_id)
```

```
apps/api/tests/test_identity_constraints.py-89-            assert
body["data"]["subject"]["platform_role_code"] == "platform_admin"
apps/api/tests/test_identity_constraints.py:90:            assert
body["data"]["effective_permissions"] == ["platform.admin"]
apps/api/tests/test_identity_constraints.py-91-            assert body["data"]["capabilities"]
== ["inspect_authorization_policy"]
apps/api/tests/test_identity_constraints.py-92-            assert
body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
apps/api/tests/test_identity_constraints.py-93-            assert
body["request_id"].startswith("req_")
apps/api/tests/test_identity_constraints.py-94-            assert body["correlation_id"] ==
body["request_id"]
apps/api/tests/test_identity_constraints.py-95-
apps/api/tests/test_identity_constraints.py-96-            denied = client.get(
apps/api/tests/test_identity_constraints.py-97-
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py-98-                cookies={SESSION_COOKIE:
tokens[1]},
apps/api/tests/test_identity_constraints.py-99-                headers={"X-Role":
"platform_admin"},
apps/api/tests/test_identity_constraints.py-100-            )
apps/api/tests/test_identity_constraints.py-101-            assert denied.status_code ==
403
apps/api/tests/test_identity_constraints.py-102-            assert denied.json() == {"detail":
"Permission denied"}
apps/api/tests/test_identity_constraints.py-103-    finally:
apps/api/tests/test_identity_constraints.py-104-        with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-105-            cur.execute("DELETE FROM
users WHERE user_id IN (%s, %s)", (admin_id, user_id))
apps/api/tests/test_identity_constraints.py-106-
apps/api/tests/test_identity_constraints.py-107-
apps/api/tests/test_identity_constraints.py-108-def
test_platform_role_assignment_rejects_workspace_scoped_roles():
apps/api/tests/test_identity_constraints.py-109-    email =
f"wrong-scope-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py-110-    with connect() as conn, conn.cursor()
as cur:
apps/api/tests/test_identity_constraints.py-111-        cur.execute(
```

```
apps/api/tests/test_identity_constraints.py-112-            "INSERT INTO roles (role_key,
display_name, scope) VALUES (%s, %s, 'workspace') RETURNING role_id",
apps/api/tests/test_identity_constraints.py-113-            (f"ws-{uuid4().hex[:12]}",
"Synthetic Workspace Role"),
apps/api/tests/test_identity_constraints.py-114-        )
apps/api/tests/test_identity_constraints.py-115-        workspace_role_id =
cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-116-        cur.execute(
apps/api/tests/test_identity_constraints.py-117-            "INSERT INTO users (email,
display_name) VALUES (%s, 'Synthetic Scope User') RETURNING user_id",
apps/api/tests/test_identity_constraints.py-118-            (email,),
apps/api/tests/test_identity_constraints.py-119-        )
apps/api/tests/test_identity_constraints.py-120-        user_id = cur.fetchone()[0]
apps/api/tests/test_identity_constraints.py-121-    try:
apps/api/tests/test_identity_constraints.py-122-        with
pytest.raises(psycopg.errors.CheckViolation):
apps/api/tests/test_identity_constraints.py-123-            with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-124-                cur.execute("UPDATE users
SET platform_role_id = %s WHERE user_id = %s", (workspace_role_id, user_id))
apps/api/tests/test_identity_constraints.py-125-    finally:
apps/api/tests/test_identity_constraints.py-126-        with connect() as conn,
conn.cursor() as cur:
apps/api/tests/test_identity_constraints.py-127-            cur.execute("DELETE FROM
users WHERE user_id = %s", (user_id,))
apps/api/tests/test_identity_constraints.py-128-            cur.execute("DELETE FROM
roles WHERE role_id = %s", (workspace_role_id,))
--
apps/api/tests/test_auth_unit.py-89-    response = TestClient(app).get("/auth/me")
apps/api/tests/test_auth_unit.py-90-
apps/api/tests/test_auth_unit.py-91-    assert response.status_code == 401
apps/api/tests/test_auth_unit.py-92-    assert response.json() == {"detail":
"Authentication required"}
apps/api/tests/test_auth_unit.py-93-
apps/api/tests/test_auth_unit.py-94-
apps/api/tests/test_auth_unit.py-95-@pytest.mark.parametrize(
apps/api/tests/test_auth_unit.py-96-    ("user", "expected_status"),
apps/api/tests/test_auth_unit.py:97:    [({"permissions": ["platform.admin"]}, 200),
({"permissions": []}, 403), ({}, 403)],
apps/api/tests/test_auth_unit.py-98-)
```

```
apps/api/tests/test_auth_unit.py:99:def
test_permission_dependency_allows_only_explicit_permission(user, expected_status):
apps/api/tests/test_auth_unit.py-100-    from fastapi import Depends, FastAPI
apps/api/tests/test_auth_unit.py-101-    from fastapi.testclient import TestClient
apps/api/tests/test_auth_unit.py-102-
apps/api/tests/test_auth_unit.py-103-    import app.main as main
apps/api/tests/test_auth_unit.py-104-
apps/api/tests/test_auth_unit.py-105-    protected_app = FastAPI()
apps/api/tests/test_auth_unit.py-106-
protected_app.dependency_overrides[main.get_current_user] = lambda: user
apps/api/tests/test_auth_unit.py-107-    protected_app.add_api_route(
apps/api/tests/test_auth_unit.py-108-        "/platform-admin",
apps/api/tests/test_auth_unit.py:109:        lambda
_authorized=Depends(main.require_permission("platform.admin")): {"allowed": True},
apps/api/tests/test_auth_unit.py-110-    )
apps/api/tests/test_auth_unit.py-111-
apps/api/tests/test_auth_unit.py-112-    response =
TestClient(protected_app).get("/platform-admin")
apps/api/tests/test_auth_unit.py-113-    assert response.status_code ==
expected_status
apps/api/tests/test_auth_unit.py-114-    if expected_status == 403:
apps/api/tests/test_auth_unit.py-115-        assert response.json() == {"detail":
"Permission denied"}
apps/api/tests/test_auth_unit.py-116-
apps/api/tests/test_auth_unit.py-117-
apps/api/tests/test_auth_unit.py:118:def
test_permission_dependency_ignores_client_supplied_role_header():
apps/api/tests/test_auth_unit.py-119-    from fastapi import Depends, FastAPI
apps/api/tests/test_auth_unit.py-120-    from fastapi.testclient import TestClient
apps/api/tests/test_auth_unit.py-121-
apps/api/tests/test_auth_unit.py-122-    import app.main as main
apps/api/tests/test_auth_unit.py-123-
apps/api/tests/test_auth_unit.py-124-    protected_app = FastAPI()
apps/api/tests/test_auth_unit.py:125:
protected_app.dependency_overrides[main.get_current_user] = lambda: {"permissions":
[]}
apps/api/tests/test_auth_unit.py-126-    protected_app.add_api_route(
apps/api/tests/test_auth_unit.py-127-        "/platform-admin",
apps/api/tests/test_auth_unit.py:128:        lambda
_authorized=Depends(main.require_permission("platform.admin")): {"allowed": True},
```

```
apps/api/tests/test_auth_unit.py-129-    )
apps/api/tests/test_auth_unit.py-130-
apps/api/tests/test_auth_unit.py-131-    response =
TestClient(protected_app).get("/platform-admin", headers={"X-Role": "platform_admin"})
apps/api/tests/test_auth_unit.py-132-    assert response.status_code == 403
apps/api/tests/test_auth_unit.py-133-
apps/api/tests/test_auth_unit.py-134-
apps/api/tests/test_auth_unit.py-135-@pytest.mark.parametrize(
apps/api/tests/test_auth_unit.py-136-    ("method", "path", "kwargs"),
apps/api/tests/test_auth_unit.py-137-    [
apps/api/tests/test_auth_unit.py-138-        ("get", "/auth/me", {"cookies":
{"finsight_session": "synthetic-token"}}),
apps/api/tests/test_auth_unit.py-139-        ("post", "/auth/logout", {"cookies":
{"finsight_session": "synthetic-token"}}),
apps/api/tests/test_auth_unit.py-140-    ],
apps/api/tests/test_auth_unit.py-141-)
apps/api/tests/test_auth_unit.py:142:def
test_session_database_outages_return_controlled_error(monkeypatch, method, path,
kwargs):
apps/api/tests/test_auth_unit.py-143-    import app.main as main
apps/api/tests/test_auth_unit.py-144-    import psycopg
apps/api/tests/test_auth_unit.py-145-
apps/api/tests/test_auth_unit.py-146-    def unavailable_database():
apps/api/tests/test_auth_unit.py-147-        raise psycopg.OperationalError("synthetic
database detail")
apps/api/tests/test_auth_unit.py-148-
apps/api/tests/test_auth_unit.py-149-    monkeypatch.setattr(main, "connect",
unavailable_database)
apps/api/tests/test_auth_unit.py-150-    response = getattr(TestClient(app),
method)(path, **kwargs)
apps/api/tests/test_auth_unit.py-151-
apps/api/tests/test_auth_unit.py-152-    assert response.status_code == 503
apps/api/tests/test_auth_unit.py-153-    assert response.json() == {"detail":
"Authentication service unavailable"}
apps/api/tests/test_auth_unit.py-154-    assert "synthetic database detail" not in
response.text
apps/api/tests/test_auth_unit.py-155-
apps/api/tests/test_auth_unit.py-156-
apps/api/tests/test_auth_unit.py-157-def
test_database_configuration_is_required(monkeypatch):
```

```
apps/api/tests/test_auth_unit.py-158-    import app.database as database
apps/api/tests/test_auth_unit.py-159-
apps/api/tests/test_auth_unit.py-160-    monkeypatch.delenv("DATABASE_URL",
raising=False)
apps/api/tests/test_auth_unit.py-161-
apps/api/tests/test_auth_unit.py-162-    with pytest.raises(RuntimeError,
match="DATABASE_URL is required"):
apps/api/tests/test_auth_unit.py-163-        database.connect()
apps/api/tests/test_auth_unit.py-164-
apps/api/tests/test_auth_unit.py-165-
apps/api/tests/test_auth_unit.py-166-def
test_login_rejects_invalid_input_before_database_access():
apps/api/tests/test_auth_unit.py-167-    response = TestClient(app).post(
apps/api/tests/test_auth_unit.py-168-        "/auth/login",
apps/api/tests/test_auth_unit.py-169-        json={"email": "not-an-email", "password": ""},
apps/api/tests/test_auth_unit.py-170-    )
apps/api/tests/test_auth_unit.py-171-
apps/api/tests/test_auth_unit.py-172-    assert response.status_code == 422
apps/api/tests/test_auth_unit.py-173-    assert "synthetic database detail" not in
response.text
apps/api/tests/test_auth_unit.py-174-
apps/api/tests/test_auth_unit.py-175-
apps/api/tests/test_auth_unit.py-176-@pytest.mark.parametrize("configured", ["1",
"true", "yes"])
apps/api/tests/test_auth_unit.py-177-def
test_secure_cookie_accepts_explicit_secure_values(monkeypatch, configured: str):
apps/api/tests/test_auth_unit.py-178-    monkeypatch.setenv("COOKIE_SECURE",
configured)
apps/api/tests/test_auth_unit.py-179-
apps/api/tests/test_auth_unit.py-180-    assert _secure_cookie()
apps/api/tests/test_auth_unit.py-181-
apps/api/tests/test_auth_unit.py-182-
apps/api/tests/test_auth_unit.py-183-@pytest.mark.parametrize("configured", ["0",
"false", "no", "invalid"])
apps/api/tests/test_auth_unit.py-184-def
test_secure_cookie_treats_other_explicit_values_as_insecure(monkeypatch,
configured: str):
apps/api/tests/test_auth_unit.py-185-    monkeypatch.setenv("COOKIE_SECURE",
configured)
apps/api/tests/test_auth_unit.py-186-
```

apps/api/tests/test_auth_unit.py-187-   assert not _secure_cookie()
apps/api/tests/test_auth_unit.py-188-
apps/api/tests/test_auth_unit.py-189-
apps/api/tests/test_auth_unit.py-190-@pytest.mark.parametrize(("app_env", "expected"), [("production", True), ("development", False), ("test", False)])
apps/api/tests/test_auth_unit.py-191-def test_secure_cookie_defaults_by_environment(monkeypatch, app_env: str, expected: bool):
apps/api/tests/test_auth_unit.py-192-   monkeypatch.delenv("COOKIE_SECURE", raising=False)
apps/api/tests/test_auth_unit.py-193-   monkeypatch.setenv("APP_ENV", app_env)
apps/api/tests/test_auth_unit.py-194-
apps/api/tests/test_auth_unit.py-195-   assert _secure_cookie() is expected

===== 3. FIN-15 TRACEABILITY =====
FUNCTION_TEST_TRACEABILITY.txt-1-FinSight AI — Function/Test Traceability
FUNCTION_TEST_TRACEABILITY.txt-2-
FUNCTION_TEST_TRACEABILITY.txt:3:FIN-15 / FS-01-02 — platform authorization capability endpoint
FUNCTION_TEST_TRACEABILITY.txt-4-Function: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-5-Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
FUNCTION_TEST_TRACEABILITY.txt-6-Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
FUNCTION_TEST_TRACEABILITY.txt:7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt-8-Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mapped tests and confirming the expected behavior.
FUNCTION_TEST_TRACEABILITY.txt-9-
FUNCTION_TEST_TRACEABILITY.txt:10:FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
FUNCTION_TEST_TRACEABILITY.txt-11-Run ID: 20261020_141030
FUNCTION_TEST_TRACEABILITY.txt-12-Endpoint: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-13-
FUNCTION_TEST_TRACEABILITY.txt-14-Observed execution:
FUNCTION_TEST_TRACEABILITY.txt-15-- tests/test_identity_constraints.py: 3 passed, 4 warnings.

FUNCTION_TEST_TRACEABILITY.txt-16-- Full API suite: 55 passed, 10 warnings.
FUNCTION_TEST_TRACEABILITY.txt-17-- Both pytest commands exited with code 0.
FUNCTION_TEST_TRACEABILITY.txt-18-- Evidence:
FUNCTION_TEST_TRACEABILITY.txt:19:
test-results/FIN-15/20261020_141030_identity_authorization.log
FUNCTION_TEST_TRACEABILITY.txt:20:
test-results/FIN-15/20261020_141030_full_api_suite.log
FUNCTION_TEST_TRACEABILITY.txt:21:
test-results/FIN-15/run_20261020_141030_summary.txt
FUNCTION_TEST_TRACEABILITY.txt-22-
FUNCTION_TEST_TRACEABILITY.txt-23-Case-status guidance:
FUNCTION_TEST_TRACEABILITY.txt:24:- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt-25- test suite passed, but broader acceptance criteria must also be checked.
FUNCTION_TEST_TRACEABILITY.txt:26:- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
FUNCTION_TEST_TRACEABILITY.txt-27- integration test; this does not imply missing model/provider operations exist.
FUNCTION_TEST_TRACEABILITY.txt:28:- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
FUNCTION_TEST_TRACEABILITY.txt-29- it was not separately rerun under run ID 20261020_141030.
FUNCTION_TEST_TRACEABILITY.txt:30:- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
FUNCTION_TEST_TRACEABILITY.txt-31- authorization are outside the approved platform-only scope.
FUNCTION_TEST_TRACEABILITY.txt:32:- TC_SYS_001: not established by the API suite alone; broader system acceptance remains
FUNCTION_TEST_TRACEABILITY.txt-33- to be verified.
FUNCTION_TEST_TRACEABILITY.txt-34-
FUNCTION_TEST_TRACEABILITY.txt-35-Do not infer full story completion from a green test suite. Historical entries are
FUNCTION_TEST_TRACEABILITY.txt-36-retained, and this addendum records the latest observed execution.
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-48-Evidence: test `test_public_registration_is_not_available`; `apps/api/app/provision_user.py`.
SPRINT_1_TEST_EXECUTION_STATUS.txt-49-Remaining: implement/verify the approved administrator-controlled onboarding workflow in its authorized scope.

SPRINT_1_TEST_EXECUTION_STATUS.txt-50-
SPRINT_1_TEST_EXECUTION_STATUS.txt:51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
SPRINT_1_TEST_EXECUTION_STATUS.txt-52-Status: PASS (session-expiry behavior exercised as a FIN-13 acceptance check; Jira scope remains unchanged)
SPRINT_1_TEST_EXECUTION_STATUS.txt-53-Actual result: A session with stale `last_seen_at` was rejected by the protected endpoint. TTL bounds are validated and expiry uses `SESSION_TTL_MINUTES`.
SPRINT_1_TEST_EXECUTION_STATUS.txt-54-Evidence: test `test_expired_session_is_rejected` in the command above.
SPRINT_1_TEST_EXECUTION_STATUS.txt-55-
SPRINT_1_TEST_EXECUTION_STATUS.txt-56-TC_AUTHN_006 — Verify passwords are not stored in plaintext
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-75-TC_DB_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Existing identity migration applied to a fresh disposable PostgreSQL database; case-insensitive email uniqueness and session cascade verified. Full case remains blocked because only identity/session schema exists; api_credentials, audit_events, execution_runs, service_health_checks and migration-runner repeatability arenot implemented | Tester/owner: Codex | Evidence: apps/api/migrations/0001_auth_identity.sql; apps/api/tests/test_identity_constraints.py; IMPLEMENTATION_STATUS.txt | Linked defect: Missing broader Sprint 1 schemas and migration runner
SPRINT_1_TEST_EXECUTION_STATUS.txt-76-TC_COV_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: CI-equivalent unit (37) and PostgreSQL integration (10) suites passed; cumulative backend line coverage 156/156 (100%) and branch coverage 28/28 (100%). Provisioning CLI, configuration and authentication/session database failure paths were tested. Frontend source coverage is not supported by current Playwright instrumentation; remote artifact retention remains unverified. | Tester/owner: Codex | Evidence: coverage.xml (ignored local report); htmlcov/index.html (ignored local report); /tmp/finsight-coverage.json; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py; apps/api/tests/test_provision_user.py; IMPLEMENTATION_STATUS.txt | Linked defect: GitHub artifact confirmation / frontend source instrumentation decision
SPRINT_1_TEST_EXECUTION_STATUS.txt-77-TC_INT_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Authentication/session persistence tested against PostgreSQL; configuration versioning, audit persistence, and authorized/denied configuration update flows are absent from the current implementation | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py;

apps/api/tests/test_identity_constraints.py; IMPLEMENTATION_STATUS.txt | Linked defect: FIN-08/FIN-09 capabilities not implemented
SPRINT_1_TEST_EXECUTION_STATUS.txt:78:TC_SYS_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Browser smoke verified current sign-in/session/logout path against live frontend, FastAPI, and PostgreSQL. Full planned dashboard/settings, dependency health, Ollama available/unavailable, and correlation-log workflow cannot run because those components are not implemented | Tester/owner: Codex | Evidence: apps/web/tests/e2e/auth.spec.js; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: Current application implements auth starter only
SPRINT_1_TEST_EXECUTION_STATUS.txt-79-TC_SEC_001 | Status: BLOCKED | Execution date: 2026-10-19 | Actual result: Local dependency audits and Bandit ran. Before remediation npm audit found 3 vulnerable dependency nodes (1 critical, 2 high); pip-audit found 14 advisory records across 3 packages. After targeted updates npm audit and pip-audit reported zero known vulnerabilities. Security job added to CI and release-package depends on it; workflow parsed locally but no GitHub runner execution was available. | Tester/owner: Codex | Evidence: /tmp/finsight-npm-audit-before.json; /tmp/finsight-npm-audit-after.json; /tmp/finsight-pip-audit.json; /tmp/finsight-pip-audit-after.json; .github/workflows/ci.yml; IMPLEMENTATION_STATUS.txt | Linked defect: GitHub Actions run required
SPRINT_1_TEST_EXECUTION_STATUS.txt-80-TC_SEC_002 | Status: BLOCKED | Execution date: 2026-10-19 | Actual result: Secret-pattern scan of application/configuration paths reported no matches. Upload validation and prompt-injection tests could not be exercised because file upload and RAG/context construction are not implemented in this repository; no related feature or tests were added. | Tester/owner: Codex | Evidence: local source/config credential-pattern scan; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt | Linked defect: Upload/RAG implementation required in authorized later stories
SPRINT_1_TEST_EXECUTION_STATUS.txt-81-TC_DOC_001 | Status: PASS | Execution date: 2026-10-19 | Actual result: Reviewed documented current endpoints and schemas against generated FastAPI OpenAPI; representative invalid login returned 422 with `detail`, and unauthenticated `/auth/me` returned 401 with the documented generic detail. Architecture and compatibility notes distinguish current implementation from target features. | Tester/owner: Codex | Evidence: docs/architecture/README.md; docs/architecture/adr/; command output recorded in IMPLEMENTATION_STATUS.txt | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-82-TC_TRACE_001 | Status: PASS | Execution date: 2026-10-19 | Actual result: All 23 Sprint 1 plan aliases have verified Jira mappings; 22 have explicit SRS requirement IDs and FS-11-09/FIN-80 is explicitly recorded as a process story with no direct SRS ID; all 54 source test cases map to a

Sprint 1 story; Release 2 labels remain intact; unmapped requirements and catalog extras are reported explicitly. | Tester/owner: Codex | Evidence: docs/requirements/traceability-matrix.md; docs/requirements/traceability-requirements.csv; docs/requirements/traceability-stories.csv; scripts/validate_traceability.py | Linkeddefect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-83-TC_MGMT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-91-TC_AUTHN_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Logout revocation and replay rejection verified | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-92-TC_AUTHN_004 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Password recovery is required while password authentication is enabled; implementation and delivery approach await user decision | Tester/owner: Codex | Evidence: conversation.txt Q-005; SRS FR-P1-03 | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-93-TC_AUTHN_005 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Public registration is absent, but admin onboarding workflow is incomplete | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:94:TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:95:TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-97-TC_AUTHSEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-98-TC_AUTHSEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-99-TC_AUTHSEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-100-TC_AUTHSEC_004 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

SPRINT_1_TEST_EXECUTION_STATUS.txt-101-TC_AUTHN_006 | Status: PASS | Execution date: 2026-10-18 | Actual result: Disposable synthetic database dump contained password/session digests; plaintext password/token absent;API test checked captured logs/stdout/stderr and response | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py; disposable scan summarized in IMPLEMENTATION_STATUS.txt (dump removed) | Linked defect: —
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-112-TC_CRED_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-113-TC_CRED_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-114-TC_PRIV_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:115:TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-116-TC_EXEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-117-TC_EXEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-118-TC_EXEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-119-TC_DASH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-120-TC_DASH_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-121-TC_INT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt:122:TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-123-TC_BOUNDARY_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
SPRINT_1_TEST_EXECUTION_STATUS.txt-124-
SPRINT_1_TEST_EXECUTION_STATUS.txt-125-Additional test evidence — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt-126-- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q tests/test_identity_constraints.py
SPRINT_1_TEST_EXECUTION_STATUS.txt-127-- Result: 3 passed, 0 failed, 3 warnings.

--
SPRINT_1_TEST_EXECUTION_STATUS.txt-132-- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
SPRINT_1_TEST_EXECUTION_STATUS.txt-133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
SPRINT_1_TEST_EXECUTION_STATUS.txt-134-
SPRINT_1_TEST_EXECUTION_STATUS.txt:135:FIN-15 route-level authorization test update — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt:136:- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
SPRINT_1_TEST_EXECUTION_STATUS.txt-137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
SPRINT_1_TEST_EXECUTION_STATUS.txt-138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
SPRINT_1_TEST_EXECUTION_STATUS.txt-139-
SPRINT_1_TEST_EXECUTION_STATUS.txt:140:FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)
SPRINT_1_TEST_EXECUTION_STATUS.txt-141-Run ID: 20261020_141030
SPRINT_1_TEST_EXECUTION_STATUS.txt-142-Python: 3.14.6
SPRINT_1_TEST_EXECUTION_STATUS.txt-143-Database: finsight_test
SPRINT_1_TEST_EXECUTION_STATUS.txt-144-Recorded Git revision: 64f2637
SPRINT_1_TEST_EXECUTION_STATUS.txt-145-
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-147-- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-148-- Full API suite: 55 passed, 10 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-149-- Evidence files:
SPRINT_1_TEST_EXECUTION_STATUS.txt:150:
test-results/FIN-15/20261020_141030_identity_authorization.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:151:
test-results/FIN-15/20261020_141030_full_api_suite.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:152:
test-results/FIN-15/run_20261020_141030_summary.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt-153-
SPRINT_1_TEST_EXECUTION_STATUS.txt-154-These results supersede earlier NOT RUN notes for the test execution performed

SPRINT_1_TEST_EXECUTION_STATUS.txt-155-in this run. They do not establish that every mapped test-plan case or the entire SPRINT_1_TEST_EXECUTION_STATUS.txt:156:FIN-15 story is complete. Workspace-level authorization remains deferred.

===== 4. API DESIGN CONTRACT =====
6-**Source hierarchy:** Original SRS → canonical SQL/schema and ERD → 72-story Jira backlog/acceptance criteria → four-sprint allocation and Sprint 1 test plan → component diagrams and this contract. This document proposes API contracts; it does not upgrade source implementation/test statuses or approve requirement scope changes.
7-
8-## Executive decision and guardrails
9-
10-
11:**Decision A is recommended and incorporated.** Implement one minimal platform-admin-only authorization/capability endpoint in the actual FastAPI app: `GET /api/v1/admin/authorization/capabilities`, protected by the real `require_permission("platform.admin")` dependency. It must return only the caller's effective permission/capability summary and policy version, not platform user lists or unrelated business resources. The route is a direct test seam for SRS backend RBAC (FR-P1-05/06/07) and Sprint 1 story FS-01-02 / Jira FIN-15; it is not a substitute for implementing authorization across all protected endpoints.
12-
13-**Release 1 boundary:** historical/read-only financial research and calculations; no broker order, paper-trading execution, broker connection, order/fill/approval or live trading paths in the Release 1 OpenAPI file. FS-07-04 / FIN-54 and FS-08-04 / FIN-60 remain Release 2 only. Do not apply the optional 15-table trading DDL. Internal portfolio ledger transactions are not broker orders and must be explicitly described as such.
14-
15-**Truthfulness:** the schema reference contains 158 core and 15 optional tables, but is a target-state design; it is not evidence those migrations have been applied. Source RTM records only a scoped subset of behaviors implemented and verified. This contract does not claim that proposed domains/routes exist in the current runtime.
16-
17-## 1. Source baseline, known runtime and open gaps
18-
19-
20-| Area | Source-grounded observation | API-design consequence |
21-| --- | --- | --- |

22-| Runtime evidenced in addendum | Next.js sign-in/runtime API-origin endpoint; FastAPI login/current-user/logout; PostgreSQL identity/session persistence through a versioned identity migration; CI/test/release-package workflow. | Preserve working auth behavior. Inspect actual app route decorators and cookie/session names before path migration; do not copy the examples here blindly. |
23-| Known gaps | Password recovery, invitation flow, MFA, role administration/enforcement, auth audit subsystem, health endpoint, document/RAG, market providers, analytics and workers are recorded absent. | These are target contracts, not existing functionality. Build tests and versioned migrations before marking stories done. |
--
89- "request_id": "req_01J...",
90- "correlation_id": "corr_01J..."
91-}
92-```
93-
94:Error codes must be stable, client-safe machine values. Suggested codes: `invalid_credentials`, `session_expired`, `permission_denied`, `resource_not_found`, `validation_error`, `conflict`, `idempotency_conflict`,`rate_limited`, `authorization_unavailable`, `dependency_unavailable`, `processing_failed`. Never return raw exception messages, stack traces, SQL, filesystem paths, tokens or secrets.
95-
96-### Idempotency and concurrency
97-
98-
99-For mutating requests that can be retried, clients send `Idempotency-Key`. Persist `(actor_id, key, operation, request_hash, status, resource/result reference)` with a unique constraint and a defined retention window. Replaying the same key and same payload returns the prior result; a different payload returns `409 idempotency_conflict`. Worker handlers must also be idempotent. Use optimistic concurrency (resource version / ETag / `If-Match`) for updates to strategies, configs, documents and workspaces.
100-
101-## 4. Authentication, authorization and decision A
102-
103-
104-### Default-deny permission model
105-
106-
--

119-| privacy.export / privacy.delete / privacy.credentials.manage | Account privacy and credential lifecycle | Step-up/confirmation and audit where required. |
120-
121-### Minimal capability endpoint — approved design
122-
123-
124:**GET `/api/v1/admin/authorization/capabilities`** | Required permission: `platform.admin` | Release: Sprint 1 authorization foundation | Must be wired through the real FastAPI dependency chain, not a test-only helper.
125-
126-Success contract (example):
127-
128-```json
129-{
130- "data": {
131-   "subject": {
132-   "user_id": "<uuid>",
133-   "platform_role_code": "platform_admin"
134-   },
135-   "effective_permissions": [
136-   "platform.admin",
--
154-| --- | --- | --- | --- |
155-| Admin success | Real persisted admin user + active database-backed session + explicit `platform.admin` grant; GET endpoint. | 200; only caller’s effective permission/capability summary; request ID; no secret fields. | Any role-name-only bypass or response containing unrelated user/workspace data. |
156-| Authenticated denied user | Real active session; lacks `platform.admin`; GET endpoint. | 403 `permission_denied`; no capabilities or policy details leaked. | 200, 404 workaround, or permission derived from caller-supplied JSON. |
157-| Anonymous | No cookie/token. | 401 `unauthorized`. | Any response with admin capabilities. |
158-| Expired/revoked session | Session persisted then expired/revoked; GET endpoint. | 401; server-side revocation and expiry checked for each request. | A previously valid cookie remains trusted after revocation. |
159:| Database/RBAC failure | Inject session or permission query failure. | 503 `authorization_unavailable`; fail closed; structured redacted log. | Fallback-to-admin, unprotected 200, or leak of SQL/stack trace. |

160-| Cross-role spoofing | Non-admin attempts to provide a fake role/user/workspace claim. | 403; server trusts authenticated principal and persisted policy only. | Any client field changes authorization. |
161-| Permission revoked after session | Create session, remove permission mapping, repeat request. | Denied on next authorization check within defined cache policy (default no positive cache in Sprint 1). | Stale grant remains valid without documented bounded cache invalidation. |
162-| CSRF/cookie posture | Browser-origin mutating request without required CSRF protection (where cookie auth used). | Rejected according to selected CSRF policy. | Cookie-authenticated mutation succeeds with missing/invalid CSRF proof. |
163-
164-Never mark FIN-15 complete from the capability endpoint alone: it is a minimal authorization proof route. The role/permission matrix, access checks for all implemented protected APIs, test evidence, route ownership checks and outstanding source acceptance criteria still have to pass.
165-
166-### FastAPI implementation pattern
167-
168-
169-The example below is a design sketch, not a drop-in replacement for the current auth/session modules. It must use the repository’s real principal, database session dependency, role/permission tables and error conventions. The dependency should be shared and applied to route groups; domain services must still check resource ownership/workspace grants.
170-
171-```python
--
185-   )
186-   except SQLAlchemyError:
187-   # Log exception with request_id; never log credentials or raw prompt/document text.
188-   raise HTTPException(
189-   status_code=status.HTTP_503_SERVICE_UNAVAILABLE,
190:                detail={"code": "authorization_unavailable"},
191-   )
192-   if not allowed:
193-   raise HTTPException(
194-   status_code=status.HTTP_403_FORBIDDEN,
195-   detail={"code": "permission_denied"},
196-   )

197-   return principal
198-   return dependency
199-
200:@admin_router.get("/authorization/capabilities",
response_model=CapabilitiesResponse)
201-async def get_authorization_capabilities(
202-   principal = Depends(require_permission("platform.admin")),
203-   db = Depends(get_db_session),
204-):
205-   return await authorization_service.capabilities_for_subject(db, principal.user_id)
206-```
207-
208-Implement `require_authenticated_user`, `get_db_session`, repository and response types using existing project conventions; do not create duplicated independent session verification. Translate exceptions centrally into the standard safe error envelope. Catch only known database/dependency failures, and do not swallow programming errors as ordinary 403 responses. In FastAPI, register static paths such as `/instruments/compare`before parameterized routes such as `/instruments/{instrument_id}` to prevent route-shadowing.
209-
210-## 5. Full endpoint catalog
211-
212-
--
235-| DELETE | `/api/v1/auth/sessions/{session_id}` | Terminate one owned session | Authenticated + resource ACL | Idempotent | PROPOSED TARGET CONTRACT |
236-| POST | `/api/v1/auth/mfa/challenges` | Begin an MFA challenge | Authenticated + resource ACL | — | PROPOSED TARGET CONTRACT |
237-| POST | `/api/v1/auth/mfa/verify` | Verify an MFA challenge | Authenticated + resource ACL | — | PROPOSED TARGET CONTRACT |
238-| GET | `/api/v1/users/me` | Read current user profile | Authenticated + resource ACL | — | PROPOSED TARGET CONTRACT |
239-| PATCH | `/api/v1/users/me` | Update current user profile/preferences | Authenticated + resource ACL | — | PROPOSED TARGET CONTRACT |
240:| GET | `/api/v1/admin/authorization/capabilities` | Inspect authorized platform capabilities | platform.admin | — | SPRINT 1 PROPOSED — DECISION A |
241-| GET | `/api/v1/admin/roles` | List platform roles | platform.roles.read | — | PROPOSED TARGET CONTRACT |
242-| POST | `/api/v1/admin/role-permissions` | Assign permissions to a role | platform.roles.manage | Idempotency-Key | PROPOSED TARGET CONTRACT |

243-| POST | `/api/v1/admin/invitations` | Create an administrator-controlled invitation | platform.users.invite | Idempotency-Key | PROPOSED TARGET CONTRACT |
244-| GET | `/api/v1/admin/audit-events` | Search security/audit events | platform.audit.read | — | PROPOSED TARGET CONTRACT |
245-
246-### Workspace & saved research
247-
248-
249-| Verb | Target path | Purpose | Permission | Execution / retry | Status |
250-| --- | --- | --- | --- | --- | --- |
251-| GET | `/api/v1/workspaces` | List caller workspaces | Authenticated + resource ACL | — | PROPOSED TARGET CONTRACT |
252-| POST | `/api/v1/workspaces` | Create a workspace | workspace.create | Idempotency-Key | PROPOSED TARGET CONTRACT |
--
560-| Scenario | Contract |
561-| --- | --- |
562-| Authentication absent/invalid | 401 `unauthorized`; do not leak whether user exists. |
563-| Permission denied | 403 `permission_denied`; message safe and generic. |
564-| Object missing or inaccessible | Use selected 404/403 policy consistently; no cross-workspace existence leak. |
565:| Authorization DB unavailable | 503 `authorization_unavailable`; fail closed; never assume platform/admin privileges. |
566-| Provider/model unavailable | 503 or domain-safe failed job; no silent fabricated data. Return run/job IDs if work was accepted. |
567-| Validation issue | 422 with field-level safe errors; no stack trace. |
568-| Duplicate request | Return original idempotent result when request hash matches; otherwise 409. |
569-| Partial indexing/deletion | Expose nonterminal/failed state, enqueue safe reconciliation, preserve audit and lineage. |
570-| Stale/missing market data | Return available data with freshness/quality disclosure only when contract permits; otherwise safe unavailable/incomplete outcome. |
571-
572-## 14. Sprint 1 implementation sequence — avoid mixing work
573-
574-
575-| Step | Concrete deliverable | Acceptance evidence |
576-| --- | --- | --- |

577-| 1. Baseline audit | Inspect actual route declarations, app router mounting/prefixes, auth dependency/session model, migrations applied, tests, cookie/CSRF policy and CI. Record existing URLs before refactor. | Before/after route inventory; migration inventory; run current tests; no scope inference. |
578-| 2. RBAC model/migration | Verify schema for permission records and role_permissions. Add only a forward migration if missing; seed stable permission codes with explicit mappings in test fixtures and controlled bootstrap process. | Migration up/down strategy; FK/unique/index checks; test DB setup; no edit to existing applied migrations. |
579-| 3. Authorization dependency | Implement `require_permission(permission_code)` over actual authenticated principal + DB-backed session and role/permission joins. Fail closed on any dependency/DB error. | Unit tests for allow/deny + integration tests with real database-backed sessions. |
580:| 4. Decision A endpoint | Add `GET /api/v1/admin/authorization/capabilities` via actual router and dependency; return small DTO only. | Admin 200, non-admin 403, anonymous/expired/revoked 401, DB/RBAC unavailable 503; permission revocation and no secret leakage. |
581-| 5. Regression + security | Verify current `/auth/login`, `/auth/me`, `/auth/logout` behavior and frontend integration; cookie/CSRF tests as applicable; lint/type/test/secret scanning. | Run actual test commandsand record outcomes; don’t alter planned test register statuses without evidence. |
582-| 6. Documentation/traceability | Generate OpenAPI from FastAPI at runtime; compare against this target spec; record implemented-vs-proposed; update the requirement/story links and append-only execution record. |`/openapi.json` route diff, test evidence, changed files, migration ID and unresolved gaps. |
583-
584-## 15. Endpoint ownership, permissions and traceability rules
585-
586-
587-The `FinSight_AI_API_Endpoint_Catalog.csv` includes every target endpoint, status, permission and derived story/requirement mapping. The `FinSight_AI_API_Story_Coverage.csv` preserves all 72 source aliases, Jira keys, acceptance summaries, test execution, implementation status and outstanding gaps from the source matrix. `FinSight_AI_API_Requirement_Traceability.csv` preserves each of the source RTM’s requirement/data-integrity rows and original evidence/status/test fields, adding only a proposed API family and explicit contract note.
588-
589-Route-to-story mapping is a design aid and is not a substitute for acceptance-criterion traceability. For each Jira story, engineers must connect every acceptance criterion to one or more endpoints/services/schema changes/tests and

```
show test evidence. Requirements without mapped source stories remain gaps; do not
infer scope or change Jira/SRS baselines from this document.
590-
591-## 16. Decisions required before broad implementation
592-

===== 5. PATCH VALIDATION =====
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

zsh: parse error near `)'
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
"$HOME/Documents/NVDIA_Play_Book/FinSight_AI" || exit 1

cd apps/api || exit 1
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q \
  tests/test_identity_constraints.py \
  tests/test_auth_unit.py \
  tests/test_auth.py
.F.F.....................................
[100%]
========================================================================
======= FAILURES
========================================================================
=======

_____________________________________________
test_platform_permission_is_resolved_from_database_role_and_session
_____________________________________________

    def test_platform_permission_is_resolved_from_database_role_and_session():
        admin_email = f"platform-admin-{uuid4().hex}@example.test"
        user_email = f"unprivileged-{uuid4().hex}@example.test"
        tokens = []
        with connect() as conn, conn.cursor() as cur:
            cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
            admin_role_id = cur.fetchone()[0]
            cur.execute(
                "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s,
%s, %s) RETURNING user_id",
                (admin_email, "Synthetic Platform Admin", admin_role_id),
```

```
            )
            admin_id = cur.fetchone()[0]
            cur.execute(
                "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
                (user_email, "Synthetic Standard User"),
            )
            user_id = cur.fetchone()[0]
            for owner_id in (admin_id, user_id):
                token, digest = new_session_token()
                tokens.append(token)
                cur.execute(
                    "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                    (owner_id, digest, session_expiry(5)),
                )

        try:
            with TestClient(app) as client:
                anonymous = client.get("/api/v1/admin/authorization/capabilities")
                assert anonymous.status_code == 401
                assert anonymous.json() == {"detail": "Authentication required"}

                invalid_session = client.get(
                    "/api/v1/admin/authorization/capabilities",
                    cookies={SESSION_COOKIE: "invalid-session-token"},
                )
                assert invalid_session.status_code == 401

                allowed = client.get(
                    "/api/v1/admin/authorization/capabilities",
                    cookies={SESSION_COOKIE: tokens[0]},
                )
                #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
                correlated = client.get(
                    "/api/v1/admin/authorization/capabilities",
                    cookies={SESSION_COOKIE: tokens[0]},
                    headers={"request_id": "client-correlation-123"},
                )
```

```
            assert correlated.status_code == 200
            correlated_body = correlated.json()
>           assert correlated_body["request_id"].startswith("req_")
E           AssertionError: assert False
E            +  where False = <built-in method startswith of str object at
0x113c97a30>('req_')
E            +    where <built-in method startswith of str object at 0x113c97a30> =
'client-correlation-123'.startswith

tests/test_identity_constraints.py:94: AssertionError
_____
test_capabilities_request_id_is_canonical_and_correlation_is_preserved
_____

    def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
            """
            SELECT u.user_id, s.refresh_token_hash
            FROM users u
            JOIN roles r ON r.role_id = u.platform_role_id
            JOIN role_permissions rp ON rp.role_id = r.role_id
            JOIN permissions p ON p.permission_id = rp.permission_id
            JOIN auth_sessions s ON s.user_id = u.user_id
            WHERE r.role_key = 'platform_admin'
            AND p.permission_key = 'platform.admin'
            AND s.revoked_at IS NULL
            AND s.expires_at > now()
            LIMIT 1
            """
            )
>       row = cur.fetchone()
            ^^^^^^^^^^^^^^

tests/test_identity_constraints.py:170:
_ _ _ _
```

```
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _
_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

self = <psycopg.Cursor [closed] [BAD] at 0x1139a3950>

    def _check_result_for_fetch(self) -> PGresult:
        if self.closed:
>           raise e.InterfaceError("the cursor is closed")
E           psycopg.InterfaceError: the cursor is closed

../../../.venv/lib/python3.12/site-packages/psycopg/_cursor_base.py:570: InterfaceError
=============================================================
=== warnings summary
=============================================================
===
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py: 3 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_auth.py: 4 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
```

```
=========================================================================
short test summary info
=========================================================================
FAILED
tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session - AssertionError: assert False
FAILED
tests/test_identity_constraints.py::test_capabilities_request_id_is_canonical_and_correl
ation_is_preserved - psycopg.InterfaceError: the cursor is closed
2 failed, 45 passed, 12 warnings in 1.07s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
(base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book %  source
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % git diff
--check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd apps/api
cd: no such file or directory: apps/api
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd
FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q \
  tests/test_identity_constraints.py \
  tests/test_auth_unit.py \
  tests/test_auth.py
.F.....................................
[100%]
=========================================================================
============== FAILURES
=========================================================================
===============

_____________________________________________________________
test_platform_permission_is_resolved_from_database_role_and_session
_____________________________________________________________

    def test_platform_permission_is_resolved_from_database_role_and_session():
        admin_email = f"platform-admin-{uuid4().hex}@example.test"
        user_email = f"unprivileged-{uuid4().hex}@example.test"
        tokens = []
        with connect() as conn, conn.cursor() as cur:
```

```
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s,
%s, %s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
            )
```

```
            #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
            correlated = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
                headers={"request_id": "client-correlation-123"},
            )
            assert correlated.status_code == 200
            correlated_body = correlated.json()
>            assert correlated_body["request_id"].startswith("req_")
E            AssertionError: assert False
E             +  where False = <built-in method startswith of str object at
0x113e5e5b0>('req_')
E             +    where <built-in method startswith of str object at 0x113e5e5b0> =
'client-correlation-123'.startswith

tests/test_identity_constraints.py:94: AssertionError
=============================================================================
========== warnings summary
=============================================================================
============
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
  from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
  _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py: 3 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_auth.py: 4 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
```

```
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=========================================================================
======== short test summary info
=========================================================================
========
FAILED
tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session - AssertionError: assert False
1 failed, 44 passed, 12 warnings in 0.96s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
=========================================================================
======== short test summary info
=========================================================================
========
FAILED
tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_databas
e_role_and_session - AssertionError: assert False
1 failed, 44 passed, 12 warnings in 0.96s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q \
  tests/test_identity_constraints.py \
  tests/test_auth_unit.py \
  tests/test_auth.py
.............................................
[100%]
=========================================================================
========== warnings summary
=========================================================================
============
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
```

```
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py: 5 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_auth.py: 4 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
45 passed, 14 warnings in 0.94s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %

apps/api/app/main.py:190: trailing whitespace.
+
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
.............................................................
[100%]
=============================================================================
========== warnings summary
=============================================================================
============
../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
```

```
    from starlette.testclient import TestClient as TestClient  # noqa

../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 5 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.02s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
whitespace.
+
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
..............................................................
[100%]
=============================================================================
========== warnings summary
=============================================================================
============
../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../.venv/lib/python3.12/site-packages/starlette/testclient.py:53
```

```
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is deprecated, use anyio.from_thread.BlockingPortal instead.
  _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 5 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the client instance instead.
  return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.02s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % python -c "from pathlib import Path; p=Path('apps/api/app/main.py'); s=p.read_text(); lines=s.splitlines(keepends=True); i=189; print('Line 190:', repr(lines[i])); lines[i]=lines[i].rstrip(' \t\r\n') + ('\n' if lines[i].endswith('\n') else ''); p.write_text(''.join(lines))"

git diff --check
Line 190: '    \n'
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
cd ../..
git diff --check
.....................................................
[100%]
=============================================================================== warnings summary ===============================================================================
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
```

```
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 5 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.05s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book %  source
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd
FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % git diff --check
apps/api/app/main.py:190: trailing whitespace.
+
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
........................................................
[100%]
========================================================================
========== warnings summary
========================================================================
============
../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1
```

```
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fastapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 5 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.02s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % python -c "from pathlib import Path; p=Path('apps/api/app/main.py'); s=p.read_text(); lines=s.splitlines(keepends=True); i=189; print('Line 190:', repr(lines[i])); lines[i]=lines[i].rstrip(' \t\r\n') + ('\n' if lines[i].endswith('\n') else ''); p.write_text(''.join(lines))"

git diff --check
Line 190: '    \n'
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
cd ../..
git diff --check
.....................................................
[100%]
```

```
============================================================================
========== warnings summary
============================================================================
============
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
  from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortal alias is
deprecated, use anyio.from_thread.BlockingPortal instead.
  _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 5 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
  return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.05s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % sed -n '45,145p'
apps/api/tests/test_identity_constraints.py
def test_platform_permission_is_resolved_from_database_role_and_session():
  admin_email = f"platform-admin-{uuid4().hex}@example.test"
  user_email = f"unprivileged-{uuid4().hex}@example.test"
  tokens = []
  with connect() as conn, conn.cursor() as cur:
    cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
    admin_role_id = cur.fetchone()[0]
```

```
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
            )
            #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
            correlated = client.get(
```

```
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[0]},
            headers={"request_id": "client-correlation-123"},
        )
        assert correlated.status_code == 200
        correlated_body = correlated.json()
        assert correlated_body["request_id"].startswith("req_")
        assert correlated_body["request_id"] != "client-correlation-123"
        assert correlated_body["correlation_id"] == "client-correlation-123"

        malformed = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[0]},
            headers={"request_id": "x" * 129},
        )
        assert malformed.status_code == 400

        # The platform-admin user should be allowed to inspect the authorization policy.
        assert allowed.status_code == 200
        body = allowed.json()
        assert body["data"]["subject"]["user_id"] == str(admin_id)
        assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
        assert body["data"]["effective_permissions"] == ["platform.admin"]
        assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
        assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
        assert body["request_id"].startswith("req_")
        assert body["correlation_id"] == body["request_id"]

        denied = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[1]},
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))
```

```
def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book %  source
/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd
FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % sed -n '110,155p'
apps/api/tests/test_identity_constraints.py
git diff --check
            assert body["data"]["effective_permissions"] == ["platform.admin"]
            assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
            assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
            assert body["request_id"].startswith("req_")
            assert body["correlation_id"] == body["request_id"]

            denied = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[1]},
                headers={"X-Role": "platform_admin"},
```

```
            )
            assert denied.status_code == 403
            assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))


def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))




# def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
#     with connect() as conn, conn.cursor() as cur:
```

```
#         cur.execute(
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % sed -n '1,45p'
apps/api/tests/test_identity_constraints.py
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s) RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
```

```
            (user_id, digest, session_expiry(5)),
        )
        cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
        cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
        assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

                "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
            )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % grep -n -A25 -B10
'role_permissions\|platform.admin' \
  apps/api/migrations/0002_platform_authorization.sql
1--- FIN-15: only the platform-scoped administrator permission is implemented.
```

```
2--- Workspace roles and workspace permissions remain unavailable until workspace membership exists.
3-BEGIN;
4-
5-CREATE TABLE permissions (
6-    permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
7-    permission_key VARCHAR(120) NOT NULL UNIQUE,
8-    description TEXT NOT NULL
9-);
10-
11:CREATE TABLE role_permissions (
12-    role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
13-    permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON DELETE CASCADE,
14-    PRIMARY KEY (role_id, permission_id)
15-);
16-
17-INSERT INTO roles (role_key, display_name, scope, description)
18:VALUES ('platform_admin', 'Platform Administrator', 'platform',
19-        'Administrator privileges for currently implemented platform operations only.')
20-ON CONFLICT (role_key) DO NOTHING;
21-
22-DO $$
23-BEGIN
24:    IF NOT EXISTS (SELECT 1 FROM roles WHERE role_key = 'platform_admin' AND scope = 'platform') THEN
25:        RAISE EXCEPTION 'Existing platform_admin role has non-platform scope';
26-    END IF;
27-END
28-$$;
29-
30-INSERT INTO permissions (permission_key, description)
31:VALUES ('platform.admin', 'Access operations explicitly assigned platform administrator permission.')
32-ON CONFLICT (permission_key) DO NOTHING;
33-
34:INSERT INTO role_permissions (role_id, permission_id)
35-SELECT r.role_id, p.permission_id
36-FROM roles r CROSS JOIN permissions p
37:WHERE r.role_key = 'platform_admin' AND r.scope = 'platform'
```

```
38:  AND p.permission_key = 'platform.admin'
39-ON CONFLICT DO NOTHING;
40-
41-CREATE FUNCTION enforce_platform_role_scope() RETURNS trigger
42-LANGUAGE plpgsql AS $$
43-BEGIN
44-    IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
45-        SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope =
'platform'
46-    ) THEN
47-        RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
48-            USING ERRCODE = '23514';
49-    END IF;
50-    RETURN NEW;
51-END
52-$$;
53-
54-CREATE TRIGGER users_platform_role_scope_check
55-BEFORE INSERT OR UPDATE OF platform_role_id ON users
56-FOR EACH ROW EXECUTE FUNCTION enforce_platform_role_scope();
57-
58-CREATE FUNCTION prevent_platform_role_scope_drift() RETURNS trigger
59-LANGUAGE plpgsql AS $$
60-BEGIN
61-    IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
62-        SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
63-    ) THEN
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

61-    IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
62-        SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
63-    ) THEN
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % grep -n -E
'DATABASE_URL|finsight_test|pytest|test database|transaction' \
  apps/api/tests/conftest.py apps/api/pyproject.toml apps/api/requirements-dev.txt \
  2>/dev/null
apps/api/requirements-dev.txt:2:pytest==9.0.3
apps/api/requirements-dev.txt:4:pytest-cov==6.2.1
 $$
60-BEGIN
```

```
61-    IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
62-        SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
63-    ) THEN
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % grep -n -E
'DATABASE_URL|finsight_test|pytest|test database|transaction' \
  apps/api/tests/conftest.py apps/api/pyproject.toml apps/api/requirements-dev.txt \
  2>/dev/null
apps/api/requirements-dev.txt:2:pytest==9.0.3
apps/api/requirements-dev.txt:4:pytest-cov==6.2.1
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % git status --short
git diff --check

cd apps/api || exit 1
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
.....................................................
[100%]
=============================================================================
=== warnings summary
=============================================================================
===
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
```

```
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 5 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.08s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
 Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
56 passed, 14 warnings in 1.08s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd
~/Documents/NVDIA_Play_Book/FinSight_AI
git status --short
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
```

```
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
...
[100%]
=============================================================================
=== warnings summary
=============================================================================
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
```

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the client instance instead.
  return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
3 passed, 7 warnings in 0.29s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
3 passed, 7 warnings in 0.29s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % sed -n '1,280p' tests/test_identity_constraints.py
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission

def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
  email = f"constraint-{uuid4().hex}@example.com"
  with connect() as conn, conn.cursor() as cur:
    cur.execute(
      "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s, %s) RETURNING user_id",
      (email, "synthetic-hash", "Synthetic Constraint Test"),
)
    user_id = cur.fetchone()[0]

  try:
    with pytest.raises(psycopg.errors.UniqueViolation):
      with connect() as conn, conn.cursor() as cur:
        cur.execute(

```
                "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
            )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
```

```
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
            )
            #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
            correlated = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
                headers={"request_id": "client-correlation-123"},
            )
            assert correlated.status_code == 200
            correlated_body = correlated.json()
            assert correlated_body["request_id"].startswith("req_")
            assert correlated_body["request_id"] != "client-correlation-123"
            assert correlated_body["correlation_id"] == "client-correlation-123"

            malformed = client.get(
```

```
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[0]},
            headers={"request_id": "x" * 129},
        )
        assert malformed.status_code == 400

        # The platform-admin user should be allowed to inspect the authorization policy.
        assert allowed.status_code == 200
        body = allowed.json()
        assert body["data"]["subject"]["user_id"] == str(admin_id)
        assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
        assert body["data"]["effective_permissions"] == ["platform.admin"]
        assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
        assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
        assert body["request_id"].startswith("req_")
        assert body["correlation_id"] == body["request_id"]

        denied = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[1]},
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))


def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
```

```
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))




# def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
#     with connect() as conn, conn.cursor() as cur:
#         cur.execute(
#         """
#         SELECT u.user_id, s.refresh_token_hash
#         FROM users u
#         JOIN roles r ON r.role_id = u.platform_role_id
#         JOIN role_permissions rp ON rp.role_id = r.role_id
#         JOIN permissions p ON p.permission_id = rp.permission_id
#         JOIN auth_sessions s ON s.user_id = u.user_id
#         WHERE r.role_key = 'platform_admin'
#         AND p.permission_key = 'platform.admin'
#         AND s.revoked_at IS NULL
#         AND s.expires_at > now()
#         LIMIT 1
#         """
#         )
#     row = cur.fetchone()

#     if row is None:
#         pytest.skip("No active platform-admin test session is available")
```

```
#     # The database stores only the token digest, so use a dedicated test
#     # session instead of attempting to recover an existing session token.
#     pytest.skip("Use the dedicated-session integration fixture for this assertion")

# def test_capabilities_rejects_malformed_request_id():
#     # Authentication runs before the endpoint validates its header.
#     # An unauthenticated request must not be mistaken for a header-validation test.
#     response = TestClient(app).get(
#     "/api/v1/admin/authorization/capabilities",
#     headers={"request_id": "x" * 129},
#     )
#     assert response.status_code == 401%
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % sed -n '1,220p'
tests/test_identity_constraints.py
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s) RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
```

```
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
```

```
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
            )
            #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
            correlated = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
                headers={"request_id": "client-correlation-123"},
            )
            assert correlated.status_code == 200
            correlated_body = correlated.json()
            assert correlated_body["request_id"].startswith("req_")
```

```
        assert correlated_body["request_id"] != "client-correlation-123"
        assert correlated_body["correlation_id"] == "client-correlation-123"

        malformed = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[0]},
            headers={"request_id": "x" * 129},
        )
        assert malformed.status_code == 400

        # The platform-admin user should be allowed to inspect the authorization policy.
        assert allowed.status_code == 200
        body = allowed.json()
        assert body["data"]["subject"]["user_id"] == str(admin_id)
        assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
        assert body["data"]["effective_permissions"] == ["platform.admin"]
        assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
        assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
        assert body["request_id"].startswith("req_")
        assert body["correlation_id"] == body["request_id"]

        denied = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[1]},
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))


def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
```

```
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))




# def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
#     with connect() as conn, conn.cursor() as cur:
#         cur.execute(
#         """
#         SELECT u.user_id, s.refresh_token_hash
#         FROM users u
#         JOIN roles r ON r.role_id = u.platform_role_id
#         JOIN role_permissions rp ON rp.role_id = r.role_id
#         JOIN permissions p ON p.permission_id = rp.permission_id
#         JOIN auth_sessions s ON s.user_id = u.user_id
#         WHERE r.role_key = 'platform_admin'
#         AND p.permission_key = 'platform.admin'
#         AND s.revoked_at IS NULL
#         AND s.expires_at > now()
#         LIMIT 1
#         """
#         )
```

```
#     row = cur.fetchone()

#     if row is None:
#         pytest.skip("No active platform-admin test session is available")

#     # The database stores only the token digest, so use a dedicated test
#     # session instead of attempting to recover an existing session token.
#     pytest.skip("Use the dedicated-session integration fixture for this assertion")

# def test_capabilities_rejects_malformed_request_id():
#     # Authentication runs before the endpoint validates its header.
#     # An unauthenticated request must not be mistaken for a header-validation test.
#     response = TestClient(app).get(
#     "/api/v1/admin/authorization/capabilities",
#     headers={"request_id": "x" * 129},
#     )
#     assert response.status_code == 401%
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % >....
        token, digest = new_session_token()
        cur.execute(
            "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) "
            "VALUES (%s, %s, %s)",
            (user_id, digest, session_expiry(5)),
        )

    try:
        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
            ]

            # Revoke this test user's role without changing shared role permissions.
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "UPDATE users SET platform_role_id = NULL WHERE user_id = %s",
```

```
                (user_id,),
            )

        next_response = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: token},
        )
        assert next_response.status_code == 403
        assert next_response.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


'''

path.write_text(source.replace(marker, test + marker, 1))
print(f"Inserted test into {path}")
PY

Inserted test into tests/test_identity_constraints.py
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
....
[100%]
=============================================================================
=== warnings summary
=============================================================================
===
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
```

```
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_role_revocation_takes_effect_
on_next_request
apps/api/tests/test_identity_constraints.py::test_platform_role_revocation_takes_effect_
on_next_request

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
4 passed, 9 warnings in 0.38s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
.........................................................
[100%]
=============================================================================
=== warnings summary
=============================================================================
===
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
```

```
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 7 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being
deprecated, because the expected behaviour on cookie persistence is ambiguous. Set
cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
57 passed, 16 warnings in 1.08s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
git diff --check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
table/how-to/capture-warnings.html
57 passed, 16 warnings in 1.08s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
git diff --check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % grep -n -A 12 -B 5
"CREATE TABLE.*roles\|CREATE TABLE.*permissions\|CREATE
TABLE.*role_permissions" apps/api/migrations/0002_platform_authorization.sql
1--- FIN-15: only the platform-scoped administrator permission is implemented.
2--- Workspace roles and workspace permissions remain unavailable until workspace
membership exists.
3-BEGIN;
4-
5:CREATE TABLE permissions (
6-    permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
```

```
7-    permission_key VARCHAR(120) NOT NULL UNIQUE,
8-    description TEXT NOT NULL
9-);
10-
11:CREATE TABLE role_permissions (
12-    role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
13-    permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON
DELETE CASCADE,
14-    PRIMARY KEY (role_id, permission_id)
15-);
16-
17-INSERT INTO roles (role_key, display_name, scope, description)
18-VALUES ('platform_admin', 'Platform Administrator', 'platform',
19-        'Administrator privileges for currently implemented platform operations only.')
20-ON CONFLICT (role_key) DO NOTHING;
21-
22-DO $$
23-BEGIN
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
id) ON DELETE CASCADE,
13-    permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON
DELETE CASCADE,
14-    PRIMARY KEY (role_id, permission_id)
15-);
16-
17-INSERT INTO roles (role_key, display_name, scope, description)
18-VALUES ('platform_admin', 'Platform Administrator', 'platform',
19-        'Administrator privileges for currently implemented platform operations only.')
20-ON CONFLICT (role_key) DO NOTHING;
21-
22-DO $$
23-BEGIN
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % sed -n '1,180p'
apps/api/migrations/0002_platform_authorization.sql
-- FIN-15: only the platform-scoped administrator permission is implemented.
-- Workspace roles and workspace permissions remain unavailable until workspace
membership exists.
BEGIN;

CREATE TABLE permissions (
```

```
    permission_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    permission_key VARCHAR(120) NOT NULL UNIQUE,
    description TEXT NOT NULL
);

CREATE TABLE role_permissions (
    role_id UUID NOT NULL REFERENCES roles(role_id) ON DELETE CASCADE,
    permission_id UUID NOT NULL REFERENCES permissions(permission_id) ON
DELETE CASCADE,
    PRIMARY KEY (role_id, permission_id)
);

INSERT INTO roles (role_key, display_name, scope, description)
VALUES ('platform_admin', 'Platform Administrator', 'platform',
        'Administrator privileges for currently implemented platform operations only.')
ON CONFLICT (role_key) DO NOTHING;

DO $$
BEGIN
    IF NOT EXISTS (SELECT 1 FROM roles WHERE role_key = 'platform_admin' AND
scope = 'platform') THEN
        RAISE EXCEPTION 'Existing platform_admin role has non-platform scope';
    END IF;
END
$$;

INSERT INTO permissions (permission_key, description)
VALUES ('platform.admin', 'Access operations explicitly assigned platform administrator
permission.')
ON CONFLICT (permission_key) DO NOTHING;

INSERT INTO role_permissions (role_id, permission_id)
SELECT r.role_id, p.permission_id
FROM roles r CROSS JOIN permissions p
WHERE r.role_key = 'platform_admin' AND r.scope = 'platform'
  AND p.permission_key = 'platform.admin'
ON CONFLICT DO NOTHING;

CREATE FUNCTION enforce_platform_role_scope() RETURNS trigger
LANGUAGE plpgsql AS $$
```

```
BEGIN
   IF NEW.platform_role_id IS NOT NULL AND NOT EXISTS (
      SELECT 1 FROM roles WHERE role_id = NEW.platform_role_id AND scope =
'platform'
   ) THEN
      RAISE EXCEPTION 'platform_role_id must reference a platform-scoped role'
         USING ERRCODE = '23514';
   END IF;
   RETURN NEW;
END
$$;

CREATE TRIGGER users_platform_role_scope_check
BEFORE INSERT OR UPDATE OF platform_role_id ON users
FOR EACH ROW EXECUTE FUNCTION enforce_platform_role_scope();

CREATE FUNCTION prevent_platform_role_scope_drift() RETURNS trigger
LANGUAGE plpgsql AS $$
BEGIN
   IF OLD.scope = 'platform' AND NEW.scope <> 'platform' AND EXISTS (
      SELECT 1 FROM users WHERE platform_role_id = OLD.role_id
   ) THEN
      RAISE EXCEPTION 'Cannot change scope of an assigned platform role';
   END IF;
   RETURN NEW;
END
$$;

CREATE TRIGGER roles_prevent_scope_drift
BEFORE UPDATE OF scope ON roles
FOR EACH ROW EXECUTE FUNCTION prevent_platform_role_scope_drift();

COMMIT;
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

COMMIT;
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % grep -n -A 65 -B 10
"def get_current_user" apps/api/app/main.py
62-        return configured.lower() in {"1", "true", "yes"}
63-    return os.environ.get("APP_ENV", "development").lower() == "production"
```

```
64-
65-
66-def _check_origin(request: Request) -> None:
67-    origin = request.headers.get("origin")
68-    if origin and origin != web_origin:
69-        raise HTTPException(status_code=403, detail="Request origin is not allowed")
70-
71-
72:def get_current_user(
73-    session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] = None,
74-) -> dict[str, Any]:
75-    if not session_token:
76-        raise HTTPException(status_code=status.HTTP_401_UNAUTHORIZED,
detail="Authentication required")
77-    try:
78-        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
79-            cur.execute(
80-                """SELECT u.user_id, u.email, u.display_name, r.role_key,
81-                          COALESCE(array_agg(DISTINCT p.permission_key)
82-                                   FILTER (WHERE p.permission_key IS NOT NULL),
ARRAY[]::varchar[]) AS permissions
83-                   FROM auth_sessions s JOIN users u ON u.user_id = s.user_id
84-                   LEFT JOIN roles r ON r.role_id = u.platform_role_id AND r.scope =
'platform'
85-                   LEFT JOIN role_permissions rp ON rp.role_id = r.role_id
86-                   LEFT JOIN permissions p ON p.permission_id = rp.permission_id
87-                   WHERE s.refresh_token_hash = %s AND s.revoked_at IS NULL
88-                     AND s.expires_at > %s AND u.account_status = 'active'
89-                     AND s.last_seen_at > %s - make_interval(mins => %s)
90-                     AND u.deleted_at IS NULL
91-                   GROUP BY u.user_id, u.email, u.display_name, r.role_key""",
92-                (token_digest(session_token), datetime.now(UTC), datetime.now(UTC),
_ttl_minutes()),
93-            )
94-            user = cur.fetchone()
95-            if not user:
96-                raise HTTPException(status_code=401, detail="Authentication required")
97-            cur.execute(
98-                "UPDATE auth_sessions SET last_seen_at = %s WHERE
refresh_token_hash = %s",
```

```
99-              (datetime.now(UTC), token_digest(session_token)),
100-          )
101-          return user
102-    except psycopg.Error as exc:
103-        raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
104-
105-
106-CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]
107-
108-
109-def require_permission(permission_key: str):
110-    """Build a deny-by-default backend permission dependency."""
111-    def dependency(user: CurrentUser) -> dict[str, Any]:
112-        if permission_key not in user.get("permissions", []):
113-            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN,
detail="Permission denied")
114-        return user
115-
116-    return dependency
117-
118-
119-@app.post("/auth/login", response_model=UserView)
120-def login(payload: LoginRequest, request: Request, response: Response) ->
UserView:
121-    _check_origin(request)
122-    email = payload.email.strip().lower()
123-    try:
124-        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
125-            cur.execute(
126-                """SELECT user_id, email, display_name, password_hash
127-                   FROM users WHERE lower(email) = %s AND account_status = 'active'
128-                     AND deleted_at IS NULL""",
129-                (email,),
130-            )
131-            user = cur.fetchone()
132-            if not user or not user["password_hash"]:
133-                verify_password(DUMMY_PASSWORD_HASH, payload.password)
134-                raise HTTPException(status_code=401,
detail=GENERIC_LOGIN_ERROR)
```

```
135-            if not verify_password(user["password_hash"], payload.password):
136-                raise HTTPException(status_code=401,
detail=GENERIC_LOGIN_ERROR)
137-            token, digest = new_session_token()
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
w_session_token()
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd apps/api
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % >....
                """
                INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
                VALUES (%s, %s, %s)
                """,
                (user_id, digest, session_expiry(5)),
            )

        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
            ]

            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "DELETE FROM role_permissions WHERE role_id = %s AND
permission_id = %s",
                    (role_id, permission_id),
                )

            next_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert next_response.status_code == 403
            assert next_response.json() == {"detail": "Permission denied"}
```

```
    finally:
        with connect() as conn, conn.cursor() as cur:
            if user_id is not None:
                cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            if role_id is not None:
                cur.execute("DELETE FROM roles WHERE role_id = %s", (role_id,))
'''

path.write_text(source.replace(marker, test + marker, 1))
print("Added permission-grant revocation regression test.")
PY

Added permission-grant revocation regression test.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
Added permission-grant revocation regression test.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
tests/test_identity_constraints.py
.....
[100%]
=============================================================================
=== warnings summary
=============================================================================
===
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas
tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient`
is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/sta
rlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is
deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
```

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_database_role_and_session
apps/api/tests/test_identity_constraints.py::test_permission_grant_revocation_takes_effect_on_next_request
apps/api/tests/test_identity_constraints.py::test_permission_grant_revocation_takes_effect_on_next_request
apps/api/tests/test_identity_constraints.py::test_platform_role_revocation_takes_effect_on_next_request
apps/api/tests/test_identity_constraints.py::test_platform_role_revocation_takes_effect_on_next_request

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the client instance instead.
  return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
5 passed, 11 warnings in 0.40s

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
5 passed, 11 warnings in 0.40s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api %
DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
.....
[100%]
=============================== warnings summary ===============================
../../../.venv/lib/python3.12/site-packages/fastapi/testclient.py:1

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/fas

tapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient # noqa

../../../.venv/lib/python3.12/site-packages/starlette/testclient.py:53

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:53: DeprecationWarning: The anyio.abc.BlockingPortalalias is deprecated, use anyio.from_thread.BlockingPortal instead.
    _PortalFactoryType = Callable[[], AbstractContextManager[anyio.abc.BlockingPortal]]

apps/api/tests/test_auth.py: 4 warnings
apps/api/tests/test_auth_unit.py: 3 warnings
apps/api/tests/test_identity_constraints.py: 9 warnings

/Users/sandeeph/Documents/NVDIA_Play_Book/.venv/lib/python3.12/site-packages/starlette/testclient.py:454: DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
58 passed, 18 warnings in 1.10s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro api % cd ../..
git diff --check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % sed -n '1,260p' test-results/FIN-15/20261020_141630_acceptance_review.txt
FIN-15 Acceptance Criteria Review
Tue Oct 20 14:16:30 IST 2026

=== FIN-15 references in project documents ===
IMPLEMENTATION_STATUS.txt-315-- CSV trailing-whitespace scan: 0 rows. `git diff --check`: PASS, exit 0.
IMPLEMENTATION_STATUS.txt-316-GitHub-side limitation: `git show --check --format= HEAD` against the existing root commit exits 2 with 1,323 diagnostics, including immutable source PDFs and other pre-existing root-commit files. No source PDF/SQL/diagram/test plan was edited. The targeted working diff passes `git diff --check`; an incremental commit/push is needed so the next GitHub run checks only the

corrective diff. No commit, push, Jira update, or remote rerun was made. A new GitHub Actions result is required before claiming the repair passed remotely; FIN-73/74/79 status is unchanged.
IMPLEMENTATION_STATUS.txt-317-Final review note (2026-10-19): `git diff --check` exited 0 for the targeted workflow/CSV/script changes before coordination records were appended. A later full `git diff --check` attempt timed out after 8 seconds (intermittent Git responsiveness); direct trailing-whitespace scansof `.github/workflows/ci.yml`, `docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both updated coordination files found zero whitespace errors and all had final newlines. The historical root-commit check result above remains distinct from the current worktree check.
IMPLEMENTATION_STATUS.txt-318-
IMPLEMENTATION_STATUS.txt:319:FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)
IMPLEMENTATION_STATUS.txt-320-Status: BLOCKED pending role-scope decision; implementation not started.
IMPLEMENTATION_STATUS.txt-321-Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
IMPLEMENTATION_STATUS.txt-322-Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorize minimal canonical workspace membership model.
IMPLEMENTATION_STATUS.txt-323-Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.

IMPLEMENTATION_STATUS.txt:324:Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
IMPLEMENTATION_STATUS.txt-325-
IMPLEMENTATION_STATUS.txt:326:FIN-15 verification update — 2026-10-20
IMPLEMENTATION_STATUS.txt-327-- PostgreSQL 17.6 is running locally.
IMPLEMENTATION_STATUS.txt-328-- Created and used the dedicated finsight_test database.
IMPLEMENTATION_STATUS.txt-329-- Applied apps/api/migrations/0001_auth_identity.sql successfully.
IMPLEMENTATION_STATUS.txt-330-- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
--
IMPLEMENTATION_STATUS.txt-332-- Full API test suite: 55 passed, 0 failed, 9 warnings.
IMPLEMENTATION_STATUS.txt-333-- git diff --check: no errors reported.
IMPLEMENTATION_STATUS.txt-334-- Warning: Starlette/httpx deprecation warnings remain.
IMPLEMENTATION_STATUS.txt-335-- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
IMPLEMENTATION_STATUS.txt:336:- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
IMPLEMENTATION_STATUS.txt-337-
IMPLEMENTATION_STATUS.txt:338:FIN-15 implementation update — 2026-10-20
IMPLEMENTATION_STATUS.txt-339-- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
IMPLEMENTATION_STATUS.txt-340-- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
IMPLEMENTATION_STATUS.txt-341-- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.

IMPLEMENTATION_STATUS.txt-342-- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
IMPLEMENTATION_STATUS.txt:343:- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are checked.
IMPLEMENTATION_STATUS.txt-344-- No migrations, commits, pushes, or workspace schema changes performed by this patch script.
IMPLEMENTATION_STATUS.txt-345-
IMPLEMENTATION_STATUS.txt:346:FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
IMPLEMENTATION_STATUS.txt-347-Latest run: 20261020_141030
IMPLEMENTATION_STATUS.txt-348-Recorded revision: 64f2637
IMPLEMENTATION_STATUS.txt-349-Python: 3.14.6
IMPLEMENTATION_STATUS.txt-350-Database: finsight_test
--
IMPLEMENTATION_STATUS.txt-355-- Both pytest commands exited with code 0.
IMPLEMENTATION_STATUS.txt-356-- The test-run summary records Overall result: PASS.
IMPLEMENTATION_STATUS.txt-357-
IMPLEMENTATION_STATUS.txt-358-Evidence:
IMPLEMENTATION_STATUS.txt:359:-
test-results/FIN-15/20261020_141030_identity_authorization.log
IMPLEMENTATION_STATUS.txt:360:-
test-results/FIN-15/20261020_141030_full_api_suite.log
IMPLEMENTATION_STATUS.txt:361:-
test-results/FIN-15/run_20261020_141030_summary.txt
IMPLEMENTATION_STATUS.txt-362-
IMPLEMENTATION_STATUS.txt-363-The warnings were Starlette/httpx deprecations. The passing test suites establish
IMPLEMENTATION_STATUS.txt:364:the behavior exercised by those tests, not automatic completion of every FIN-15
IMPLEMENTATION_STATUS.txt-365-acceptance criterion. Workspace membership and resource-level authorization remain
IMPLEMENTATION_STATUS.txt-366-deferred under the approved platform-only scope. Earlier entries are retained as
IMPLEMENTATION_STATUS.txt-367-historical records; this addendum records the later successful run.
--

SPRINT_1_TEST_EXECUTION_STATUS.txt-131-- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
SPRINT_1_TEST_EXECUTION_STATUS.txt-132-- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
SPRINT_1_TEST_EXECUTION_STATUS.txt-133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
SPRINT_1_TEST_EXECUTION_STATUS.txt-134-
SPRINT_1_TEST_EXECUTION_STATUS.txt:135:FIN-15 route-level authorization test update — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt-136-- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
SPRINT_1_TEST_EXECUTION_STATUS.txt-137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
SPRINT_1_TEST_EXECUTION_STATUS.txt-138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
SPRINT_1_TEST_EXECUTION_STATUS.txt-139-
SPRINT_1_TEST_EXECUTION_STATUS.txt:140:FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)
SPRINT_1_TEST_EXECUTION_STATUS.txt-141-Run ID: 20261020_141030
SPRINT_1_TEST_EXECUTION_STATUS.txt-142-Python: 3.14.6
SPRINT_1_TEST_EXECUTION_STATUS.txt-143-Database: finsight_test
SPRINT_1_TEST_EXECUTION_STATUS.txt-144-Recorded Git revision: 64f2637
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-146-Results:
SPRINT_1_TEST_EXECUTION_STATUS.txt-147-- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-148-- Full API suite: 55 passed, 10 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-149-- Evidence files:
SPRINT_1_TEST_EXECUTION_STATUS.txt:150:
test-results/FIN-15/20261020_141030_identity_authorization.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:151:
test-results/FIN-15/20261020_141030_full_api_suite.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:152:
test-results/FIN-15/run_20261020_141030_summary.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt-153-

SPRINT_1_TEST_EXECUTION_STATUS.txt-154-These results supersede earlier NOT RUN notes for the test execution performed
SPRINT_1_TEST_EXECUTION_STATUS.txt-155-in this run. They do not establish that every mapped test-plan case or the entire
SPRINT_1_TEST_EXECUTION_STATUS.txt:156:FIN-15 story is complete. Workspace-level authorization remains deferred.
--
FUNCTION_TEST_TRACEABILITY.txt-1-FinSight AI — Function/Test Traceability
FUNCTION_TEST_TRACEABILITY.txt-2-
FUNCTION_TEST_TRACEABILITY.txt:3:FIN-15 / FS-01-02 — platform authorization capability endpoint
FUNCTION_TEST_TRACEABILITY.txt-4-Function: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-5-Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
FUNCTION_TEST_TRACEABILITY.txt-6-Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
FUNCTION_TEST_TRACEABILITY.txt-7-Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt-8-Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mapped tests and confirming the expected behavior.
FUNCTION_TEST_TRACEABILITY.txt-9-
FUNCTION_TEST_TRACEABILITY.txt:10:FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
FUNCTION_TEST_TRACEABILITY.txt-11-Run ID: 20261020_141030
FUNCTION_TEST_TRACEABILITY.txt-12-Endpoint: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-13-
FUNCTION_TEST_TRACEABILITY.txt-14-Observed execution:
FUNCTION_TEST_TRACEABILITY.txt-15-- tests/test_identity_constraints.py: 3 passed, 4 warnings.
FUNCTION_TEST_TRACEABILITY.txt-16-- Full API suite: 55 passed, 10 warnings.
FUNCTION_TEST_TRACEABILITY.txt-17-- Both pytest commands exited with code 0.
FUNCTION_TEST_TRACEABILITY.txt-18-- Evidence:
FUNCTION_TEST_TRACEABILITY.txt:19:
test-results/FIN-15/20261020_141030_identity_authorization.log
FUNCTION_TEST_TRACEABILITY.txt:20:
test-results/FIN-15/20261020_141030_full_api_suite.log

FUNCTION_TEST_TRACEABILITY.txt:21:
test-results/FIN-15/run_20261020_141030_summary.txt
FUNCTION_TEST_TRACEABILITY.txt-22-
FUNCTION_TEST_TRACEABILITY.txt-23-Case-status guidance:
FUNCTION_TEST_TRACEABILITY.txt-24-- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt-25- test suite passed, but broader acceptance criteria must also be checked.

=== Authorization and permission test references ===
docs/requirements/traceability-stories.csv:2:FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout invalidates it; invalidcredentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001;TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:4:FS-01-03,FIN-14,LIVE JIRA VERIFIED 2026-10-19,Protect accounts and audit authentication,Sprint 1,Release 1 perJira

issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-10; FR-P1-11; FR-P1-12; FR-P9-13; NFR-G-08; NFR-G-11; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P9-02,Security events are auditable; repeated failures are throttled; MFA/session features are enabled only when configured. detected and limited.,TC_AUTHSEC_001; TC_AUTHSEC_002; TC_AUTHSEC_003; TC_INT_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_002=NOT RUN; TC_AUTHSEC_003=NOT RUN; TC_INT_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:6:FS-01-05,FIN-17,LIVE JIRA VERIFIED 2026-10-19,Meet identity security and accessibility requirements,Sprint 1,Release 1 per Jira issue,FR-P1-01; NFR-G-03; NFR-G-18; NFR-G-19; NFR-G-20; NFR-G-21; NFR-P1-01; NFR-P1-02; NFR-P1-03; NFR-P1-04; NFR-P1-05; NFR-P1-06,"No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:14:FS-02-08,FIN-25,LIVE JIRA VERIFIED 2026-10-19,"Keep dashboard responsive, isolated and freshness-aware",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-01; NFR-P2-02; NFR-P2-03; NFR-P2-04; NFR-P2-05; NFR-P8-04,Primary content meets agreed performance target; layouts work on supported screens; onlyauthorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001;

TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:45:FS-08-01,FIN-57,LIVE JIRA VERIFIED 2026-10-19,"Configure Ollama, model selection and inference parameters",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-01; FR-P8-02; FR-P8-03; FR-P8-04; FR-P8-05; FR-P8-12; FR-P8-14; FR-P8-16; NFR-G-08; NFR-G-13; NFR-G-22; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02,Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:49:FS-08-05,FIN-61,LIVE JIRA VERIFIED 2026-10-19,Secure and validate configuration changes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-14; FR-P8-16; NFR-G-03; NFR-G-07; NFR-G-08; NFR-G-14; NFR-G-22; NFR-G-26; NFR-P8-01; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02; NFR-P9-03,Secrets are referenced securely; config changes are audited; validation precedes activation; retrieval/index compatibility is checked. production unexpectedly.,TC_CFG_001; TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_INT_001; TC_TRACE_001,TC_CFG_001=NOT RUN; TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_INT_001=NOT RUN;TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user

read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:65:FS-11-04,FIN-75,LIVE JIRA VERIFIED 2026-10-19,Apply TDD and maintain unit/integration/E2E suites,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-07; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-27; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-04; NFR-P8-02; NFR-P9-02,"Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably. implementation where practical so that behavior is verified continuously.",TC_CI_001; TC_COV_001; TC_DB_001; TC_INT_001; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_COV_001=PASS; TC_DB_001=BLOCKED; TC_INT_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,IMPLEMENTATION_STATUS.txt; issue-specific paths in prior records,Acceptanceremains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:72:FS-11-11,FIN-82,LIVE JIRA VERIFIED 2026-10-19,"Document usability, AI use, licenses and data rights",Sprint 1,Release 1 per Jira issue,NFR-G-18; NFR-G-19; NFR-G-20; NFR-G-21; NFR-G-27; NFR-P1-06,AI-generated code is reviewed and tested; license/data rights are recorded; usability checks include accessibility and understandable failures. compliant.,TC_AUTHN_009; TC_ETH_001,TC_AUTHN_009=NOT RUN; TC_ETH_001=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:73:FS-11-12,FIN-83,LIVE JIRA VERIFIED 2026-10-19,"Add health checks, structured logs, retry and recovery runbook",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-06; NFR-G-07; NFR-G-08; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02;

NFR-P2-03; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-02; NFR-P7-04; NFR-P7-05; NFR-P8-04; NFR-P9-03,Health endpoints work; logs include run IDs and redact secrets; retries are bounded/idempotent; outage drill has recorded outcome. are diagnosable.,TC_BUILD_002; TC_DASH_002; TC_DB_001; TC_EXEC_001; TC_EXEC_002; TC_OPS_001; TC_OPS_002; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TRACE_001,TC_BUILD_002=BLOCKED; TC_DASH_002=NOT RUN; TC_DB_001=BLOCKED; TC_EXEC_001=NOT RUN; TC_EXEC_002=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-matrix.md:31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions| Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create asession, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |

docs/requirements/traceability-matrix.md:33:| FS-01-03 | [FIN-14](https://sandeephgowda8618.atlassian.net/browse/FIN-14) | Protect accounts and audit authentication | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-10, FR-P1-11, FR-P1-12, FR-P9-13, NFR-G-08, NFR-G-11, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P9-02 | Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:35:| FS-01-05 | [FIN-17](https://sandeephgowda8618.atlassian.net/browse/FIN-17) | Meet identity security and accessibility requirements | Sprint 1 | Release 1 per Jira issue | FR-P1-01, NFR-G-03, NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-P1-01, NFR-P1-02, NFR-P1-03, NFR-P1-04, NFR-P1-05, NFR-P1-06 | No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13,

NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05,FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:78:| FS-08-05 | [FIN-61](https://sandeephgowda8618.atlassian.net/browse/FIN-61) | Secure and validate configuration changes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-14, FR-P8-16, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-22, NFR-G-26, NFR-P8-01, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02, NFR-P9-03 | Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy

and safe accountadministration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:101:| FS-11-11 | [FIN-82](https://sandeephgowda8618.atlassian.net/browse/FIN-82) | Document usability, AI use, licenses and data rights | Sprint 1 | Release 1 per Jira issue | NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-G-27, NFR-P1-06 | AI-generated code is reviewed and tested, license/data rights are recorded, usability checks include accessibility and understandable failures. compliant. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |

docs/requirements/traceability-matrix.md:102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS,

TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002,TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL |
apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
docs/requirements/traceability-matrix.md:122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plansource refs |
FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role

enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers onlypart of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02,FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOTRUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has noorder-execution path,

sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED |— | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75,

FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004,TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. |

TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED |— | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs| No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED| — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02,FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorizedowners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
docs/requirements/traceability-matrix.md:377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
docs/requirements/traceability-matrix.md:378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label|

docs/requirements/traceability-matrix.md:416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs| No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001,TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
docs/requirements/traceability-matrix.md:449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | Nomapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among

the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19,test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOTRUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target and committed-SHA evidence are absent. | Unmapped to source story |
docs/requirements/traceability-matrix.md:458:| NFR-P1-05 | Information Disclosure | PDF p.5, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05| FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_004, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py,

apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:459:| NFR-P1-06 | Accessibility | PDF p.5, SRS P1 requirements | Identity and access | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/web/app/page.js, apps/web/tests/ui/auth.spec.js | Current code covers only part of this source requirement. | Preserve source story releaselabel |
docs/requirements/traceability-matrix.md:460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performancetarget, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — |

Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOTRUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04,FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01,FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and

workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS |NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05, FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs |

FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changesare auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,LiveJira JQL

verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py,Evidencesupports the current scoped behavior only.,Preserve source story release label docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials createa session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows

admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local operator CLI only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label
docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03;FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this sourcerequirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN;

TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional tradingDDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT

RUN; TC_AUTHZ_002=NOT RUN;TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01;FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inferencewith versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN;

TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundationscope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN;TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62;

FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized ownersmanage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02;

FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN;

TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03; FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74; FIN-75;FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
docs/requirements/traceability-requirements.csv:352:NFR-P1-05,Information Disclosure,PDF p.5; SRS P1 requirements,Identity and access,FS-01-01; FS-01-05,FIN-13; FIN-17,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_004; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:353:NFR-P1-06,Accessibility,PDF p.5; SRS P1 requirements,Identity and access,FS-01-05; FS-11-11,FIN-17; FIN-82,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/web/app/page.js; apps/web/tests/ui/auth.spec.js,Current code covers only part of this source requirement.,Preserve source story release label

docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001;TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01;FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label

docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive Changes,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05;

FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and cleardestructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001; TC_CFG_003;TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace dataremain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label

docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
FUNCTION_TEST_TRACEABILITY.txt:7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt:24:- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt:26:- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
FUNCTION_TEST_TRACEABILITY.txt:28:- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
FUNCTION_TEST_TRACEABILITY.txt:30:- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
FUNCTION_TEST_TRACEABILITY.txt:32:- TC_SYS_001: not established by the API suite alone; broader system acceptance remains

```
=== FIN-15 test implementation ===
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s) RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
```

(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

            "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
            (user_id, digest, session_expiry(5)),
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % cd
~/Documents/NVDIA_Play_Book/FinSight_AI && cat
test-results/FIN-15/20261020_141630_acceptance_review.txt
FIN-15 Acceptance Criteria Review
Tue Oct 20 14:16:30 IST 2026

=== FIN-15 references in project documents ===
IMPLEMENTATION_STATUS.txt-315-- CSV trailing-whitespace scan: 0 rows. `git diff
--check`: PASS, exit 0.
IMPLEMENTATION_STATUS.txt-316-GitHub-side limitation: `git show --check --format=
HEAD` against the existing root commit exits 2 with 1,323 diagnostics, including
immutable source PDFs and other pre-existing root-commit files. No source
PDF/SQL/diagram/test plan was edited. The targeted working diff passes `git diff
--check`; an incremental commit/push is needed so the next GitHub run checks only the
corrective diff. No commit, push, Jira update, or remote rerun was made. A new GitHub
Actions result is required before claiming the repair passed remotely; FIN-73/74/79
status is unchanged.
IMPLEMENTATION_STATUS.txt-317-Final review note (2026-10-19): `git diff --check`
exited 0 for the targeted workflow/CSV/script changes before coordination records were
appended. A later full `git diff --check` attempt timed out after 8 seconds (intermittent Git
responsiveness); direct trailing-whitespace scansof `.github/workflows/ci.yml`,
`docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both
updated coordination files found zero whitespace errors and all had final newlines. The
historical root-commit check result above remains distinct from the current worktree
check.
IMPLEMENTATION_STATUS.txt-318-
IMPLEMENTATION_STATUS.txt:319:FIN-15 / FS-01-02 — Enforce roles and protected
routes (2026-10-19)
IMPLEMENTATION_STATUS.txt-320-Status: BLOCKED pending role-scope decision;
implementation not started.
IMPLEMENTATION_STATUS.txt-321-Inspected relevant SRS access-control
requirements, canonical schema and reference seeds, FS-01-02 backlog,
four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001,
trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`,

POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
IMPLEMENTATION_STATUS.txt-322-Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorize minimal canonical workspace membership model.
IMPLEMENTATION_STATUS.txt-323-Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.
IMPLEMENTATION_STATUS.txt:324:Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
IMPLEMENTATION_STATUS.txt-325-
IMPLEMENTATION_STATUS.txt:326:FIN-15 verification update — 2026-10-20
IMPLEMENTATION_STATUS.txt-327-- PostgreSQL 17.6 is running locally.
IMPLEMENTATION_STATUS.txt-328-- Created and used the dedicated finsight_test database.
IMPLEMENTATION_STATUS.txt-329-- Applied apps/api/migrations/0001_auth_identity.sql successfully.
IMPLEMENTATION_STATUS.txt-330-- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
--
IMPLEMENTATION_STATUS.txt-332-- Full API test suite: 55 passed, 0 failed, 9 warnings.
IMPLEMENTATION_STATUS.txt-333-- git diff --check: no errors reported.

IMPLEMENTATION_STATUS.txt-334-- Warning: Starlette/httpx deprecation warnings remain.
IMPLEMENTATION_STATUS.txt-335-- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
IMPLEMENTATION_STATUS.txt:336:- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
IMPLEMENTATION_STATUS.txt-337-
IMPLEMENTATION_STATUS.txt:338:FIN-15 implementation update — 2026-10-20
IMPLEMENTATION_STATUS.txt-339-- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
IMPLEMENTATION_STATUS.txt-340-- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
IMPLEMENTATION_STATUS.txt-341-- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
IMPLEMENTATION_STATUS.txt-342-- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
IMPLEMENTATION_STATUS.txt:343:- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are checked.
IMPLEMENTATION_STATUS.txt-344-- No migrations, commits, pushes, or workspace schema changes performed by this patch script.
IMPLEMENTATION_STATUS.txt-345-
IMPLEMENTATION_STATUS.txt:346:FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
IMPLEMENTATION_STATUS.txt-347-Latest run: 20261020_141030
IMPLEMENTATION_STATUS.txt-348-Recorded revision: 64f2637
IMPLEMENTATION_STATUS.txt-349-Python: 3.14.6
IMPLEMENTATION_STATUS.txt-350-Database: finsight_test
--
IMPLEMENTATION_STATUS.txt-355-- Both pytest commands exited with code 0.
IMPLEMENTATION_STATUS.txt-356-- The test-run summary records Overall result: PASS.
IMPLEMENTATION_STATUS.txt-357-
IMPLEMENTATION_STATUS.txt-358-Evidence:

IMPLEMENTATION_STATUS.txt:359:-
test-results/FIN-15/20261020_141030_identity_authorization.log
IMPLEMENTATION_STATUS.txt:360:-
test-results/FIN-15/20261020_141030_full_api_suite.log
IMPLEMENTATION_STATUS.txt:361:-
test-results/FIN-15/run_20261020_141030_summary.txt
IMPLEMENTATION_STATUS.txt-362-
IMPLEMENTATION_STATUS.txt-363-The warnings were Starlette/httpx deprecations. The passing test suites establish
IMPLEMENTATION_STATUS.txt:364:the behavior exercised by those tests, not automatic completion of every FIN-15
IMPLEMENTATION_STATUS.txt-365-acceptance criterion. Workspace membership and resource-level authorization remain
IMPLEMENTATION_STATUS.txt-366-deferred under the approved platform-only scope. Earlier entries are retained as
IMPLEMENTATION_STATUS.txt-367-historical records; this addendum records the later successful run.
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-131-- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
SPRINT_1_TEST_EXECUTION_STATUS.txt-132-- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
SPRINT_1_TEST_EXECUTION_STATUS.txt-133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
SPRINT_1_TEST_EXECUTION_STATUS.txt-134-
SPRINT_1_TEST_EXECUTION_STATUS.txt:135:FIN-15 route-level authorization test update — 2026-10-20
SPRINT_1_TEST_EXECUTION_STATUS.txt-136-- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
SPRINT_1_TEST_EXECUTION_STATUS.txt-137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
SPRINT_1_TEST_EXECUTION_STATUS.txt-138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
SPRINT_1_TEST_EXECUTION_STATUS.txt-139-
SPRINT_1_TEST_EXECUTION_STATUS.txt:140:FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)
SPRINT_1_TEST_EXECUTION_STATUS.txt-141-Run ID: 20261020_141030

SPRINT_1_TEST_EXECUTION_STATUS.txt-142-Python: 3.14.6
SPRINT_1_TEST_EXECUTION_STATUS.txt-143-Database: finsight_test
SPRINT_1_TEST_EXECUTION_STATUS.txt-144-Recorded Git revision: 64f2637
--
SPRINT_1_TEST_EXECUTION_STATUS.txt-146-Results:
SPRINT_1_TEST_EXECUTION_STATUS.txt-147-- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-148-- Full API suite: 55 passed, 10 warnings; exit code 0.
SPRINT_1_TEST_EXECUTION_STATUS.txt-149-- Evidence files:
SPRINT_1_TEST_EXECUTION_STATUS.txt:150:
test-results/FIN-15/20261020_141030_identity_authorization.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:151:
test-results/FIN-15/20261020_141030_full_api_suite.log
SPRINT_1_TEST_EXECUTION_STATUS.txt:152:
test-results/FIN-15/run_20261020_141030_summary.txt
SPRINT_1_TEST_EXECUTION_STATUS.txt-153-
SPRINT_1_TEST_EXECUTION_STATUS.txt-154-These results supersede earlier NOT RUN notes for the test execution performed
SPRINT_1_TEST_EXECUTION_STATUS.txt-155-in this run. They do not establish that every mapped test-plan case or the entire
SPRINT_1_TEST_EXECUTION_STATUS.txt:156:FIN-15 story is complete. Workspace-level authorization remains deferred.
--
FUNCTION_TEST_TRACEABILITY.txt-1-FinSight AI — Function/Test Traceability
FUNCTION_TEST_TRACEABILITY.txt-2-
FUNCTION_TEST_TRACEABILITY.txt:3:FIN-15 / FS-01-02 — platform authorization capability endpoint
FUNCTION_TEST_TRACEABILITY.txt-4-Function: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-5-Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
FUNCTION_TEST_TRACEABILITY.txt-6-Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
FUNCTION_TEST_TRACEABILITY.txt-7-Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt-8-Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mapped tests and confirming the expected behavior.

FUNCTION_TEST_TRACEABILITY.txt-9-
FUNCTION_TEST_TRACEABILITY.txt:10:FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
FUNCTION_TEST_TRACEABILITY.txt-11-Run ID: 20261020_141030
FUNCTION_TEST_TRACEABILITY.txt-12-Endpoint: GET /platform/admin/capability
FUNCTION_TEST_TRACEABILITY.txt-13-
FUNCTION_TEST_TRACEABILITY.txt-14-Observed execution:
FUNCTION_TEST_TRACEABILITY.txt-15-- tests/test_identity_constraints.py: 3 passed, 4 warnings.
FUNCTION_TEST_TRACEABILITY.txt-16-- Full API suite: 55 passed, 10 warnings.
FUNCTION_TEST_TRACEABILITY.txt-17-- Both pytest commands exited with code 0.
FUNCTION_TEST_TRACEABILITY.txt-18-- Evidence:
FUNCTION_TEST_TRACEABILITY.txt:19:
test-results/FIN-15/20261020_141030_identity_authorization.log
FUNCTION_TEST_TRACEABILITY.txt:20:
test-results/FIN-15/20261020_141030_full_api_suite.log
FUNCTION_TEST_TRACEABILITY.txt:21:
test-results/FIN-15/run_20261020_141030_summary.txt
FUNCTION_TEST_TRACEABILITY.txt-22-
FUNCTION_TEST_TRACEABILITY.txt-23-Case-status guidance:
FUNCTION_TEST_TRACEABILITY.txt-24-- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt-25- test suite passed, but broader acceptance criteria must also be checked.

=== Authorization and permission test references ===
docs/requirements/traceability-stories.csv:2:FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout invalidates it; invalidcredentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001;TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py;

apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:4:FS-01-03,FIN-14,LIVE JIRA VERIFIED 2026-10-19,Protect accounts and audit authentication,Sprint 1,Release 1 perJira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-10; FR-P1-11; FR-P1-12; FR-P9-13; NFR-G-08; NFR-G-11; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P9-02,Security events are auditable; repeated failures are throttled; MFA/session features are enabled only when configured. detected and limited.,TC_AUTHSEC_001; TC_AUTHSEC_002; TC_AUTHSEC_003; TC_INT_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_002=NOT RUN; TC_AUTHSEC_003=NOT RUN; TC_INT_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:6:FS-01-05,FIN-17,LIVE JIRA VERIFIED 2026-10-19,Meet identity security and accessibility requirements,Sprint 1,Release 1 per Jira issue,FR-P1-01; NFR-G-03; NFR-G-18; NFR-G-19; NFR-G-20; NFR-G-21;

NFR-P1-01; NFR-P1-02; NFR-P1-03; NFR-P1-04; NFR-P1-05; NFR-P1-06,"No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:14:FS-02-08,FIN-25,LIVE JIRA VERIFIED 2026-10-19,"Keep dashboard responsive, isolated and freshness-aware",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-01; NFR-P2-02; NFR-P2-03; NFR-P2-04; NFR-P2-05; NFR-P8-04,Primary content meets agreed performance target; layouts work on supported screens; onlyauthorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:45:FS-08-01,FIN-57,LIVE JIRA VERIFIED 2026-10-19,"Configure Ollama, model selection and inference parameters",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-01; FR-P8-02; FR-P8-03; FR-P8-04; FR-P8-05; FR-P8-12; FR-P8-14; FR-P8-16; NFR-G-08; NFR-G-13; NFR-G-22; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02,Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:49:FS-08-05,FIN-61,LIVE JIRA VERIFIED 2026-10-19,Secure and validate configuration changes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-14; FR-P8-16; NFR-G-03; NFR-G-07; NFR-G-08;

NFR-G-14; NFR-G-22; NFR-G-26; NFR-P8-01; NFR-P8-02; NFR-P8-03; NFR-P8-04; NFR-P8-05; NFR-P8-06; NFR-P8-07; NFR-P8-08; NFR-P9-02; NFR-P9-03,Secrets are referenced securely; config changes are audited; validation precedes activation; retrieval/index compatibility is checked. production unexpectedly.,TC_CFG_001; TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_INT_001; TC_TRACE_001,TC_CFG_001=NOT RUN; TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_INT_001=NOT RUN;TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:65:FS-11-04,FIN-75,LIVE JIRA VERIFIED 2026-10-19,Apply TDD and maintain unit/integration/E2E suites,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-07; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-27; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-04; NFR-P8-02; NFR-P9-02,"Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably. implementation where practical so that behavior is verified continuously.",TC_CI_001; TC_COV_001; TC_DB_001; TC_INT_001; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_COV_001=PASS; TC_DB_001=BLOCKED; TC_INT_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN;

TC_TEST_001=PASS,PARTIAL,IMPLEMENTATION_STATUS.txt; issue-specific paths in prior records,Acceptanceremains incomplete or externally unverified; see implementation record.
docs/requirements/traceability-stories.csv:72:FS-11-11,FIN-82,LIVE JIRA VERIFIED 2026-10-19,"Document usability, AI use, licenses and data rights",Sprint 1,Release 1 per Jira issue,NFR-G-18; NFR-G-19; NFR-G-20; NFR-G-21; NFR-G-27; NFR-P1-06,AI-generated code is reviewed and tested; license/data rights are recorded; usability checks include accessibility and understandable failures. compliant.,TC_AUTHN_009; TC_ETH_001,TC_AUTHN_009=NOT RUN; TC_ETH_001=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-stories.csv:73:FS-11-12,FIN-83,LIVE JIRA VERIFIED 2026-10-19,"Add health checks, structured logs, retry and recovery runbook",Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-06; FR-P2-08; FR-P2-39; FR-P8-02; FR-P8-12; NFR-G-04; NFR-G-06; NFR-G-07; NFR-G-08; NFR-G-11; NFR-G-13; NFR-G-14; NFR-G-15; NFR-G-16; NFR-G-17; NFR-G-23; NFR-G-26; NFR-G-30; NFR-G-31; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P2-02; NFR-P2-03; NFR-P3-05; NFR-P3-06; NFR-P3-07; NFR-P4-01; NFR-P4-06; NFR-P7-01; NFR-P7-02; NFR-P7-04; NFR-P7-05; NFR-P8-04; NFR-P9-03,Health endpoints work; logs include run IDs and redact secrets; retries are bounded/idempotent; outage drill has recorded outcome. are diagnosable.,TC_BUILD_002; TC_DASH_002; TC_DB_001; TC_EXEC_001; TC_EXEC_002; TC_OPS_001; TC_OPS_002; TC_OPS_003; TC_SEC_002; TC_SYS_001; TC_TRACE_001,TC_BUILD_002=BLOCKED; TC_DASH_002=NOT RUN; TC_DB_001=BLOCKED; TC_EXEC_001=NOT RUN; TC_EXEC_002=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_OPS_003=NOT RUN; TC_SEC_002=BLOCKED; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.
docs/requirements/traceability-matrix.md:31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions| Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create asession, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL

| apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:33:| FS-01-03 | [FIN-14](https://sandeephgowda8618.atlassian.net/browse/FIN-14) | Protect accounts and audit authentication | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-10, FR-P1-11, FR-P1-12, FR-P9-13, NFR-G-08, NFR-G-11, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P9-02 | Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |

docs/requirements/traceability-matrix.md:35:| FS-01-05 | [FIN-17](https://sandeephgowda8618.atlassian.net/browse/FIN-17) | Meet identity security and accessibility requirements | Sprint 1 | Release 1 per Jira issue | FR-P1-01, NFR-G-03, NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-P1-01, NFR-P1-02, NFR-P1-03, NFR-P1-04, NFR-P1-05, NFR-P1-06 | No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05,FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN,

TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | docs/requirements/traceability-matrix.md:78:| FS-08-05 | [FIN-61](https://sandeephgowda8618.atlassian.net/browse/FIN-61) | Secure and validate configuration changes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-14, FR-P8-16, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-22, NFR-G-26, NFR-P8-01, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02, NFR-P9-03 | Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. | docs/requirements/traceability-matrix.md:83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe accountadministration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | docs/requirements/traceability-matrix.md:94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04,

NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:101:| FS-11-11 | [FIN-82](https://sandeephgowda8618.atlassian.net/browse/FIN-82) | Document usability, AI use, licenses and data rights | Sprint 1 | Release 1 per Jira issue | NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-G-27, NFR-P1-06 | AI-generated code is reviewed and tested, license/data rights are recorded, usability checks include accessibility and understandable failures. compliant. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a

session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002,TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 |

TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
docs/requirements/traceability-matrix.md:122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plansource refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers onlypart of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02,FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) |

Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOTRUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has noorder-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT

RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED |— | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004,TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |

docs/requirements/traceability-matrix.md:343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED |— | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs| No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED| — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02,FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorizedowners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |

docs/requirements/traceability-matrix.md:377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
docs/requirements/traceability-matrix.md:378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label|
docs/requirements/traceability-matrix.md:416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs| No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001,TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL

| apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
docs/requirements/traceability-matrix.md:449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | Nomapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19,test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not

infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOTRUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target and committed-SHA evidence are absent. | Unmapped to source story | docs/requirements/traceability-matrix.md:458:| NFR-P1-05 | Information Disclosure | PDF p.5, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05| FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_004, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label | docs/requirements/traceability-matrix.md:459:| NFR-P1-06 | Accessibility | PDF p.5, SRS P1 requirements | Identity and access | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/web/app/page.js, apps/web/tests/ui/auth.spec.js | Current code covers only part of this source requirement. | Preserve source story releaselabel | docs/requirements/traceability-matrix.md:460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |

docs/requirements/traceability-matrix.md:461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performancetarget, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOTRUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04,FS-09-05 |

FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01,FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS |NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05, FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — |

Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT

IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changesare auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,LiveJira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py;

apps/api/tests/test_auth.py,Evidencesupports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials createa session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local operator CLI only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label
docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label

docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03;FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this sourcerequirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT

RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional tradingDDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN;TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01;FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source

refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inferencewith versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundationscope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN;TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a

controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized ownersmanage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration

respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25;

FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03; FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74; FIN-75;FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story
docs/requirements/traceability-requirements.csv:352:NFR-P1-05,Information Disclosure,PDF p.5; SRS P1 requirements,Identity and access,FS-01-01; FS-01-05,FIN-13; FIN-17,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that

login is safe and usable.",TC_AUTHN_002; TC_AUTHN_004; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:353:NFR-P1-06,Accessibility,PDF p.5; SRS P1 requirements,Identity and access,FS-01-05; FS-11-11,FIN-17; FIN-82,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/web/app/page.js; apps/web/tests/ui/auth.spec.js,Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001;TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label

docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01;FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT

IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive Changes,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05; FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and cleardestructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001; TC_CFG_003;TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003;

TC_INT_001; TC_PRIV_001; TC_PRIV_002;
TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;
TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN;
TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT
IMPLEMENTED,—,Mapped foundation scope is absent from the current
implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change
Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and
reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19;
test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege
changes are auditable; data lifecycle follows retention policy. sensitive-action checks
and clear destructive-change confirmation so that personal and workspace dataremain
protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003;
TC_INT_001; TC_PRIV_001; TC_PRIV_002;
TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;
TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN;
TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT
IMPLEMENTED,—,Mapped foundation scope is absent from the current
implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative
Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and
reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified
2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail;
privilege changes are auditable; data lifecycle follows retention policy. sensitive-action
checks and clear destructive-change confirmation so that personal and workspace data
remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002;
TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002;
TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;
TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN;
TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT
IMPLEMENTED,—,Mapped foundation scope is absent from the current
implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF
p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03;
FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source
refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are
auditable; data lifecycle follows retention policy. sensitive-action checks and clear
destructive-change confirmation so that personal and workspace data remain
protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003;
TC_INT_001; TC_PRIV_001; TC_PRIV_002;

TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
FUNCTION_TEST_TRACEABILITY.txt:7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
FUNCTION_TEST_TRACEABILITY.txt:24:- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
FUNCTION_TEST_TRACEABILITY.txt:26:- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
FUNCTION_TEST_TRACEABILITY.txt:28:- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
FUNCTION_TEST_TRACEABILITY.txt:30:- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
FUNCTION_TEST_TRACEABILITY.txt:32:- TC_SYS_001: not established by the API suite alone; broader system acceptance remains

=== FIN-15 test implementation ===
```
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s, %s) RETURNING user_id",
```

```
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
```

```
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/platform/admin/capability")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/platform/admin/capability",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/platform/admin/capability",
                cookies={SESSION_COOKIE: tokens[0]},
            )
            assert allowed.status_code == 200
            assert allowed.json() == {"permission": "platform.admin", "allowed": True}

            denied = client.get(
                "/platform/admin/capability",
                cookies={SESSION_COOKIE: tokens[1]},
```

```
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))


def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))

=== Authorization endpoint and dependency ===
101-            return user
102-    except psycopg.Error as exc:
```

```
103-        raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
104-
105-
106-CurrentUser = Annotated[dict[str, Any], Depends(get_current_user)]
107-
108-
109:def require_permission(permission_key: str):
110-    """Build a deny-by-default backend permission dependency."""
111-    def dependency(user: CurrentUser) -> dict[str, Any]:
112-        if permission_key not in user.get("permissions", []):
113-            raise HTTPException(status_code=status.HTTP_403_FORBIDDEN,
detail="Permission denied")
114-        return user
115-
116-    return dependency
117-
118-
119-@app.post("/auth/login", response_model=UserView)
120-def login(payload: LoginRequest, request: Request, response: Response) ->
UserView:
121-    _check_origin(request)
122-    email = payload.email.strip().lower()
123-    try:
124-        with connect() as conn, conn.cursor(row_factory=dict_row) as cur:
125-            cur.execute(
126-                """SELECT user_id, email, display_name, password_hash
127-                   FROM users WHERE lower(email) = %s AND account_status = 'active'
128-                     AND deleted_at IS NULL""",
129-                (email,),
130-            )
131-            user = cur.fetchone()
132-            if not user or not user["password_hash"]:
133-                verify_password(DUMMY_PASSWORD_HASH, payload.password)
--
176-    return response
177-
178-
179-@app.get("/auth/me", response_model=UserView)
180-def who_am_i(user: CurrentUser) -> UserView:
```

```
181-    return UserView(**user)
182-
183-
184:@app.get("/platform/admin/capability")
185-def platform_admin_capability(
186:    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
187-) -> dict[str, str | bool]:
188-    """Minimal capability endpoint proving platform-admin authorization at the API
boundary."""
189-    return {"permission": "platform.admin", "allowed": True}
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

185-def platform_admin_capability(
186:    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
187-) -> dict[str, str | bool]:
188-    """Minimal capability endpoint proving platform-admin authorization at the API
boundary."""
189-    return {"permission": "platform.admin", "allowed": True}
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI && grep -n -E
'platform/admin/capability|admin/authorization/capabilities|require_permission|test_platf
orm_permission_is_resolved' apps/api/app/main.py
apps/api/tests/test_identity_constraints.py

apps/api/app/main.py:109:def require_permission(permission_key: str):
apps/api/app/main.py:184:@app.get("/api/v1/admin/authorization/capabilities")
apps/api/app/main.py:187:    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
apps/api/tests/test_identity_constraints.py:11:from app.main import SESSION_COOKIE,
app, require_permission
apps/api/tests/test_identity_constraints.py:45:def
test_platform_permission_is_resolved_from_database_role_and_session():
apps/api/tests/test_identity_constraints.py:72:            anonymous =
client.get("/api/v1/admin/authorization/capabilities")
apps/api/tests/test_identity_constraints.py:77:
"/api/v1/admin/authorization/capabilities",
```

```
apps/api/tests/test_identity_constraints.py:83:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:88:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:99:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:117:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:182:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:197:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:260:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:276:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:316:#
"/api/v1/admin/authorization/capabilities",
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
sed -n '160,215p' apps/api/app/main.py
sed -n '1,135p' apps/api/tests/test_identity_constraints.py
sed -n '160,290p' apps/api/tests/test_identity_constraints.py

@app.post("/auth/logout", status_code=204)
def logout(request: Request, response: Response,
          session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] =
None) -> Response:
    _check_origin(request)
    if session_token:
        try:
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    """UPDATE auth_sessions SET revoked_at = %s, revoke_reason = 'logout'
                       WHERE refresh_token_hash = %s AND revoked_at IS NULL""",
                    (datetime.now(UTC), token_digest(session_token)),
                )
        except psycopg.Error as exc:
            raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
```

```
    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
    response.status_code = status.HTTP_204_NO_CONTENT
    return response


@app.get("/auth/me", response_model=UserView)
def who_am_i(user: CurrentUser) -> UserView:
    return UserView(**user)


@app.get("/api/v1/admin/authorization/capabilities")
def platform_admin_capabilities(
    request: Request,
    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
) -> dict[str, Any]:
    """Return the authenticated caller's database-backed platform capabilities."""

    supplied_request_id = request.headers.get("request_id", "").strip()
    if supplied_request_id and (
        len(supplied_request_id) > 128
        or any(ord(char) < 32 or ord(char) == 127 for char in supplied_request_id)
    ):
        raise HTTPException(status_code=400, detail="Invalid request_id")

    # Always issue a server-generated canonical request ID.
    request_id = f"req_{secrets.token_urlsafe(12)}"
    correlation_id = supplied_request_id or request_id
    permissions = sorted(set(_authorized.get("permissions", [])))
    capabilities = (
        ["inspect_authorization_policy"]
        if "platform.admin" in permissions
        else []
    )

    return {
        "data": {
            "subject": {
                "user_id": str(_authorized["user_id"]),
```

```
            "platform_role_code": _authorized.get("role_key"),
        },
        "effective_permissions": permissions,
        "capabilities": capabilities,
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s) RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
```

```
            "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
            (user_id, digest, session_expiry(5)),
        )
        cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
        cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
        assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
```

```
        )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
            )
            #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
            correlated = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
                headers={"request_id": "client-correlation-123"},
            )
            assert correlated.status_code == 200
            correlated_body = correlated.json()
            assert correlated_body["request_id"].startswith("req_")
            assert correlated_body["request_id"] != "client-correlation-123"
            assert correlated_body["correlation_id"] == "client-correlation-123"

            malformed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
                headers={"request_id": "x" * 129},
            )
            assert malformed.status_code == 400

            # The platform-admin user should be allowed to inspect the authorization policy.
            assert allowed.status_code == 200
```

```
        body = allowed.json()
        assert body["data"]["subject"]["user_id"] == str(admin_id)
        assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
        assert body["data"]["effective_permissions"] == ["platform.admin"]
        assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
        assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
        assert body["request_id"].startswith("req_")
        assert body["correlation_id"] == body["request_id"]

        denied = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[1]},
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))



def test_permission_grant_revocation_takes_effect_on_next_request():
    suffix = uuid4().hex
    role_key = f"test-admin-{suffix}"
    email = f"permission-revocation-{suffix}@example.test"
    user_id = None
    role_id = None
    permission_id = None
        )
        cur.execute(
            """
            INSERT INTO users (email, display_name, platform_role_id)
            VALUES (%s, %s, %s)
            RETURNING user_id
            """,
            (email, "Synthetic Permission Revocation User", role_id),
        )
        user_id = cur.fetchone()[0]
```

```
            token, digest = new_session_token()
            cur.execute(
                """
                INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
                VALUES (%s, %s, %s)
                """,
                (user_id, digest, session_expiry(5)),
            )

        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
            ]

            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "DELETE FROM role_permissions WHERE role_id = %s AND
permission_id = %s",
                    (role_id, permission_id),
                )

            next_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert next_response.status_code == 403
            assert next_response.json() == {"detail": "Permission denied"}

    finally:
        with connect() as conn, conn.cursor() as cur:
            if user_id is not None:
                cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            if role_id is not None:
                cur.execute("DELETE FROM roles WHERE role_id = %s", (role_id,))
```

```
def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))




def test_platform_role_revocation_takes_effect_on_next_request():
    email = f"revoked-platform-admin-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "SELECT role_id FROM roles WHERE role_key = 'platform_admin' AND scope
= 'platform'"
        )
        row = cur.fetchone()
        assert row is not None, "Platform-admin role must exist"
        admin_role_id = row[0]
```

```
    cur.execute(
        "INSERT INTO users (email, display_name, platform_role_id) "
        "VALUES (%s, %s, %s) RETURNING user_id",
        (email, "Synthetic Revocation Test", admin_role_id),
    )
    user_id = cur.fetchone()[0]
    token, digest = new_session_token()
    cur.execute(
        "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) "
        "VALUES (%s, %s, %s)",
        (user_id, digest, session_expiry(5)),
    )

try:
    with TestClient(app) as client:
        first_response = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: token},
        )
        assert first_response.status_code == 200
        assert first_response.json()["data"]["effective_permissions"] == [
            "platform.admin"
        ]

        # Revoke this test user's role without changing shared role permissions.
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "UPDATE users SET platform_role_id = NULL WHERE user_id = %s",
                (user_id,),
            )

        next_response = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: token},
        )
        assert next_response.status_code == 403
        assert next_response.json() == {"detail": "Permission denied"}
finally:
    with connect() as conn, conn.cursor() as cur:
        cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
```

```
# def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
#     with connect() as conn, conn.cursor() as cur:
#         cur.execute(
#         """
#         SELECT u.user_id, s.refresh_token_hash
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

188-    """Minimal capability endpoint proving platform-admin authorization at the API
boundary."""
189-    return {"permission": "platform.admin", "allowed": True}
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI && grep -n -E
'platform/admin/capability|admin/authorization/capabilities|require_permission|test_platf
orm_permission_is_resolved' apps/api/app/main.py
apps/api/tests/test_identity_constraints.py

apps/api/app/main.py:109:def require_permission(permission_key: str):
apps/api/app/main.py:184:@app.get("/api/v1/admin/authorization/capabilities")
apps/api/app/main.py:187:    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
apps/api/tests/test_identity_constraints.py:11:from app.main import SESSION_COOKIE,
app, require_permission
apps/api/tests/test_identity_constraints.py:45:def
test_platform_permission_is_resolved_from_database_role_and_session():
apps/api/tests/test_identity_constraints.py:72:            anonymous =
client.get("/api/v1/admin/authorization/capabilities")
apps/api/tests/test_identity_constraints.py:77:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:83:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:88:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:99:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:117:
"/api/v1/admin/authorization/capabilities",
```

```
apps/api/tests/test_identity_constraints.py:182:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:197:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:260:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:276:
"/api/v1/admin/authorization/capabilities",
apps/api/tests/test_identity_constraints.py:316:#
"/api/v1/admin/authorization/capabilities",
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
sed -n '160,215p' apps/api/app/main.py
sed -n '1,135p' apps/api/tests/test_identity_constraints.py
sed -n '160,290p' apps/api/tests/test_identity_constraints.py

@app.post("/auth/logout", status_code=204)
def logout(request: Request, response: Response,
          session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] =
None) -> Response:
    _check_origin(request)
    if session_token:
        try:
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    """UPDATE auth_sessions SET revoked_at = %s, revoke_reason = 'logout'
                       WHERE refresh_token_hash = %s AND revoked_at IS NULL""",
                    (datetime.now(UTC), token_digest(session_token)),
                )
        except psycopg.Error as exc:
            raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
    response.status_code = status.HTTP_204_NO_CONTENT
    return response


@app.get("/auth/me", response_model=UserView)
def who_am_i(user: CurrentUser) -> UserView:
    return UserView(**user)
```

```
@app.get("/api/v1/admin/authorization/capabilities")
def platform_admin_capabilities(
    request: Request,
    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
) -> dict[str, Any]:
    """Return the authenticated caller's database-backed platform capabilities."""

    supplied_request_id = request.headers.get("request_id", "").strip()
    if supplied_request_id and (
        len(supplied_request_id) > 128
        or any(ord(char) < 32 or ord(char) == 127 for char in supplied_request_id)
    ):
        raise HTTPException(status_code=400, detail="Invalid request_id")

    # Always issue a server-generated canonical request ID.
    request_id = f"req_{secrets.token_urlsafe(12)}"
    correlation_id = supplied_request_id or request_id
    permissions = sorted(set(_authorized.get("permissions", [])))
    capabilities = (
        ["inspect_authorization_policy"]
        if "platform.admin" in permissions
        else []
    )

    return {
        "data": {
            "subject": {
                "user_id": str(_authorized["user_id"]),
                "platform_role_code": _authorized.get("role_key"),
            },
            "effective_permissions": permissions,
            "capabilities": capabilities,
from __future__ import annotations

from uuid import uuid4

import psycopg
```

```
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s) RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
```

```
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
```

```
        cookies={SESSION_COOKIE: "invalid-session-token"},
    )
    assert invalid_session.status_code == 401

    allowed = client.get(
        "/api/v1/admin/authorization/capabilities",
        cookies={SESSION_COOKIE: tokens[0]},
    )
    #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
    correlated = client.get(
        "/api/v1/admin/authorization/capabilities",
        cookies={SESSION_COOKIE: tokens[0]},
        headers={"request_id": "client-correlation-123"},
    )
    assert correlated.status_code == 200
    correlated_body = correlated.json()
    assert correlated_body["request_id"].startswith("req_")
    assert correlated_body["request_id"] != "client-correlation-123"
    assert correlated_body["correlation_id"] == "client-correlation-123"

    malformed = client.get(
        "/api/v1/admin/authorization/capabilities",
        cookies={SESSION_COOKIE: tokens[0]},
        headers={"request_id": "x" * 129},
    )
    assert malformed.status_code == 400

    # The platform-admin user should be allowed to inspect the authorization policy.
    assert allowed.status_code == 200
    body = allowed.json()
    assert body["data"]["subject"]["user_id"] == str(admin_id)
    assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
    assert body["data"]["effective_permissions"] == ["platform.admin"]
    assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
    assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
    assert body["request_id"].startswith("req_")
    assert body["correlation_id"] == body["request_id"]

    denied = client.get(
```

```
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[1]},
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))



def test_permission_grant_revocation_takes_effect_on_next_request():
    suffix = uuid4().hex
    role_key = f"test-admin-{suffix}"
    email = f"permission-revocation-{suffix}@example.test"
    user_id = None
    role_id = None
    permission_id = None
        )
        cur.execute(
            """
            INSERT INTO users (email, display_name, platform_role_id)
            VALUES (%s, %s, %s)
            RETURNING user_id
            """,
            (email, "Synthetic Permission Revocation User", role_id),
        )
        user_id = cur.fetchone()[0]

        token, digest = new_session_token()
        cur.execute(
            """
            INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
            VALUES (%s, %s, %s)
            """,
            (user_id, digest, session_expiry(5)),
        )
```

```
        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
            ]

            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "DELETE FROM role_permissions WHERE role_id = %s AND
permission_id = %s",
                    (role_id, permission_id),
                )

            next_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert next_response.status_code == 403
            assert next_response.json() == {"detail": "Permission denied"}

    finally:
        with connect() as conn, conn.cursor() as cur:
            if user_id is not None:
                cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            if role_id is not None:
                cur.execute("DELETE FROM roles WHERE role_id = %s", (role_id,))

def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
```

```
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))




def test_platform_role_revocation_takes_effect_on_next_request():
    email = f"revoked-platform-admin-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "SELECT role_id FROM roles WHERE role_key = 'platform_admin' AND scope
= 'platform'"
        )
        row = cur.fetchone()
        assert row is not None, "Platform-admin role must exist"
        admin_role_id = row[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) "
            "VALUES (%s, %s, %s) RETURNING user_id",
            (email, "Synthetic Revocation Test", admin_role_id),
        )
        user_id = cur.fetchone()[0]
        token, digest = new_session_token()
        cur.execute(
            "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) "
            "VALUES (%s, %s, %s)",
```

```
            (user_id, digest, session_expiry(5)),
        )

    try:
        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
            ]

            # Revoke this test user's role without changing shared role permissions.
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "UPDATE users SET platform_role_id = NULL WHERE user_id = %s",
                    (user_id,),
                )

            next_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert next_response.status_code == 403
            assert next_response.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


# def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
#     with connect() as conn, conn.cursor() as cur:
#         cur.execute(
#         """
#         SELECT u.user_id, s.refresh_token_hash
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
sed -n '160,215p' apps/api/app/main.py
sed -n '1,135p' apps/api/tests/test_identity_constraints.py
```

```
sed -n '160,290p' apps/api/tests/test_identity_constraints.py

@app.post("/auth/logout", status_code=204)
def logout(request: Request, response: Response,
          session_token: Annotated[str | None, Cookie(alias=SESSION_COOKIE)] =
None) -> Response:
    _check_origin(request)
    if session_token:
        try:
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    """UPDATE auth_sessions SET revoked_at = %s, revoke_reason = 'logout'
                       WHERE refresh_token_hash = %s AND revoked_at IS NULL""",
                    (datetime.now(UTC), token_digest(session_token)),
                )
        except psycopg.Error as exc:
            raise HTTPException(status_code=503, detail="Authentication service
unavailable") from exc
    response.delete_cookie(SESSION_COOKIE, path="/", httponly=True,
secure=_secure_cookie(), samesite="lax")
    response.status_code = status.HTTP_204_NO_CONTENT
    return response


@app.get("/auth/me", response_model=UserView)
def who_am_i(user: CurrentUser) -> UserView:
    return UserView(**user)


@app.get("/api/v1/admin/authorization/capabilities")
def platform_admin_capabilities(
    request: Request,
    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
) -> dict[str, Any]:
    """Return the authenticated caller's database-backed platform capabilities."""

    supplied_request_id = request.headers.get("request_id", "").strip()
    if supplied_request_id and (
        len(supplied_request_id) > 128
```

```
        or any(ord(char) < 32 or ord(char) == 127 for char in supplied_request_id)
    ):
        raise HTTPException(status_code=400, detail="Invalid request_id")

    # Always issue a server-generated canonical request ID.
    request_id = f"req_{secrets.token_urlsafe(12)}"
    correlation_id = supplied_request_id or request_id
    permissions = sorted(set(_authorized.get("permissions", [])))
    capabilities = (
        ["inspect_authorization_policy"]
        if "platform.admin" in permissions
        else []
    )

    return {
        "data": {
            "subject": {
                "user_id": str(_authorized["user_id"]),
                "platform_role_code": _authorized.get("role_key"),
            },
            "effective_permissions": permissions,
            "capabilities": capabilities,
from __future__ import annotations

from uuid import uuid4

import psycopg
import pytest
from fastapi.testclient import TestClient

from app.auth import new_session_token, session_expiry
from app.database import connect
from app.main import SESSION_COOKIE, app, require_permission


def test_identity_schema_rejects_duplicate_email_and_cascades_sessions():
    email = f"constraint-{uuid4().hex}@example.com"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
```

```
            "INSERT INTO users (email, password_hash, display_name) VALUES (%s, %s,
%s) RETURNING user_id",
            (email, "synthetic-hash", "Synthetic Constraint Test"),
        )
        user_id = cur.fetchone()[0]

    try:
        with pytest.raises(psycopg.errors.UniqueViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute(
                    "INSERT INTO users (email, password_hash, display_name) VALUES (%s,
%s, %s)",
                    (email.upper(), "synthetic-hash", "Duplicate Synthetic Test"),
                )

        _, digest = new_session_token()
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (user_id, digest, session_expiry(5)),
            )
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("SELECT count(*) FROM auth_sessions WHERE user_id = %s",
(user_id,))
            assert cur.fetchone()[0] == 0
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


def test_platform_permission_is_resolved_from_database_role_and_session():
    admin_email = f"platform-admin-{uuid4().hex}@example.test"
    user_email = f"unprivileged-{uuid4().hex}@example.test"
    tokens = []
    with connect() as conn, conn.cursor() as cur:
        cur.execute("SELECT role_id FROM roles WHERE role_key = 'platform_admin'
AND scope = 'platform'")
        admin_role_id = cur.fetchone()[0]
        cur.execute(
```

```
            "INSERT INTO users (email, display_name, platform_role_id) VALUES (%s, %s,
%s) RETURNING user_id",
            (admin_email, "Synthetic Platform Admin", admin_role_id),
        )
        admin_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, %s) RETURNING
user_id",
            (user_email, "Synthetic Standard User"),
        )
        user_id = cur.fetchone()[0]
        for owner_id in (admin_id, user_id):
            token, digest = new_session_token()
            tokens.append(token)
            cur.execute(
                "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
VALUES (%s, %s, %s)",
                (owner_id, digest, session_expiry(5)),
            )

    try:
        with TestClient(app) as client:
            anonymous = client.get("/api/v1/admin/authorization/capabilities")
            assert anonymous.status_code == 401
            assert anonymous.json() == {"detail": "Authentication required"}

            invalid_session = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: "invalid-session-token"},
            )
            assert invalid_session.status_code == 401

            allowed = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: tokens[0]},
            )
            #₹ The request_id header is optional, but if supplied it must be validated and
preserved as the correlation_id.
            correlated = client.get(
                "/api/v1/admin/authorization/capabilities",
```

```
            cookies={SESSION_COOKIE: tokens[0]},
            headers={"request_id": "client-correlation-123"},
        )
        assert correlated.status_code == 200
        correlated_body = correlated.json()
        assert correlated_body["request_id"].startswith("req_")
        assert correlated_body["request_id"] != "client-correlation-123"
        assert correlated_body["correlation_id"] == "client-correlation-123"

        malformed = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[0]},
            headers={"request_id": "x" * 129},
        )
        assert malformed.status_code == 400

        # The platform-admin user should be allowed to inspect the authorization policy.
        assert allowed.status_code == 200
        body = allowed.json()
        assert body["data"]["subject"]["user_id"] == str(admin_id)
        assert body["data"]["subject"]["platform_role_code"] == "platform_admin"
        assert body["data"]["effective_permissions"] == ["platform.admin"]
        assert body["data"]["capabilities"] == ["inspect_authorization_policy"]
        assert body["data"]["policy_version"] == "sprint-1-platform-rbac-v1"
        assert body["request_id"].startswith("req_")
        assert body["correlation_id"] == body["request_id"]

        denied = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: tokens[1]},
            headers={"X-Role": "platform_admin"},
        )
        assert denied.status_code == 403
        assert denied.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id IN (%s, %s)", (admin_id,
user_id))
```

```
def test_permission_grant_revocation_takes_effect_on_next_request():
    suffix = uuid4().hex
    role_key = f"test-admin-{suffix}"
    email = f"permission-revocation-{suffix}@example.test"
    user_id = None
    role_id = None
    permission_id = None
            )
            cur.execute(
                """
                INSERT INTO users (email, display_name, platform_role_id)
                VALUES (%s, %s, %s)
                RETURNING user_id
                """,
                (email, "Synthetic Permission Revocation User", role_id),
            )
            user_id = cur.fetchone()[0]

            token, digest = new_session_token()
            cur.execute(
                """
                INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
                VALUES (%s, %s, %s)
                """,
                (user_id, digest, session_expiry(5)),
            )

        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
            ]

            with connect() as conn, conn.cursor() as cur:
                cur.execute(
```

```
                "DELETE FROM role_permissions WHERE role_id = %s AND
permission_id = %s",
                (role_id, permission_id),
            )

        next_response = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: token},
        )
        assert next_response.status_code == 403
        assert next_response.json() == {"detail": "Permission denied"}

    finally:
        with connect() as conn, conn.cursor() as cur:
            if user_id is not None:
                cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            if role_id is not None:
                cur.execute("DELETE FROM roles WHERE role_id = %s", (role_id,))

def test_platform_role_assignment_rejects_workspace_scoped_roles():
    email = f"wrong-scope-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "INSERT INTO roles (role_key, display_name, scope) VALUES (%s, %s,
'workspace') RETURNING role_id",
            (f"ws-{uuid4().hex[:12]}", "Synthetic Workspace Role"),
        )
        workspace_role_id = cur.fetchone()[0]
        cur.execute(
            "INSERT INTO users (email, display_name) VALUES (%s, 'Synthetic Scope
User') RETURNING user_id",
            (email,),
        )
        user_id = cur.fetchone()[0]
    try:
        with pytest.raises(psycopg.errors.CheckViolation):
            with connect() as conn, conn.cursor() as cur:
                cur.execute("UPDATE users SET platform_role_id = %s WHERE user_id =
%s", (workspace_role_id, user_id))
    finally:
```

```
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))
            cur.execute("DELETE FROM roles WHERE role_id = %s",
(workspace_role_id,))



def test_platform_role_revocation_takes_effect_on_next_request():
    email = f"revoked-platform-admin-{uuid4().hex}@example.test"
    with connect() as conn, conn.cursor() as cur:
        cur.execute(
            "SELECT role_id FROM roles WHERE role_key = 'platform_admin' AND scope
= 'platform'"
        )
        row = cur.fetchone()
        assert row is not None, "Platform-admin role must exist"
        admin_role_id = row[0]
        cur.execute(
            "INSERT INTO users (email, display_name, platform_role_id) "
            "VALUES (%s, %s, %s) RETURNING user_id",
            (email, "Synthetic Revocation Test", admin_role_id),
        )
        user_id = cur.fetchone()[0]
        token, digest = new_session_token()
        cur.execute(
            "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) "
            "VALUES (%s, %s, %s)",
            (user_id, digest, session_expiry(5)),
        )

    try:
        with TestClient(app) as client:
            first_response = client.get(
                "/api/v1/admin/authorization/capabilities",
                cookies={SESSION_COOKIE: token},
            )
            assert first_response.status_code == 200
            assert first_response.json()["data"]["effective_permissions"] == [
                "platform.admin"
```

```
        ]

        # Revoke this test user's role without changing shared role permissions.
        with connect() as conn, conn.cursor() as cur:
            cur.execute(
                "UPDATE users SET platform_role_id = NULL WHERE user_id = %s",
                (user_id,),
            )

        next_response = client.get(
            "/api/v1/admin/authorization/capabilities",
            cookies={SESSION_COOKIE: token},
        )
        assert next_response.status_code == 403
        assert next_response.json() == {"detail": "Permission denied"}
    finally:
        with connect() as conn, conn.cursor() as cur:
            cur.execute("DELETE FROM users WHERE user_id = %s", (user_id,))


# def test_capabilities_request_id_is_canonical_and_correlation_is_preserved():
#     with connect() as conn, conn.cursor() as cur:
#         cur.execute(
#         """
#         SELECT u.user_id, s.refresh_token_hash
re-warnings.html
58 passed, 18 warnings in 1.15s
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

echo "===== FIN-15 STORY TRACEABILITY ====="
grep -n -i -C 2 'FIN-15' docs/requirements/traceability-stories.csv

echo "===== RELATED REQUIREMENT TRACEABILITY ====="
grep -n -E
'FR-P1-05|FR-P1-06|FR-P1-07|TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_
PRIV_002|TC_SYS_001' docs/requirements/traceability-requirements.csv
docs/requirements/traceability-matrix.md

echo "===== SPRINT TEST EXECUTION STATUS ====="
```

```
grep -n -E
'TC_AUTHZ_001|TC_AUTHZ_002|TC_AUTHZ_003|TC_PRIV_002|TC_SYS_001|FIN-1
5|58 passed|55 passed' SPRINT_1_TEST_EXECUTION_STATUS.txt

echo "===== IMPLEMENTATION STATUS ====="
grep -n -i -C 3 'FIN-15' IMPLEMENTATION_STATUS.txt

===== FIN-15 STORY TRACEABILITY =====
1-Story alias,Verified Jira issue key,Jira mapping verification,Story title,Four-sprint
assignment,Source release label,SRS references from Jira/test-plan mapping,Relevant
acceptance criteria,Test case IDs,Test execution status,Implementation status,Evidence
path/reference,Outstanding gap/dependency
2-FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage
sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04;
FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12;
NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35; NFR-G-36;
NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid
credentials create a session; logout invalidates it; invalid credentials reveal no account
existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002;
TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001;
TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS;
TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED;
TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN;
TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py;
apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains
incomplete or externally unverified; see implementation record.
3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected
routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07;
FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01;
NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38;
NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected;
role/permission matrix is tested server-side; inactive sessions expire per
configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002;
TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN;
TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT
RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js;
IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally
unverified; see implementation record.
4-FS-01-03,FIN-14,LIVE JIRA VERIFIED 2026-10-19,Protect accounts and audit
authentication,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03;
```

FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-10; FR-P1-11; FR-P1-12; FR-P9-13; NFR-G-08; NFR-G-11; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P9-02,Security events are auditable; repeated failures are throttled; MFA/session features are enabled only when configured. detected and limited.,TC_AUTHSEC_001; TC_AUTHSEC_002; TC_AUTHSEC_003; TC_INT_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_002=NOT RUN; TC_AUTHSEC_003=NOT RUN; TC_INT_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.
5-FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
===== RELATED REQUIREMENT TRACEABILITY =====
docs/requirements/traceability-requirements.csv:12:FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,LiveJira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/app/auth.py; apps/api/tests/test_auth.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:13:FR-P1-02,Session Termination,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001;

TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py,Evidencesupports the current scoped behavior only.,Preserve source story release label docs/requirements/traceability-requirements.csv:14:FR-P1-03,Password Recovery,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label docs/requirements/traceability-requirements.csv:15:FR-P1-04,User Onboarding,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials createa session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/provision_user.py (trusted local operator CLI only),Local provisioning exists; administrator invitation/onboarding workflow is absent.,Preserve source story release label docs/requirements/traceability-requirements.csv:16:FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN;

TC_SYS_001=NOT RUN,PARTIAL,apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:17:FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03;FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (/auth/me only),Current code covers only part of this sourcerequirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:18:FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py (authentication dependency; no role/operation matrix),Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:19:FR-P1-08,Session Expiry,PDF p.4; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:24:FR-P1-13,Step-Up Authentication,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source

refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:25:FR-P1-14,Data and Trading Permissions,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05; FS-11-08; FS-11-10,FIN-16; FIN-65; FIN-79; FIN-81,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,PARTIAL,apps/api/app/main.py (no trading routes); optional tradingDDL remains reference-only,Separate permission policy is absent; no trading routes are enabled and trading remains Release 2 gated.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:26:FR-P1-15,Connection Ownership,PDF p.4; SRS P1 requirements,Identity and access,FS-01-04; FS-09-05,FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-04/FIN-16: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN;TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Release 1 boundary / mixed with Release 2
docs/requirements/traceability-requirements.csv:234:FR-P8-01,Ollama Configuration,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label

docs/requirements/traceability-requirements.csv:235:FR-P8-02,Connection Validation,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-01-01;FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inferencewith versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:236:FR-P8-03,Model Discovery,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundationscope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:237:FR-P8-04,Default Model,PDF p.29; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN;TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label

docs/requirements/traceability-requirements.csv:238:FR-P8-05,Inference Parameters,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-08-01,FIN-57,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-08-01/FIN-57: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable. configure inference with versioning so that AI behavior is controlled.,TC_CFG_002; TC_CFG_003; TC_CFG_004; TC_DASH_002; TC_LLM_001; TC_LLM_002; TC_LLM_003; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_CFG_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CFG_004=NOT RUN; TC_DASH_002=NOT RUN; TC_LLM_001=NOT RUN; TC_LLM_002=NOT RUN; TC_LLM_003=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:245:FR-P8-12,Service Diagnostics,PDF p.30; SRS P8 requirements,"Models, providers and settings",FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_LLM_001; TC_OPS_001; TC_SYS_001,TC_LLM_001=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:270:FR-P9-06,Workspace Settings,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized ownersmanage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:271:FR-P9-07,Member Management,PDF p.33; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label

docs/requirements/traceability-requirements.csv:272:FR-P9-08,Role Management,PDF p.34; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-02; FS-09-05,FIN-15; FIN-16; FIN-62; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.,TC_PRIV_002,TC_PRIV_002=NOT RUN,PLANNED,—,Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.,Preserve source story release label
docs/requirements/traceability-requirements.csv:310:NFR-G-01,Authorization Enforcement,PDF p.36; SRS global NFR,Cross-cutting quality and operations,FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_AUTHZ_001; TC_AUTHZ_002,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:322:NFR-G-13,Controlled Failure,PDF p.38; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:332:NFR-G-23,Automated Testing,PDF p.39; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-02; FS-11-04; FS-11-05; FS-11-06; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-73; FIN-75; FIN-76; FIN-77; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_CI_001; TC_CI_002; TC_COV_001; TC_SEC_001; TC_SYS_001; TC_TEST_001,TC_CI_001=BLOCKED; TC_CI_002=BLOCKED; TC_COV_001=PASS; TC_SEC_001=BLOCKED; TC_SYS_001=NOT RUN; TC_TEST_001=PASS,PARTIAL,apps/api/tests; apps/web/tests; scripts/run_live_e2e.py,Current code covers only part of this source requirement.,Unmapped to source story
docs/requirements/traceability-requirements.csv:343:NFR-G-34,Health Checks,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_DASH_002; TC_OPS_001; TC_SYS_001,TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN;

TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:344:NFR-G-35,Structured Logs,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-09-03; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-63; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_002; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_002=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:345:NFR-G-36,Operational Monitoring,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01;FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:346:NFR-G-37,Graceful Shutdown,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-04; FS-11-12,FIN-13; FIN-15; FIN-25; FIN-55; FIN-57; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_OPS_001; TC_OPS_003; TC_SYS_001,TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_SYS_001=NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
docs/requirements/traceability-requirements.csv:347:NFR-G-38,Deployment Reproducibility,PDF p.40; SRS global NFR,Cross-cutting quality and operations,FS-01-01; FS-01-02; FS-02-08; FS-07-05; FS-08-01; FS-11-01; FS-11-03; FS-11-04; FS-11-10; FS-11-12,FIN-13; FIN-15; FIN-2; FIN-25; FIN-55; FIN-57; FIN-74; FIN-75;FIN-81; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,No mapped story criterion; do not infer.,TC_BUILD_001; TC_BUILD_002; TC_ENV_001; TC_OPS_001; TC_OPS_003; TC_REL_001; TC_SYS_001,TC_BUILD_001=BLOCKED; TC_BUILD_002=BLOCKED; TC_ENV_001=NOT RUN; TC_OPS_001=NOT RUN; TC_OPS_003=NOT RUN; TC_REL_001=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,scripts/package_release.py; docs/release/RELEASE_README.md (no deployment target),Versioned package process exists; deployment target and committed-SHA evidence are absent.,Unmapped to source story

docs/requirements/traceability-requirements.csv:352:NFR-P1-05,Information Disclosure,PDF p.5; SRS P1 requirements,Identity and access,FS-01-01; FS-01-05,FIN-13; FIN-17,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_004; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,IMPLEMENTED — VERIFIED,apps/api/app/main.py; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py,Evidence supports the current scoped behavior only.,Preserve source story release label
docs/requirements/traceability-requirements.csv:353:NFR-P1-06,Accessibility,PDF p.5; SRS P1 requirements,Identity and access,FS-01-05; FS-11-11,FIN-17; FIN-82,Live Jira JQL verified 2026-10-19; test-plan source refs,"FS-01-05/FIN-17: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested. that login is safe and usable.",TC_AUTHN_002; TC_AUTHN_006; TC_AUTHN_007; TC_AUTHN_008; TC_AUTHN_009; TC_TRACE_001,TC_AUTHN_002=PASS; TC_AUTHN_006=PASS; TC_AUTHN_007=BLOCKED; TC_AUTHN_008=NOT RUN; TC_AUTHN_009=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/web/app/page.js; apps/web/tests/ui/auth.spec.js,Current code covers only part of this source requirement.,Preserve source story release label
docs/requirements/traceability-requirements.csv:354:NFR-P2-01,Rendering Performance,PDF p.8; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:355:NFR-P2-02,Graceful Degradation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01; FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001;

TC_SYS_001;TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:356:NFR-P2-03,Data Freshness,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08; FS-08-01;FS-11-12,FIN-25; FIN-57; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:357:NFR-P2-04,Data Isolation,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:358:NFR-P2-05,Responsive Layout,PDF p.9; SRS P2 requirements,Dashboard and market overview,FS-02-08,FIN-25,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-02-08/FIN-25: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.,TC_DASH_001; TC_DASH_002; TC_OPS_001; TC_SYS_001; TC_TRACE_001,TC_DASH_001=NOT RUN; TC_DASH_002=NOT RUN; TC_OPS_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:404:NFR-P9-01,Privacy,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003;

TC_INT_001; TC_PRIV_001; TC_PRIV_002;
TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN;
TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN;
TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT
IMPLEMENTED,—,Mapped foundation scope is absent from the current
implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:405:NFR-P9-02,Sensitive
Changes,PDF p.35; SRS P9 requirements,"Account, workspace and
reporting",FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-01; FS-08-05; FS-09-03;
FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-57; FIN-61; FIN-63; FIN-65;
FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65:
Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle
follows retention policy. sensitive-action checks and clear destructive-change
confirmation so that personal and workspace data remain
protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003;
TC_CRED_002; TC_INT_001; TC_PRIV_001; TC_PRIV_002;
TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT
RUN;TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_CRED_002=NOT
RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN;
TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent
from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:406:NFR-P9-03,Secret Handling,PDF
p.35; SRS P9 requirements,"Account, workspace and reporting",FS-07-05; FS-08-05;
FS-09-03; FS-09-05; FS-11-06; FS-11-12,FIN-55; FIN-61; FIN-63; FIN-65; FIN-77;
FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65:
Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle
follows retention policy. sensitive-action checks and cleardestructive-change
confirmation so that personal and workspace data remain
protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_001;
TC_CFG_003;TC_CRED_001; TC_CRED_002; TC_INT_001; TC_OPS_002;
TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN;
TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_001=NOT
RUN; TC_CFG_003=NOT RUN; TC_CRED_001=NOT RUN; TC_CRED_002=NOT
RUN; TC_INT_001=NOT RUN; TC_OPS_002=NOT RUN; TC_PRIV_001=NOT RUN;
TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped
foundation scope is absent from the current implementation.,Preserve source story
release label
docs/requirements/traceability-requirements.csv:407:NFR-P9-04,Preference
Persistence,PDF p.35; SRS P9 requirements,"Account, workspace and
reporting",FS-09-05,FIN-65,Live Jira JQL verified 2026-10-19; test-plan source

refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:408:NFR-P9-05,Change Confirmation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace dataremain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:409:NFR-P9-06,Administrative Isolation,PDF p.35; SRS P9 requirements,"Account, workspace and reporting",FS-01-02; FS-01-04; FS-09-05,FIN-15; FIN-16; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-requirements.csv:410:NFR-P9-07,Data Lifecycle,PDF p.36; SRS P9 requirements,"Account, workspace and reporting",FS-09-03; FS-09-05,FIN-63; FIN-65,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-09-05/FIN-65: Cross-user read/write attempts fail; privilege changes are

auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,Mapped foundation scope is absent from the current implementation.,Preserve source story release label
docs/requirements/traceability-matrix.md:31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions| Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create asession, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:33:| FS-01-03 | [FIN-14](https://sandeephgowda8618.atlassian.net/browse/FIN-14) | Protect accounts and audit authentication | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02,

FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-10, FR-P1-11, FR-P1-12, FR-P9-13, NFR-G-08, NFR-G-11, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P9-02 | Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:35:| FS-01-05 | [FIN-17](https://sandeephgowda8618.atlassian.net/browse/FIN-17) | Meet identity security and accessibility requirements | Sprint 1 | Release 1 per Jira issue | FR-P1-01, NFR-G-03, NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-P1-01, NFR-P1-02, NFR-P1-03, NFR-P1-04, NFR-P1-05, NFR-P1-06 | No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records

are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05,FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:78:| FS-08-05 | [FIN-61](https://sandeephgowda8618.atlassian.net/browse/FIN-61) | Secure and validate configuration changes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-14, FR-P8-16, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-22, NFR-G-26, NFR-P8-01, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02, NFR-P9-03 | Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
docs/requirements/traceability-matrix.md:83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe accountadministration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10,

FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. | docs/requirements/traceability-matrix.md:94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. | docs/requirements/traceability-matrix.md:101:| FS-11-11 | [FIN-82](https://sandeephgowda8618.atlassian.net/browse/FIN-82) | Document usability, AI use, licenses and data rights | Sprint 1 | Release 1 per Jira issue | NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-G-27, NFR-P1-06 | AI-generated code is reviewed and tested, license/data rights are recorded, usability checks include accessibility and understandable failures. compliant. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. | docs/requirements/traceability-matrix.md:102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04,

NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
docs/requirements/traceability-matrix.md:118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |

docs/requirements/traceability-matrix.md:120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002,TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
docs/requirements/traceability-matrix.md:122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plansource refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25,

FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers onlypart of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02,FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement. | Preserve source story release label |
docs/requirements/traceability-matrix.md:125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOTRUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has noorder-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |

docs/requirements/traceability-matrix.md:131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
docs/requirements/traceability-matrix.md:340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED |— | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001,

TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004,TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN,

TC_TRACE_001=PASS | NOT IMPLEMENTED |— | Mapped foundation scope is absent from the current implementation. | Preserve source story release label | docs/requirements/traceability-matrix.md:351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs| No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED| — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story | docs/requirements/traceability-matrix.md:376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02,FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorizedowners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label | docs/requirements/traceability-matrix.md:377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label | docs/requirements/traceability-matrix.md:378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label| docs/requirements/traceability-matrix.md:416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No

direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs| No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001,TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
docs/requirements/traceability-matrix.md:449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | Nomapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55,

FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19,test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
docs/requirements/traceability-matrix.md:453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOTRUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target and committed-SHA evidence are absent. | Unmapped to source story |
docs/requirements/traceability-matrix.md:458:| NFR-P1-05 | Information Disclosure | PDF p.5, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05| FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_004, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
docs/requirements/traceability-matrix.md:459:| NFR-P1-06 | Accessibility | PDF p.5, SRS P1 requirements | Identity and access | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext

passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/web/app/page.js, apps/web/tests/ui/auth.spec.js | Current code covers only part of this source requirement. | Preserve source story releaselabel |
docs/requirements/traceability-matrix.md:460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performancetarget, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content

meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOTRUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label | docs/requirements/traceability-matrix.md:464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label | docs/requirements/traceability-matrix.md:510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04,FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label | docs/requirements/traceability-matrix.md:511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01,FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN,

TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS |NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05, FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 |

TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
docs/requirements/traceability-matrix.md:516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changesare auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
===== SPRINT TEST EXECUTION STATUS =====
51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
78:TC_SYS_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Browser smoke verified current sign-in/session/logout path against live frontend, FastAPI, and PostgreSQL. Full planned dashboard/settings, dependency health, Ollama available/unavailable, and correlation-log workflow cannot run because those components are not implemented | Tester/owner: Codex | Evidence: apps/web/tests/e2e/auth.spec.js; scripts/run_live_e2e.py;

IMPLEMENTATION_STATUS.txt | Linked defect: Current application implements auth starter only
94:TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
95:TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
115:TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
122:TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
129:- Result: 55 passed, 0 failed, 9 warnings in 9.52s.
135:FIN-15 route-level authorization test update — 2026-10-20
136:- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
140:FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)
148:- Full API suite: 55 passed, 10 warnings; exit code 0.
150: test-results/FIN-15/20261020_141030_identity_authorization.log
151: test-results/FIN-15/20261020_141030_full_api_suite.log
152: test-results/FIN-15/run_20261020_141030_summary.txt
156:FIN-15 story is complete. Workspace-level authorization remains deferred.
===== IMPLEMENTATION STATUS =====
316-GitHub-side limitation: `git show --check --format= HEAD` against the existing root commit exits 2 with 1,323 diagnostics, including immutable source PDFs and other pre-existing root-commit files. No source PDF/SQL/diagram/test plan was edited. The targeted working diff passes `git diff --check`; an incremental commit/push is needed so the next GitHub run checks only the corrective diff. No commit, push, Jira update, or remote rerun was made. A new GitHub Actions result is required before claiming the repair passed remotely; FIN-73/74/79 status is unchanged.
317-Final review note (2026-10-19): `git diff --check` exited 0 for the targeted workflow/CSV/script changes before coordination records were appended. A later full `git diff --check` attempt timed out after 8 seconds (intermittent Git responsiveness); direct trailing-whitespace scans of `.github/workflows/ci.yml`, `docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both updated coordination files found zero whitespace errors andall had final newlines. The historical root-commit check result above remains distinct from the current worktree check.
318-

319:FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)
320-Status: BLOCKED pending role-scope decision; implementation not started.
321-Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecturedocs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests. Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists. Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
322-Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global rolesor silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorize minimal canonical workspace membership model.
323-Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.
324:Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.
325-
326:FIN-15 verification update — 2026-10-20
327-- PostgreSQL 17.6 is running locally.
328-- Created and used the dedicated finsight_test database.
329-- Applied apps/api/migrations/0001_auth_identity.sql successfully.
--
333-- git diff --check: no errors reported.
334-- Warning: Starlette/httpx deprecation warnings remain.

335-- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
336:- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
337-
338:FIN-15 implementation update — 2026-10-20
339-- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
340-- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
341-- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
342-- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
343:- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results andall acceptance criteria are checked.
344-- No migrations, commits, pushes, or workspace schema changes performed by this patch script.
345-
346:FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
347-Latest run: 20261020_141030
348-Recorded revision: 64f2637
349-Python: 3.14.6
--
356-- The test-run summary records Overall result: PASS.
357-
358-Evidence:
359:- test-results/FIN-15/20261020_141030_identity_authorization.log
360:- test-results/FIN-15/20261020_141030_full_api_suite.log
361:- test-results/FIN-15/run_20261020_141030_summary.txt
362-
363-The warnings were Starlette/httpx deprecations. The passing test suites establish
364:the behavior exercised by those tests, not automatic completion of every FIN-15
365-acceptance criterion. Workspace membership and resource-level authorization remain
366-deferred under the approved platform-only scope. Earlier entries are retained as

367-historical records; this addendum records the later successful run.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
nly scope. Earlier entries are retained as
367-historical records; this addendum records the later successful run.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

echo "===== FUNCTION TEST TRACEABILITY ====="
grep -n -i -C 3 'TC_AUTHZ_001\|TC_AUTHZ_002\|TC_AUTHZ_003\|FIN-15'
FUNCTION_TEST_TRACEABILITY.txt

echo "===== AVAILABLE TRACEABILITY VALIDATORS ====="
grep -n -E
'validate_traceability|traceability-stories|traceability-requirements|traceability-matrix'
README.md AGENTS.md scripts/validate_traceability.py pyproject.toml 2>/dev/null

echo "===== CURRENT WORKING TREE ====="
git status --short

===== FUNCTION TEST TRACEABILITY =====
1-FinSight AI — Function/Test Traceability
2-
3:FIN-15 / FS-01-02 — platform authorization capability endpoint
4-Function: GET /platform/admin/capability
5-Authorization rule: requires a valid active session and database-resolved
`platform.admin` permission; deny by default.
6-Scope: platform-only. Workspace roles, membership, and workspace tables are
deferred.
7:Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial),
TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied;
client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior
via existing session dependency).
8-Evidence note: route integration assertions were added to
apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing
the mapped tests and confirming the expected behavior.
9-
10:FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
11-Run ID: 20261020_141030
12-Endpoint: GET /platform/admin/capability
13-

--
16-- Full API suite: 55 passed, 10 warnings.
17-- Both pytest commands exited with code 0.
18-- Evidence:
19: test-results/FIN-15/20261020_141030_identity_authorization.log
20: test-results/FIN-15/20261020_141030_full_api_suite.log
21: test-results/FIN-15/run_20261020_141030_summary.txt
22-
23-Case-status guidance:
24:- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
25- test suite passed, but broader acceptance criteria must also be checked.
26:- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
27- integration test; this does not imply missing model/provider operations exist.
28:- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded run;
29- it was not separately rerun under run ID 20261020_141030.
30-- TC_PRIV_002: BLOCKED / deferred because workspace membership and resource-level
31- authorization are outside the approved platform-only scope.
===== AVAILABLE TRACEABILITY VALIDATORS =====
README.md:118:Requirements and story traceability:
[matrix](docs/requirements/traceability-matrix.md), [SRS addendum](docs/requirements/srs-addendum.md), [requirement register](docs/requirements/traceability-requirements.csv), and [story register](docs/requirements/traceability-stories.csv).
scripts/validate_traceability.py:8:REQ=DOCS/"traceability-requirements.csv"
scripts/validate_traceability.py:9:STORY=DOCS/"traceability-stories.csv"
===== CURRENT WORKING TREE =====
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js

```
 M conversation.txt
 M docs/architecture/README.md
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI
sed -n '1,240p' scripts/validate_traceability.py

#!/usr/bin/env python3
"""Check RTM registers against source inventories; does not call Jira or edit sources."""
from __future__ import annotations
import csv, re, subprocess, sys
from pathlib import Path
ROOT=Path(__file__).resolve().parents[1]
DOCS=ROOT/"docs/requirements"
REQ=DOCS/"traceability-requirements.csv"
STORY=DOCS/"traceability-stories.csv"
SRS=ROOT/"Dcos/FinSight_Software Requirements Specification (SRS).pdf"
BACKLOG=ROOT/"Dcos/FinSight_AI_Jira_Backlog_72_Stories_with_Acceptance_crite
ria.pdf"
TESTPLAN=ROOT/"Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt"
EXECUTION=ROOT/"SPRINT_1_TEST_EXECUTION_STATUS.txt"
def pdf(path):
    return
subprocess.run(["pdftotext","-layout",str(path),"-"],check=True,capture_output=True,text
=True).stdout
def read(path):
    with path.open(newline="",encoding="utf-8") as f: return list(csv.DictReader(f))
def main():
    srs=pdf(SRS); backlog=pdf(BACKLOG)

reqsrc=set(re.findall(r"\b(?:FR|NFR)-[A-Z0-9]+-\d{2}\b",srs))|set(re.findall(r"\bDIR-\d{2}\b
",srs))
    alias_src=set(re.findall(r"\bFS-\d{2}-\d{2}\b",backlog))
    plan=TESTPLAN.read_text(encoding="utf-8")
```

```
    test_src=set(re.findall(r"^TEST CASE ID:\s*(TC_[A-Z0-9_]+)",plan,re.M))
    test_blocks=re.split(r"(?=^TEST CASE ID:)",plan,flags=re.M)
    test_aliases={}
    for block in test_blocks:
        tm=re.search(r"^TEST CASE ID:\s*(TC_[A-Z0-9_]+)",block,re.M)
        lm=re.search(r"^LINKED JIRA STORY:\s*(.*)$",block,re.M)
        if tm: test_aliases[tm.group(1)]=set(re.findall(r"FS-\d{2}-\d{2}",lm.group(1))) if lm
else set()
    execution=EXECUTION.read_text(encoding="utf-8")
    req=read(REQ); stories=read(STORY); errors=[]
    reqids=[x["Requirement ID"] for x in req]; aliases=[x["Story alias"] for x in stories]
    if len(reqids)!=len(set(reqids)): errors.append("duplicate requirement rows")
    if set(reqids)!=reqsrc: errors.append(f"requirement inventory mismatch: missing
{len(reqsrc-set(reqids))}, extra {len(set(reqids)-reqsrc)}")
    if len(aliases)!=len(set(aliases)): errors.append("duplicate story alias rows")
    if set(aliases)!=alias_src: errors.append(f"story inventory mismatch: missing
{len(alias_src-set(aliases))}, extra {len(set(aliases)-alias_src)}")
    valid={"IMPLEMENTED — VERIFIED","PARTIAL","PLANNED","NOT
IMPLEMENTED","BLOCKED","NOT ASSESSED"}
    for row in req:
        if row["Implementation status"] not in valid: errors.append(row["Requirement ID"]+":
invalid implementation status")
        if row["Implementation status"]=="IMPLEMENTED — VERIFIED" and not
row["Evidence path/reference"].strip(" —"): errors.append(row["Requirement ID"]+":
verified without evidence")
        for tid in re.findall(r"TC_[A-Z0-9_]+",row["Test case IDs"]):
            if tid not in test_src: errors.append(row["Requirement ID"]+": unknown test ID
"+tid)
    for row in stories:
        if not re.fullmatch(r"FIN-\d+",row["Verified Jira issue key"]):
errors.append(row["Story alias"]+": malformed Jira key")
        if row["Jira mapping verification"]!="LIVE JIRA VERIFIED 2026-10-19":
errors.append(row["Story alias"]+": dated live lookup evidence missing")
        for tid in re.findall(r"TC_[A-Z0-9_]+",row["Test case IDs"]):
            if tid not in test_src: errors.append(row["Story alias"]+": unknown test ID "+tid)
    known_aliases=set(aliases)
    unlinked_tests=sorted(tid for tid,linked in test_aliases.items() if not (linked &
known_aliases))
    if unlinked_tests: errors.append("source tests without a catalog story link: "+",
".join(unlinked_tests))
```

```
    sprint1=[x for x in stories if x["Four-sprint assignment"]=="Sprint 1"]
    if len(sprint1)!=23: errors.append(f"Sprint 1 story count is {len(sprint1)}, expected 23")
    if any(x["SRS references from Jira/test-plan mapping"].strip(" —") and not x["Verified
Jira issue key"] for x in sprint1):
        errors.append("Sprint 1 story has SRS references but no Jira mapping")
    process=next((x for x in sprint1 if x["Story alias"]=="FS-11-09"),None)
    if not process or process["SRS references from Jira/test-plan mapping"]!="—":
        errors.append("FS-11-09 process-story no-SRS-ID exception is not explicit")
    for alias in ("FS-07-04","FS-08-04"):

        x=next((r for r in stories if r["Story alias"]==alias),None)
        if not x or x["Source release label"]!="Release 2 only": errors.append(alias+":
Release 2-only label missing/changed")
    mapped=sum(bool(x["Source story aliases"].strip(" —")) for x in req)
    no_test=sum(not x["Test case IDs"].strip(" —") for x in req)
    missing=sorted(test_src-set(re.findall(r"^(TC_[A-Z0-9_]+) \| Status:",execution,re.M)))
    print(f"SRS requirement IDs: {len(reqids)}; source story aliases: {len(aliases)}; Sprint
1 source tests: {len(test_src)}")
    print(f"Requirements with Jira/test-plan story links: {mapped}; unmapped:
{len(reqids)-mapped}; no linked Sprint 1 test: {no_test}")
    print(f"Source tests linked to a catalog story:
{len(test_src)-len(unlinked_tests)}/{len(test_src)}")
    print(f"Sprint 1 stories: {len(sprint1)}; with SRS IDs: {sum(bool(x['SRS references
from Jira/test-plan mapping'].strip(' —')) for x in sprint1)}; process-story exception:
FS-11-09")
    print("Tests lacking explicit execution rows (source default NOT RUN): "+(",
".join(missing) if missing else "none"))
    print("Jira key shape and dated live-query marker checked; this offline script does not
query Jira.")
    if errors:
        print("VALIDATION FAILED",file=sys.stderr)
        for e in errors: print("- "+e,file=sys.stderr)
        return 1
    print("VALIDATION PASS: inventories, test references, evidence fields, and Release
2 labels are consistent.")
    return 0
if __name__=="__main__": raise SystemExit(main())
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
 Jira mapping")
    process=next((x for x in sprint1 if x["Story alias"]=="FS-11-09"),None)
```

```
    if not process or process["SRS references from Jira/test-plan mapping"]!="—":
        errors.append("FS-11-09 process-story no-SRS-ID exception is not explicit")
    for alias in ("FS-07-04","FS-08-04"):

        x=next((r for r in stories if r["Story alias"]==alias),None)
        if not x or x["Source release label"]!="Release 2 only": errors.append(alias+":
Release 2-only label missing/changed")
    mapped=sum(bool(x["Source story aliases"].strip(" —")) for x in req)
    no_test=sum(not x["Test case IDs"].strip(" —") for x in req)
    missing=sorted(test_src-set(re.findall(r"^(TC_[A-Z0-9_]+) \| Status:",execution,re.M)))
    print(f"SRS requirement IDs: {len(reqids)}; source story aliases: {len(aliases)}; Sprint
1 source tests: {len(test_src)}")
    print(f"Requirements with Jira/test-plan story links: {mapped}; unmapped:
{len(reqids)-mapped}; no linked Sprint 1 test: {no_test}")
    print(f"Source tests linked to a catalog story:
{len(test_src)-len(unlinked_tests)}/{len(test_src)}")
    print(f"Sprint 1 stories: {len(sprint1)}; with SRS IDs: {sum(bool(x['SRS references
from Jira/test-plan mapping'].strip(' —')) for x in sprint1)}; process-story exception:
FS-11-09")
    print("Tests lacking explicit execution rows (source default NOT RUN): "+(",
".join(missing) if missing else "none"))
    print("Jira key shape and dated live-query marker checked; this offline script does not
query Jira.")
    if errors:
        print("VALIDATION FAILED",file=sys.stderr)
        for e in errors: print("- "+e,file=sys.stderr)
        return 1
    print("VALIDATION PASS: inventories, test references, evidence fields, and Release
2 labels are consistent.")
    return 0
if __name__=="__main__": raise SystemExit(main())
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

echo "===== OFFICIAL AUTHORIZATION TEST CASES ====="
grep -n -A 14 -E '^TEST CASE ID:[[:space:]]*TC_AUTHZ_00[123]|^TEST CASE
ID:[[:space:]]*TC_PRIV_002|^TEST CASE ID:[[:space:]]*TC_SYS_001' \
  "Dcos/FinSight_AI_Sprint_1_Test_Plan_Management.txt"

echo
```

```
echo "===== FIN-15 STORY REGISTER ROW ====="
python -c 'import csv; p="docs/requirements/traceability-stories.csv";
rows=list(csv.DictReader(open(p, newline="", encoding="utf-8"))); [print(r) for r in rows if
r.get("Verified Jira issue key")=="FIN-15"]'

echo
echo "===== RELEVANT REQUIREMENT REGISTER ROWS ====="
python -c 'import csv; p="docs/requirements/traceability-requirements.csv";
rows=list(csv.DictReader(open(p, newline="", encoding="utf-8"))); [print(r) for r in rows if
r.get("Requirement ID") in
{"FR-P1-05","FR-P1-06","FR-P1-07","FR-P9-06","FR-P9-07","FR-P9-08"}]'

echo
echo "===== TRACEABILITY VALIDATOR ====="
python scripts/validate_traceability.py

===== OFFICIAL AUTHORIZATION TEST CASES =====
594:TEST CASE ID: TC_AUTHZ_001
595-TEST DESCRIPTION / TITLE: Reject anonymous access to protected pages and
backend APIs
596-TEST LEVEL / TYPE: API integration / Security negative
597-LINKED JIRA STORY: FS-01-02
598-REQUIREMENT TRACEABILITY: FR-P1-06; FR-P1-07; NFR-G-01
599-PRECONDITIONS: At least one protected page and one protected API endpoint
exist.
600-TEST DATA: No cookie, no bearer token, expired token.
601-TEST STEPS:
602-  1. Request the protected frontend route in a private session.
603-  2. Call the protected backend API without credentials.
604-  3. Repeat with an expired or malformed token.
605-  4. Inspect response and logs for information leakage.
606-EXPECTED RESULT: Unauthenticated or invalid-session access is denied
consistently by the backend; frontend routing does not substitute for API
authorization; responses do not reveal secrets or internal stack traces.
607-ACTUAL RESULT:
_____________________________________________________________________
608-STATUS: [ ] PASS  [ ] FAIL  [ ] BLOCKED  [x] NOT RUN
--
615:TEST CASE ID: TC_AUTHZ_002
```

616-TEST DESCRIPTION / TITLE: Enforce the backend role and permission matrix for protected operations
617-TEST LEVEL / TYPE: API integration / Authorization matrix
618-LINKED JIRA STORY: FS-01-02, FS-01-04, FS-09-05
619-REQUIREMENT TRACEABILITY: FR-P1-05, FR-P1-07; NFR-G-01, NFR-P9-06
620-PRECONDITIONS: Roles and a protected admin operation are configured; test accounts with Administrator, Operator and Standard User roles exist.
621-TEST DATA: admin@example.test (Administrator); operator@example.test (Operator); analyst@example.test (Standard User); sample model/provider setting resource.
622-TEST STEPS:
623- 1. Call the permitted operation as the administrator.
624- 2. Call the same operation as operator and standard user according to the configured permission matrix.
625- 3. Bypass frontend controls and call the backend API directly.
626- 4. Try changing role/owner identifiers in the request body.
627-EXPECTED RESULT: Each role is allowed or denied according to the documented role/permission matrix; backend authorization is authoritative; users cannot escalate privilege by modifying request data.
628-ACTUAL RESULT:
_____
629-STATUS: [ ] PASS [ ] FAIL [ ] BLOCKED [x] NOT RUN
--
637:TEST CASE ID: TC_AUTHZ_003
638-TEST DESCRIPTION / TITLE: Expire inactive sessions according to configured policy
639-TEST LEVEL / TYPE: API integration / Security
640-LINKED JIRA STORY: FS-01-02
641-REQUIREMENT TRACEABILITY: FR-P1-08; schema: auth_sessions
642-PRECONDITIONS: Session inactivity/expiry policy is configured in test settings; time can be advanced using test clock or short test timeout.
643-TEST DATA: Session with `last_seen_at` older than configured threshold; active-session control case.
644-TEST STEPS:
645- 1. Create a session and verify access while active.
646- 2. Advance the test clock or wait for the configured inactivity threshold.
647- 3. Call a protected API with the expired session.
648- 4. Inspect whether reauthentication is requested and the session is marked/treated as expired.

649-EXPECTED RESULT: Inactive sessions expire under the configured policy and protected requests require reauthentication; no hard-coded timeout contradicts the deployment configuration.
650-ACTUAL RESULT:

651-STATUS: [ ] PASS [ ] FAIL [ ] BLOCKED [x] NOT RUN
--
1057:TEST CASE ID: TC_PRIV_002
1058-TEST DESCRIPTION / TITLE: Prevent cross-user profile reads/writes and unauthorized workspace administration
1059-TEST LEVEL / TYPE: API integration / Security negative
1060-LINKED JIRA STORY: FS-09-05, FS-01-02, FS-01-04
1061-REQUIREMENT TRACEABILITY: FR-P9-06..08; NFR-P9-01, NFR-P9-02, NFR-P9-06
1062-PRECONDITIONS: Two users and at least one workspace with owner/member roles are seeded.
1063-TEST DATA: User A and User B IDs; workspace A and workspace B IDs; attempted foreign resource ID changes.
1064-TEST STEPS:
1065- 1. Authenticate as User A and read/update User A profile.
1066- 2. Attempt to read/update User B profile by changing path/body identifiers.
1067- 3. Attempt workspace member/role administration as a standard user.
1068- 4. Inspect audit trail for any denied sensitive operation.
1069-EXPECTED RESULT: Users cannot view or modify another user's private information without explicit authorization; only entitled administrators can manage membership/roles; denied privilege attempts do not mutate data and are audited where required.
1070-ACTUAL RESULT:

1071-STATUS: [ ] PASS [ ] FAIL [ ] BLOCKED [x] NOT RUN
--
1212:TEST CASE ID: TC_SYS_001
1213-TEST DESCRIPTION / TITLE: Execute the repeatable Sprint 1 end-to-end smoke path
1214-TEST LEVEL / TYPE: System / E2E
1215-LINKED JIRA STORY: FS-11-04, FS-01-01, FS-01-02, FS-08-01, FS-11-12, FS-02-08
1216-REQUIREMENT TRACEABILITY: FR-P1-01, FR-P1-06; FR-P8-02, FR-P8-12; NFR-G-13, NFR-G-23, NFR-G-34..38

1217-PRECONDITIONS: Frontend and FastAPI are running; PostgreSQL test migrations applied; a valid standard user exists; Ollama can be healthy or deliberately unavailable.
1218-TEST DATA: `analyst@example.test`; synthetic test password; working Ollama test URL or controlled unavailable URL; no production data.
1219-TEST STEPS:
1220- 1. Open the app and sign in as the test user.
1221- 2. Open a protected dashboard/settings shell and confirm an anonymous request is separately denied.
1222- 3. Read dependency health and verify Ollama status.
1223- 4. When Ollama is unavailable, trigger an operation that requires it and inspect controlled error behavior.
1224- 5. Inspect run/correlation logs for traceability and secret redaction.
1225- 6. Repeat the smoke path after resetting the test data.
1226-EXPECTED RESULT: The authenticated core workflow works repeatedly; protected endpoints reject anonymous access; health state is truthful; dependency failure is controlled; logs are correlatable and do not leak secrets; test data remains consistent.

===== FIN-15 STORY REGISTER ROW =====
{'Story alias': 'FS-01-02', 'Verified Jira issue key': 'FIN-15', 'Jira mapping verification': 'LIVE JIRA VERIFIED 2026-10-19', 'Story title': 'Enforce roles and protected routes', 'Four-sprint assignment': 'Sprint 1', 'Source release label': 'Release 1 per Jira issue', 'SRS references from Jira/test-plan mapping': 'FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06', 'Relevant acceptance criteria': 'Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt', 'Outstanding gap/dependency': 'Acceptance remains incomplete or externally unverified; see implementation record.'}

===== RELEVANT REQUIREMENT REGISTER ROWS =====
{'Requirement ID': 'FR-P1-05', 'Concise title': 'Role-Based Access Control', 'SRS reference': 'PDF p.3; SRS P1 requirements', 'Application page/component or domain':

'Identity and access', 'Source story aliases': 'FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04', 'Verified Jira issue keys': 'FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P1-06', 'Concise title': 'Protected Routes', 'SRS reference': 'PDF p.3; SRS P1 requirements', 'Application page/component or domain': 'Identity and access', 'Source story aliases': 'FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12', 'Verified Jira issue keys': 'FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py (/auth/me only)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P1-07', 'Concise title': 'Permission Enforcement', 'SRS reference': 'PDF p.3; SRS P1 requirements', 'Application page/component or domain': 'Identity and access', 'Source story aliases': 'FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04', 'Verified Jira issue keys': 'FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOTRUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py

(authentication dependency; no role/operation matrix)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P9-06', 'Concise title': 'Workspace Settings', 'SRS reference': 'PDF p.33; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62; FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P9-07', 'Concise title': 'Member Management', 'SRS reference': 'PDF p.33; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62; FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Onlyauthorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source storyrelease label'}
{'Requirement ID': 'FR-P9-08', 'Concise title': 'Role Management', 'SRS reference': 'PDF p.34; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62;FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source story release label'}

===== TRACEABILITY VALIDATOR =====
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test: 305
Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001, TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

What this step does not change

- The FIN-15 story remains PARTIAL, not fully accepted.
- `TC_AUTHZ_001`, `TC_AUTHZ_002`, `TC_PRIV_002`, and `TC_SYS_001` remain NOT RUN at full test-plan level.
- Workspace-level authorization remains deferred.
- FIN-14 and the requirement/story CSVs remain untouched until we have a precise, evidence-backed mapping for those records.

ON_STATUS.txt.
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test: 305
Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001, TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % git diff --check
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % python scripts/validate_traceability.py
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test: 305

Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001, TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

```
python - <<'PY'
import csv
from pathlib import Path

for filename in (
    "docs/requirements/traceability-stories.csv",
    "docs/requirements/traceability-requirements.csv",
):
    print(f"\n===== {filename} =====")
    with Path(filename).open(newline="", encoding="utf-8") as f:
        reader = csv.DictReader(f)
        print("COLUMNS:", reader.fieldnames)
        for row in reader:
            if row.get("Verified Jira issue key") == "FIN-15":
                print(row)
            elif row.get("Requirement ID") in {
                "FR-P1-05", "FR-P1-06", "FR-P1-07",
                "FR-P9-06", "FR-P9-07", "FR-P9-08",
            }:
                print(row)
PY
```

===== docs/requirements/traceability-stories.csv =====
COLUMNS: ['Story alias', 'Verified Jira issue key', 'Jira mapping verification', 'Story title', 'Four-sprint assignment', 'Source release label', 'SRS references from Jira/test-plan mapping', 'Relevant acceptance criteria', 'Test case IDs', 'Test execution status', 'Implementation status', 'Evidence path/reference', 'Outstanding gap/dependency']

{'Story alias': 'FS-01-02', 'Verified Jira issue key': 'FIN-15', 'Jira mapping verification': 'LIVE JIRA VERIFIED 2026-10-19', 'Story title': 'Enforce roles and protected routes', 'Four-sprint assignment': 'Sprint 1', 'Source release label': 'Release 1 per Jira issue', 'SRS references from Jira/test-plan mapping': 'FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06', 'Relevant acceptance criteria': 'Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt', 'Outstanding gap/dependency': 'Acceptance remains incomplete or externally unverified; see implementation record.'}

===== docs/requirements/traceability-requirements.csv =====
COLUMNS: ['Requirement ID', 'Concise title', 'SRS reference', 'Application page/component or domain', 'Source story aliases', 'Verified Jira issue keys', 'Jira mapping verification', 'Relevant acceptance criterion', 'Test case IDs', 'Test execution status', 'Implementation status', 'Evidence path/reference', 'Outstanding gap/dependency/decision', 'Release scope']
{'Requirement ID': 'FR-P1-05', 'Concise title': 'Role-Based Access Control', 'SRS reference': 'PDF p.3; SRS P1 requirements', 'Application page/component or domain': 'Identity and access', 'Source story aliases': 'FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04', 'Verified Jira issue keys': 'FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/migrations/0001_auth_identity.sql (roles table only; no role enforcement)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P1-06', 'Concise title': 'Protected Routes', 'SRS reference': 'PDF p.3; SRS P1 requirements', 'Application page/component or domain': 'Identity and

access', 'Source story aliases': 'FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12', 'Verified Jira issue keys': 'FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py (/auth/me only)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P1-07', 'Concise title': 'Permission Enforcement', 'SRS reference': 'PDF p.3; SRS P1 requirements', 'Application page/component or domain': 'Identity and access', 'Source story aliases': 'FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04', 'Verified Jira issue keys': 'FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOTRUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py (authentication dependency; no role/operation matrix)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P9-06', 'Concise title': 'Workspace Settings', 'SRS reference': 'PDF p.33; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62; FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source story release label'}

{'Requirement ID': 'FR-P9-07', 'Concise title': 'Member Management', 'SRS reference': 'PDF p.33; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62; FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Onlyauthorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source storyrelease label'}
{'Requirement ID': 'FR-P9-08', 'Concise title': 'Role Management', 'SRS reference': 'PDF p.34; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62;FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source story release label'}
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
s are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.', 'Test case IDs': 'TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001', 'Test execution status': 'TC_AUTHZ_001=NOTRUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN', 'Implementation status': 'PARTIAL', 'Evidence path/reference': 'apps/api/app/main.py (authentication dependency; no role/operation matrix)', 'Outstanding gap/dependency/decision': 'Current code covers only part of this source requirement.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P9-06', 'Concise title': 'Workspace Settings', 'SRS reference': 'PDF p.33; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62; FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Only authorized owners manage membership;

shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source story release label'}
{'Requirement ID': 'FR-P9-07', 'Concise title': 'Member Management', 'SRS reference': 'PDF p.33; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62; FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Onlyauthorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source storyrelease label'}
{'Requirement ID': 'FR-P9-08', 'Concise title': 'Role Management', 'SRS reference': 'PDF p.34; SRS P9 requirements', 'Application page/component or domain': 'Account, workspace and reporting', 'Source story aliases': 'FS-01-02; FS-01-04; FS-09-02; FS-09-05', 'Verified Jira issue keys': 'FIN-15; FIN-16; FIN-62;FIN-65', 'Jira mapping verification': 'Live Jira JQL verified 2026-10-19; test-plan source refs', 'Relevant acceptance criterion': 'FS-09-02/FIN-62: Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass. collaboration respects permission boundaries.', 'Test case IDs': 'TC_PRIV_002', 'Test execution status': 'TC_PRIV_002=NOT RUN', 'Implementation status': 'PLANNED', 'Evidence path/reference': '—', 'Outstanding gap/dependency/decision': 'Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence.', 'Release scope': 'Preserve source story release label'}
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

```
echo "===== OFFICIAL TC_AUTHZ_003 EXECUTION RECORD ====="
grep -n -i -C 3 'TC_AUTHZ_003' SPRINT_1_TEST_EXECUTION_STATUS.txt

echo
echo "===== SESSION EXPIRY TESTS IN CODE ====="
grep -n -i -E 'expire|expired|revok|last_seen|inactivity' \
  apps/api/tests/test_auth_unit.py \
```

apps/api/tests/test_identity_constraints.py

===== OFFICIAL TC_AUTHZ_003 EXECUTION RECORD =====
48-Evidence: test `test_public_registration_is_not_available`;
`apps/api/app/provision_user.py`.
49-Remaining: implement/verify the approved administrator-controlled onboarding workflow in its authorized scope.
50-
51:TC_AUTHZ_003 — Expire inactive sessions according to configured policy
52-Status: PASS (session-expiry behavior exercised as a FIN-13 acceptance check; Jira scope remains unchanged)
53-Actual result: A session with stale `last_seen_at` was rejected by the protected endpoint. TTL bounds are validated and expiry uses `SESSION_TTL_MINUTES`.
54-Evidence: test `test_expired_session_is_rejected` in the command above.
--
93-TC_AUTHN_005 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Public registration is absent, but admin onboarding workflow is incomplete | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
94-TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
95-TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
96:TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
97-TC_AUTHSEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
98-TC_AUTHSEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
99-TC_AUTHSEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
--
133-- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.
134-
135-FIN-15 route-level authorization test update — 2026-10-20
136:- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).

137-- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
138-- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.
139-

===== SESSION EXPIRY TESTS IN CODE =====
apps/api/tests/test_identity_constraints.py:34:   "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py:66:   "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py:174:   INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at)
apps/api/tests/test_identity_constraints.py:236:   email = f"revoked-platform-admin-{uuid4().hex}@example.test"
apps/api/tests/test_identity_constraints.py:252:   "INSERT INTO auth_sessions (user_id, refresh_token_hash, expires_at) "
apps/api/tests/test_identity_constraints.py:268:   # Revoke this test user's role without changing shared role permissions.
apps/api/tests/test_identity_constraints.py:298:#   AND s.revoked_at IS NULL
apps/api/tests/test_identity_constraints.py:299:#   AND s.expires_at > now()
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....
        "TC_PRIV_002=NOT RUN / DEFERRED; TC_SYS_001=NOT RUN"
)
    row["Implementation status"] = "PARTIAL"
    row["Evidence path/reference"] = (
        "apps/api/app/main.py; apps/api/tests/test_identity_constraints.py; "
        "apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt"
)
    row["Outstanding gap/dependency"] = (
        "Latest API suite: 58 passed, 18 warnings. TC_AUTHZ_001 and "
        "TC_AUTHZ_002 remain NOT RUN as complete test-plan cases; "
        "TC_PRIV_002 workspace/resource authorization is deferred; "
        "TC_SYS_001 end-to-end smoke remains NOT RUN. Platform-only scope."
)
    return True

```
def update_requirements(row):
    rid = row.get("Requirement ID")
    if rid in {"FR-P1-05", "FR-P1-06", "FR-P1-07"}:
        row["Evidence path/reference"] = (
            "apps/api/app/main.py; apps/api/app/auth.py; "
            "apps/api/migrations/0002_platform_authorization.sql; "
            "apps/api/tests/test_identity_constraints.py; "
            "apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt"
        )
        row["Implementation status"] = "PARTIAL"
        row["Outstanding gap/dependency/decision"] = (
            "Platform-level permission enforcement has passing API-test "
            "evidence, but complete role-matrix, protected frontend, and "
            "end-to-end acceptance steps remain unverified. Workspace/resource "
            "authorization remains deferred. Do not infer complete requirement "
            "acceptance from the API suite alone."
        )
        return True
    return False

update_csv(story_path, update_fin15)
update_csv(req_path, update_requirements)
PY

git diff --check
python scripts/validate_traceability.py

docs/requirements/traceability-stories.csv: 1 row(s) updated
docs/requirements/traceability-requirements.csv: 3 row(s) updated
docs/requirements/traceability-requirements.csv:16: trailing whitespace.
+FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and
access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05;
FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified
2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests
arerejected; role/permission matrix is tested server-side; inactive sessions expire per
configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001;
TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT
RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN;
TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py;
apps/api/migrations/0002_platform_authorization.sql;
```

apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt,"Platform-level permission enforcement has passing API-test evidence, but complete role-matrix, protected frontend, and end-to-end acceptance steps remain unverified. Workspace/resource authorization remains deferred. Do not infer complete requirement acceptance from the API suite alone.",Preserve source story release label^M
docs/requirements/traceability-requirements.csv:17: trailing whitespace.
+FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04;FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/api/migrations/0002_platform_authorization.sql; apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt,"Platform-level permission enforcement has passing API-test evidence, but complete role-matrix, protected frontend, and end-to-end acceptance steps remain unverified. Workspace/resource authorization remains deferred. Do not infer complete requirement acceptance from the API suite alone.",Preserve source story release label^M
docs/requirements/traceability-requirements.csv:18: trailing whitespace.
+FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/api/migrations/0002_platform_authorization.sql; apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt,"Platform-level permission enforcement has passing API-test evidence, but complete role-matrix, protected frontend,and end-to-end acceptance steps remain unverified. Workspace/resource authorization remains deferred. Do not infer complete requirement acceptance from theAPI suite alone.",Preserve source story release label^M

docs/requirements/traceability-stories.csv:1: trailing whitespace.
+Story alias,Verified Jira issue key,Jira mapping verification,Story title,Four-sprint assignment,Source release label,SRS references from Jira/test-plan mapping,Relevant acceptance criteria,Test case IDs,Test execution status,Implementation status,Evidence path/reference,Outstanding gap/dependency^M
docs/requirements/traceability-stories.csv:2: trailing whitespace.
+FS-01-01,FIN-13,LIVE JIRA VERIFIED 2026-10-19,Authenticate and manage sessions,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P8-02; FR-P8-12; NFR-G-13; NFR-G-14; NFR-G-23; NFR-G-26; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P1-03; NFR-P1-05; NFR-P8-02; NFR-P9-02,Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS;TC_AUTHN_002=PASS; TC_AUTHN_003=PASS; TC_AUTHN_004=BLOCKED; TC_AUTHN_005=BLOCKED; TC_INT_001=NOT RUN; TC_SYS_001=NOT RUN; TC_TRACE_001=PASS,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt,Acceptance remains incomplete or externally unverified; see implementation record.^M
docs/requirements/traceability-stories.csv:3: trailing whitespace.
+FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07;FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_00
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test: 305
Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001, TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

```
nce fields, and Release 2 labels are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....
    )
    row["Implementation status"] = "PARTIAL"
    row["Evidence path/reference"] = (
        "apps/api/app/main.py; apps/api/tests/test_identity_constraints.py; "
        "apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt"
    )
    row["Outstanding gap/dependency"] = (
        "Latest API suite: 58 passed, 18 warnings. TC_AUTHZ_001 and "
        "TC_AUTHZ_002 remain NOT RUN as complete test-plan cases; "
        "TC_PRIV_002 workspace/resource authorization is deferred; "
        "TC_SYS_001 end-to-end smoke remains NOT RUN. Platform-only scope."
    )
    return True

def requirements(row):
    if row.get("Requirement ID") not in {"FR-P1-05", "FR-P1-06", "FR-P1-07"}:
        return False
    row["Evidence path/reference"] = (
        "apps/api/app/main.py; apps/api/app/auth.py; "
        "apps/api/migrations/0002_platform_authorization.sql; "
        "apps/api/tests/test_identity_constraints.py; "
        "apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt"
    )
    row["Implementation status"] = "PARTIAL"
    row["Outstanding gap/dependency/decision"] = (
        "Platform-level permission enforcement has passing API-test evidence, "
        "but complete role-matrix, protected frontend, and end-to-end acceptance "
        "steps remain unverified. Workspace/resource authorization remains "
        "deferred. Do not infer complete requirement acceptance from the API suite alone."
    )
    return True

edit("docs/requirements/traceability-stories.csv", fin15)
edit("docs/requirements/traceability-requirements.csv", requirements)
PY

echo "===== WHITESPACE VALIDATION ====="
git diff --check
```

```
echo "===== TRACEABILITY VALIDATION ====="
python scripts/validate_traceability.py

docs/requirements/traceability-stories.csv: 1 row(s) updated
docs/requirements/traceability-requirements.csv: 3 row(s) updated
===== WHITESPACE VALIDATION =====
===== TRACEABILITY VALIDATION =====
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test:
305
Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001,
TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query
Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels
are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

echo "===== CHANGE SUMMARY ====="
git diff --stat

echo
echo "===== TRACEABILITY DIFF ====="
git diff -- docs/requirements/traceability-stories.csv
docs/requirements/traceability-requirements.csv

echo
echo "===== FIN-15 TRACKING ====="
grep -n 'FIN-15' IMPLEMENTATION_STATUS.txt | tail -10

echo
echo "===== WORKING TREE ====="
git status --short

===== CHANGE SUMMARY =====
```

```
 .github/workflows/ci.yml                      |   4 +
 IMPLEMENTATION_STATUS.txt                     |  77 ++++++++++
 README.md                                     |   8 +-
 SPRINT_1_TEST_EXECUTION_STATUS.txt            |  33 ++++
 apps/api/app/main.py                          |  59 +++++++-
 apps/api/app/provision_user.py                |  16 +-
 apps/api/tests/test_auth_unit.py              |  44 ++++++
 apps/api/tests/test_identity_constraints.py   | 279
++++++++++++++++++++++++++++++++++
 apps/api/tests/test_provision_user.py         |  37 ++++-
 apps/web/tests/ui/auth.spec.js                |  10 ++
 conversation.txt                              |  25 ++++
 docs/architecture/README.md                   |   4 +-
 docs/requirements/traceability-requirements.csv | 820
++++++++++++++++++++++++++++++++++
```

among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-03,Authorized Retrieval,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-04,Indexing State,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-05,Update Safety,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-06,Deletion Propagation,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-07,Retry Safety,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; donot infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-08,Configuration Compatibility,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping isneeded.,Unmapped to source story
-DIR-09,Audit Separation,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion; do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-DIR-10,Backup Recovery,"PDF p.43; SRS Section 6, data-integrity rules",Data integrity and retrieval lifecycle,—,—,No mapped key,No mapped story criterion;do not infer.,—,No linked test; NOT RUN,NOT ASSESSED,—,No direct source-story link

among the 72 catalog aliases; product disposition/mapping is needed.,Unmapped to source story
-FR-P1-01,User Authentication,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-05; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04; FS-11-12,FIN-13; FIN-14; FIN-15; FIN-17; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-01/FIN-13: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.,TC_AUTHN_001; TC_AUTHN_002; TC_AUTHN_003; TC_AUTHN_004; TC_AUTHN_005; TC_INT_001; TC_SYS_001; TC_TRACE_001,TC_AUTHN_001=PASS; TC_AUTHN_002=PASS; TC_AUTH

===== FIN-15 TRACKING =====
336:- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.
338:FIN-15 implementation update — 2026-10-20
343:- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results andall acceptance criteria are checked.
346:FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
359:- test-results/FIN-15/20261020_141030_identity_authorization.log
360:- test-results/FIN-15/20261020_141030_full_api_suite.log
361:- test-results/FIN-15/run_20261020_141030_summary.txt
364:the behavior exercised by those tests, not automatic completion of every FIN-15
370:FIN-15 — CURRENT VERIFICATION ADDENDUM (2026-10-20)
392:Overall FIN-15 status: PARTIAL. Passing API tests do not constitute

===== WORKING TREE =====
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md

```
 M docs/requirements/traceability-requirements.csv
 M docs/requirements/traceability-stories.csv
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js

(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....
            )
            changed += 1

        elif name == "requirements" and row.get("Requirement ID") in {
            "FR-P1-05", "FR-P1-06", "FR-P1-07"
        }:
            row["Evidence path/reference"] = (
                "apps/api/app/main.py; apps/api/app/auth.py; "
                "apps/api/migrations/0002_platform_authorization.sql; "
                "apps/api/tests/test_identity_constraints.py; "
                "apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt"
            )
            row["Implementation status"] = "PARTIAL"
            row["Outstanding gap/dependency/decision"] = (
                "Platform-level permission enforcement has passing API-test evidence, "
                "but complete role-matrix, protected frontend, and end-to-end acceptance "
                "steps remain unverified. Workspace/resource authorization remains "
                "deferred. Do not infer complete requirement acceptance from the API suite
alone."
            )
            changed += 1

    with target.open("w", newline="", encoding="utf-8") as f:
        writer = csv.DictWriter(
            f, fieldnames=fields, lineterminator=newline
        )
        writer.writeheader()
        writer.writerows(rows)

    print(f"{target}: restored original newline style; {changed} targeted row(s) updated")
PY
```

```
echo "===== TRACEABILITY DIFF SIZE ====="
git diff --numstat -- docs/requirements/traceability-stories.csv
docs/requirements/traceability-requirements.csv

echo
echo "===== WHITESPACE CHECK ====="
git diff --check

echo
echo "===== TRACEABILITY VALIDATOR ====="
python scripts/validate_traceability.py

docs/requirements/traceability-stories.csv: restored original newline style; 1 targeted
row(s) updated
docs/requirements/traceability-requirements.csv: restored original newline style; 3
targeted row(s) updated
===== TRACEABILITY DIFF SIZE =====
3       3       docs/requirements/traceability-requirements.csv
1       1       docs/requirements/traceability-stories.csv

===== WHITESPACE CHECK =====
docs/requirements/traceability-requirements.csv:16: trailing whitespace.
+FR-P1-05,Role-Based Access Control,PDF p.3; SRS P1 requirements,Identity and
access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05;
FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified
2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests
arerejected; role/permission matrix is tested server-side; inactive sessions expire per
configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001;
TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT
RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN;
TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py;
apps/api/migrations/0002_platform_authorization.sql;
apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py;
IMPLEMENTATION_STATUS.txt,"Platform-level permission enforcement has passing
API-test evidence, but complete role-matrix, protected frontend, and end-to-end
acceptance steps remain unverified. Workspace/resource authorization remains
deferred. Do not infer complete requirement acceptance from the API suite
alone.",Preserve source story release label^M
docs/requirements/traceability-requirements.csv:17: trailing whitespace.
```

+FR-P1-06,Protected Routes,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-02-08; FS-08-01; FS-08-05; FS-09-05; FS-11-04;FS-11-12,FIN-13; FIN-14; FIN-15; FIN-25; FIN-57; FIN-61; FIN-65; FIN-75; FIN-83,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/api/migrations/0002_platform_authorization.sql; apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt,"Platform-level permission enforcement has passing API-test evidence, but complete role-matrix, protected frontend, and end-to-end acceptance steps remain unverified. Workspace/resource authorization remains deferred. Do not infer complete requirement acceptance from the API suite alone.",Preserve source story release label^M
docs/requirements/traceability-requirements.csv:18: trailing whitespace.
+FR-P1-07,Permission Enforcement,PDF p.3; SRS P1 requirements,Identity and access,FS-01-01; FS-01-02; FS-01-03; FS-01-04; FS-08-05; FS-09-05; FS-11-04,FIN-13; FIN-14; FIN-15; FIN-16; FIN-61; FIN-65; FIN-75,Live Jira JQL verified 2026-10-19; test-plan source refs,FS-01-02/FIN-15: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_INT_001; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS; TC_INT_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/app/auth.py; apps/api/migrations/0002_platform_authorization.sql; apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt,"Platform-level permission enforcement has passing API-test evidence, but complete role-matrix, protected frontend,and end-to-end acceptance steps remain unverified. Workspace/resource authorization remains deferred. Do not infer complete requirement acceptance from theAPI suite alone.",Preserve source story release label^M

===== TRACEABILITY VALIDATOR =====
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test: 305
Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09

```
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001,
TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query
Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels
are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

docs/requirements/traceability-requirements.csv: CSV text
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

python - <<'PY'
from pathlib import Path

p = Path("docs/requirements/traceability-requirements.csv")
data = p.read_bytes()
targets = (b"FR-P1-05,", b"FR-P1-06,", b"FR-P1-07,")

lines = data.splitlines(keepends=True)
fixed = 0
out = []

for line in lines:
    if line.startswith(targets) and line.endswith(b"\r\n"):
        line = line[:-2] + b"\n"
        fixed += 1
    out.append(line)

if fixed != 3:
    raise SystemExit(f"Expected to fix 3 lines, found {fixed}; file not written.")

p.write_bytes(b"".join(out))
print(f"Normalized line endings on {fixed} edited rows only.")
PY

git diff --check
git diff --numstat -- docs/requirements/traceability-requirements.csv
docs/requirements/traceability-stories.csv
```

```
python scripts/validate_traceability.py

Normalized line endings on 3 edited rows only.
3       3       docs/requirements/traceability-requirements.csv
1       1       docs/requirements/traceability-stories.csv
SRS requirement IDs: 409; source story aliases: 72; Sprint 1 source tests: 54
Requirements with Jira/test-plan story links: 328; unmapped: 81; no linked Sprint 1 test:
305
Source tests linked to a catalog story: 54/54
Sprint 1 stories: 23; with SRS IDs: 22; process-story exception: FS-11-09
Tests lacking explicit execution rows (source default NOT RUN): TC_ENV_001,
TC_ENV_002
Jira key shape and dated live-query marker checked; this offline script does not query
Jira.
VALIDATION PASS: inventories, test references, evidence fields, and Release 2 labels
are consistent.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
y_Book %  source /Users/sandeeph/Documents/NVDIA_Play_Book/.venv/bin/activate
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd
FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

echo "===== PROJECT INSTRUCTIONS ====="
sed -n '1,220p' AGENTS.md

echo
echo "===== IMPLEMENTATION STATUS (LATEST ENTRIES) ====="
tail -100 IMPLEMENTATION_STATUS.txt

echo
echo "===== TEST EXECUTION STATUS (LATEST ENTRIES) ====="
tail -100 SPRINT_1_TEST_EXECUTION_STATUS.txt

echo
echo "===== FUNCTION TEST TRACEABILITY ====="
cat FUNCTION_TEST_TRACEABILITY.txt

echo
echo "===== API DESIGN PACK FILES ====="
```

find FinSight_AI_API_Design_Pack -maxdepth 2 -type f -print

echo
echo "===== CURRENT DIFF SUMMARY ====="
git diff --stat

===== PROJECT INSTRUCTIONS =====
FinSight AI — Mandatory Repository Rules for Codex

Status: Project-wide engineering instructions
Applies to: The entire repository, unless a more-specific `AGENTS.md` exists in a subdirectory.
Primary objective: Implement FinSight AI incrementally and safely against the approved project artifacts, with verifiable tests and an honest record ofprogress.

Codex must read and follow this file at the beginning of every task and reread the relevant source artifacts before changing code in that domain. These instructions remain active across the project; do not treat them as a one-time checklist.

---

1. Role and operating principles

Act as a coordinated technical leadership and engineering team: system architect, technical lead, backend/frontend/data/AI engineer, QA engineer, and DevSecOps reviewer. Make implementation decisions consistent with the supplied project artifacts and the existing repository.

1. **Inspect before changing.** Establish the current repository state, actual stack, current branch, existing conventions, available tests, and Jira issue/sprint mapping before editing files. Do not assume the repository is empty or that a documented feature already exists.
2. **Preserve existing work.** Prefer small, reviewable changes. Do not overwrite working code, discard user changes, regenerate the whole project, or replace the existing architecture just because another approach is familiar.
3. **Follow the active scope.** Work only on the issue/story or bounded task the user has authorized. The existence of 72 planned stories does not authorize implementing all 72 at once.

4. **Test the behavior, not just the build.** Add or update tests that map to acceptance criteria. Report actual command results; do not claim a test passed unless it was run and passed.
5. **Use the smallest sound design.** Keep the backend modular. Do not introduce microservices, infrastructure, dependencies, abstractions, or frameworks without a concrete requirement and a clear reason.
6. **Keep the user involved in material decisions.** Ask before making a decision that changes product scope, architecture, data model meaning, security posture, release boundaries, external spending, or irreversible repository/Jira state.
7. **Never fabricate progress.** Distinguish `NOT STARTED`, `IN PROGRESS`, `BLOCKED`, `PARTIAL`, `FAILED`, and `VERIFIED COMPLETE`. A story is not completemerely because code was written or a task was attempted.

2. Source-of-truth hierarchy

Read the actual files present in the repository. Filenames and directories may vary; the screenshot showed a project root containing `Component_diagrams/` and a directory spelled `Dcos/`, so search for the documents rather than assuming a corrected folder name. Do not copy, rename, or “clean up” these source artifacts without authorization.

Use the sources in this order, according to the question being answered:

1. **Software Requirements Specification (SRS):** authoritative functional and non-functional requirements, security expectations, page responsibilities, and observable user behavior.
2. **Core SQL schema and Database Schema/ERD Reference:** authoritative target relational entities, column types, PK/FK relationships, constraints, provenance, and domain model. Treat the SQL files supplied as reference inputs, not disposable migration scripts.
3. **Technical Design and Implementation Plan:** architectural boundaries, contracts, configuration patterns, testing/release gates, operational design, and implementation approach.
4. **The 72-story Jira backlog with acceptance criteria:** story goals, acceptance criteria, priority, dependencies, proposed role-based ownership, implementation subtasks, and original story aliases.
5. **Full Project Four-Sprint Plan:** four-sprint allocation and intended sequencing for the 72 catalog entries. It is a plan, not proof that work has beencompleted and not permission to bypass release guards.
6. **Sprint 1 Test Plan PDF and Sprint 1 Test Plan Management TXT:** Sprint 1 test inventory, story-to-test traceability, setup and execution rules. The original files are

read-only reference documents; record actual execution results in a new status/execution file, not by editing the source register.
7. **Component diagrams and their companion/explanation document:** clarify components and relationships. They do not overrule explicit SRS requirements orschema definitions.
8. **Live repository, tests, configuration, and Jira state:** evidence of what exists now and what has actually been executed. The repository is authoritative about implementation state; Jira is authoritative about current issue keys, assignments, status, and sprint membership. Neither silently changes approved product requirements.

If two sources genuinely conflict, do not silently choose, rewrite a source file, or invent a resolution. Record the conflict and its impact in `conversation.txt`, cite the relevant filenames/sections/pages, recommend the safest interpretation, and ask the user when the decision affects implementation or scope. You may continue independent, reversible inspection work while waiting.

3. Product architecture baseline

Unless the source documents or current repository establish a documented, user-approved variation, follow this baseline:

- **Frontend:** Next.js / React.
- **Backend:** modular FastAPI application with clear domain boundaries and typed API contracts.
- **Structured database:** PostgreSQL; structured relational records are the source of truth.
- **Vector retrieval:** pgvector in the PostgreSQL deployment for the initial RAG design; document/chunk IDs and permissions remain relationally authoritative.
- **LLM inference:** Ollama behind a provider/adapter interface, so model access can be configured, mocked in tests, or replaced without changing business logic.
- **Embedding and market-data providers:** typed adapters with validation, timeouts, useful error mapping, and deterministic test doubles.
- **Long-running operations:** persisted job/run states, stable IDs, bounded retries, idempotency, and safe recovery. Redis is optional and must not becomethe authoritative record unless an approved design change says so.
- **Financial calculations:** deterministic, tested backend functions/services own numeric outputs. The LLM may explain those outputs and assumptions; it must not be the authoritative calculator.
- **Authorization:** validate authentication and resource/operation permissions on the backend. Filter document permissions before any content is added to an LLM context.

First inspect the actual repository. Do not create a second frontend/backend, replace a working framework, or invent directory structures until the existing structure and gaps have been mapped.

4. Scope, planning, and Jira rules

4.1 Four-sprint baseline

The active project plan is the **four-sprint** plan for 72 story/task entries. Do not resurrect the superseded seven-day plan or use it to reorder the project. Preserve the `FS-*` aliases as traceability labels and map them to the real Jira issue keys found in the live project.

The source allocation describes Sprint 1 as foundation, identity, secure configuration, and delivery controls (23 entries, 63 source story points), with a total of 72 entries and 251 source story points across four sprints. These are source planning estimates, not evidence of actual team velocity or a promise that every acceptance criterion can be delivered on the stated calendar dates.

4.2 Verify Jira before relying on it

Before changing Jira, inspect current issue keys, stories, epics, status, assignees, dependencies, and sprint membership. A provided screenshot showed a `FIN Sprint 1` section with **0 work items**, while the surrounding backlog showed many issues in `To Do`. Treat that as a discrepancy to verify, not as proofthat the sprint is populated.

If Sprint 1's actual Jira membership conflicts with the four-sprint plan:

- Record the discrepancy in `conversation.txt` with the relevant issue keys and counts.
- Tell the user precisely what needs confirming.
- Do not bulk-move stories, change estimates, alter priorities, assign people, start a sprint, or create/close issues without explicit authorization.
- Continue repository inspection and safe, independent Sprint 1 preparation when possible.

Do not claim that Jira has been updated unless the change was actually made and verified. If no Jira integration/tool is available, prepare instructions oran import artifact instead of claiming direct modification.

4.3 Scope gates

- Implement only authorized work, starting with the current Sprint 1 scope unless the user explicitly directs otherwise.
- Preserve original priorities, estimates, release labels, acceptance criteria, and dependencies unless the user approves a change.
- Do not mark a grouped story complete while any required acceptance criterion remains unimplemented or unverified. Use subtasks and status notes to show partial progress.
- A story can be marked complete only when its acceptance criteria, appropriate automated tests, code review, relevant security/data-isolation checks, and required traceability/evidence satisfy the Definition of Done.

5. Release and database safety rules

5.1 Release 1 is read-only financial research

The Release 1 guardrail is mandatory:

- No live broker order submission, modification, or cancellation endpoints.
- No enabled broker execution flow or live-trading credentials.
- Do not apply `schema_optional_trading.sql` or otherwise create its optional 15-table trading extension in Release 1.
- The trading-related stories identified in the backlog as Future / Release 2 remain gated even if they appear in a sprint allocation.
- A read-only connection or analytical feature must not silently expand into trading permission.

Any future change to this boundary requires explicit user approval and the separate security/operational review specified in the project documents.

5.2 PostgreSQL schema handling

- The supplied core `schema.sql` describes a 158-table target-state schema. It is **not** an instruction to implement all tables or all features immediately.
- Inspect the current database, migrations, and code before proposing changes. Do not run the supplied full schema directly against an existing or non-disposable database without explicit approval and a verified backup/recovery plan.

- Create new, version-controlled migrations in the repository's established migration system. Never edit the source SQL/schema/reference PDFs to show implementation progress.
- Apply migrations only to a confirmed development/test database. Verify a clean install and, where supported, a forward migration from the previous schemaversion.
- Preserve declared types, PK/FK constraints, uniqueness, checks, ownership, source lineage, timestamps, and financial precision. Use `NUMERIC` rather thanbinary floating point for stored money/financial quantities in accordance with the schema and design.
- Treat `seed_reference_data.sql` as optional development reference seed data, not production market data. Check that target tables and conflict behavior are compatible before use.
- Use PostgreSQL 16+ and pgvector as the design baseline unless the existing supported environment documents otherwise. Confirm required extensions are available before depending on them.
- Never drop tables, truncate user data, reset a database, rewrite migration history, or run destructive SQL without the user's explicit approval and a clear recovery plan.

6. Immutable project artifacts

The following supplied items are reference inputs and must remain unchanged unless the user specifically authorizes a revision:

- SRS PDF and source requirements documents.
- Technical Design and Implementation Plan PDF.
- Database Schema/ERD Reference PDF and source SQL files, including `schema.sql`, `seed_reference_data.sql`, and `schema_optional_trading.sql`.
- Original Jira backlog PDFs, 72-story backlog/acceptance-criteria document, and four-sprint plan.
- Sprint 1 Test Plan PDF and its existing management TXT.
- Component architecture PNG/SVG/Mermaid files and companion/explanation PDF.

Do not edit their contents, overwrite them with generated text, rename them, regenerate them, or alter their dates/claims. Use code, migrations, tests, configuration, ADRs, and new coordination/status files for implementation outputs. If an approved design change is needed, write a separate addendum/ADR ratherthan silently rewriting a source baseline.

Before and after a task that touches project files, inspect `git status` and the diff. Do not discard uncommitted user changes. Do not run `git reset --hard`, `git clean -fd`, forced

pushes, or equivalent destructive Git commands. Do not commit, push, merge, create a pull request, or alter remote branches unless the user explicitly asks for that action.

7. Required coordination files

Use small root-level coordination files so implementation progress and questions are visible without altering the source documents. If a file already exists, read it first and preserve existing entries.

7.1 `conversation.txt` — user/Codex question and decision log

Create this file in the repository root if it does not exist. Treat it as a shared conversation/decision log, not as source code or a place to store secrets. It should contain:

- Open questions, each with an ID, why the answer matters, choices if useful, a recommended choice, and the exact next action needed from the user.
- Requests for missing provider/service configuration, with the **environment variable names only**, purpose, whether required now or later, and step-by-step safe setup instructions.
- User-provided non-secret answers/decisions, decision date, and the task/story affected.
- Blocking issues, source conflicts, and a `WAITING FOR USER` or `ANSWERED` marker.

When a question requires user action, explain exact steps: which application/provider to open, where to find/create the setting or credential, where to configure it locally, and what non-secret confirmation to add to `conversation.txt`. Then pause any work dependent on the answer. Continue only work that is independent and safe.

Secrets policy: never ask the user to paste API keys, passwords, tokens, private keys, database passwords, or session secrets into `conversation.txt`, source files, terminal output, screenshots, Jira descriptions, or Git. Never print, echo, or commit actual secret values. Request that the user add secret values directly to a local ignored `.env` file or approved secret manager and return only a confirmation such as `Configured locally; value not shared`. Ensure `.env`, credentials, tokens, local database dumps, and other sensitive artifacts are ignored by Git. `.env.example` may contain variable names and safe placeholders only.

If Codex discovers a secret already tracked or exposed, stop further exposure, avoid repeating its value, notify the user, recommend revocation/rotation, and follow the repository's established secret-removal procedure only with authorization.

7.2 `IMPLEMENTATION_STATUS.txt` — completion markers

Create this file if missing and update it after meaningful work. Include the task/story alias and real Jira key when known, status, concise implementation summary, changed file paths, commands actually run, tests and observed outcomes, unresolved acceptance criteria, blockers, and evidence paths/links if available.

Use these states only:

- `NOT STARTED`
- `IN PROGRESS`
- `BLOCKED`
- `PARTIAL`
- `FAILED`
- `VERIFIED COMPLETE`

Only use `VERIFIED COMPLETE` when the applicable Definition of Done is met and evidence is recorded. Otherwise use `PARTIAL`, `FAILED`, or `BLOCKED` as appropriate. Never infer success from an exit code that was not observed, from a planned test, or from code inspection alone when runtime verification is required.

7.3 Test-execution record

Do not edit the supplied test-plan files. If actual Sprint 1 test results need recording, create a separate root file such as `SPRINT_1_TEST_EXECUTION_STATUS.txt` with each test ID, initial status `NOT RUN`, execution date, actual result, tester/owner, evidence, and linked defect if any. Update statuses only after executing the case. Use `PASS`, `FAIL`, `BLOCKED`, and `NOT RUN`; `N/A` requires documented justification. Do not represent a test as passed if its dependency/component does not exist.

Do not create unnecessary coordination files beyond these needs. Keep records concise and factual.

8. Clarification and stop conditions

Ask a clear, focused user question before proceeding when any of the following is true:

- A conflict in source documents changes behavior, schema meaning, scope, or release eligibility.
- A decision is irreversible/destructive or could lose user work/data.
- A required external credential, licensed data feed, paid service, or permission is unavailable.
- The Jira issue/sprint mapping or scope is ambiguous and changing it would affect commitments.
- An acceptance criterion cannot be met without choosing between materially different product behaviors.
- An architecture/security decision is not established by the source documents or current repository.

Do not ask questions whose answers can be determined safely from the repository or supplied documents. Before asking, investigate the available evidence and report what you found. When blocked, write the question and next action to `conversation.txt`, summarize the blocker to the user, and stop only the dependent work.

9. Credentials, API keys, and external providers

- Do not assume that any specific API key is required until a selected feature/provider actually needs it.
- Ollama may be available locally without a hosted LLM API key; inspect the approved setup and test connectivity before concluding it is configured.
- Market-data providers, embedding services, hosted models, email delivery, or other integrations may require credentials depending on the selected adapterand environment. Do not choose a paid provider or trigger spending without approval.
- Use provider interfaces and deterministic fixtures/mocks so tests can run without live API access where appropriate.
- If a key is required, add a non-secret request to `conversation.txt` containing the variable name, service, reason, whether it blocks the active story, and exact setup steps. Wait for confirmation that it has been configured safely; do not request the secret itself.
- Distinguish `missing configuration`, `provider unavailable`, `invalid credentials`, `rate limited`, and `no data` in internal error handling. Do not leakprovider responses or secrets to users/logs.

10. Coding standards and engineering workflow

Apply the repository's existing formatter, linter, type checker, tests, dependency manager, and naming conventions. Do not introduce a competing toolchain without approval.

For each authorized story or task:

1. **Read:** reread relevant SRS requirements, schema entities, technical design sections, backlog acceptance criteria, dependencies, and relevant test-plan cases.
2. **Inspect:** review the current implementation, `git status`, recent relevant commits where available, and existing test patterns.
3. **Plan:** identify the smallest vertical slice, dependencies, impacted files, migration impact, security concerns, test cases, and any user decision needed. Record concise intent in the status file.
4. **Test first where practical:** add or adjust a failing test for a clearly defined behavior before implementing it (TDD). Do not claim TDD was followed if it was not.
5. **Implement:** make small, typed, maintainable changes; validate all inputs at boundaries; use explicit timeouts and bounded retries for external calls;preserve ownership and provenance; keep side effects controlled.
6. **Verify:** run focused tests first, then relevant integration/regression tests, lint/type/static/security checks and builds available in the repo. Use disposable/test resources and synthetic data.
7. **Review:** inspect the complete diff for accidental changes, secrets, unsafe defaults, unrelated formatting churn, altered source documents, schema drift, missing tests, and unmet acceptance criteria.
8. **Record:** update only the new coordination/status files with actual results. Include exact commands and concise output summaries; redact environment values and secrets.
9. **Report:** state what changed, what tests ran, what passed/failed/was blocked, remaining criteria, and the next recommended step. Do not claim deployment or Jira updates unless they happened and were verified.

Do not weaken or delete a test simply to make the build pass. If a test exposes a product/design ambiguity, stop and ask rather than encoding a convenient assumption.

General code requirements

- Prefer explicit types, cohesive modules, small functions, and clear dependency boundaries.
- Validate and normalize user/provider input at the boundary.

- Use parameterized SQL/ORM operations. Never interpolate untrusted input into SQL or permit arbitrary SQL execution through Data Explorer features.
- Use transactions for coupled database updates and enforce constraints in the database where appropriate.
- Make retried ingestion and job operations idempotent. Use stable run IDs and safe state transitions.
- Keep logs structured and useful but redact secrets and sensitive user data; never return stack traces or internal secrets to end users.
- Set realistic timeouts and bounded retries for database, network, model, and provider operations. Fail gracefully when optional dependencies are down.
- Add accessible labels, keyboard operation, visible focus, useful loading/error/empty states, and responsive behavior for UI work.
- Avoid nondeterministic unit tests and internet-dependent CI tests. Use fixtures or mocks for external integrations; separately verify real integration connections when needed.
- Keep financial calculations reproducible: document formulas/units, input snapshots, assumptions, data timestamps, precision, and formula/model versions as applicable.

11. Security, privacy, RAG, and financial correctness gates

The following are release-blocking if violated:

===== IMPLEMENTATION STATUS (LATEST ENTRIES) =====
- `python3 scripts/validate_traceability.py`: PASS; extracted 409 SRS IDs, 72 aliases, 54 test IDs; checked CSV inventories, valid test references, live Jira evidence markers, verified evidence fields, 23 Sprint 1 stories (22 with explicit SRS IDs; FS-11-09 process-story exception), Release 2 labels. Validatorclearly states it does not query Jira.
- `python3 -m py_compile scripts/validate_traceability.py`: PASS.
- CSV counts: 409 requirements; 72 stories; 104 requirement rows linked to supplied tests; 305 without supplied test links. Requirement status counts: NOT ASSESSED 110; IMPLEMENTED — VERIFIED 6; NOT IMPLEMENTED 45; PARTIAL 15; PLANNED 233.
- Local relative-link check across matrix, addendum, and root README: PASS, no missing relative links.
- TC_TRACE_001: PASS based on verified 23 Sprint 1 aliases/Jira mappings, 22 explicit SRS-ID links with the FS-11-09 process exception, 54/54 source test cases linked to a catalog story, intact Release 2 labels, and visible gaps. TC_ENV_001 and TC_ENV_002 remain without execution rows and default to NOT RUN; all other unexecuted tests retain their prior states.

Remaining criteria: FIN-79 remains PARTIAL. Product-owner decisions are required for 81 unmapped requirements and for Jira-only FIN-84–FIN-87 without source aliases; see Q-009 and Q-010 in `conversation.txt`. The supplied test plan covers Sprint 1, not full project-wide validation. No source-document or Git diff review was attempted; Git responsiveness remains the separately recorded blocker.

FIN-73 targeted CI repair — GitHub Actions run 39203215763 (2026-10-19)
Status: PARTIAL; local fixes verified, remote run pending.
Repairs:
- In `.github/workflows/ci.yml`, changed the frontend archive source to `.next` relative to the job working directory `apps/web`, and added hard checks that `.next/standalone` and `.next/static` exist before archiving. Archive still contains top-level `standalone/` and `static/`, matching E2E extraction and release-package restoration paths.
- Normalized line endings in `docs/requirements/traceability-stories.csv` from CRLF to LF. Parsed CSV values were compared against HEAD and all 73 rows (including the header) were identical. The current file has no trailing whitespace.
- Removed the extra blank line at EOF from `scripts/validate_traceability.py`; one required final newline remains. There is no in-repository generator for the traceability CSV; the validator only reads it.
Checks (2026-10-19):
- PyYAML parse and targeted archive-step assertions: PASS.
- `NEXT_TELEMETRY_DISABLED=1 npm run build` in `apps/web`: PASS, exit 0; Next.js 16.4.2 production build completed and emitted standalone output.
- Confirmed `apps/web/.next/standalone` and `apps/web/.next/static` exist after build.
- `tar -czf /tmp/finsight-frontend-build.tar.gz -C .next standalone static` (with macOS `COPYFILE_DISABLE=1` for local archive inspection): PASS. Archive inspection found only root entries `standalone/` and `static/` (1,466 entries); SHA-256 verified: `651f28563199baf95574f9c23fc78e2b8d6a10a88bf4a114c3fc033b744c3513`.
- `python3 scripts/validate_traceability.py`: PASS (409 requirements, 72 aliases, 54 tests; 328 mapped, 81 unmapped; source test IDs TC_ENV_001/002 remain NOT RUN).
- `python3 -m py_compile scripts/validate_traceability.py`: PASS.
- CSV trailing-whitespace scan: 0 rows. `git diff --check`: PASS, exit 0.
GitHub-side limitation: `git show --check --format= HEAD` against the existing root commit exits 2 with 1,323 diagnostics, including immutable source PDFs and other pre-existing root-commit files. No source PDF/SQL/diagram/test plan was edited. The targeted working diff passes `git diff --check`; an incremental commit/push is needed so the next GitHub run checks only the corrective diff. No commit, push, Jira update, or remote rerun was made. A new GitHub Actionsresult is required before claiming the repair passed remotely; FIN-73/74/79 status is unchanged.

Final review note (2026-10-19): `git diff --check` exited 0 for the targeted workflow/CSV/script changes before coordination records were appended. A laterfull `git diff --check` attempt timed out after 8 seconds (intermittent Git responsiveness); direct trailing-whitespace scans of `.github/workflows/ci.yml`, `docs/requirements/traceability-stories.csv`, `scripts/validate_traceability.py`, and both updated coordination files found zero whitespace errors and allhad final newlines. The historical root-commit check result above remains distinct from the current worktree check.

FIN-15 / FS-01-02 — Enforce roles and protected routes (2026-10-19)
Status: BLOCKED pending role-scope decision; implementation not started.
Inspected relevant SRS access-control requirements, canonical schema and reference seeds, FS-01-02 backlog, four-sprint/test-plan mapping, architecture docs, identity/session API, migration 0001, trusted provisioning CLI, and relevant tests.
Existing routes: public POST `/auth/login`, POST `/auth/logout`, protected GET `/auth/me`; no product/admin operation or protected frontend page currently exists.
Existing session dependency already rejects absent, revoked, and expired sessions; prior `TC_AUTHZ_003` expiry result remains PASS as previously recorded.
Schema blocker: migration 0001 has only nullable `users.platform_role_id`; it has no permission/role_permissions/workspace/workspace_members persistence. Canonical schema seeds `platform_admin` as platform scope and `operator`/`standard_user` as workspace scope. Converting workspace roles into global roles or silently creating a default workspace would change authorization/data semantics. See Q-011 in `conversation.txt`; user decision requested: platform roles only and defer workspace roles, or authorize minimal canonical workspace membership model.
Verification: attempted `.venv/bin/python -m pytest -q apps/api/tests/test_auth_unit.py -k 'unauthenticated or protected_routes_require_authentication'`; command returned no output during bounded polling and was interrupted. Outcome is NOT RUN / no test evidence. No application, migration, frontend, traceability, test-register, source, Jira, or Git files were changed. Relevant test statuses remain unchanged pending decision and executable verification.
Remaining acceptance criteria: role/permission matrix, 403 behavior, trusted role resolution/provisioning assignment, protected route application, and frontend guard cannot be completed safely until scope decision and a concrete capability/resource mapping are established. TC_AUTHZ_001 also requires a protected frontend page (none exists); TC_AUTHZ_002 currently names a model/provider admin operation that does not exist; TC_PRIV_002 requires workspace membership/resources not implemented. FIN-15 is not ready for acceptance.

FIN-15 verification update — 2026-10-20

- PostgreSQL 17.6 is running locally.
- Created and used the dedicated finsight_test database.
- Applied apps/api/migrations/0001_auth_identity.sql successfully.
- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API test suite: 55 passed, 0 failed, 9 warnings.
- git diff --check: no errors reported.
- Warning: Starlette/httpx deprecation warnings remain.
- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.

FIN-15 implementation update — 2026-10-20
- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and allacceptance criteria are checked.
- No migrations, commits, pushes, or workspace schema changes performed by this patch script.

FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
Latest run: 20261020_141030
Recorded revision: 64f2637
Python: 3.14.6
Database: finsight_test

Observed results:
- tests/test_identity_constraints.py: 3 passed, 4 warnings.
- Full API suite: 55 passed, 10 warnings.

- Both pytest commands exited with code 0.
- The test-run summary records Overall result: PASS.

Evidence:
- test-results/FIN-15/20261020_141030_identity_authorization.log
- test-results/FIN-15/20261020_141030_full_api_suite.log
- test-results/FIN-15/run_20261020_141030_summary.txt

The warnings were Starlette/httpx deprecations. The passing test suites establish the behavior exercised by those tests, not automatic completion of every FIN-15 acceptance criterion. Workspace membership and resource-level authorization remain deferred under the approved platform-only scope. Earlier entries are retained as historical records; this addendum records the later successful run.

FIN-15 — CURRENT VERIFICATION ADDENDUM (2026-10-20)
Scope: platform-level authorization only; workspace membership and resource-level authorization remain deferred under the approved scope decision.

Current API test evidence:
- Full API suite: 58 passed, 18 warnings.
- Traceability validator: PASS.
- Endpoint: GET /api/v1/admin/authorization/capabilities.
- Permission checks use database-resolved authorization; tests cover administrator access, standard-user denial, permission revocation, and platform-role revocation.
- TC_AUTHZ_001 remains NOT RUN as a complete test-plan case because its protected-frontend and response/log inspection steps are not all evidenced.
- TC_AUTHZ_002 remains NOT RUN as a complete test-plan case because its full role matrix, protected model/provider operation, and request-body privilege-manipulation steps are not all evidenced.
- TC_AUTHZ_003 retains its existing recorded status; the current 58-test result alone does not establish that every test-plan step was rerun.
- TC_PRIV_002 remains NOT RUN / deferred: workspace and cross-user resource authorization are not implemented by this platform-only change.
- TC_SYS_001 remains NOT RUN until the required end-to-end smoke path is run.

Overall FIN-15 status: PARTIAL. Passing API tests do not constitute acceptance of every story criterion. No claim is made that the story is fully accepted. Historical entries above this addendum are retained.

===== TEST EXECUTION STATUS (LATEST ENTRIES) =====
Status: PASS
Execution date: 2026-10-18
Actual result: A synthetic random password and session token were inserted into the disposable PostgreSQL database; the generated `pg_dump` contained theirpassword/session digests and neither plaintext value. The login test also verified response and captured log/stdout/stderr privacy. The synthetic user was deleted and dump removed.
Evidence: `test_password_hash_is_argon2_and_never_plaintext`, `test_login_creates_protected_hashed_expiring_session`, and the disposable scan command/result summarized in `IMPLEMENTATION_STATUS.txt`.

TC_AUTHN_007 — Verify HTTPS transport and secure cookie handling in deployed configuration
Status: BLOCKED
Actual result: The cookie was verified HttpOnly and SameSite=Lax in local HTTP tests; `COOKIE_SECURE=true` sets Secure. No deployed HTTPS endpoint was available to verify transport enforcement.
Evidence: `test_secure_cookie_can_be_required_by_deployment`.

Other cases remain NOT RUN unless listed below. Password recovery is required by SRS FR-P1-03 while password authentication is enabled, and is BLOCKED pending the decision in conversation.txt Q-005. Broader RBAC/security cases, deployment checks, and manual browser accessibility were not executed.

Full Sprint 1 inventory status index (source register contains 54 cases):
TC_CI_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Workflow YAML parsed locally; GitHub Actions pull-request run not available without publishing changes | Tester/owner: Codex | Evidence: .github/workflows/ci.yml; workflow validation command in IMPLEMENTATION_STATUS.txt | Linked defect: GitHub run required
TC_CI_002 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Local checks pass, but GitHub required-check/failing-job enforcement not verifiedon an actual PR | Tester/owner: Codex | Evidence: .github/workflows/ci.yml; conversation.txt Q-006 | Linked defect: GitHub rules/run required
TC_BUILD_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Versioned local package built with runtime API configuration and verified checksum/repeatable packaging; no full source commit SHA was available because implementation changes are uncommitted | Tester/owner: Codex | Evidence:

dist/finsight-0.1.0-local.tar.gz; adjacent build-info/checksum; IMPLEMENTATION_STATUS.txt | Linked defect: committed candidate SHA required
TC_BUILD_002 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Deployment/rollback runbook recorded and extracted package smoke-tested locally; no hosting target or previous known-good release exists to execute a deployment rollback | Tester/owner: Codex | Evidence: docs/release/RELEASE_README.md; local extracted bundle smoke result in IMPLEMENTATION_STATUS.txt | Linked defect: target and prior release required
TC_TEST_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: Backend unit and PostgreSQL integration suites passed; frontend interaction tests passed; live browser smoke passed twice against fresh synthetic accounts and once against production standalone output; exit codes and JUnit reports reviewed | Tester/owner: Codex | Evidence: apps/api/tests/test_auth_unit.py; apps/api/tests/test_auth.py; apps/api/tests/test_identity_constraints.py; apps/web/test-results/ui/results.xml; apps/web/test-results/e2e/results.xml; coverage.xml; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: —
TC_DB_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Existing identity migration applied to a fresh disposable PostgreSQL database; case-insensitive email uniqueness and session cascade verified. Full case remains blocked because only identity/session schema exists; api_credentials, audit_events, execution_runs, service_health_checks and migration-runner repeatability are not implemented | Tester/owner: Codex | Evidence: apps/api/migrations/0001_auth_identity.sql; apps/api/tests/test_identity_constraints.py; IMPLEMENTATION_STATUS.txt | Linked defect: Missing broader Sprint 1 schemas and migration runner
TC_COV_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: CI-equivalent unit (37) and PostgreSQL integration (10) suites passed; cumulative backend line coverage 156/156 (100%) and branch coverage 28/28 (100%). Provisioning CLI, configuration and authentication/session database failure paths weretested. Frontend source coverage is not supported by current Playwright instrumentation; remote artifact retention remains unverified. | Tester/owner: Codex | Evidence: coverage.xml (ignored local report); htmlcov/index.html (ignored local report); /tmp/finsight-coverage.json; apps/api/tests/test_auth.py; apps/api/tests/test_auth_unit.py; apps/api/tests/test_provision_user.py; IMPLEMENTATION_STATUS.txt | Linked defect: GitHub artifact confirmation / frontend source instrumentation decision
TC_INT_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Authentication/session persistence tested against PostgreSQL; configuration versioning, audit persistence, and authorized/denied configuration update flows are absent from the current implementation | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py; apps/api/tests/test_identity_constraints.py;

IMPLEMENTATION_STATUS.txt | Linked defect: FIN-08/FIN-09 capabilities not implemented
TC_SYS_001 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Browser smoke verified current sign-in/session/logout path against live frontend, FastAPI, and PostgreSQL. Full planned dashboard/settings, dependency health, Ollama available/unavailable, and correlation-log workflow cannot run becausethose components are not implemented | Tester/owner: Codex | Evidence: apps/web/tests/e2e/auth.spec.js; scripts/run_live_e2e.py; IMPLEMENTATION_STATUS.txt | Linked defect: Current application implements auth starter only
TC_SEC_001 | Status: BLOCKED | Execution date: 2026-10-19 | Actual result: Local dependency audits and Bandit ran. Before remediation npm audit found 3 vulnerable dependency nodes (1 critical, 2 high); pip-audit found 14 advisory records across 3 packages. After targeted updates npm audit and pip-audit reported zero known vulnerabilities. Security job added to CI and release-package depends on it; workflow parsed locally but no GitHub runner execution was available. | Tester/owner: Codex | Evidence: /tmp/finsight-npm-audit-before.json; /tmp/finsight-npm-audit-after.json; /tmp/finsight-pip-audit.json; /tmp/finsight-pip-audit-after.json; .github/workflows/ci.yml; IMPLEMENTATION_STATUS.txt | Linked defect: GitHub Actions run required
TC_SEC_002 | Status: BLOCKED | Execution date: 2026-10-19 | Actual result: Secret-pattern scan of application/configuration paths reported no matches. Upload validation and prompt-injection tests could not be exercised because file upload and RAG/context construction are not implemented in this repository; no related feature or tests were added. | Tester/owner: Codex | Evidence: local source/config credential-pattern scan; apps/web/app/page.js; IMPLEMENTATION_STATUS.txt | Linked defect: Upload/RAG implementation required in authorized later stories
TC_DOC_001 | Status: PASS | Execution date: 2026-10-19 | Actual result: Reviewed documented current endpoints and schemas against generated FastAPI OpenAPI; representative invalid login returned 422 with `detail`, and unauthenticated `/auth/me` returned 401 with the documented generic detail. Architecture and compatibility notes distinguish current implementation from target features. | Tester/owner: Codex | Evidence: docs/architecture/README.md; docs/architecture/adr/; command output recorded in IMPLEMENTATION_STATUS.txt | Linked defect: —
TC_TRACE_001 | Status: PASS | Execution date: 2026-10-19 | Actual result: All 23 Sprint 1 plan aliases have verified Jira mappings; 22 have explicit SRS requirement IDs and FS-11-09/FIN-80 is explicitly recorded as a process story with no direct SRS ID; all 54 source test cases map to a Sprint 1 story; Release2 labels remain intact; unmapped requirements and catalog extras are reported explicitly. | Tester/owner: Codex | Evidence: docs/requirements/traceability-matrix.md; docs/requirements/traceability-requirements.csv;

docs/requirements/traceability-stories.csv; scripts/validate_traceability.py | Linked defect: —
TC_MGMT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_REL_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_ETH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_OPS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_OPS_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_OPS_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHN_001 | Status: PASS | Execution date: 2026-10-18 | Actual result: Login/session/persistence/protected request verified | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
TC_AUTHN_002 | Status: PASS | Execution date: 2026-10-18 | Actual result: Generic failure responses verified | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
TC_AUTHN_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Logout revocation and replay rejection verified | Tester/owner: Codex | Evidence:apps/api/tests/test_auth.py | Linked defect: —
TC_AUTHN_004 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Password recovery is required while password authentication is enabled; implementation and delivery approach await user decision | Tester/owner: Codex | Evidence: conversation.txt Q-005; SRS FR-P1-03 | Linked defect: —
TC_AUTHN_005 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Public registration is absent, but admin onboarding workflow is incomplete | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
TC_AUTHZ_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHZ_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHZ_003 | Status: PASS | Execution date: 2026-10-18 | Actual result: Stale session rejected under configured TTL | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
TC_AUTHSEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_AUTHSEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHSEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHSEC_004 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHN_006 | Status: PASS | Execution date: 2026-10-18 | Actual result: Disposable synthetic database dump contained password/session digests; plaintext password/token absent; API test checked captured logs/stdout/stderr and response | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py; disposable scan summarized in IMPLEMENTATION_STATUS.txt (dump removed) | Linked defect: —
TC_AUTHN_007 | Status: BLOCKED | Execution date: 2026-10-18 | Actual result: Local cookie flags checked; deployed HTTPS verification unavailable | Tester/owner: Codex | Evidence: apps/api/tests/test_auth.py | Linked defect: —
TC_AUTHN_008 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_AUTHN_009 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_LLM_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_LLM_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_LLM_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_CFG_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_CFG_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_CFG_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_CFG_004 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_CRED_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_CRED_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_PRIV_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_PRIV_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

TC_EXEC_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_EXEC_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_EXEC_003 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_DASH_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_DASH_002 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_INT_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_SYS_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —
TC_BOUNDARY_001 | Status: NOT RUN | Execution date: — | Actual result: — | Tester/owner: — | Evidence: — | Linked defect: —

Additional test evidence — 2026-10-20
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q tests/test_identity_constraints.py
- Result: 3 passed, 0 failed, 3 warnings.
- Command: DATABASE_URL="postgresql:///finsight_test" python -m pytest -q
- Result: 55 passed, 0 failed, 9 warnings in 9.52s.
- Environment: local PostgreSQL 17.6; dedicated finsight_test database.
- Migrations applied successfully before test execution: 0001_auth_identity.sql and 0002_platform_authorization.sql.
- Warnings are Starlette/httpx deprecations; no test failures in the final full-suite run.
- Note: these results record the executed suite only; do not infer individual test-case IDs as PASS without verifying their mapping to the test inventory.

FIN-15 route-level authorization test update — 2026-10-20
- Test mapping: TC_AUTHZ_001 / TC_AUTHZ_002 / TC_AUTHZ_003 (existing session expiry regression coverage).
- Added integration assertions for GET /platform/admin/capability against the real FastAPI app: anonymous request expects 401; platform-admin session expects 200; authenticated user without permission expects 403 even with X-Role: platform_admin.
- Status after code edit: NOT RUN. Execute the mapped tests and update statuses only from observed results.

FIN-15 — VERIFIED EXECUTION ADDENDUM (2026-10-20)

Run ID: 20261020_141030
Python: 3.14.6
Database: finsight_test
Recorded Git revision: 64f2637

Results:
- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
- Full API suite: 55 passed, 10 warnings; exit code 0.
- Evidence files:
  test-results/FIN-15/20261020_141030_identity_authorization.log
  test-results/FIN-15/20261020_141030_full_api_suite.log
  test-results/FIN-15/run_20261020_141030_summary.txt

These results supersede earlier NOT RUN notes for the test execution performed in this run. They do not establish that every mapped test-plan case or the entire FIN-15 story is complete. Workspace-level authorization remains deferred.

===== FUNCTION TEST TRACEABILITY =====
FinSight AI — Function/Test Traceability

FIN-15 / FS-01-02 — platform authorization capability endpoint
Function: GET /api/v1/admin/authorization/capabilities
Authorization rule: requires a valid active session and database-resolved `platform.admin` permission; deny by default.
Scope: platform-only. Workspace roles, membership, and workspace tables are deferred.
Test mapping: TC_AUTHZ_001 (unauthenticated/invalid session denial), TC_AUTHZ_002 (permission matrix: platform admin allowed, standard user denied; client-supplied X-Role ignored), TC_AUTHZ_003 (session expiry/revocation behavior via existing session dependency).
Evidence note: route integration assertions were added to apps/api/tests/test_identity_constraints.py. Mark test cases PASS only after executing the mappedtests and confirming the expected behavior.

FIN-15 — EXECUTION EVIDENCE ADDENDUM (2026-10-20)
Run ID: 20261020_141030
Endpoint: GET /api/v1/admin/authorization/capabilities

Observed execution:
- tests/test_identity_constraints.py: 3 passed, 4 warnings.

- Full API suite: 55 passed, 10 warnings.
- Both pytest commands exited with code 0.
- Evidence:
  test-results/FIN-15/20261020_141030_identity_authorization.log
  test-results/FIN-15/20261020_141030_full_api_suite.log
  test-results/FIN-15/run_20261020_141030_summary.txt

Case-status guidance:
- TC_AUTHZ_001: verify its exact assertions before marking fully PASS; the integration
  test suite passed, but broader acceptance criteria must also be checked.
- TC_AUTHZ_002: PASS for the platform permission behavior explicitly asserted by the
  integration test; this does not imply missing model/provider operations exist.
- TC_AUTHZ_003: existing expiry/revocation regression passed in an earlier recorded
run;
  it was not separately rerun under run ID 20261020_141030.
- TC_PRIV_002: BLOCKED / deferred because workspace membership and
resource-level
  authorization are outside the approved platform-only scope.
- TC_SYS_001: not established by the API suite alone; broader system acceptance
remains
  to be verified.

Do not infer full story completion from a green test suite. Historical entries are
retained, and this addendum records the latest observed execution.

===== API DESIGN PACK FILES =====
FinSight_AI_API_Design_Pack/FinSight_AI_OpenAPI_3.1.yaml
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contrac
t.md
FinSight_AI_API_Design_Pack/FinSight_AI_API_Requirement_Traceability.csv
FinSight_AI_API_Design_Pack/README.md
FinSight_AI_API_Design_Pack/FinSight_AI_API_Endpoint_Catalog.csv
FinSight_AI_API_Design_Pack/FinSight_AI_API_Story_Coverage.csv
FinSight_AI_API_Design_Pack/FinSight_AI_API_Design_and_Implementation_Contrac
t.docx

===== CURRENT DIFF SUMMARY =====
 .github/workflows/ci.yml | 4 ++
 IMPLEMENTATION_STATUS.txt | 77
++++++++++++++++++++++++++++

```
 README.md                                  |   8 ++-
 SPRINT_1_TEST_EXECUTION_STATUS.txt         |  33 ++++++++++++
 apps/api/app/main.py                       |  59 ++++++++++++++++++++-
 apps/api/app/provision_user.py             |  16 +++---
 apps/api/tests/test_auth_unit.py           |  44 +++++++++++++++++
 apps/api/tests/test_identity_constraints.py     | 279
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
++++++++++++++++++++++++++++++++
 apps/api/tests/test_provision_user.py      |  37 ++++++++++++++-
 apps/web/tests/ui/auth.spec.js             |  10 ++++
 conversation.txt                           |  25 +++++++++
 docs/architecture/README.md                |   4 +-
 docs/requirements/traceability-requirements.csv |   6 +--
 docs/requirements/traceability-stories.csv      |   2 +-
 scripts/package_release.py                 |   2 +-
 15 files changed, 588 insertions(+), 18 deletions(-)
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
++++++++++++++++++++++++++++++++
 apps/api/tests/test_provision_user.py      |  37 ++++++++++++++-
 apps/web/tests/ui/auth.spec.js             |  10 ++++
 conversation.txt                           |  25 +++++++++
 docs/architecture/README.md                |   4 +-
 docs/requirements/traceability-requirements.csv |   6 +--
 docs/requirements/traceability-stories.csv      |   2 +-
 scripts/package_release.py                 |   2 +-
 15 files changed, 588 insertions(+), 18 deletions(-)
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
cd ~/Documents/NVDIA_Play_Book/FinSight_AI

echo "===== CURRENT FIN-15 EVIDENCE FILES ====="
ls -l test-results/FIN-15/

echo
echo "===== LATEST RUN SUMMARY ====="
cat test-results/FIN-15/run_20261020_141030_summary.txt

echo
echo "===== LATEST IDENTITY/AUTHORIZATION TEST LOG ====="
tail -60 test-results/FIN-15/20261020_141030_identity_authorization.log
```

```
echo
echo "===== CURRENT CONVERSATION LOG ====="
tail -70 conversation.txt

echo
echo "===== TRACEABILITY MATRIX FIN-15 REFERENCES ====="
grep -n -i -C 3 'FIN-15\|FS-01-02\|FR-P1-05\|FR-P1-06\|FR-P1-07'
docs/requirements/traceability-matrix.md

===== CURRENT FIN-15 EVIDENCE FILES =====
total 288
-rw-r--r--@ 1 sandeeph  staff    1601 Oct 20 13:55
20261020_135513_auth_regression.log
-rw-r--r--@ 1 sandeeph  staff    1781 Oct 20 13:55 20261020_135513_full_api_suite.log
-rw-r--r--@ 1 sandeeph  staff    1292 Oct 20 13:55
20261020_135513_identity_authorization.log
-rw-r--r--@ 1 sandeeph  staff    1243 Oct 20 14:04
20261020_140453_identity_authorization.log
-rw-r--r--@ 1 sandeeph  staff    1762 Oct 20 14:10 20261020_141030_full_api_suite.log
-rw-r--r--@ 1 sandeeph  staff    1243 Oct 20 14:10
20261020_141030_identity_authorization.log
-rw-r--r--@ 1 sandeeph  staff  109341 Oct 20 14:16
20261020_141630_acceptance_review.txt
-rw-r--r--@ 1 sandeeph  staff     296 Oct 20 13:55 run_20261020_135513_summary.txt
-rw-r--r--@ 1 sandeeph  staff     131 Oct 20 14:04 run_20261020_140453_summary.txt
-rw-r--r--@ 1 sandeeph  staff     365 Oct 20 14:10 run_20261020_141030_summary.txt

===== LATEST RUN SUMMARY =====
FinSight AI — FIN-15 Test Execution
Run ID: 20261020_141030
Git revision: 64f2637
Python: Python 3.14.6
Database: finsight_test


Identity/authorization exit code: 0
Full API suite exit code: 0
Overall result: PASS
Identity log: test-results/FIN-15/20261020_141030_identity_authorization.log
```

Full suite log: test-results/FIN-15/20261020_141030_full_api_suite.log

===== LATEST IDENTITY/AUTHORIZATION TEST LOG =====
...   [100%]
============================== warnings summary ==============================
../../../../../../../opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1
  /opt/anaconda3/lib/python3.14/site-packages/fastapi/testclient.py:1:
StarletteDeprecationWarning: Using `httpx` with `starlette.testclient` is deprecated;
install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient # noqa

apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
apps/api/tests/test_identity_constraints.py::test_platform_permission_is_resolved_from_
database_role_and_session
  /opt/anaconda3/lib/python3.14/site-packages/starlette/testclient.py:454:
DeprecationWarning: Setting per-request cookies=<...> is being deprecated, because
the expected behaviour on cookie persistence is ambiguous. Set cookies directly on the
client instance instead.
    return super().request(

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
3 passed, 4 warnings in 0.49s

===== CURRENT CONVERSATION LOG =====

FIN-75 / FS-11-04 — Test strategy expansion (2026-10-18)
Status: IN PROGRESS; acceptance remains partial.
Implemented test infrastructure: unit coverage for password/session/config helpers and controlled API errors; a PostgreSQL email-uniqueness/session-cascadeintegration test; deterministic Playwright tests for login error/success/logout and service-unavailable UI; and a live browser smoke runner that uses synthetic accounts and cleans them up. CI now runs frontend browser checks, backend unit/integration suites with coverage evidence, and live browser authentication against disposable PostgreSQL. Source traceability consulted: detailed backlog FS-11-04 (five critical validators/authorization/idempotency/API errors plus repeatable smoke), and Sprint 1

plan TC_TEST_001, TC_DB_001, TC_COV_001, TC_INT_001, TC_SYS_001. Original PDFs and source test plan were not modified.
Observed results: backend suite against fresh migrated `finsight_fin75` PostgreSQL: 23 passed; coverage 80% total (`app/auth.py` 100%, `app/main.py` 95%, `app/database.py` 91%, provisioning CLI 0%). Playwright UI interaction suite: 2 passed. Live browser smoke using development frontend/API passed twice; production standalone smoke passed once after restoring the required `.next/static` assets in the runner and preserving both standalone/static outputs in the CI artifact archive. JUnit reports were generated at ignored `apps/web/test-results/ui/results.xml` and `apps/web/test-results/e2e/results.xml`, and coverage XML at ignored `coverage.xml`. Frontend lockfile install, production build, Python compile, pip check, dev-lock consistency, workflow YAML parse and shell syntax checks passed. Exact commands/results and the first sandbox permission failures are recorded in `IMPLEMENTATION_STATUS.txt`; only relevant test IDs were updated in `SPRINT_1_TEST_EXECUTION_STATUS.txt`.
Known gaps: TC_DB_001 is BLOCKED for non-identity Sprint 1 schemas and migration-runner repeatability; TC_INT_001 is BLOCKED for configuration/audit persistence flows; TC_SYS_001 is BLOCKED for dashboard/settings, health, and Ollama paths that do not exist. Coverage leaves `apps/api/app/provision_user.py` at 0%, explicitly recorded. Existing npm install output summarized 3 advisories (2 high, 1 critical); they were not triaged in this test-only change. CI syntax and commands were validated locally, but no GitHub Actions run or branch protection check exists. Existing FIN-13 password-recovery, application-admin onboarding, and deployed-HTTPS gaps remain unchanged. No feature code, source references, Git history, or Jira state was changed.
Post-change repository review note: `git status --short --branch && git diff --check && git diff --stat` again produced no output within 10 seconds and remained stalled. Per the separate Git recovery task instruction, no troubleshooting or Git mutation was attempted. Therefore this task's Git diff/status review is incomplete; publication remains separately blocked under Q-007.

FIN-76 / FS-11-05 — Coverage and test quality (2026-10-18)
Status: PARTIAL. Enabled backend branch coverage in the existing CI test commands and retained XML and HTML reports as a 14-day GitHub artifact (workflow configured; remote upload not yet observed). Updated README commands. Added focused tests for missing session access, login/session database failures, required DATABASE_URL, logout without an active session, provisioning validation/hash/upsert behavior, and the provisioning module CLI entry point. CI-equivalent local suites passed: unit 37 tests; PostgreSQL integration 10 tests; combined 47 passed. Final cumulative backend coverage: line 156/156 (100%), branch 28/28 (100%). Evidence: ignored local

`coverage.xml`, `htmlcov/index.html`, and `/tmp/finsight-coverage.json`. No overall threshold was invented. Frontend coverage is not measured: existing Playwright tests cover interactions but do not instrument source code. A minimal future configuration would instrument client source modules and connect coverage reporting to the existing interaction suite; decide whether that additional frontend metric is required for acceptance.
Verification detail: the first PostgreSQL run from the sandbox could not connect (`Operation not permitted`); using approved access to the existing disposable `finsight_fin75` test database, both CI-equivalent coverage commands passed. PyYAML parsed the edited workflow. No Git command was run and no GitHub Actions execution occurred.

FIN-77 advisory triage initial note (2026-10-18; superseded by the execution below): the prior install reported 3 dependency advisories (2 high and 1 critical), with package-level detail pending FIN-77.

FIN-77 / FS-11-06 — Security validation and dependency checks (2026-10-19)
Status: PARTIAL. Consulted the FS-11-06 detailed-backlog entry (P0, 3 SP), four-sprint plan (3 SP), and relevant Sprint 1 cases. Original documents were not changed.

Npm audit before remediation: 3 affected package nodes, npm package severity summary 1 critical / 2 high. `next@16.2.12` is direct and had three critical advisories: Windows-hosted unauthenticated RCE (GHSA-p293-qw3h-jr36, `<16.3.3`), AVIF Image Optimization RCE (GHSA-2xp9-vwfh-vxw4, `<16.3.3`), and `next/og` ImageResponse RCE (GHSA-vcvr-r3jv-pc5j, `<16.3.6`). npm also reported a high Next Image Optimization SSRF advisory plus moderate/low findings. `postcss@8.4.31` was transitive through Next and had high arbitrary source-map file-read/path traversal findings (GHSA-6g55-p6wh-862q, GHSA-r28c-9q8g-f849) plus moderateadvisories. Optional transitive `sharp@0.34.5` had three high inherited libvips/libheif/librsvg findings (GHSA-f88m-g3jw-g9cj, GHSA-rgj7-g3m4-5g8c, GHSA-wq5f-xc86-pv6w). npm recommended compatible Next `16.4.2`; package manifests now resolve Next `16.4.2`, PostCSS `8.5.23`, Sharp `0.35.5`. `npm audit`, production-only audit, and `npm audit --audit-level=low` after update: 0 advisories. Audit JSON evidence is in `/tmp/finsight-npm-audit-before.json`, `/tmp/finsight-npm-audit-after.json`, `/tmp/finsight-npm-audit-production-after.json`.

Python lock audit before update: pip-audit found 14 advisory records across 3 packages / 7 unique IDs: Starlette 0.52.1 (Host URL reconstruction CVE-2026-48710; Windows StaticFiles UNC SSRF CVE-2026-48818; endpoint method dispatch CVE-2026-48817; form field limits CVE-2026-54283; malformed-path URL parsing CVE-2026-54282),

pytest 8.4.2 (Unix temp-directory issue CVE-2025-71176), and python-dotenv 1.2.1 (symlink-following arbitrary file overwrite CVE-2026-28684). Starlette fixes required 1.3.1; FastAPI 0.129.0 required Starlette `<1.0.0`. Checked PyPI metadata and upgraded to the earliest checked compatible FastAPI release, 0.133.0, plus Starlette 1.3.1, python-dotenv 1.2.2, and dev-only pytest 9.0.3. After lock update pip-audit reported no known vulnerabilities. Before/after JSON evidence is in `/tmp/finsight-pip-audit.json` and `/tmp/finsight-pip-audit-after.json`.

Changed files: `.github/workflows/ci.yml`; frontend `package.json` and `package-lock.json`; backend runtime/dev requirement manifests and locks; `IMPLEMENTATION_STATUS.txt`, this file, and relevant security test-register rows. CI now runs npm audit, pinned pip-audit 2.10.1, pinned Bandit 1.9.4, and the existing secret/environment hygiene check. Release packaging depends on the new security job. Frontend/e2e `npm ci` uses `--ignore-scripts`; no install-script approvals were given. Workflow YAML parse passed locally; GitHub Actions has not run.

Verification: frontend production build passed on Next 16.4.2; Playwright UI suite 2/2 passed (initial sandbox loopback bind denied, rerun with approved access passed). Focused auth/session/database integration suite passed 38 tests using the disposable PostgreSQL database after FastAPI/Starlette upgrades. `.venv` pip check, temporary lock-resolution environment pip check, exact dev-lock freeze comparison, direct pin/lock consistency, npm lock consistency, and Bandit scan passed. Local secret-pattern scan of app/config paths found no matches; only placeholder `.env.example` files were present. No local credential env file was found. A complete tracked/staged/history Git scan was not repeated. Eight Starlette/httpx deprecation warnings appeared in the backend regressionrun.

CI update adds blocking dependency-security checks but remote workflow execution and branch-protection enforcement are not verified. TC_SEC_001 is recordedBLOCKED pending GitHub Actions evidence. TC_SEC_002 is BLOCKED because file-upload validation and RAG/prompt-context functionality are not implemented; no related features were added. Rate limiting, password recovery, admin invitations, secret-config workflows, and execution diagnostics were not modified or retested. No Git/Jira actions were taken, and no source docs, SQL, diagrams, or test-plan sources were changed.

FIN-78 / FS-11-07 — Architecture and compatibility documentation (2026-10-19)
Status: PARTIAL. Added `docs/architecture/README.md` and five numbered ADRs under `docs/architecture/adr/`. The docs describe the current Next.js/FastAPI/PostgreSQL authentication slice and explicitly distinguish it from target

architecture/features not implemented. Checked API contracts against generated OpenAPI and actual TestClient responses; checked local Markdown links. TC_DOC_001 is PASS with evidence in `IMPLEMENTATION_STATUS.txt` and `SPRINT_1_TEST_EXECUTION_STATUS.txt`. TC_TRACE_001 remains NOT RUN; that full traceability audit is assigned to FS-11-08. Source PDFs, SQL references, diagrams, and original test plan were not modified.

Q-008 — Public API versioning and migration ownership — OPEN / NOT BLOCKING THIS DOCUMENTATION SLICE
Why it matters: Current API routes are unprefixed (`/auth/*`) and no formal breaking-change/deprecation policy or production migration owner/runner exists.The technical design asks for versioned public routes and the SRS requires controlled, versioned migrations, but no production consumer/deployment or migration platform is configured in the repository.
Recommended resolution: Keep existing routes and one-time identity migration unchanged for this slice. Before a public consumer or incompatible API change is introduced, decide whether to introduce a versioned path (for example `/v1`) and define a deprecation window. Before deployment, name the migration ownerand choose/approve a migration runner and forward/rollback procedure. Do not apply the full reference schema.
Exact next action: Before the first externally consumed breaking API change, tell Codex whether to adopt a versioned path and the desired deprecation policy; before production deployment, identify the migration owner and approved migration-runner approach. No immediate action is required to keep documenting ortesting the current local auth slice.

Q-009 — Unmapped SRS scope — WAITING FOR USER
Why it matters: The SRS identifier inventory contains 409 FR/NFR/DIR items. After combining explicit Jira issue references and the Sprint 1 test-plan traceability links, 328 requirement rows map to one or more of the 72 source story aliases; 81 do not. The matrix marks those rows NOT ASSESSED and does not infer that they are deferred, non-MVP, or approved for omission.
Recommended decision: Identify which of the 81 requirements are required in Release 1/MVP, which are deferred (with target release), and whether missing story/test coverage should be added through normal backlog change control. Keep the SRS authoritative until a reviewed addendum is approved.
Exact next action: Review the unmapped rows in `docs/requirements/traceability-requirements.csv` (filter `Source story aliases` = `—`) and reply with each requirement's disposition: Release 1, deferred plus release, or propose a scoped backlog change. Do not paste secrets. No Jira changes are pending/authorized.

Q-010 — Jira issues without source aliases — WAITING FOR USER
Why it matters: The read-only Jira project query returned FIN-84, FIN-85, FIN-86, and FIN-87 without a source FS alias; these are not among the 72 documented source stories and have not been silently added to the source catalog.
Recommended decision: Confirm whether the four issues are supplemental Jira work outside the source catalog, or provide an approved source alias/document reference for each. Keep them separate until confirmed.
Exact next action: Reply with `FIN-84–FIN-87 are supplemental` or provide the approved alias and source document reference for each issue. No Jira changes are pending/authorized.

FIN-79 / FS-11-08 — SRS addendum and requirement traceability (2026-10-19)
Status: PARTIAL. Added `docs/requirements/traceability-matrix.md`, 409-row `traceability-requirements.csv`, 72-row `traceability-stories.csv`, and `srs-addendum.md`; added `scripts/validate_traceability.py` and README links. All source requirements and aliases are represented; Jira keys and test statuses remain separately identified. 328 requirement rows map to story aliases via Jira text or explicit test-plan traceability; 81 remain unmapped. Of 23 Sprint 1 stories, 22 carry explicit SRS IDs; FS-11-09/FIN-80 is a management/process story without a direct SRS ID. All 54 supplied test cases map to a catalog story. 104 requirement rows have supplied linked tests; 305 do not. Test-plan requirement ranges were expanded across all IDs in each interval. Q-009/Q-010 request disposition of unmapped requirements and FIN-84–FIN-87. TC_TRACE_001 is PASS; no other test status was changed. Validation command: `python3 scripts/validate_traceability.py` (PASS; 409 requirements, 72 aliases, 54 tests; records the two source tests missing explicit execution rows as NOT RUN). `python3 -m py_compile scripts/validate_traceability.py` and local Markdown relative-link checks passed. Source PDFs, SQL, diagrams, and original test plan remain read-only.No Jira or Git action was taken.

FIN-73 targeted CI repair — run 39203215763 (2026-10-19)
Status: local fixes verified; remote confirmation pending. Corrected frontend artifact packaging in `.github/workflows/ci.yml` to archive from `.next` under working directory `apps/web`, with explicit hard-failing checks for `.next/standalone` and `.next/static`. Existing E2E and release-package extract/restore paths continue to use archive-root `standalone/` and `static/`. Normalized `docs/requirements/traceability-stories.csv` CRLF to LF; CSV parsing against HEAD proved all 73 rows and field values identical. No trailing whitespace remains. Removed one extra blank EOF line in `scripts/validate_traceability.py`, retaining the final newline. No repository CSV generator exists; validator is read-only.

Local checks: PyYAML workflow parse/target assertions PASS; `NEXT_TELEMETRY_DISABLED=1 npm run build` PASS (exit 0; Next 16.4.2); `.next/standalone` and `.next/static` exist; exact tar packaging command succeeded and archive inspection confirmed only `standalone/` and `static/` roots, 1,466 entries, SHA-256 `651f28563199baf95574f9c23fc78e2b8d6a10a88bf4a114c3fc033b744c3513`; `python3 scripts/validate_traceability.py` PASS; Python compilation PASS; CSV whitespace scan 0 rows; `git diff --check` PASS. No backend/security/Playwright suites were rerun.
Caveat: `git show --check --format= HEAD` on the existing root commit exits 2 with 1,323 historical whitespace diagnostics including immutable PDFs and other existing files. These were not changed. Current incremental worktree diff passes. A new incremental commit/push and GitHub Actions run are required to confirm the corrected workflow; no commit, push, Jira update, or rerun was performed.
Final validation note: after updating the coordination records, bounded `git diff --check` timed out at 8 seconds. Earlier targeted `git diff --check` completed with exit 0, and direct whitespace scans of all affected text files found zero trailing-whitespace lines and valid final newlines. Treat final full Git diff hygiene as incomplete due intermittent Git responsiveness; the incremental GitHub Actions run remains required.

2026-10-20 — FIN-15 verification checkpoint
- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.

FIN-15 implementation update — 2026-10-20
- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.

- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and allacceptance criteria are checked.
- No migrations, commits, pushes, or workspace schema changes performed by this patch script.

===== TRACEABILITY MATRIX FIN-15 REFERENCES =====
28-
29-| Story alias | Verified Jira issue key | Story title | Four-sprint assignment | Source release label | SRS references from Jira/test-plan mapping | Relevant acceptance criteria | Test case IDs | Test execution status | Implementation status | Evidence path/reference | Outstanding gap/dependency |
30-| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remainsincomplete or externally unverified, see implementation record. |
32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js,

IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
33:| FS-01-03 | [FIN-14](https://sandeephgowda8618.atlassian.net/browse/FIN-14) | Protect accounts and audit authentication | Sprint 1 | Release 1 per Jiraissue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-10, FR-P1-11, FR-P1-12, FR-P9-13, NFR-G-08, NFR-G-11, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P9-02 | Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Noimplementation evidence in current repository. |
35:| FS-01-05 | [FIN-17](https://sandeephgowda8618.atlassian.net/browse/FIN-17) | Meet identity security and accessibility requirements | Sprint 1 | Release 1 per Jira issue | FR-P1-01, NFR-G-03, NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-P1-01, NFR-P1-02, NFR-P1-03, NFR-P1-04, NFR-P1-05, NFR-P1-06 | No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
36-| FS-02-01 | [FIN-18](https://sandeephgowda8618.atlassian.net/browse/FIN-18) | Show dashboard health and activity | Sprint 2 | Release 1 per Jira issue | FR-P2-01, FR-P2-02, FR-P2-03, FR-P2-04, FR-P2-05, FR-P2-06, FR-P2-07, FR-P2-08, FR-P2-09 | Dashboard scopes data to the user/workspace, shows service health and job status, refresh failures and empty states are explicit. understand system status. | — | No linked

test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
37-| FS-02-02 | [FIN-19](https://sandeephgowda8618.atlassian.net/browse/FIN-19) | Show market overview, sessions, movers and heatmaps | Sprint 2 | Release 1 per Jira issue | FR-P2-10, FR-P2-11, FR-P2-12, FR-P2-13, FR-P2-14 | Values show source/as-of/freshness, exchange session follows configured calendar, unavailable classifications are not fabricated. conditions quickly. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
38-| FS-02-03 | [FIN-20](https://sandeephgowda8618.atlassian.net/browse/FIN-20) | Explore interactive historical price charts | Sprint 2 | Release 1 per Jira issue | FR-P2-15, FR-P2-16, FR-P2-17, FR-P2-18 | Supported intervals match provider coverage, indicator values are reproducible, zoom/pan and timestamp inspection work. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--
40-| FS-02-05 | [FIN-22](https://sandeephgowda8618.atlassian.net/browse/FIN-22) | Manage watchlists | Sprint 3 | Release 1 per Jira issue | FR-P2-21, FR-P2-22, FR-P9-16 | Create/rename/reorder/delete and add/remove work, watchlist data is owner-scoped and includes freshness metadata. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
41-| FS-02-06 | [FIN-23](https://sandeephgowda8618.atlassian.net/browse/FIN-23) | View portfolio performance, allocation and risk | Sprint 3 | Release 1 per Jira issue | FR-P2-23, FR-P2-24, FR-P2-25, FR-P2-26, FR-P2-27, FR-P2-28, FR-P2-29, FR-P2-30 | Metrics use matching snapshots/date ranges, risk measures state assumptions, absent portfolio inputs produce a clear empty state. portfolio behavior. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
42-| FS-02-07 | [FIN-24](https://sandeephgowda8618.atlassian.net/browse/FIN-24) | View news, events, alerts and custom dashboard layout | Sprint 3 | Release scope not explicit in Jira issue | FR-P2-31, FR-P2-32, FR-P2-33, FR-P2-34, FR-P2-35, FR-P2-36 | News shows timestamp/source, filters apply consistently, layout persists and respects permissions. summaries, filters and saved dashboard widgets so that my workspace reflects my research needs. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only

authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
44-| FS-03-01 | [FIN-26](https://sandeephgowda8618.atlassian.net/browse/FIN-26) | Create and manage AI conversations | Sprint 3 | Release 1 per Jira issue | FR-P3-01, FR-P3-02, FR-P3-03, FR-P3-04, FR-P3-05, FR-P3-06 | Conversation ownership is enforced, model selection only offers configured models, delete/archive behavior is confirmed. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
45-| FS-03-02 | [FIN-27](https://sandeephgowda8618.atlassian.net/browse/FIN-27) | Stream, stop and regenerate answers | Sprint 3 | Release 1 per Jira issue| FR-P3-02, FR-P3-03 | Partial output is ordered, stop cancels generation where supported, retries do not duplicate persisted user messages. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
46-| FS-03-03 | [FIN-28](https://sandeephgowda8618.atlassian.net/browse/FIN-28) | Answer with authorized retrieval and precise citations | Sprint 3 | Release 1 per Jira issue | FR-P3-07, FR-P3-08, FR-P3-09, FR-P3-10, FR-P4-24 | Only authorized chunks enter context, citations resolve to source/page/section metadata where available, no evidence is presented as a citation if absent. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--
71-| FS-07-03 | [FIN-53](https://sandeephgowda8618.atlassian.net/browse/FIN-53) | Analyze, compare, validate and export backtests | Sprint 4 | Release scope not explicit in Jira issue | FR-P7-17, FR-P7-18, FR-P7-19, FR-P7-20, FR-P7-21, FR-P7-22, FR-P7-23, FR-P7-24, FR-P7-25, FR-P7-26, FR-P7-27, FR-P7-28 | Look-ahead/survivorship issues are checked where supported, out-of-sample boundaries are explicit, saved runs retain parameters and data I can assess robustness. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
72-| FS-07-04 | [FIN-54](https://sandeephgowda8618.atlassian.net/browse/FIN-54) | Implement paper trading and broker execution controls | Sprint 4 | Release 2 only | FR-P7-29, FR-P7-30, FR-P7-31, FR-P7-32, FR-P7-33, FR-P7-34, FR-P7-35, FR-P7-36, FR-P7-37, FR-P7-38 | Trading schema is not applied in R1, any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation. reconciliation, journal and notifications so that trades are controlled and auditable. | — | No linked test, NOT RUN | PLANNED | — | Explicit Release 2 gate, no current implementation. |

73-| FS-07-05 | [FIN-55](https://sandeephgowda8618.atlassian.net/browse/FIN-55) | Secure execution logs and retain reliable run history | Sprint 1 | Release 1 per Jira issue | NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P7-01, NFR-P7-02, NFR-P7-03, NFR-P7-04, NFR-P7-05, NFR-P7-06, NFR-P7-07, NFR-P9-03 | Run IDs link logs/steps, status freshness is measurable, transient UI failure cannot delete records, retention and pagination are configured. so that failures can be investigated without exposing sensitive data. | TC_EXEC_001, TC_EXEC_002, TC_EXEC_003, TC_OPS_002, TC_OPS_003, TC_TRACE_001 | TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_EXEC_003=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05, FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06,NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable.configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
75-| FS-08-02 | [FIN-56](https://sandeephgowda8618.atlassian.net/browse/FIN-56) | Configure embeddings, chunking and retrieval | Sprint 2 | Release 1 per Jira issue | FR-P8-06, FR-P8-07, FR-P8-08, FR-P8-09, FR-P8-10, FR-P8-11 | Embedding model/dimension/index version match, metadata filters are tested, changesrequire re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
76-| FS-08-03 | [FIN-58](https://sandeephgowda8618.atlassian.net/browse/FIN-58) | Manage market providers, data coverage and analytics defaults | Sprint 2 | Release 1 per Jira issue | FR-P8-17, FR-P8-18, FR-P8-19, FR-P8-20, FR-P8-21, FR-P8-22, FR-P8-23, FR-P8-24, FR-P8-25 | Provider coverage and entitlements are visible, settings validate before activation, changes record actor/time, assumptions are

versioned. and cost assumptions so that outputs reflect supported data and explicit settings. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
77-| FS-08-04 | [FIN-60](https://sandeephgowda8618.atlassian.net/browse/FIN-60) | Keep broker modes and trading safety controls gated | Sprint 4 | Release 2 only | FR-P8-26, FR-P8-27, FR-P8-28 | mode changes require authorization and step-up confirmation, controls default to disabled. controls so that future broker features cannot activate accidentally. | — | No linked test, NOT RUN | PLANNED | — | Explicit Release 2 gate, no current implementation. |
78:| FS-08-05 | [FIN-61](https://sandeephgowda8618.atlassian.net/browse/FIN-61) | Secure and validate configuration changes | Sprint 1 | Release 1 per Jiraissue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-14, FR-P8-16, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-22, NFR-G-26, NFR-P8-01, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02, NFR-P9-03 | Secrets are referencedsecurely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incompleteor externally unverified, see implementation record. |
79-| FS-09-01 | [FIN-59](https://sandeephgowda8618.atlassian.net/browse/FIN-59) | Manage profile, security, interface and notification preferences | Sprint2 | Release scope not explicit in Jira issue | FR-P9-01, FR-P9-02, FR-P9-03, FR-P9-04, FR-P9-05 | Preferences persist across sessions, private fields are isolated, notification choices are honored. preferences so that the application fits my workflow. Acceptance criteria | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
80-| FS-09-02 | [FIN-62](https://sandeephgowda8618.atlassian.net/browse/FIN-62) | Manage workspaces, members, roles and sharing | Sprint 3 | Release 1 per Jira issue | FR-P9-06, FR-P9-07, FR-P9-08 | Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
81-| FS-09-03 | [FIN-63](https://sandeephgowda8618.atlassian.net/browse/FIN-63) | Manage API credentials, privacy, export, deletion and audit | Sprint 1 | Release 1 per Jira issue | FR-P1-09, FR-P9-09, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-35, NFR-P7-01, NFR-P7-02,

NFR-P8-01, NFR-P8-07, NFR-P9-02, NFR-P9-03, NFR-P9-05, NFR-P9-07 | Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
82-| FS-09-04 | [FIN-64](https://sandeephgowda8618.atlassian.net/browse/FIN-64) | Save dashboards, watchlists, screens, strategies, reports and preferences| Sprint 4 | Release 1 per Jira issue | FR-P9-15, FR-P9-16, FR-P9-17, FR-P9-18, FR-P9-19, FR-P9-20, FR-P9-21, FR-P9-22 | Saved items retain owner/workspace, timestamps and relevant source/snapshot lineage, edits respect access grants. sessions. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe account administration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
84-| FS-10-01 | [FIN-66](https://sandeephgowda8618.atlassian.net/browse/FIN-66) | Calculate DCF valuation with versioned assumptions | Sprint 4 | Release 1per Jira issue | — | Run stores company, data snapshot, model version, assumptions, forecasts and outputs, sensitivity results link to the run, missing inputs are surfaced. explicit assumptions so that valuation outputs can be reproduced. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
85-| FS-10-02 | [FIN-67](https://sandeephgowda8618.atlassian.net/browse/FIN-67) | Calculate portfolio VaR/CVaR and drawdown | Sprint 4 | Release scope not explicit in Jira issue | — | Risk run stores input snapshot, configuration, lookback, frequency, seed/method and limitations, test cases validate calculations. understand downside

exposure. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
86-| FS-10-03 | [FIN-68](https://sandeephgowda8618.atlassian.net/browse/FIN-68) | Run Monte Carlo and stress scenarios | Sprint 4 | Release scope not explicit in Jira issue | — | Scenario parameters are versioned, outputs link to risk run and assumptions, invalid/incomplete data is flagged. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--
91-| FS-11-01 | [FIN-2](https://sandeephgowda8618.atlassian.net/browse/FIN-2) | Create reproducible repository and environment setup | Sprint 1 | Release 1per Jira issue | NFR-G-03, NFR-G-07, NFR-G-25, NFR-G-26, NFR-G-38 | Clean clone starts with documented steps., .env.example has placeholders only., No secrets or generated junk are committed., Repository structure, branch policy, pull requests, and code review are documented. | TC_ENV_001, TC_ENV_002, TC_TRACE_001 | TC_ENV_001=NOT RUN, TC_ENV_002=NOT RUN, TC_TRACE_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
92-| FS-11-02 | [FIN-73](https://sandeephgowda8618.atlassian.net/browse/FIN-73) | Run CI quality gates on every pull request | Sprint 1 | Release 1 per Jira issue | NFR-G-03, NFR-G-05, NFR-G-07, NFR-G-23, NFR-G-27 | A deliberately failing test/check makes CI fail, default branch stays green, reports are retained. defects are caught before merge. | TC_CI_001, TC_CI_002, TC_SEC_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_SEC_001=BLOCKED | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
93-| FS-11-03 | [FIN-74](https://sandeephgowda8618.atlassian.net/browse/FIN-74) | Build and deploy a versioned release artifact | Sprint 1 | Release 1 per Jira issue | NFR-G-15, NFR-G-16, NFR-G-25, NFR-G-27, NFR-G-38 | Build artifact is tagged, configuration is environment-driven, deployment/rollback steps aredocumented and tested if hosting is available. | TC_BUILD_001, TC_BUILD_002, TC_REL_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_REL_001=NOT RUN | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01,

NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
95-| FS-11-05 | [FIN-76](https://sandeephgowda8618.atlassian.net/browse/FIN-76) | Measure line/branch coverage and test quality | Sprint 1 | Release 1 per Jira issue | NFR-G-23 | Coverage report is generated, branch coverage is reported where tooling supports it, critical gaps have follow-up | TC_COV_001 | TC_COV_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
96-| FS-11-06 | [FIN-77](https://sandeephgowda8618.atlassian.net/browse/FIN-77) | Run security validation and dependency checks | Sprint 1 | Release 1 per Jira issue | FR-P1-10, NFR-G-03, NFR-G-04, NFR-G-05, NFR-G-06, NFR-G-07, NFR-G-11, NFR-G-23, NFR-G-25, NFR-G-27, NFR-G-30, NFR-G-31, NFR-P1-01, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-02, NFR-P7-05, NFR-P8-01, NFR-P8-07, NFR-P9-03 | Auth, workspace isolation, file validation, prompt injection and secret-leak cases are tested, critical issues block release. so that high-risk defects block release. Acceptance criteria | TC_AUTHN_006, TC_AUTHSEC_002, TC_CFG_001, TC_CI_001, TC_ENV_002, TC_EXEC_002, TC_SEC_001, TC_SEC_002 | TC_AUTHN_006=PASS, TC_AUTHSEC_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CI_001=BLOCKED, TC_ENV_002=NOT RUN, TC_EXEC_002=NOT RUN, TC_SEC_001=BLOCKED, TC_SEC_002=BLOCKED | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
97-| FS-11-07 | [FIN-78](https://sandeephgowda8618.atlassian.net/browse/FIN-78) | Document architecture, APIs, ADRs and compatibility rules | Sprint 1 | Release 1 per Jira issue | FR-P8-16, NFR-G-14, NFR-G-22, NFR-G-24, NFR-G-26, NFR-P8-06 | Architecture reflects implementation, API examples and error codes exist, schema/API breaking changes have migration/version notes. documented so that changes remain maintainable. | TC_CFG_004, TC_DB_001, TC_DOC_001 | TC_CFG_004=NOT RUN, TC_DB_001=BLOCKED, TC_DOC_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incompleteor externally unverified, see implementation record. |
98-| FS-11-08 | [FIN-79](https://sandeephgowda8618.atlassian.net/browse/FIN-79) | Maintain SRS addendum and requirement traceability matrix | Sprint 1 | Release 1 per

Jira issue | FR-P1-14, FR-P3-36 | Every MVP requirement maps to story and test ID, deferred requirements have release labels, changes trigger impact analysis. verification are auditable. | TC_BOUNDARY_001, TC_TRACE_001 | TC_BOUNDARY_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
99-| FS-11-09 | [FIN-80](https://sandeephgowda8618.atlassian.net/browse/FIN-80) | Run planning, daily review, demo and retrospective | Sprint 1 | Release 1per Jira issue | — | Each day has sprint goal, accepted/rejected stories, demo evidence and one retro action, work in progress is limited. impediments are managed transparently. | TC_MGMT_001 | TC_MGMT_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
100-| FS-11-10 | [FIN-81](https://sandeephgowda8618.atlassian.net/browse/FIN-81) | Manage baselines, bugs, versions, SBOM and release notes | Sprint 1 | Release 1 per Jira issue | FR-P1-14, FR-P3-36, NFR-G-15, NFR-G-16, NFR-G-25, NFR-G-27, NFR-G-38 | Version baseline and changelog exist, bugs link to regression tests, SBOM is generated if tooling/time permits or limitation recorded. changes can be audited and maintained. | TC_BOUNDARY_001, TC_BUILD_001, TC_BUILD_002, TC_REL_001 | TC_BOUNDARY_001=NOT RUN, TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_REL_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidencein current repository. |
101:| FS-11-11 | [FIN-82](https://sandeephgowda8618.atlassian.net/browse/FIN-82) | Document usability, AI use, licenses and data rights | Sprint 1 | Release 1 per Jira issue | NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-G-27, NFR-P1-06 | AI-generated code is reviewed and tested, license/data rights are recorded, usability checks include accessibility and understandable failures. compliant. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDsand redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED,

TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
103-
104-## SRS requirement matrix (399 FR/NFR IDs plus 10 DIR rules)
105-
--
115-| DIR-08 | Configuration Compatibility | PDF p.43, SRS Section 6, data-integrity rules | Data integrity and retrieval lifecycle | — | — | No mapped key| No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
116-| DIR-09 | Audit Separation | PDF p.43, SRS Section 6, data-integrity rules | Data integrity and retrieval lifecycle | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
117-| DIR-10 | Backup Recovery | PDF p.43, SRS Section 6, data-integrity rules | Data integrity and retrieval lifecycle | — | — | No mapped key | No mappedstory criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
119-| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs |

FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the currentscoped behavior only. | Preserve source story release label |
120-| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs |
FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
121-| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs |
FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOTRUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001,

TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs |FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers only part of this source requirement. | Preserve source story release label |
124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement.| Preserve source story release label |
125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13,FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected,role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
126-| FR-P1-09 | Authentication Event Recording | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-03, FS-09-05, FS-11-04 |

FIN-13, FIN-14, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
127-| FR-P1-10 | Account Protection | PDF p.4, SRS P1 requirements | Identity and access | FS-01-03, FS-11-06 | FIN-14, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only whenconfigured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
128-| FR-P1-11 | Multi-Factor Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-03 | FIN-14 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
--
338-| FR-P7-37 | Trade Journal | PDF p.28, SRS P7 requirements | Execution and backtesting | FS-07-04 | FIN-54 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-07-04/FIN-54: Trading schema is not applied in R1, any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation. reconciliation, journal and notifications so that trades are controlled and auditable. | — | No linked test, NOT RUN | PLANNED | — | The mapped source story is explicitly Release 2 only, absent from current runtime. | Release 2 only |
339-| FR-P7-38 | Trading Notifications | PDF p.28, SRS P7 requirements | Execution and backtesting | FS-07-04 | FIN-54 | Live Jira JQL verified 2026-10-19,test-plan source refs | FS-07-04/FIN-54: Trading schema is not applied in R1, any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation. reconciliation, journal and notifications so that trades are controlled and auditable. | — |

No linked test, NOT RUN | PLANNED | — | The mapped source story is explicitly Release 2 only, absent from current runtime. | Release 2 only |
340-| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters aretraceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04,FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
342-| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |

343-| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
344-| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters aretraceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
--
348-| FR-P8-09 | Retrieval Configuration | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
349-| FR-P8-10 | Metadata Filtering | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |

350-| FR-P8-11 | RAG Testing | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
352-| FR-P8-13 | Configuration Versioning | PDF p.30, SRS P8 requirements | Models, providers and settings | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
353-| FR-P8-14 | Configuration Validation | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05 | FIN-57, FIN-61 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CFG_002, TC_LLM_003 | TC_CFG_002=NOT RUN, TC_LLM_003=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
354-| FR-P8-15 | Model Compatibility | PDF p.31, SRS P8 requirements | Models, providers and settings | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
373-| FR-P9-03 | Security Preferences | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-09-01 | FIN-59 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-01/FIN-59: Preferences persist across sessions, private fields are isolated, notification choices are honored. preferences so that the application fits my workflow. Acceptance criteria | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |

374-| FR-P9-04 | Interface Preferences | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-09-01 | FIN-59 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-01/FIN-59: Preferences persist across sessions, private fields are isolated, notification choices are honored. preferences so that the application fits my workflow. Acceptance criteria | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
375-| FR-P9-05 | Notification Preferences | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-09-01 | FIN-59 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-01/FIN-59: Preferences persist across sessions, private fields are isolated, notification choices are honored. preferences so that the application fits my workflow. Acceptance criteria | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — |Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
379-| FR-P9-09 | API Credentials | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-09-03 | FIN-63 | Live Jira JQL verified 2026-10-19,

test-plan source refs | FS-09-03/FIN-63: Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN,TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
380-| FR-P9-10 | Data Export | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-03/FIN-63: Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
381-| FR-P9-11 | Account Deletion | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-03/FIN-63: Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
--
407-| NFR-FIN-12 | Data Provenance | PDF p.45, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
408-| NFR-FIN-13 | Calculation and AI Separation | PDF p.45, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |

409-| NFR-FIN-14 | Provider Failure Handling | PDF p.45, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
410:| NFR-FIN-15 | Data Licensing | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
411-| NFR-FIN-16 | Alert Reliability | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped storycriterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
412-| NFR-FIN-17 | Scalable Analytics | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
413-| NFR-FIN-18 | Integration Security | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
414-| NFR-FIN-19 | Graceful Degradation | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
415-| NFR-FIN-20 | Verification | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link

among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
417-| NFR-G-02 | Data Encryption | PDF p.36, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
418-| NFR-G-03 | Secrets Management | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-05, FS-08-05, FS-09-03, FS-11-01, FS-11-02, FS-11-06 | FIN-17, FIN-2, FIN-61, FIN-63, FIN-73, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHN_006, TC_CFG_001, TC_ENV_002, TC_SEC_001 | TC_AUTHN_006=PASS, TC_CFG_001=NOT RUN, TC_ENV_002=NOT RUN, TC_SEC_001=BLOCKED | NOT ASSESSED | — | Nodirect source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
419-| NFR-G-04 | Input Validation | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-11-04, FS-11-06, FS-11-12 | FIN-75, FIN-77, FIN-83| Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_SEC_002 | TC_SEC_002=BLOCKED | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
425-| NFR-G-10 | Long-Running Tasks | PDF p.37, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
426-| NFR-G-11 | Bounded Resource Usage | PDF p.37, SRS global NFR | Cross-cutting quality and operations | FS-01-03, FS-11-04, FS-11-06, FS-11-12 | FIN-14, FIN-75, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHSEC_002, TC_SEC_002 | TC_AUTHSEC_002=NOT RUN, TC_SEC_002=BLOCKED | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
427-| NFR-G-12 | Capacity Testing | PDF p.37, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, donot infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19,

test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
429-| NFR-G-14 | Data Consistency | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-03, FS-07-05, FS-08-05, FS-09-05, FS-11-04, FS-11-07, FS-11-12 | FIN-13, FIN-14, FIN-55, FIN-61, FIN-65, FIN-75, FIN-78, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DB_001, TC_INT_001, TC_OPS_003 | TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN | NOT ASSESSED | — | Nodirect source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
430-| NFR-G-15 | Backup and Restore | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-07-05, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-55, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_002,TC_OPS_003 | TC_BUILD_002=BLOCKED, TC_OPS_003=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
431-| NFR-G-16 | Recovery Targets | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-07-05, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-55, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_002, TC_OPS_003 | TC_BUILD_002=BLOCKED, TC_OPS_003=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
435-| NFR-G-20 | Responsive Design | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
436-| NFR-G-21 | Error Understandability | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |

437-| NFR-G-22 | Modular Architecture | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-08-01, FS-08-05, FS-11-07 | FIN-57, FIN-61, FIN-78 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CFG_004, TC_DOC_001 | TC_CFG_004=NOT RUN, TC_DOC_001=PASS | PARTIAL | apps/web/app, apps/api/app, docs/architecture/README.md | Current code covers only part of this source requirement. | Unmapped to source story |
438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05, FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plansource refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmapped to source story |
439-| NFR-G-24 | API Documentation | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-11-07 | FIN-78 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DOC_001 | TC_DOC_001=PASS | IMPLEMENTED — VERIFIED | docs/architecture/README.md, apps/api/app/main.py, generated OpenAPI/TestClient review | Evidence supports the current scoped behavior only. | Unmapped to source story |
440-| NFR-G-25 | Configuration Separation | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-11-01, FS-11-03, FS-11-06, FS-11-10 | FIN-2, FIN-74, FIN-77, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_ENV_001, TC_ENV_002 | TC_BUILD_001=BLOCKED, TC_ENV_001=NOT RUN, TC_ENV_002=NOT RUN | PARTIAL | .env.example, apps/web/.env.example, apps/api/app/main.py, apps/web/app/api/runtime-config/route.js | Current code covers only part of this source requirement. | Unmapped to source story |
441-| NFR-G-26 | Database Migrations | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-01, FS-11-04, FS-11-07, FS-11-12 | FIN-13, FIN-14, FIN-2, FIN-61, FIN-65, FIN-75, FIN-78, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | Nomapped story criterion, do not infer. | TC_DB_001, TC_DOC_001, TC_ENV_001, TC_INT_001 | TC_DB_001=BLOCKED, TC_DOC_001=PASS, TC_ENV_001=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql, docs/release/RELEASE_README.md | One-time identity SQL exists, a general runner and production migration owner do not. | Unmapped to source story |
--

446-| NFR-G-31 | Retrieval Permission Enforcement | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-11-04, FS-11-06, FS-11-12 | FIN-75, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_SEC_002 | TC_SEC_002=BLOCKED | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
447-| NFR-G-32 | Model and Index Compatibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
448-| NFR-G-33 | Model Replacement | PDF p.40, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |

452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target and committed-SHA evidence are absent. | Unmapped to source story |
454-| NFR-P1-01 | Credential Security | PDF p.4, SRS P1 requirements | Identity and access | FS-01-05, FS-11-06 | FIN-17, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/auth.py, apps/api/app/provision_user.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source storyrelease label |
455-| NFR-P1-02 | Transport Security | PDF p.4, SRS P1 requirements | Identity and access | FS-01-05 | FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py (Secure cookie switch), no deployed HTTPS endpoint | Deployed

HTTPS cannot be verified without an approved deployment target. | Preserve source story release label |
456-| NFR-P1-03 | Session Security | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05 | FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/tests/test_auth.py (deployed verification pending) | Current code covers only part ofthis source requirement. | Preserve source story release label |
457-| NFR-P1-04 | Authentication Performance | PDF p.4, SRS P1 requirements | Identity and access | FS-01-05 | FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
458:| NFR-P1-05 | Information Disclosure | PDF p.5, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05 | FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_004, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009,TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
459:| NFR-P1-06 | Accessibility | PDF p.5, SRS P1 requirements | Identity and access | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are

tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/web/app/page.js, apps/web/tests/ui/auth.spec.js | Current code covers only part of this source requirement. | Preserve source story release label |
460-| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
461-| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
462-| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN,TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
--
507-| NFR-P8-06 | Extensibility | PDF p.32, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05, FS-11-07 | FIN-57, FIN-61, FIN-78 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-05/FIN-61: Secrets are referenced securely, config changes are audited, validation precedesactivation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_LLM_002, TC_TRACE_001 |

TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_LLM_002=NOT RUN, TC_TRACE_001=PASS | NOTIMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
508-| NFR-P8-07 | Diagnostic Security | PDF p.32, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05, FS-09-03, FS-11-06 | FIN-57, FIN-61, FIN-63, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-05/FIN-61: Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_LLM_001, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_LLM_001=NOT RUN,TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
509-| NFR-P8-08 | Performance Configuration | PDF p.32, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05 | FIN-57, FIN-61 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-05/FIN-61: Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_LLM_003, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_LLM_003=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | LiveJira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecyclefollows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57,

FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002,TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
512-| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05, FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
513-| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
514-| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified

2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | —| Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
516-| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
517-
518-## Known coverage gaps
) (base) sandeeph@Sandeeps-MacBook-Pro NVDIA_Play_Book % cd FinSight_AI
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % >....
  echo "No test-results/FIN-15 directory found."
fi

```
echo
echo "========== 3. LATEST FIN-15 SUMMARY FILES =========="
if [ -d test-results/FIN-15 ]; then
  find test-results/FIN-15 -maxdepth 2 -type f \

− iname' * summary * ' − o − iname' * acceptance * ' − o − iname' * identity * ' − o − iname'
\
    -print | sort
fi

echo
echo "========== 4. FIN-15 TRACEABILITY =========="
grep -n -i -C 2 \

'FIN-15\|FS-01-02\|TC_AUTHZ_001\|TC_AUTHZ_002\|TC_AUTHZ_003\|TC_PRIV_002
\|TC_SYS_001' \
  docs/requirements/traceability-matrix.md

echo
echo "========== 5. STORY TRACEABILITY CSV =========="
grep -n
'FIN-15\|FS-01-02\|TC_AUTHZ_001\|TC_AUTHZ_002\|TC_AUTHZ_003\|TC_PRIV_002
' \
  docs/requirements/traceability-stories.csv

echo
echo "========== 6. LATEST IMPLEMENTATION NOTES =========="
tail -n 65 IMPLEMENTATION_STATUS.txt

echo
echo "========== 7. RECENT CONVERSATION NOTES =========="
tail -n 45 conversation.txt

========== 1. GIT STATUS — PRESERVE ALL CHANGES ==========
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
```

```
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M docs/requirements/traceability-requirements.csv
 M docs/requirements/traceability-stories.csv
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js

========== 2. FIN-15 EVIDENCE FILES ==========
test-results/FIN-15/20261020_135513_auth_regression.log
test-results/FIN-15/20261020_135513_full_api_suite.log
test-results/FIN-15/20261020_135513_identity_authorization.log
test-results/FIN-15/20261020_140453_identity_authorization.log
test-results/FIN-15/20261020_141030_full_api_suite.log
test-results/FIN-15/20261020_141030_identity_authorization.log
test-results/FIN-15/20261020_141630_acceptance_review.txt
test-results/FIN-15/run_20261020_135513_summary.txt
test-results/FIN-15/run_20261020_140453_summary.txt
test-results/FIN-15/run_20261020_141030_summary.txt

========== 3. LATEST FIN-15 SUMMARY FILES ==========
test-results/FIN-15/20261020_135513_identity_authorization.log
test-results/FIN-15/20261020_140453_identity_authorization.log
test-results/FIN-15/20261020_141030_identity_authorization.log
test-results/FIN-15/20261020_141630_acceptance_review.txt
test-results/FIN-15/run_20261020_135513_summary.txt
test-results/FIN-15/run_20261020_140453_summary.txt
test-results/FIN-15/run_20261020_141030_summary.txt

========== 4. FIN-15 TRACEABILITY ==========
29-| Story alias | Verified Jira issue key | Story title | Four-sprint assignment | Source release label | SRS references from Jira/test-plan mapping | Relevant acceptance
```

criteria | Test case IDs | Test execution status | Implementation status | Evidence path/reference | Outstanding gap/dependency |
30-| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
31:| FS-01-01 | [FIN-13](https://sandeephgowda8618.atlassian.net/browse/FIN-13) | Authenticate and manage sessions | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-14, NFR-G-23, NFR-G-26, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P1-03, NFR-P1-05, NFR-P8-02, NFR-P9-02 | Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboardingfollows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
32:| FS-01-02 | [FIN-15](https://sandeephgowda8618.atlassian.net/browse/FIN-15) | Enforce roles and protected routes | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P8-02, FR-P8-12, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
33-| FS-01-03 | [FIN-14](https://sandeephgowda8618.atlassian.net/browse/FIN-14) | Protect accounts and audit authentication | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-10, FR-P1-11, FR-P1-12, FR-P9-13, NFR-G-08, NFR-G-11, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P9-02 | Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js,

IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementation record. |
34:| FS-01-04 | [FIN-16](https://sandeephgowda8618.atlassian.net/browse/FIN-16) | Separate read-only and trading permissions | Sprint 1 | Release 1 boundary, trading scope Release 2 | FR-P1-05, FR-P1-07, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, NFR-G-01, NFR-P9-01, NFR-P9-02, NFR-P9-06 | Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
35-| FS-01-05 | [FIN-17](https://sandeephgowda8618.atlassian.net/browse/FIN-17) | Meet identity security and accessibility requirements | Sprint 1 | Release 1 per Jira issue | FR-P1-01, NFR-G-03, NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-P1-01, NFR-P1-02, NFR-P1-03, NFR-P1-04, NFR-P1-05, NFR-P1-06 | No plaintext passwords, deployed auth usesHTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007,TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py, apps/api/app/auth.py, apps/web/app/page.js, IMPLEMENTATION_STATUS.txt | Acceptance remains incomplete or externally unverified, see implementationrecord. |
36-| FS-02-01 | [FIN-18](https://sandeephgowda8618.atlassian.net/browse/FIN-18) | Show dashboard health and activity | Sprint 2 | Release 1 per Jira issue | FR-P2-01, FR-P2-02, FR-P2-03, FR-P2-04, FR-P2-05, FR-P2-06, FR-P2-07, FR-P2-08, FR-P2-09 | Dashboard scopes data to the user/workspace, shows service health and job status, refresh failures and empty states are explicit. understand system status. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--
41-| FS-02-06 | [FIN-23](https://sandeephgowda8618.atlassian.net/browse/FIN-23) | View portfolio performance, allocation and risk | Sprint 3 | Release 1 per Jira issue | FR-P2-23, FR-P2-24, FR-P2-25, FR-P2-26, FR-P2-27, FR-P2-28, FR-P2-29, FR-P2-30 | Metrics use matching snapshots/date ranges, risk measures state assumptions, absent portfolio inputs produce a clear empty state. portfolio behavior. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
42-| FS-02-07 | [FIN-24](https://sandeephgowda8618.atlassian.net/browse/FIN-24) | View news, events, alerts and custom dashboard layout | Sprint 3 | Release scope not

explicit in Jira issue | FR-P2-31, FR-P2-32, FR-P2-33, FR-P2-34, FR-P2-35, FR-P2-36 | News shows timestamp/source, filters apply consistently, layout persists and respects permissions. summaries, filters and saved dashboard widgets so that my workspace reflects my research needs. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
43:| FS-02-08 | [FIN-25](https://sandeephgowda8618.atlassian.net/browse/FIN-25) | Keep dashboard responsive, isolated and freshness-aware | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12, NFR-G-13, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-01, NFR-P2-02, NFR-P2-03, NFR-P2-04, NFR-P2-05, NFR-P8-04 | Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS| NOT IMPLEMENTED | — | No implementation evidence in current repository. |
44-| FS-03-01 | [FIN-26](https://sandeephgowda8618.atlassian.net/browse/FIN-26) | Create and manage AI conversations | Sprint 3 | Release 1 per Jira issue | FR-P3-01, FR-P3-02, FR-P3-03, FR-P3-04, FR-P3-05, FR-P3-06 | Conversation ownership is enforced, model selection only offers configured models, delete/archive behavior is confirmed. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
45-| FS-03-02 | [FIN-27](https://sandeephgowda8618.atlassian.net/browse/FIN-27) | Stream, stop and regenerate answers | Sprint 3 | Release 1 per Jira issue | FR-P3-02, FR-P3-03 | Partial output is ordered, stop cancels generation where supported, retries do not duplicate persisted user messages. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--
72-| FS-07-04 | [FIN-54](https://sandeephgowda8618.atlassian.net/browse/FIN-54) | Implement paper trading and broker execution controls | Sprint 4 | Release 2 only | FR-P7-29, FR-P7-30, FR-P7-31, FR-P7-32, FR-P7-33, FR-P7-34, FR-P7-35, FR-P7-36, FR-P7-37, FR-P7-38 | Trading schema is not applied in R1, any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation. reconciliation, journal and notifications so that trades are controlled and auditable. | — | No linked test, NOT RUN | PLANNED | — | Explicit Release 2 gate, no current implementation. |
73-| FS-07-05 | [FIN-55](https://sandeephgowda8618.atlassian.net/browse/FIN-55) | Secure execution logs and retain reliable run history | Sprint 1 | Release 1 per Jira issue | NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P7-01, NFR-P7-02, NFR-P7-03,

NFR-P7-04, NFR-P7-05, NFR-P7-06, NFR-P7-07, NFR-P9-03 | Run IDs link logs/steps, status freshness is measurable, transient UI failure cannot delete records, retention and pagination are configured. so that failures can be investigated without exposing sensitive data. | TC_EXEC_001, TC_EXEC_002, TC_EXEC_003, TC_OPS_002, TC_OPS_003, TC_TRACE_001 | TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_EXEC_003=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
74:| FS-08-01 | [FIN-57](https://sandeephgowda8618.atlassian.net/browse/FIN-57) | Configure Ollama, model selection and inference parameters | Sprint 1 | Release 1 per Jiraissue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-01, FR-P8-02, FR-P8-03, FR-P8-04, FR-P8-05, FR-P8-12, FR-P8-14, FR-P8-16, NFR-G-08, NFR-G-13, NFR-G-22, NFR-G-23, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P8-02, NFR-P8-03, NFR-P8-04, NFR-P8-05, NFR-P8-06, NFR-P8-07, NFR-P8-08, NFR-P9-02 | Invalid settingsfail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED| — | No implementation evidence in current repository. |
75-| FS-08-02 | [FIN-56](https://sandeephgowda8618.atlassian.net/browse/FIN-56) | Configure embeddings, chunking and retrieval | Sprint 2 | Release 1 per Jira issue | FR-P8-06, FR-P8-07, FR-P8-08, FR-P8-09, FR-P8-10, FR-P8-11 | Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
76-| FS-08-03 | [FIN-58](https://sandeephgowda8618.atlassian.net/browse/FIN-58) | Manage market providers, data coverage and analytics defaults | Sprint 2 | Release 1 per Jira issue | FR-P8-17, FR-P8-18, FR-P8-19, FR-P8-20, FR-P8-21, FR-P8-22, FR-P8-23, FR-P8-24, FR-P8-25 | Provider coverage and entitlements are visible, settings validate before activation, changes record actor/time, assumptions are versioned. and cost assumptions so that outputs reflect supported data and explicit settings. | — | No linked test,NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--

81-| FS-09-03 | [FIN-63](https://sandeephgowda8618.atlassian.net/browse/FIN-63) | Manage API credentials, privacy, export, deletion and audit | Sprint 1 | Release 1 per Jira issue | FR-P1-09, FR-P9-09, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-03, NFR-G-07, NFR-G-08, NFR-G-35, NFR-P7-01, NFR-P7-02, NFR-P8-01, NFR-P8-07,NFR-P9-02, NFR-P9-03, NFR-P9-05, NFR-P9-07 | Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
82-| FS-09-04 | [FIN-64](https://sandeephgowda8618.atlassian.net/browse/FIN-64) | Save dashboards, watchlists, screens, strategies, reports and preferences | Sprint 4 | Release 1 per Jira issue | FR-P9-15, FR-P9-16, FR-P9-17, FR-P9-18, FR-P9-19, FR-P9-20, FR-P9-21, FR-P9-22 | Saved items retain owner/workspace, timestamps and relevant source/snapshot lineage, edits respect access grants. sessions. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
83:| FS-09-05 | [FIN-65](https://sandeephgowda8618.atlassian.net/browse/FIN-65) | Enforce privacy and safe account administration | Sprint 1 | Release 1 per Jira issue | FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P1-13, FR-P1-14, FR-P1-15, FR-P3-36, FR-P9-06, FR-P9-07, FR-P9-08, FR-P9-10, FR-P9-11, FR-P9-12, FR-P9-13, FR-P9-14, FR-P9-25, NFR-G-01, NFR-G-08, NFR-G-14, NFR-G-26, NFR-P8-02, NFR-P8-03, NFR-P9-01, NFR-P9-02, NFR-P9-03, NFR-P9-04, NFR-P9-05, NFR-P9-06, NFR-P9-07 | Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
84-| FS-10-01 | [FIN-66](https://sandeephgowda8618.atlassian.net/browse/FIN-66) | Calculate DCF valuation with versioned assumptions | Sprint 4 | Release 1 per Jira issue |— | Run stores company, data snapshot, model version, assumptions, forecasts and outputs, sensitivity results link to the run, missing inputs are surfaced. explicit assumptions so that valuation outputs can be reproduced. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |

85-| FS-10-02 | [FIN-67](https://sandeephgowda8618.atlassian.net/browse/FIN-67) | Calculate portfolio VaR/CVaR and drawdown | Sprint 4 | Release scope not explicit in Jira issue | — | Risk run stores input snapshot, configuration, lookback, frequency, seed/method and limitations, test cases validate calculations. understand downside exposure. | — | No linked test, NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
--
92-| FS-11-02 | [FIN-73](https://sandeephgowda8618.atlassian.net/browse/FIN-73) | Run CI quality gates on every pull request | Sprint 1 | Release 1 per Jira issue | NFR-G-03, NFR-G-05, NFR-G-07, NFR-G-23, NFR-G-27 | A deliberately failing test/check makes CI fail, default branch stays green, reports are retained. defects are caught before merge. | TC_CI_001, TC_CI_002, TC_SEC_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_SEC_001=BLOCKED | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records| Acceptance remains incomplete or externally unverified, see implementation record. |
93-| FS-11-03 | [FIN-74](https://sandeephgowda8618.atlassian.net/browse/FIN-74) | Build and deploy a versioned release artifact | Sprint 1 | Release 1 per Jira issue | NFR-G-15, NFR-G-16, NFR-G-25, NFR-G-27, NFR-G-38 | Build artifact is tagged, configuration is environment-driven, deployment/rollback steps are documented and tested if hosting is available. | TC_BUILD_001, TC_BUILD_002, TC_REL_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_REL_001=NOT RUN | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specificpaths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
94:| FS-11-04 | [FIN-75](https://sandeephgowda8618.atlassian.net/browse/FIN-75) | Apply TDD and maintain unit/integration/E2E suites | Sprint 1 | Release 1 per Jira issue |FR-P1-01, FR-P1-02, FR-P1-03, FR-P1-04, FR-P1-05, FR-P1-06, FR-P1-07, FR-P1-08, FR-P1-09, FR-P8-02, FR-P8-12, NFR-G-04, NFR-G-07, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17, NFR-G-23, NFR-G-26, NFR-G-27, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-04, NFR-P8-02, NFR-P9-02 | Critical validators, authorization filters, idempotency and API errors have automated tests, smoke path runs repeatably. implementation where practical so that behavior is verified continuously. | TC_CI_001, TC_COV_001, TC_DB_001, TC_INT_001, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_COV_001=PASS, TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |

95-| FS-11-05 | [FIN-76](https://sandeephgowda8618.atlassian.net/browse/FIN-76) | Measure line/branch coverage and test quality | Sprint 1 | Release 1 per Jira issue | NFR-G-23 | Coverage report is generated, branch coverage is reported where tooling supports it, critical gaps have follow-up | TC_COV_001 | TC_COV_001=PASS | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
96-| FS-11-06 | [FIN-77](https://sandeephgowda8618.atlassian.net/browse/FIN-77) | Run security validation and dependency checks | Sprint 1 | Release 1 per Jira issue | FR-P1-10, NFR-G-03, NFR-G-04, NFR-G-05, NFR-G-06, NFR-G-07, NFR-G-11, NFR-G-23, NFR-G-25, NFR-G-27, NFR-G-30, NFR-G-31, NFR-P1-01, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-02, NFR-P7-05, NFR-P8-01, NFR-P8-07, NFR-P9-03 | Auth, workspace isolation, file validation, prompt injection and secret-leak cases are tested, critical issues block release. so that high-risk defects block release. Acceptance criteria | TC_AUTHN_006, TC_AUTHSEC_002, TC_CFG_001, TC_CI_001, TC_ENV_002, TC_EXEC_002, TC_SEC_001, TC_SEC_002 | TC_AUTHN_006=PASS, TC_AUTHSEC_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CI_001=BLOCKED, TC_ENV_002=NOT RUN, TC_EXEC_002=NOT RUN, TC_SEC_001=BLOCKED, TC_SEC_002=BLOCKED | PARTIAL | IMPLEMENTATION_STATUS.txt, issue-specific paths in prior records | Acceptance remains incomplete or externally unverified, see implementation record. |
--
100-| FS-11-10 | [FIN-81](https://sandeephgowda8618.atlassian.net/browse/FIN-81) | Manage baselines, bugs, versions, SBOM and release notes | Sprint 1 | Release 1 per Jira issue | FR-P1-14, FR-P3-36, NFR-G-15, NFR-G-16, NFR-G-25, NFR-G-27, NFR-G-38 | Version baseline and changelog exist, bugs link to regression tests, SBOM is generated if tooling/time permits or limitation recorded. changes can be audited and maintained. | TC_BOUNDARY_001, TC_BUILD_001, TC_BUILD_002, TC_REL_001 | TC_BOUNDARY_001=NOT RUN, TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_REL_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
101-| FS-11-11 | [FIN-82](https://sandeephgowda8618.atlassian.net/browse/FIN-82) | Document usability, AI use, licenses and data rights | Sprint 1 | Release 1 per Jira issue | NFR-G-18, NFR-G-19, NFR-G-20, NFR-G-21, NFR-G-27, NFR-P1-06 | AI-generated code is reviewed and tested, license/data rights are recorded, usability checks include accessibility and understandable failures. compliant. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
102:| FS-11-12 | [FIN-83](https://sandeephgowda8618.atlassian.net/browse/FIN-83) | Add health checks, structured logs, retry and recovery runbook | Sprint 1 | Release 1 perJira issue | FR-P1-01, FR-P1-06, FR-P2-08, FR-P2-39, FR-P8-02, FR-P8-12,

NFR-G-04, NFR-G-06, NFR-G-07, NFR-G-08, NFR-G-11, NFR-G-13, NFR-G-14, NFR-G-15, NFR-G-16, NFR-G-17,NFR-G-23, NFR-G-26, NFR-G-30, NFR-G-31, NFR-G-34, NFR-G-35, NFR-G-36, NFR-G-37, NFR-G-38, NFR-P2-02, NFR-P2-03, NFR-P3-05, NFR-P3-06, NFR-P3-07, NFR-P4-01, NFR-P4-06, NFR-P7-01, NFR-P7-02, NFR-P7-04, NFR-P7-05, NFR-P8-04, NFR-P9-03 | Health endpoints work, logs include run IDs and redact secrets, retries are bounded/idempotent, outage drill has recorded outcome. are diagnosable. | TC_BUILD_002, TC_DASH_002, TC_DB_001, TC_EXEC_001, TC_EXEC_002, TC_OPS_001, TC_OPS_002, TC_OPS_003, TC_SEC_002, TC_SYS_001, TC_TRACE_001 | TC_BUILD_002=BLOCKED, TC_DASH_002=NOT RUN, TC_DB_001=BLOCKED, TC_EXEC_001=NOT RUN, TC_EXEC_002=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_OPS_003=NOT RUN, TC_SEC_002=BLOCKED, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | No implementation evidence in current repository. |
103-
104-## SRS requirement matrix (399 FR/NFR IDs plus 10 DIR rules)
--
116-| DIR-09 | Audit Separation | PDF p.43, SRS Section 6, data-integrity rules | Data integrity and retrieval lifecycle | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
117-| DIR-10 | Backup Recovery | PDF p.43, SRS Section 6, data-integrity rules | Data integrity and retrieval lifecycle | — | — | No mapped key | No mapped story criterion,do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmappedto source story |
118:| FR-P1-01 | User Authentication | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-05, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-17, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/app/auth.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |

119:| FR-P1-02 | Session Termination | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials revealno account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
120:| FR-P1-03 | Password Recovery | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65,FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
121:| FR-P1-04 | User Onboarding | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-01/FIN-13: Valid credentials create a session, logout invalidates it, invalid credentials reveal no account existence, onboarding follows admin policy. | TC_AUTHN_001, TC_AUTHN_002, TC_AUTHN_003, TC_AUTHN_004, TC_AUTHN_005, TC_INT_001, TC_SYS_001, TC_TRACE_001 | TC_AUTHN_001=PASS, TC_AUTHN_002=PASS, TC_AUTHN_003=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_005=BLOCKED, TC_INT_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/provision_user.py (trusted local operator CLI only) | Local provisioning exists, administrator invitation/onboarding workflow is absent. | Preserve source story release label |
122:| FR-P1-05 | Role-Based Access Control | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified

2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/migrations/0001_auth_identity.sql (roles table only, no role enforcement) | Current code covers only part of this source requirement. | Preserve source story release label |
123:| FR-P1-06 | Protected Routes | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-02-08, FS-08-01, FS-08-05, FS-09-05, FS-11-04, FS-11-12 | FIN-13, FIN-14, FIN-15, FIN-25, FIN-57, FIN-61, FIN-65, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (/auth/me only) | Current code covers only part of this source requirement. | Preserve source story release label |
124:| FR-P1-07 | Permission Enforcement | PDF p.3, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | apps/api/app/main.py (authentication dependency, no role/operation matrix) | Current code covers only part of this source requirement. | Preserve source story release label |
125:| FR-P1-08 | Session Expiry | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-02, FS-01-03, FS-08-05, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-61, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-02/FIN-15: Unauthenticated requests are rejected, role/permission matrix is tested server-side, inactive sessions expire per configuration. | TC_AUTHZ_001, TC_AUTHZ_002, TC_AUTHZ_003, TC_INT_001, TC_PRIV_002, TC_SYS_001 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_AUTHZ_003=PASS, TC_INT_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_SYS_001=NOT RUN | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py,

apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
126-| FR-P1-09 | Authentication Event Recording | PDF p.4, SRS P1 requirements | Identity and access | FS-01-01, FS-01-03, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
127-| FR-P1-10 | Account Protection | PDF p.4, SRS P1 requirements | Identity and access | FS-01-03, FS-11-06 | FIN-14, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited.| TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
128-| FR-P1-11 | Multi-Factor Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-03 | FIN-14 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
129-| FR-P1-12 | Active Session Management | PDF p.4, SRS P1 requirements | Identity and access | FS-01-03 | FIN-14 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-03/FIN-14: Security events are auditable, repeated failures are throttled, MFA/session features are enabled only when configured. detected and limited. | TC_AUTHSEC_001, TC_AUTHSEC_002, TC_AUTHSEC_003, TC_INT_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_002=NOT RUN, TC_AUTHSEC_003=NOT RUN, TC_INT_001=NOT RUN | PARTIAL | apps/api/app/main.py (current-session logout only) | Current code covers only part of this source requirement. | Preserve source story release label |

130:| FR-P1-13 | Step-Up Authentication | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mappedfoundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
131:| FR-P1-14 | Data and Trading Permissions | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05, FS-11-08, FS-11-10 | FIN-16, FIN-65, FIN-79, FIN-81| Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | PARTIAL | apps/api/app/main.py (no trading routes), optional trading DDL remains reference-only | Separate permission policy is absent, no trading routes are enabled and trading remains Release 2 gated. | Release 1 boundary / mixed with Release 2 |
132:| FR-P1-15 | Connection Ownership | PDF p.4, SRS P1 requirements | Identity and access | FS-01-04, FS-09-05 | FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-04/FIN-16: Users cannot use another user's credentials, Release 1 has no order-execution path, sensitive actions require policy checks. | TC_AUTHSEC_004, TC_AUTHZ_002, TC_BOUNDARY_001, TC_PRIV_002 | TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_BOUNDARY_001=NOT RUN, TC_PRIV_002=NOT RUN | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Release 1 boundary / mixed with Release 2 |
133-| FR-P2-01 | Overview Metrics | PDF p.5, SRS P2 requirements | Dashboard and market overview | FS-02-01 | FIN-18 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-01/FIN-18: Dashboard scopes data to the user/workspace, shows service health and job status, refresh failures and empty states are explicit. understand system status. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
134-| FR-P2-02 | Service Health | PDF p.5, SRS P2 requirements | Dashboard and market overview | FS-02-01 | FIN-18 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-01/FIN-18: Dashboard scopes data to the user/workspace, shows service health and job status, refresh failures and empty states are explicit. understand

system status. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
--
338-| FR-P7-37 | Trade Journal | PDF p.28, SRS P7 requirements | Execution and backtesting | FS-07-04 | FIN-54 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-07-04/FIN-54: Trading schema is not applied in R1, any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation. reconciliation,journal and notifications so that trades are controlled and auditable. | — | No linked test, NOT RUN | PLANNED | — | The mapped source story is explicitly Release 2 only, absent from current runtime. | Release 2 only |
339-| FR-P7-38 | Trading Notifications | PDF p.28, SRS P7 requirements | Execution and backtesting | FS-07-04 | FIN-54 | Live Jira JQL verified 2026-10-19, test-plan sourcerefs | FS-07-04/FIN-54: Trading schema is not applied in R1, any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation. reconciliation, journal and notifications so that trades are controlled and auditable. | — | No linked test, NOT RUN | PLANNED | — | The mapped source story is explicitly Release 2only, absent from current runtime. | Release 2 only |
340:| FR-P8-01 | Ollama Configuration | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
341:| FR-P8-02 | Connection Validation | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN,TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN,

TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
342:| FR-P8-03 | Model Discovery | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
343:| FR-P8-04 | Default Model | PDF p.29, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
344:| FR-P8-05 | Inference Parameters | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01 | FIN-57 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-01/FIN-57: Invalid settings fail before activation, unavailable model yields a controlled state, model and parameters are traceable. configure inference with versioning so that AI behavior is controlled. | TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_DASH_002, TC_LLM_001, TC_LLM_002, TC_LLM_003, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_DASH_002=NOT RUN, TC_LLM_001=NOT RUN, TC_LLM_002=NOT RUN, TC_LLM_003=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |

345-| FR-P8-06 | Embedding Model | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
346-| FR-P8-07 | Vector Database Configuration | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
--
349-| FR-P8-10 | Metadata Filtering | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
350-| FR-P8-11 | RAG Testing | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-02 | FIN-56 | Live Jira JQL verified 2026-10-19, test-plan source refs| FS-08-02/FIN-56: Embedding model/dimension/index version match, metadata filters are tested, changes require re-index where needed, sample RAG test results are recorded. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
351:| FR-P8-12 | Service Diagnostics | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13,FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_LLM_001, TC_OPS_001, TC_SYS_001 | TC_LLM_001=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mappingis needed. | Unmapped to source story |
352-| FR-P8-13 | Configuration Versioning | PDF p.30, SRS P8 requirements | Models, providers and settings | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link

among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
353-| FR-P8-14 | Configuration Validation | PDF p.30, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05 | FIN-57, FIN-61 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CFG_002, TC_LLM_003 | TC_CFG_002=NOT RUN, TC_LLM_003=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
374-| FR-P9-04 | Interface Preferences | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-09-01 | FIN-59 | Live Jira JQL verified 2026-10-19, test-plansource refs | FS-09-01/FIN-59: Preferences persist across sessions, private fields are isolated, notification choices are honored. preferences so that the application fits my workflow. Acceptance criteria | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
375-| FR-P9-05 | Notification Preferences | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-09-01 | FIN-59 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-01/FIN-59: Preferences persist across sessions, private fields are isolated, notification choices are honored. preferences so that the application fits my workflow. Acceptance criteria | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
376:| FR-P9-06 | Workspace Settings | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and hasno current runtime evidence. | Preserve source story release label |
377:| FR-P9-07 | Member Management | PDF p.33, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |

378:| FR-P9-08 | Role Management | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-02, FS-09-05 | FIN-15, FIN-16, FIN-62, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-02/FIN-62: Only authorized owners manage membership, shared items follow explicit grants, cross-workspace negative tests pass. collaboration respects permission boundaries. | TC_PRIV_002 | TC_PRIV_002=NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has nocurrent runtime evidence. | Preserve source story release label |
379-| FR-P9-09 | API Credentials | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-09-03 | FIN-63 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-03/FIN-63: Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
380-| FR-P9-10 | Data Export | PDF p.34, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-03/FIN-63: Secrets are never redisplayed, destructive actions require confirmation, export/deletion follow documented retention rules, audit records are scoped. | TC_AUTHSEC_001, TC_CFG_001, TC_CRED_001, TC_CRED_002, TC_OPS_002, TC_PRIV_001, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_CFG_001=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
--
408-| NFR-FIN-13 | Calculation and AI Separation | PDF p.45, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
409-| NFR-FIN-14 | Provider Failure Handling | PDF p.45, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |

410:| NFR-FIN-15 | Data Licensing | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
411-| NFR-FIN-16 | Alert Reliability | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
412-| NFR-FIN-17 | Scalable Analytics | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
414-| NFR-FIN-19 | Graceful Degradation | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, donot infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped tosource story |
415-| NFR-FIN-20 | Verification | PDF p.46, SRS Section 11, financial NFR | Financial correctness and safety | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
416:| NFR-G-01 | Authorization Enforcement | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHZ_001, TC_AUTHZ_002 | TC_AUTHZ_001=NOT RUN, TC_AUTHZ_002=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
417-| NFR-G-02 | Data Encryption | PDF p.36, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
418-| NFR-G-03 | Secrets Management | PDF p.36, SRS global NFR | Cross-cutting quality and operations | FS-01-05, FS-08-05, FS-09-03, FS-11-01, FS-11-02, FS-11-06 | FIN-17,FIN-2, FIN-61, FIN-63, FIN-73, FIN-77 | Live Jira JQL verified 2026-10-19,

test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHN_006, TC_CFG_001, TC_ENV_002, TC_SEC_001 | TC_AUTHN_006=PASS, TC_CFG_001=NOT RUN, TC_ENV_002=NOT RUN, TC_SEC_001=BLOCKED | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
426-| NFR-G-11 | Bounded Resource Usage | PDF p.37, SRS global NFR | Cross-cutting quality and operations | FS-01-03, FS-11-04, FS-11-06, FS-11-12 | FIN-14, FIN-75, FIN-77,FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHSEC_002, TC_SEC_002 | TC_AUTHSEC_002=NOT RUN, TC_SEC_002=BLOCKED | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
427-| NFR-G-12 | Capacity Testing | PDF p.37, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | —|No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
428:| NFR-G-13 | Controlled Failure | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13,FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
429-| NFR-G-14 | Data Consistency | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-03, FS-07-05, FS-08-05, FS-09-05, FS-11-04, FS-11-07, FS-11-12 | FIN-13, FIN-14, FIN-55, FIN-61, FIN-65, FIN-75, FIN-78, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DB_001, TC_INT_001, TC_OPS_003 | TC_DB_001=BLOCKED, TC_INT_001=NOT RUN, TC_OPS_003=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
430-| NFR-G-15 | Backup and Restore | PDF p.38, SRS global NFR | Cross-cutting quality and operations | FS-07-05, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-55, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_002, TC_OPS_003 | TC_BUILD_002=BLOCKED, TC_OPS_003=NOT RUN | NOT ASSESSED | — | No

direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
--
436-| NFR-G-21 | Error Understandability | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_AUTHN_009, TC_ETH_001 | TC_AUTHN_009=NOT RUN, TC_ETH_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
437-| NFR-G-22 | Modular Architecture | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-08-01, FS-08-05, FS-11-07 | FIN-57, FIN-61, FIN-78 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CFG_004, TC_DOC_001 | TC_CFG_004=NOT RUN, TC_DOC_001=PASS | PARTIAL | apps/web/app, apps/api/app, docs/architecture/README.md | Current code covers only part of this source requirement. | Unmapped to source story |
438:| NFR-G-23 | Automated Testing | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-02, FS-11-04, FS-11-05,FS-11-06, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-73, FIN-75, FIN-76, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_CI_001, TC_CI_002, TC_COV_001, TC_SEC_001, TC_SYS_001, TC_TEST_001 | TC_CI_001=BLOCKED, TC_CI_002=BLOCKED, TC_COV_001=PASS, TC_SEC_001=BLOCKED, TC_SYS_001=NOT RUN, TC_TEST_001=PASS | PARTIAL | apps/api/tests, apps/web/tests, scripts/run_live_e2e.py | Current code covers only part of this source requirement. | Unmappedto source story |
439-| NFR-G-24 | API Documentation | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-11-07 | FIN-78 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DOC_001 | TC_DOC_001=PASS | IMPLEMENTED — VERIFIED | docs/architecture/README.md, apps/api/app/main.py, generated OpenAPI/TestClient review | Evidence supports the current scoped behavior only. | Unmapped to source story |
440-| NFR-G-25 | Configuration Separation | PDF p.39, SRS global NFR | Cross-cutting quality and operations | FS-11-01, FS-11-03, FS-11-06, FS-11-10 | FIN-2, FIN-74, FIN-77, FIN-81 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_ENV_001, TC_ENV_002 | TC_BUILD_001=BLOCKED,TC_ENV_001=NOT RUN, TC_ENV_002=NOT RUN | PARTIAL | .env.example, apps/web/.env.example, apps/api/app/main.py, apps/web/app/api/runtime-config/route.js | Current code coversonly part of this source requirement. | Unmapped to source story |
--

447-| NFR-G-32 | Model and Index Compatibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do notinfer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
448-| NFR-G-33 | Model Replacement | PDF p.40, SRS global NFR | Cross-cutting quality and operations | — | — | No mapped key | No mapped story criterion, do not infer. | — | No linked test, NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
449:| NFR-G-34 | Health Checks | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_DASH_002, TC_OPS_001, TC_SYS_001 | TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping isneeded. | Unmapped to source story |
450:| NFR-G-35 | Structured Logs | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-09-03, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-63, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_002, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_002=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
451:| NFR-G-36 | Operational Monitoring | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
452:| NFR-G-37 | Graceful Shutdown | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-04, FS-11-12 | FIN-13, FIN-15, FIN-25, FIN-55, FIN-57, FIN-75, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_OPS_001, TC_OPS_003, TC_SYS_001 | TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_SYS_001=NOT RUN | NOT ASSESSED | — | No direct

source-story link among the 72 catalog aliases, product disposition/mapping is needed. | Unmapped to source story |
453:| NFR-G-38 | Deployment Reproducibility | PDF p.40, SRS global NFR | Cross-cutting quality and operations | FS-01-01, FS-01-02, FS-02-08, FS-07-05, FS-08-01, FS-11-01, FS-11-03, FS-11-04, FS-11-10, FS-11-12 | FIN-13, FIN-15, FIN-2, FIN-25, FIN-55, FIN-57, FIN-74, FIN-75, FIN-81, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | No mapped story criterion, do not infer. | TC_BUILD_001, TC_BUILD_002, TC_ENV_001, TC_OPS_001, TC_OPS_003, TC_REL_001, TC_SYS_001 | TC_BUILD_001=BLOCKED, TC_BUILD_002=BLOCKED, TC_ENV_001=NOT RUN, TC_OPS_001=NOT RUN, TC_OPS_003=NOT RUN, TC_REL_001=NOT RUN, TC_SYS_001=NOT RUN | PARTIAL | scripts/package_release.py, docs/release/RELEASE_README.md (no deployment target) | Versioned package process exists, deployment target and committed-SHA evidence are absent. | Unmapped to source story |
454-| NFR-P1-01 | Credential Security | PDF p.4, SRS P1 requirements | Identity and access | FS-01-05, FS-11-06 | FIN-17, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/auth.py, apps/api/app/provision_user.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
455-| NFR-P1-02 | Transport Security | PDF p.4, SRS P1 requirements | Identity and access | FS-01-05 | FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/api/app/main.py (Secure cookie switch), no deployed HTTPS endpoint | Deployed HTTPS cannot be verified without an approved deployment target. | Preserve source story release label |
--
458-| NFR-P1-05 | Information Disclosure | PDF p.5, SRS P1 requirements | Identity and access | FS-01-01, FS-01-05 | FIN-13, FIN-17 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses

HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_004, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_004=BLOCKED, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | IMPLEMENTED — VERIFIED | apps/api/app/main.py, apps/api/tests/test_auth.py, apps/api/tests/test_auth_unit.py | Evidence supports the current scoped behavior only. | Preserve source story release label |
459-| NFR-P1-06 | Accessibility | PDF p.5, SRS P1 requirements | Identity and access | FS-01-05, FS-11-11 | FIN-17, FIN-82 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-01-05/FIN-17: No plaintext passwords, deployed auth uses HTTPS, session controls are secure, keyboard, labels, focus and understandable errors are tested. that login is safe and usable. | TC_AUTHN_002, TC_AUTHN_006, TC_AUTHN_007, TC_AUTHN_008, TC_AUTHN_009, TC_TRACE_001 | TC_AUTHN_002=PASS, TC_AUTHN_006=PASS, TC_AUTHN_007=BLOCKED, TC_AUTHN_008=NOT RUN, TC_AUTHN_009=NOT RUN, TC_TRACE_001=PASS | PARTIAL | apps/web/app/page.js, apps/web/tests/ui/auth.spec.js | Current code covers only part of this source requirement. | Preserve source story release label |
460:| NFR-P2-01 | Rendering Performance | PDF p.8, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
461:| NFR-P2-02 | Graceful Degradation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
462:| NFR-P2-03 | Data Freshness | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08, FS-08-01, FS-11-12 | FIN-25, FIN-57, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content

meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
463:| NFR-P2-04 | Data Isolation | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. |TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
464:| NFR-P2-05 | Responsive Layout | PDF p.9, SRS P2 requirements | Dashboard and market overview | FS-02-08 | FIN-25 | Live Jira JQL verified 2026-10-19, test-plan sourcerefs | FS-02-08/FIN-25: Primary content meets agreed performance target, layouts work on supported screens, only authorized records are shown, freshness states are explicit. | TC_DASH_001, TC_DASH_002, TC_OPS_001, TC_SYS_001, TC_TRACE_001 | TC_DASH_001=NOT RUN, TC_DASH_002=NOT RUN, TC_OPS_001=NOT RUN, TC_SYS_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
465-| NFR-P3-01 | Response Latency | PDF p.13, SRS P3 requirements | AI analyst | FS-03-07 | FIN-32 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-03-07/FIN-32: Failures do not corrupt history, retrieved content is untrusted, sensitive prompts/secrets are not leaked, status and model limitations are visible. trustworthy. | — |No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
466-| NFR-P3-02 | Streaming Stability | PDF p.13, SRS P3 requirements | AI analyst | FS-03-07 | FIN-32 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-03-07/FIN-32: Failures do not corrupt history, retrieved content is untrusted, sensitive prompts/secrets are not leaked, status and model limitations are visible. trustworthy. | — | No linked test, NOT RUN | PLANNED | — | Mapped story is scheduled beyond Sprint 1 and has no current runtime evidence. | Preserve source story release label |
--

508-| NFR-P8-07 | Diagnostic Security | PDF p.32, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05, FS-09-03, FS-11-06 | FIN-57, FIN-61, FIN-63, FIN-77 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-05/FIN-61: Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_LLM_001, TC_TRACE_001 | TC_CFG_001=NOTRUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_LLM_001=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
509-| NFR-P8-08 | Performance Configuration | PDF p.32, SRS P8 requirements | Models, providers and settings | FS-08-01, FS-08-05 | FIN-57, FIN-61 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-08-05/FIN-61: Secrets are referenced securely, config changes are audited, validation precedes activation, retrieval/index compatibility is checked. production unexpectedly. | TC_CFG_001, TC_CFG_002, TC_CFG_003, TC_CFG_004, TC_INT_001, TC_LLM_003, TC_TRACE_001 | TC_CFG_001=NOT RUN, TC_CFG_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CFG_004=NOT RUN, TC_INT_001=NOT RUN, TC_LLM_003=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
510:| NFR-P9-01 | Privacy | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
511:| NFR-P9-02 | Sensitive Changes | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-01, FS-01-02, FS-01-03, FS-01-04, FS-08-01, FS-08-05, FS-09-03, FS-09-05, FS-11-04 | FIN-13, FIN-14, FIN-15, FIN-16, FIN-57, FIN-61, FIN-63, FIN-65, FIN-75 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.

| TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_CRED_002, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
512:| NFR-P9-03 | Secret Handling | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-07-05, FS-08-05, FS-09-03, FS-09-05, FS-11-06, FS-11-12 | FIN-55, FIN-61, FIN-63, FIN-65, FIN-77, FIN-83 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_001, TC_CFG_003, TC_CRED_001, TC_CRED_002, TC_INT_001, TC_OPS_002, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_001=NOT RUN, TC_CFG_003=NOT RUN, TC_CRED_001=NOT RUN, TC_CRED_002=NOT RUN, TC_INT_001=NOT RUN, TC_OPS_002=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
513:| NFR-P9-04 | Preference Persistence | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-05 | FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
514:| NFR-P9-05 | Change Confirmation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004,

TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
515:| NFR-P9-06 | Administrative Isolation | PDF p.35, SRS P9 requirements | Account, workspace and reporting | FS-01-02, FS-01-04, FS-09-05 | FIN-15, FIN-16, FIN-65 | LiveJira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001, TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
516:| NFR-P9-07 | Data Lifecycle | PDF p.36, SRS P9 requirements | Account, workspace and reporting | FS-09-03, FS-09-05 | FIN-63, FIN-65 | Live Jira JQL verified 2026-10-19, test-plan source refs | FS-09-05/FIN-65: Cross-user read/write attempts fail, privilege changes are auditable, data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected. | TC_AUTHSEC_001, TC_AUTHSEC_004, TC_AUTHZ_002, TC_CFG_003, TC_INT_001,TC_PRIV_001, TC_PRIV_002, TC_TRACE_001 | TC_AUTHSEC_001=NOT RUN, TC_AUTHSEC_004=NOT RUN, TC_AUTHZ_002=NOT RUN, TC_CFG_003=NOT RUN, TC_INT_001=NOT RUN, TC_PRIV_001=NOT RUN, TC_PRIV_002=NOT RUN, TC_TRACE_001=PASS | NOT IMPLEMENTED | — | Mapped foundation scope is absent from the current implementation. | Preserve source story release label |
517-
518-## Known coverage gaps

========== 5. STORY TRACEABILITY CSV ==========
3:FS-01-02,FIN-15,LIVE JIRA VERIFIED 2026-10-19,Enforce roles and protected routes,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P8-02; FR-P8-12; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-G-13; NFR-G-23; NFR-G-34; NFR-G-35; NFR-G-36; NFR-G-37; NFR-G-38; NFR-P9-01; NFR-P9-02; NFR-P9-06,Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per

configuration.,TC_AUTHZ_001; TC_AUTHZ_002; TC_AUTHZ_003; TC_PRIV_002; TC_SYS_001,TC_AUTHZ_001=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_AUTHZ_003=PASS (2026-10-18 session-expiry evidence); TC_PRIV_002=NOT RUN / DEFERRED; TC_SYS_001=NOT RUN,PARTIAL,apps/api/app/main.py; apps/api/tests/test_identity_constraints.py; apps/api/tests/test_auth_unit.py; IMPLEMENTATION_STATUS.txt,"Latest API suite: 58 passed, 18 warnings. TC_AUTHZ_001 and TC_AUTHZ_002 remain NOT RUN as complete test-plan cases; TC_PRIV_002 workspace/resource authorization is deferred; TC_SYS_001 end-to-end smoke remains NOT RUN. Platform-only scope."
5:FS-01-04,FIN-16,LIVE JIRA VERIFIED 2026-10-19,Separate read-only and trading permissions,Sprint 1,Release 1 boundary; trading scope Release 2,FR-P1-05; FR-P1-07; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; NFR-G-01; NFR-P9-01; NFR-P9-02; NFR-P9-06,Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.,TC_AUTHSEC_004; TC_AUTHZ_002; TC_BOUNDARY_001; TC_PRIV_002,TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_BOUNDARY_001=NOT RUN; TC_PRIV_002=NOT RUN,NOT IMPLEMENTED,—,No implementation evidence in current repository.
54:FS-09-05,FIN-65,LIVE JIRA VERIFIED 2026-10-19,Enforce privacy and safe account administration,Sprint 1,Release 1 per Jira issue,FR-P1-01; FR-P1-02; FR-P1-03; FR-P1-04; FR-P1-05; FR-P1-06; FR-P1-07; FR-P1-08; FR-P1-09; FR-P1-13; FR-P1-14; FR-P1-15; FR-P3-36; FR-P9-06; FR-P9-07; FR-P9-08; FR-P9-10; FR-P9-11; FR-P9-12; FR-P9-13; FR-P9-14; FR-P9-25; NFR-G-01; NFR-G-08; NFR-G-14; NFR-G-26; NFR-P8-02; NFR-P8-03; NFR-P9-01; NFR-P9-02; NFR-P9-03; NFR-P9-04; NFR-P9-05; NFR-P9-06; NFR-P9-07,Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy. sensitive-action checks and clear destructive-change confirmation so that personal and workspace data remain protected.,TC_AUTHSEC_001; TC_AUTHSEC_004; TC_AUTHZ_002; TC_CFG_003; TC_INT_001; TC_PRIV_001; TC_PRIV_002; TC_TRACE_001,TC_AUTHSEC_001=NOT RUN; TC_AUTHSEC_004=NOT RUN; TC_AUTHZ_002=NOT RUN; TC_CFG_003=NOT RUN; TC_INT_001=NOT RUN; TC_PRIV_001=NOT RUN; TC_PRIV_002=NOT RUN; TC_TRACE_001=PASS,NOT IMPLEMENTED,—,No implementation evidence in current repository.

========== 6. LATEST IMPLEMENTATION NOTES ==========
- Applied apps/api/migrations/0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API test suite: 55 passed, 0 failed, 9 warnings.
- git diff --check: no errors reported.
- Warning: Starlette/httpx deprecation warnings remain.

- Outstanding acceptance gap: require_permission is defined and unit-tested, but no actual application route was found using it in the current route inspection.
- FIN-15 is not yet marked complete pending route-level authorization verification and remaining acceptance checks.

FIN-15 implementation update — 2026-10-20
- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are checked.
- No migrations, commits, pushes, or workspace schema changes performed by this patch script.

FIN-15 — VERIFIED TEST RUN ADDENDUM (2026-10-20)
Latest run: 20261020_141030
Recorded revision: 64f2637
Python: 3.14.6
Database: finsight_test

Observed results:
- tests/test_identity_constraints.py: 3 passed, 4 warnings.
- Full API suite: 55 passed, 10 warnings.
- Both pytest commands exited with code 0.
- The test-run summary records Overall result: PASS.

Evidence:
- test-results/FIN-15/20261020_141030_identity_authorization.log
- test-results/FIN-15/20261020_141030_full_api_suite.log
- test-results/FIN-15/run_20261020_141030_summary.txt

The warnings were Starlette/httpx deprecations. The passing test suites establish the behavior exercised by those tests, not automatic completion of every FIN-15 acceptance criterion. Workspace membership and resource-level authorization remain deferred under the approved platform-only scope. Earlier entries are retained as historical records; this addendum records the later successful run.

FIN-15 — CURRENT VERIFICATION ADDENDUM (2026-10-20)
Scope: platform-level authorization only; workspace membership and resource-level authorization remain deferred under the approved scope decision.

Current API test evidence:
- Full API suite: 58 passed, 18 warnings.
- Traceability validator: PASS.
- Endpoint: GET /api/v1/admin/authorization/capabilities.
- Permission checks use database-resolved authorization; tests cover administrator access, standard-user denial, permission revocation, and platform-role revocation.
- TC_AUTHZ_001 remains NOT RUN as a complete test-plan case because its protected-frontend and response/log inspection steps are not all evidenced.
- TC_AUTHZ_002 remains NOT RUN as a complete test-plan case because its full role matrix, protected model/provider operation, and request-body privilege-manipulation steps are not all evidenced.
- TC_AUTHZ_003 retains its existing recorded status; the current 58-test result alone does not establish that every test-plan step was rerun.
- TC_PRIV_002 remains NOT RUN / deferred: workspace and cross-user resource authorization are not implemented by this platform-only change.
- TC_SYS_001 remains NOT RUN until the required end-to-end smoke path is run.

Overall FIN-15 status: PARTIAL. Passing API tests do not constitute acceptance of every story criterion. No claim is made that the story is fully accepted. Historical entries above this addendum are retained.

========== 7. RECENT CONVERSATION NOTES ==========
CI update adds blocking dependency-security checks but remote workflow execution and branch-protection enforcement are not verified. TC_SEC_001 is recorded BLOCKED pending GitHub Actions evidence. TC_SEC_002 is BLOCKED because file-upload validation and RAG/prompt-context functionality are not implemented; no related features were added. Rate limiting, password recovery, admin invitations, secret-config workflows, and execution diagnostics were not modified or retested. No

Git/Jira actions were taken, and no source docs, SQL, diagrams, or test-plan sources were changed.

FIN-78 / FS-11-07 — Architecture and compatibility documentation (2026-10-19)
Status: PARTIAL. Added `docs/architecture/README.md` and five numbered ADRs under `docs/architecture/adr/`. The docs describe the current Next.js/FastAPI/PostgreSQL authentication slice and explicitly distinguish it from target architecture/features not implemented. Checked API contracts against generated OpenAPI and actual TestClient responses; checked local Markdown links. TC_DOC_001 is PASS with evidence in `IMPLEMENTATION_STATUS.txt` and `SPRINT_1_TEST_EXECUTION_STATUS.txt`. TC_TRACE_001 remains NOT RUN; thatfull traceability audit is assigned to FS-11-08. Source PDFs, SQL references, diagrams, and original test plan were not modified.

Q-008 — Public API versioning and migration ownership — OPEN / NOT BLOCKING THIS DOCUMENTATION SLICE
Why it matters: Current API routes are unprefixed (`/auth/*`) and no formal breaking-change/deprecation policy or production migration owner/runner exists. The technical design asks for versioned public routes and the SRS requires controlled, versioned migrations, but no production consumer/deployment or migration platform is configured in therepository.
Recommended resolution: Keep existing routes and one-time identity migration unchanged for this slice. Before a public consumer or incompatible API change is introduced, decide whether to introduce a versioned path (for example `/v1`) and define a deprecation window. Before deployment, name the migration owner and choose/approve a migration runner and forward/rollback procedure. Do not apply the full reference schema.
Exact next action: Before the first externally consumed breaking API change, tell Codex whether to adopt a versioned path and the desired deprecation policy; before production deployment, identify the migration owner and approved migration-runner approach. No immediate action is required to keep documenting or testing the current local auth slice.

Q-009 — Unmapped SRS scope — WAITING FOR USER
Why it matters: The SRS identifier inventory contains 409 FR/NFR/DIR items. After combining explicit Jira issue references and the Sprint 1 test-plan traceability links, 328 requirement rows map to one or more of the 72 source story aliases; 81 do not. The matrix marks those rows NOT ASSESSED and does not infer that they are deferred, non-MVP,or approved for omission.
Recommended decision: Identify which of the 81 requirements are required in Release 1/MVP, which are deferred (with target release), and whether missing story/test

coverageshould be added through normal backlog change control. Keep the SRS authoritative until a reviewed addendum is approved.
Exact next action: Review the unmapped rows in `docs/requirements/traceability-requirements.csv` (filter `Source story aliases` = `—`) and reply with each requirement's disposition: Release 1, deferred plus release, or propose a scoped backlog change. Do not paste secrets. No Jira changes are pending/authorized.

Q-010 — Jira issues without source aliases — WAITING FOR USER
Why it matters: The read-only Jira project query returned FIN-84, FIN-85, FIN-86, and FIN-87 without a source FS alias; these are not among the 72 documented source storiesand have not been silently added to the source catalog.
Recommended decision: Confirm whether the four issues are supplemental Jira work outside the source catalog, or provide an approved source alias/document reference for each. Keep them separate until confirmed.
Exact next action: Reply with `FIN-84–FIN-87 are supplemental` or provide the approved alias and source document reference for each issue. No Jira changes are pending/authorized.

FIN-79 / FS-11-08 — SRS addendum and requirement traceability (2026-10-19)
Status: PARTIAL. Added `docs/requirements/traceability-matrix.md`, 409-row `traceability-requirements.csv`, 72-row `traceability-stories.csv`, and `srs-addendum.md`; added `scripts/validate_traceability.py` and README links. All source requirements and aliases are represented; Jira keys and test statuses remain separately identified. 328 requirement rows map to story aliases via Jira text or explicit test-plan traceability; 81 remain unmapped. Of 23 Sprint 1 stories, 22 carry explicit SRS IDs; FS-11-09/FIN-80 is a management/process story without a direct SRS ID. All 54 supplied test cases map to a catalog story. 104 requirement rows have supplied linked tests; 305 do not. Test-planrequirement ranges were expanded across all IDs in each interval. Q-009/Q-010 request disposition of unmapped requirements and FIN-84–FIN-87. TC_TRACE_001 is PASS; no othertest status was changed. Validation command: `python3 scripts/validate_traceability.py` (PASS; 409 requirements, 72 aliases, 54 tests; records the two source tests missing explicit execution rows as NOT RUN). `python3 -m py_compile scripts/validate_traceability.py` and local Markdown relative-link checks passed. Source PDFs, SQL, diagrams, andoriginal test plan remain read-only. No Jira or Git action was taken.

FIN-73 targeted CI repair — run 39203215763 (2026-10-19)
Status: local fixes verified; remote confirmation pending. Corrected frontend artifact packaging in `.github/workflows/ci.yml` to archive from `.next` under working directory

`apps/web`, with explicit hard-failing checks for `.next/standalone` and `.next/static`. Existing E2E and release-package extract/restore paths continue to use archive-root `standalone/` and `static/`. Normalized `docs/requirements/traceability-stories.csv` CRLF to LF; CSV parsing against HEAD proved all 73 rows and field values identical. No trailing whitespace remains. Removed one extra blank EOF line in `scripts/validate_traceability.py`, retaining the final newline. No repository CSV generator exists; validator is read-only.
Local checks: PyYAML workflow parse/target assertions PASS; `NEXT_TELEMETRY_DISABLED=1 npm run build` PASS (exit 0; Next 16.4.2); `.next/standalone` and `.next/static` exist; exact tar packaging command succeeded and archive inspection confirmed only `standalone/` and `static/` roots, 1,466 entries, SHA-256 `651f28563199baf95574f9c23fc78e2b8d6a10a88bf4a114c3fc033b744c3513`; `python3 scripts/validate_traceability.py` PASS; Python compilation PASS; CSV whitespace scan 0 rows; `git diff --check` PASS. No backend/security/Playwright suites were rerun.
Caveat: `git show --check --format= HEAD` on the existing root commit exits 2 with 1,323 historical whitespace diagnostics including immutable PDFs and other existing files. These were not changed. Current incremental worktree diff passes. A new incremental commit/push and GitHub Actions run are required to confirm the corrected workflow; no commit, push, Jira update, or rerun was performed.
Final validation note: after updating the coordination records, bounded `git diff --check` timed out at 8 seconds. Earlier targeted `git diff --check` completed with exit 0, and direct whitespace scans of all affected text files found zero trailing-whitespace lines and valid final newlines. Treat final full Git diff hygiene as incomplete due intermittent Git responsiveness; the incremental GitHub Actions run remains required.

2026-10-20 — FIN-15 verification checkpoint
- Created a dedicated local finsight_test database after resolving low disk space.
- Applied migrations 0001_auth_identity.sql and 0002_platform_authorization.sql successfully.
- Database integration tests: 3 passed.
- Full API suite: 55 passed, 0 failed, 9 warnings in 9.52 seconds.
- git diff --check returned no errors.
- Remaining gap: current inspection found require_permission defined and tested but not used by an actual application route. FIN-15 remains unverified/incomplete until route-level authorization and remaining acceptance criteria are checked.
- No commit or push performed.

FIN-15 implementation update — 2026-10-20

- Approved scope: platform-level authorization only; workspace roles, membership, and workspace tables deferred.
- Added GET /platform/admin/capability to the real FastAPI application, protected by the database-backed platform.admin permission dependency. This endpoint is a minimal authorization capability check and does not mutate data.
- Updated the database integration test to exercise the real application route for anonymous, platform-admin, and unprivileged-user access; the unprivileged request also supplies X-Role to verify client headers do not grant permission.
- Function/test traceability added in FUNCTION_TEST_TRACEABILITY.txt for TC_AUTHZ_001, TC_AUTHZ_002, and related existing session coverage TC_AUTHZ_003.
- Verification status: implementation edits prepared; tests have NOT RUN after this change. Do not mark FIN-15 VERIFIED COMPLETE until test results and all acceptance criteria are checked.
- No migrations, commits, pushes, or workspace schema changes performed by this patch script.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % python3 update_fin15_tracking.py
Updated: IMPLEMENTATION_STATUS.txt
Updated: SPRINT_1_TEST_EXECUTION_STATUS.txt
Updated: FUNCTION_TEST_TRACEABILITY.txt
Done. Historical records were preserved; no code, CSV, Git, Jira, or FIN-14 changes made.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %

Updated: FUNCTION_TEST_TRACEABILITY.txt
Done. Historical records were preserved; no code, CSV, Git, Jira, or FIN-14 changes made.
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % clear
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % git diff --check

tail -n 45 IMPLEMENTATION_STATUS.txt
tail -n 35 SPRINT_1_TEST_EXECUTION_STATUS.txt
tail -n 35 FUNCTION_TEST_TRACEABILITY.txt

git status --short
  resource authorization are not implemented by this platform-only change.
- TC_SYS_001 remains NOT RUN until the required end-to-end smoke path is run.

Overall FIN-15 status: PARTIAL. Passing API tests do not constitute acceptance of every story criterion. No claim is made that the story is fully accepted. Historical entries above this addendum are retained.

FIN-15 TRACKING RECONCILIATION — 2026-10-20 17:38 IST
Evidence source: recorded run 20261020_141030; this is a documentation reconciliation,
not a new test execution. Historical entries above are intentionally retained.

Recorded execution:
- Identity/authorization integration tests: 3 passed, 4 warnings; exit code 0.
- Full API suite: 55 passed, 10 warnings; exit code 0.
- Evidence: test-results/FIN-15/20261020_141030_identity_authorization.log, test-results/FIN-15/20261020_141030_full_api_suite.log, and test-results/FIN-15/run_20261020_141030_summary.txt.
- Warnings recorded as Starlette/httpx deprecations and per-request cookie deprecation warnings; no test failures were recorded in that run.

FIN-15 status: PARTIAL — do not mark story accepted/complete from these test results alone.
- Demonstrated by the recorded integration test: unauthenticated and invalid session denial; platform-admin success; standard-user denial despite an X-Role: platform_admin request header; platform role scope constraint.
- TC_AUTHZ_001: PARTIAL. API anonymous/invalid-session checks are evidenced, but the source test case also requires a protected frontend page and broader end-to-end checks. Do not mark fully PASS until those are exercised.
- TC_AUTHZ_002: PARTIAL for the narrow platform permission behavior asserted. The planned model/provider admin operation and full operator/standard-user operation matrix are not evidenced by the capability endpoint.
- TC_AUTHZ_003: retain the previously recorded PASS only as historical evidence for the existing session-expiry regression. It was not separately rerun in run 20261020_141030; confirm the configured idle-inactivity threshold if required by the source test case.
- TC_PRIV_002: DEFERRED / NOT RUN under the approved platform-only scope. Workspace membership, workspace resources, and resource-level isolation remain outside this implementation.
- TC_SYS_001: NOT RUN / NOT ESTABLISHED by the API suite alone.
- Approved decision remains platform-level authorization only. Workspace roles, membership, and workspace tables are deferred. FIN-14 is not changed.

- Before marking FIN-15 complete, verify the actual route path in
  apps/api/app/main.py and its tests, align stale route references in the
  tracking records, and close the remaining story-level acceptance gaps.

Results:
- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
- Full API suite: 55 passed, 10 warnings; exit code 0.
- Evidence files:
  test-results/FIN-15/20261020_141030_identity_authorization.log
  test-results/FIN-15/20261020_141030_full_api_suite.log
  test-results/FIN-15/run_20261020_141030_summary.txt

These results supersede earlier NOT RUN notes for the test execution performed
in this run. They do not establish that every mapped test-plan case or the entire
FIN-15 story is complete. Workspace-level authorization remains deferred.

FIN-15 TEST-STATUS RECONCILIATION — 2026-10-20 17:38 IST
Recorded run: 20261020_141030. This addendum does not claim a new execution.
- Identity/authorization integration suite: 3 passed, 4 warnings; exit code 0.
- Full API suite: 55 passed, 10 warnings; exit code 0.
- Evidence paths:
  test-results/FIN-15/20261020_141030_identity_authorization.log
  test-results/FIN-15/20261020_141030_full_api_suite.log
  test-results/FIN-15/run_20261020_141030_summary.txt

Conservative case disposition:
- TC_AUTHZ_001: PARTIAL — API unauthenticated/invalid-session behavior was
  exercised; protected frontend page and full test-plan scope remain unverified.
- TC_AUTHZ_002: PARTIAL — the narrow platform-admin/standard-user permission
  behavior and X-Role spoof rejection were exercised; the planned model/provider
  admin operation and complete role/operation matrix remain unverified.
- TC_AUTHZ_003: historical PASS only — the existing expiry regression was
  recorded earlier; it was not separately rerun in run 20261020_141030.
- TC_PRIV_002: DEFERRED / NOT RUN — workspace/resource authorization is
outside
  the approved platform-only scope.
- TC_SYS_001: NOT RUN — a passing API suite is not a browser/system smoke test.
Overall FIN-15 remains PARTIAL, not accepted. Do not alter FIN-14 tracking.
  to be verified.

Do not infer full story completion from a green test suite. Historical entries are retained, and this addendum records the latest observed execution.

FIN-15 TRACEABILITY RECONCILIATION — 2026-10-20 17:38 IST
Recorded run: 20261020_141030. The existing execution record reports 3 authorization integration tests and 55 full API tests passing; this entry does not represent a new run.

Status interpretation:
- TC_AUTHZ_001: PARTIAL; API anonymous/invalid-session assertions passed, but the source test case also requires a protected frontend page and broader end-to-end verification.
- TC_AUTHZ_002: PARTIAL; platform permission allow/deny and client-supplied X-Role rejection are evidenced. A model/provider admin operation and the full role/operation matrix are not evidenced.
- TC_AUTHZ_003: previously recorded PASS is historical; this run did not separately rerun the configured idle-inactivity test.
- TC_PRIV_002: DEFERRED / NOT RUN; workspace membership and resource-level authorization are outside the approved platform-only scope.
- TC_SYS_001: NOT RUN / not established by the API suite alone.

Route reconciliation warning: historical sections in this file and other tracking files contain conflicting route names. Before changing the canonical route text, inspect the current route decorator in apps/api/app/main.py and the matching test request path, then make all tracking references agree with that source. Do not infer the route from an older historical note.

Story disposition: FIN-15 / FS-01-02 remains PARTIAL. The capability endpoint is a narrow API authorization test seam, not proof that every protected operation, frontend guard, or system-level acceptance criterion is complete. Workspace roles, membership, and workspace tables remain deferred. FIN-14 is unchanged.
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py

```
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M docs/requirements/traceability-requirements.csv
 M docs/requirements/traceability-stories.csv
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
?? apps/web/proxy.js
?? update_fin15_tracking.py
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI %
```

Story disposition: FIN-15 / FS-01-02 remains PARTIAL. The capability endpoint is a narrow API authorization test seam, not proof that every protected operation, frontend guard, or system-level acceptance criterion is complete. Workspace roles, membership, and workspace tables remain deferred. FIN-14 is unchanged.

```
 M .github/workflows/ci.yml
 M IMPLEMENTATION_STATUS.txt
 M README.md
 M SPRINT_1_TEST_EXECUTION_STATUS.txt
 M apps/api/app/main.py
 M apps/api/app/provision_user.py
 M apps/api/tests/test_auth_unit.py
 M apps/api/tests/test_identity_constraints.py
 M apps/api/tests/test_provision_user.py
 M apps/web/tests/ui/auth.spec.js
 M conversation.txt
 M docs/architecture/README.md
 M docs/requirements/traceability-requirements.csv
 M docs/requirements/traceability-stories.csv
 M scripts/package_release.py
?? FUNCTION_TEST_TRACEABILITY.txt
?? FinSight_AI_API_Design_Pack/
?? apps/api/migrations/0002_platform_authorization.sql
```

```
?? apps/web/proxy.js
?? update_fin15_tracking.py
(.venv) (base) sandeeph@Sandeeps-MacBook-Pro FinSight_AI % grep -n -B 8 -A 15
'capability\|authorization/capabilities' \
  apps/api/app/main.py

grep -n -B 8 -A 15 'capability\|authorization/capabilities' \
  apps/api/tests/test_identity_constraints.py \
  apps/api/tests/test_auth_unit.py
176-    return response
177-
178-
179-@app.get("/auth/me", response_model=UserView)
180-def who_am_i(user: CurrentUser) -> UserView:
181-    return UserView(**user)
182-
183-
184:@app.get("/api/v1/admin/authorization/capabilities")
185-def platform_admin_capabilities(
186-    request: Request,
187-    _authorized: Annotated[dict[str, Any],
Depends(require_permission("platform.admin"))],
188-) -> dict[str, Any]:
189-    """Return the authenticated caller's database-backed platform capabilities."""
190-
191-    supplied_request_id = request.headers.get("request_id", "").strip()
192-    if supplied_request_id and (
193-        len(supplied_request_id) > 128
194-        or any(ord(char) < 32 or ord(char) == 127 for char in supplied_request_id)
195-    ):
196-        raise HTTPException(status_code=400, detail="Invalid request_id")
197-
198-    # Always issue a server-generated canonical request ID.
199-    request_id = f"req_{secrets.token_urlsafe(12)}"
apps/api/tests/test_identity_constraints.py-64-            tokens.append(token)
apps/api/tests/test_identity_constraints.py-65-            cur.execute(
apps/api/tests/test_identity_constraints.py-66-                "INSERT INTO auth_sessions
(user_id, refresh_token_hash, expires_at) VALUES (%s, %s, %s)",
apps/api/tests/test_identity_constraints.py-67-                (owner_id, digest,
session_expiry(5)),
```