FINSIGHT AI

Enhanced Jira Product Backlog

72 source user stories • testable acceptance criteria • dependencies • role-based assignees • implementation subtasks

Backlog baseline	Decision
Scope	Exactly the 72 FS-* story entries from the supplied Jira backlog; its delivery/day plan is intentionally ignored.
Source hierarchy	SRS for requirements; schema/ERD for canonical entities and relationships; technical design for module boundaries, testing, security and release controls.
Architecture	Next.js/React; modular FastAPI; PostgreSQL + pgvector; Ollama/provider adapters; background workers and observability.
Release boundary	Release 1 is read-only financial research. FS-07-04 and FS-08-04 are Release 2 only; no trading schema or order endpoints in Release 1.
Assignee policy	Role-based proposed assignees are used because individual team member names were not supplied. Assign a named engineer in Jira after team capacity review.
Estimation	Original story-point estimates retained where extractable as planning hints; re-estimate collaboratively during XP planning.
Definition of Done	All AC pass; automated tests pass; code reviewed; security and data isolation checked; evidence/PR linked; docs and SRS traceability updated.

How to use this backlog

- Create/import one Jira Story for each FS-* alias. Jira will generate its own issue key; retain FS-* as an external reference/label.
- Use Epic Link E1–E11, source requirement references in the Description, and the proposed assignee role as the initial owner.
- Create the listed implementation subtasks beneath each story. Subtasks are delivery decomposition, not additional user stories and do not change the 72-story scope.
- Dependencies are blocking relationships to validate with the team. Avoid circular dependencies; where a dependency is a shared foundation, track the prerequisite as a story link.
- Priorities P0/P1/P2 and Future are preserved from the source backlog where extractable. P0 = critical foundation/blocker; P1 = high; P2 = normal/later; Future = Release 2 only.
- Do not mark a grouped story Done when only one part of its acceptance criteria is complete. Use subtasks and evidence to show partial progress.

Epic index

E1: E1 — Identity, Authentication & Security — primary role: Backend / Security Engineer; pairing/review: Frontend Engineer.

E2: E2 — Dashboard, Market Views & Watchlists — primary role: Frontend / Analytics Engineer; pairing/review: Backend Engineer.

E3: E3 — AI Financial Analyst & Conversations — primary role: AI / Backend Engineer; pairing/review: Frontend Engineer.

E4: E4 — Research Library, Documents & RAG — primary role: AI / Data Engineer; pairing/review: Backend Engineer.

E5: E5 — Market Data Ingestion, Quality & Explorer — primary role: Data / Backend Engineer; pairing/review: QA Engineer.

E6: E6 — Screening, Strategies, Signals & Workflow — primary role: Backend / Quant Engineer; pairing/review: Frontend Engineer.

E7: E7 — Execution Monitoring, Backtesting & Future Trading — primary role: Backend / Quant Engineer; pairing/review: QA / SRE Engineer.

E8: E8 — Models, Providers, RAG & Settings — primary role: Backend / Platform Engineer; pairing/review: DevOps / Security Engineer.

E9: E9 — Account, Workspace, Saved Research & Reporting — primary role: Full-stack Engineer; pairing/review: Backend Engineer.

E10: E10 — Quantitative Finance, Valuation & Portfolio Analytics — primary role: Quant / Backend Engineer; pairing/review: Data Engineer.

E11: E11 — Engineering Quality, CI/CD, SCM & Evidence — primary role: DevOps / QA Engineer; pairing/review: All engineers.

Story-level backlog

FS-01-01 — Authenticate and manage sessions

Epic	E1 — Identity, Authentication & Security	Priority	P0	Estimate	3 SP
Proposed assignee	Backend / Security Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Authenticate and manage sessions. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.

Acceptance criteria (testable):

1. Valid credentials create a session; logout invalidates it; invalid credentials reveal no account existence; onboarding follows admin policy.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: None; foundational story. Confirm external provider/configuration assumptions before implementation.

Implementation subtasks:

1. Define acceptance examples and API/data contracts; add failing tests
2. Implement domain service and persistence using canonical schema/PK/FK constraints
3. Implement UI/API integration with ownership and authorization checks
4. Add security/negative tests and update runbook/traceability

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-01-02 — Enforce roles and protected routes

Epic	E1 — Identity, Authentication & Security	Priority	P0	Estimate	3 SP

Proposed assignee	Backend / Security Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Enforce roles and protected routes. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.

Acceptance criteria (testable):

1. Unauthenticated requests are rejected; role/permission matrix is tested server-side; inactive sessions expire per configuration.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define acceptance examples and API/data contracts; add failing tests
2. Implement domain service and persistence using canonical schema/PK/FK constraints
3. Implement UI/API integration with ownership and authorization checks
4. Add security/negative tests and update runbook/traceability

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-01-03 — Protect accounts and audit authentication

Epic	E1 — Identity, Authentication & Security	Priority	P1	Estimate	3 SP
Proposed assignee	Backend / Security Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Protect accounts and audit authentication. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Security events are auditable; repeated failures are throttled; MFA/session features are enabled only when configured.

Acceptance criteria (testable):

1. Security events are auditable; repeated failures are throttled; MFA/session features are enabled only when configured.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define acceptance examples and API/data contracts; add failing tests
2. Implement domain service and persistence using canonical schema/PK/FK constraints
3. Implement UI/API integration with ownership and authorization checks
4. Add security/negative tests and update runbook/traceability

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-01-04 — Separate read-only and trading permissions

Epic	E1 — Identity, Authentication & Security	Priority	P0	Estimate	3 SP
Proposed assignee	Backend / Security Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Separate read-only and trading permissions. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.

Acceptance criteria (testable):

1. Users cannot use another user's credentials; Release 1 has no order-execution path; sensitive actions require policy checks.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define acceptance examples and API/data contracts; add failing tests
2. Implement domain service and persistence using canonical schema/PK/FK constraints
3. Implement UI/API integration with ownership and authorization checks
4. Add security/negative tests and update runbook/traceability

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-01-05 — Meet identity security and accessibility

Epic	E1 — Identity, Authentication & Security	Priority	P0	Estimate	3 SP
Proposed assignee	Backend / Security Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Meet identity security and accessibility. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested.

Acceptance criteria (testable):

1. No plaintext passwords; deployed auth uses HTTPS; session controls are secure; keyboard, labels, focus and understandable errors are tested.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define acceptance examples and API/data contracts; add failing tests
2. Implement domain service and persistence using canonical schema/PK/FK constraints
3. Implement UI/API integration with ownership and authorization checks
4. Add security/negative tests and update runbook/traceability

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-01 — Show dashboard health and activity

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Show dashboard health and activity. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Dashboard scopes data to the user/workspace; shows service health and job status; refresh failures and empty states are explicit.

Acceptance criteria (testable):

1. Dashboard scopes data to the user/workspace; shows service health and job status; refresh failures and empty states are explicit.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-02 — Show market overview, sessions, movers and

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Show market overview, sessions, movers and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Values show source/as-of/freshness; exchange session follows configured calendar; unavailable classifications are not fabricated.

Acceptance criteria (testable):

1. Values show source/as-of/freshness; exchange session follows configured calendar; unavailable classifications are not fabricated.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset

2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-03 — Explore interactive historical price charts

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Explore interactive historical price charts. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Supported intervals match provider coverage; indicator values are reproducible; zoom/pan and timestamp inspection work.

Acceptance criteria (testable):

1. Supported intervals match provider coverage; indicator values are reproducible; zoom/pan and timestamp inspection work.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-04 — Compare instruments and fundamentals

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Compare instruments and fundamentals. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Comparison uses matching date windows; fundamentals show period/source where available; missing data is marked.

Acceptance criteria (testable):

1. Comparison uses matching date windows; fundamentals show period/source where available; missing data is marked.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-05 — Manage watchlists

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage watchlists. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Create/rename/reorder/delete and add/remove work; watchlist data is owner-scoped and includes freshness metadata.

Acceptance criteria (testable):

1. Create/rename/reorder/delete and add/remove work; watchlist data is owner-scoped and includes freshness metadata.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-06 — View portfolio performance, allocation and risk

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: View portfolio performance, allocation and risk. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Metrics use matching snapshots/date ranges; risk measures state assumptions; absent portfolio inputs produce a clear empty state.

Acceptance criteria (testable):

1. Metrics use matching snapshots/date ranges; risk measures state assumptions; absent portfolio inputs produce a clear empty state.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.

3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-07 — View news, events, alerts and custom

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P2	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: View news, events, alerts and custom. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: News shows timestamp/source; filters apply consistently; layout persists and respects permissions.

Acceptance criteria (testable):

1. News shows timestamp/source; filters apply consistently; layout persists and respects permissions.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-02-08 — Keep dashboard responsive, isolated and

Epic	E2 — Dashboard, Market Views & Watchlists	Priority	P1	Estimate	3 SP
Proposed assignee	Frontend / Analytics Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Keep dashboard responsive, isolated and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.

Acceptance criteria (testable):

1. Primary content meets agreed performance target; layouts work on supported screens; only authorized records are shown; freshness states are explicit.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-01

Implementation subtasks:

1. Define typed analytics/query contract and fixture dataset
2. Implement data aggregation/query with source, as-of and freshness metadata
3. Build responsive dashboard/chart interaction and loading/error/empty states
4. Test data isolation, date boundaries, degraded provider behavior and performance

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-01 — Create and manage AI conversations

Epic	E3 — AI Financial Analyst & Conversations	Priority	P1	Estimate	3 SP
Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Create and manage ai conversations. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Conversation ownership is enforced; model selection only offers configured models; delete/archive behavior is confirmed.

Acceptance criteria (testable):

1. Conversation ownership is enforced; model selection only offers configured models; delete/archive behavior is confirmed.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace
3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-02 — Stream, stop and regenerate answers

Epic	E3 — AI Financial Analyst & Conversations	Priority	P1	Estimate	3 SP
Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Stream, stop and regenerate answers. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Partial output is ordered; stop cancels generation where supported; retries do not duplicate persisted user messages.

Acceptance criteria (testable):

1. Partial output is ordered; stop cancels generation where supported; retries do not duplicate persisted user messages.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace
3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-03 — Answer with authorized retrieval and precise

Epic	E3 — AI Financial Analyst & Conversations	Priority	P0	Estimate	3 SP
Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Answer with authorized retrieval and precise. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Only authorized chunks enter context; citations resolve to source/page/section metadata where available; no evidence is presented as a citation if absent.

Acceptance criteria (testable):

1. Only authorized chunks enter context; citations resolve to source/page/section metadata where available; no evidence is presented as a citation if absent.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace
3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-04 — Answer financial questions using deterministic

Epic	E3 — AI Financial Analyst & Conversations	Priority	P1	Estimate	3 SP

Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Answer financial questions using deterministic. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Numeric outputs come from backend services; formulas/assumptions and as-of timestamps are shown; unsupported calculations are declined or marked unavailable.

Acceptance criteria (testable):

1. Numeric outputs come from backend services; formulas/assumptions and as-of timestamps are shown; unsupported calculations are declined or marked unavailable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace
3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-05 — Create natural-language screening requests

Epic	E3 — AI Financial Analyst & Conversations	Priority	P2	Estimate	3 SP
Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Create natural-language screening requests. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Parsed rules are displayed for confirmation; unsupported fields are rejected; result set is reproducible against a data snapshot.

Acceptance criteria (testable):

1. Parsed rules are displayed for confirmation; unsupported fields are rejected; result set is reproducible against a data snapshot.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace
3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-06 — Search, export, save and invoke approved

Epic	E3 — AI Financial Analyst & Conversations	Priority	P1	Estimate	3 SP
Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Search, export, save and invoke approved. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Conversation isolation is enforced; export/save includes provenance; tool calls are allowlisted; analysis never silently submits a trade.

Acceptance criteria (testable):

1. Conversation isolation is enforced; export/save includes provenance; tool calls are allowlisted; analysis never silently submits a trade.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace
3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-03-07 — Make AI behavior safe, traceable and

Epic	E3 — AI Financial Analyst & Conversations	Priority	P0	Estimate	3 SP
Proposed assignee	AI / Backend Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Make ai behavior safe, traceable and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Failures do not corrupt history; retrieved content is untrusted; sensitive prompts/secrets are not leaked; status and model limitations are visible.

Acceptance criteria (testable):

1. Failures do not corrupt history; retrieved content is untrusted; sensitive prompts/secrets are not leaked; status and model limitations are visible.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-01

Implementation subtasks:

1. Define conversation/tool/retrieval contract and deterministic fixtures
2. Implement orchestration/service flow with authorization and persisted trace

3. Integrate UI streaming/citations/status and safe failure handling
4. Test no-evidence, unauthorized context, retry/cancel and prompt-injection cases

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-04-01 — Upload, validate and extract documents

Epic	E4 — Research Library, Documents & RAG	Priority	P0	Estimate	3 SP
Proposed assignee	AI / Data Engineer	Reviewer / pair	Backend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Upload, validate and extract documents. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Type/size/content validation runs; parser errors are visible; extracted text retains document/version metadata.

Acceptance criteria (testable):

1. Type/size/content validation runs; parser errors are visible; extracted text retains document/version metadata.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Implement upload/document lifecycle and schema metadata contract
2. Implement parser/chunker/embedding/index pipeline with idempotent job state
3. Integrate search/preview/re-index/delete flow with permission filters
4. Test malformed/duplicate files, vector reconciliation and source-coordinate citations

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-04-02 — Chunk, embed, index and track processing

Epic	E4 — Research Library, Documents & RAG	Priority	P0	Estimate	3 SP
Proposed assignee	AI / Data Engineer	Reviewer / pair	Backend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Chunk, embed, index and track processing. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Chunks retain source/page/section; model/dimension metadata is stored; indexing is idempotent and incompatible vectors fail clearly.

Acceptance criteria (testable):

1. Chunks retain source/page/section; model/dimension metadata is stored; indexing is idempotent and incompatible vectors fail clearly.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-02

Implementation subtasks:

1. Implement upload/document lifecycle and schema metadata contract
2. Implement parser/chunker/embedding/index pipeline with idempotent job state
3. Integrate search/preview/re-index/delete flow with permission filters
4. Test malformed/duplicate files, vector reconciliation and source-coordinate citations

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-04-03 — Search, preview, filter and manage research

Epic	E4 — Research Library, Documents & RAG	Priority	P1	Estimate	3 SP
Proposed assignee	AI / Data Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Search, preview, filter and manage research. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Results are permission-filtered; metadata filters work; deleted/superseded chunks are not retrievable; evidence links point to source.

Acceptance criteria (testable):

1. Results are permission-filtered; metadata filters work; deleted/superseded chunks are not retrievable; evidence links point to source.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-02

Implementation subtasks:

1. Implement upload/document lifecycle and schema metadata contract
2. Implement parser/chunker/embedding/index pipeline with idempotent job state
3. Integrate search/preview/re-index/delete flow with permission filters
4. Test malformed/duplicate files, vector reconciliation and source-coordinate citations

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-04-04 — Handle duplicates and recover processing

Epic	E4 — Research Library, Documents & RAG	Priority	P0	Estimate	3 SP
Proposed assignee	AI / Data Engineer	Reviewer / pair	Backend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Handle duplicates and recover processing. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Duplicate files/versions are detected by configured identity/hash; retry is safe; partial failures are traceable and recoverable.

Acceptance criteria (testable):

1. Duplicate files/versions are detected by configured identity/hash; retry is safe; partial failures are traceable and recoverable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-02

Implementation subtasks:

1. Implement upload/document lifecycle and schema metadata contract
2. Implement parser/chunker/embedding/index pipeline with idempotent job state
3. Integrate search/preview/re-index/delete flow with permission filters
4. Test malformed/duplicate files, vector reconciliation and source-coordinate citations

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-04-05 — Enrich financial metadata and track document

Epic	E4 — Research Library, Documents & RAG	Priority	P2	Estimate	3 SP
Proposed assignee	AI / Data Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Enrich financial metadata and track document. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Provider/publication metadata is retained; supported tables are extracted; versions/collections preserve access grants and lineage.

Acceptance criteria (testable):

1. Provider/publication metadata is retained; supported tables are extracted; versions/collections preserve access grants and lineage.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-02

Implementation subtasks:

1. Implement upload/document lifecycle and schema metadata contract
2. Implement parser/chunker/embedding/index pipeline with idempotent job state
3. Integrate search/preview/re-index/delete flow with permission filters
4. Test malformed/duplicate files, vector reconciliation and source-coordinate citations

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-04-06 — Protect file processing, index consistency and

Epic	E4 — Research Library, Documents & RAG	Priority	P0	Estimate	3 SP
Proposed assignee	AI / Data Engineer	Reviewer / pair	Backend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Protect file processing, index consistency and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Prohibited files are rejected; metadata and vectors reconcile; long jobs are isolated; delete/reindex lifecycle is documented; unauthorized titles/content are not discoverable.

Acceptance criteria (testable):

1. Prohibited files are rejected; metadata and vectors reconcile; long jobs are isolated; delete/reindex lifecycle is documented; unauthorized titles/content are not discoverable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.

4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-02

Implementation subtasks:

1. Implement upload/document lifecycle and schema metadata contract
2. Implement parser/chunker/embedding/index pipeline with idempotent job state
3. Integrate search/preview/re-index/delete flow with permission filters
4. Test malformed/duplicate files, vector reconciliation and source-coordinate citations

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-05-01 — Register and configure data sources securely

Epic	E5 — Market Data Ingestion, Quality & Explorer	Priority	P1	Estimate	3 SP
Proposed assignee	Data / Backend Engineer	Reviewer / pair	QA Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Register and configure data sources securely. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Connection tests show safe diagnostics; secrets are not returned; allowlists and ownership are enforced; minimum privileges are used.

Acceptance criteria (testable):

1. Connection tests show safe diagnostics; secrets are not returned; allowlists and ownership are enforced; minimum privileges are used.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define provider adapter and canonical instrument/time/currency mapping
2. Implement ingestion/query service, snapshots, quality checks and lineage
3. Expose safe API/UI with bounded queries and explicit freshness/error states
4. Test duplicates, gaps, provider failures, query limits and snapshot reproducibility

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-05-02 — Query structured datasets safely

Epic	E5 — Market Data Ingestion, Quality & Explorer	Priority	P2	Estimate	3 SP
Proposed assignee	Data / Backend Engineer	Reviewer / pair	QA Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Query structured datasets safely. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Only permitted read operations run; queries have timeout/row limits; invalid queries are rejected; results are paginated and export permissions enforced.

Acceptance criteria (testable):

1. Only permitted read operations run; queries have timeout/row limits; invalid queries are rejected; results are paginated and export permissions enforced.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-03

Implementation subtasks:

1. Define provider adapter and canonical instrument/time/currency mapping
2. Implement ingestion/query service, snapshots, quality checks and lineage
3. Expose safe API/UI with bounded queries and explicit freshness/error states
4. Test duplicates, gaps, provider failures, query limits and snapshot reproducibility

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-05-03 — Ingest market prices, instruments,

Epic	E5 — Market Data Ingestion, Quality & Explorer	Priority	P0	Estimate	3 SP
Proposed assignee	Data / Backend Engineer	Reviewer / pair	QA Engineer	Release	Release 1 foundation/core

Goal / user outcome: Ingest market prices, instruments,. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Provider adapter normalizes instruments/time/currency; records identify source and snapshot; supported data types are explicit; no false real-time claim.

Acceptance criteria (testable):

1. Provider adapter normalizes instruments/time/currency; records identify source and snapshot; supported data types are explicit; no false real-time claim.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-03

Implementation subtasks:

1. Define provider adapter and canonical instrument/time/currency mapping
2. Implement ingestion/query service, snapshots, quality checks and lineage
3. Expose safe API/UI with bounded queries and explicit freshness/error states
4. Test duplicates, gaps, provider failures, query limits and snapshot reproducibility

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-05-04 — Import, preview, clean, transform and combine

Epic	E5 — Market Data Ingestion, Quality & Explorer	Priority	P2	Estimate	3 SP
Proposed assignee	Data / Backend Engineer	Reviewer / pair	QA Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Import, preview, clean, transform and combine. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Operations are explicit and validated; original input remains traceable; compatible joins are checked; saved queries/datasets are access-controlled.

Acceptance criteria (testable):

1. Operations are explicit and validated; original input remains traceable; compatible joins are checked; saved queries/datasets are access-controlled.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-03

Implementation subtasks:

1. Define provider adapter and canonical instrument/time/currency mapping
2. Implement ingestion/query service, snapshots, quality checks and lineage
3. Expose safe API/UI with bounded queries and explicit freshness/error states
4. Test duplicates, gaps, provider failures, query limits and snapshot reproducibility

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-05-05 — Backfill and refresh data with quality and

Epic	E5 — Market Data Ingestion, Quality & Explorer	Priority	P0	Estimate	3 SP
Proposed assignee	Data / Backend Engineer	Reviewer / pair	QA Engineer	Release	Release 1 foundation/core

Goal / user outcome: Backfill and refresh data with quality and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Runs are idempotent; missing/duplicate/outlier outcomes are reported; adjustment policy and source/as-of metadata are stored; snapshot IDs trace inputs.

Acceptance criteria (testable):

1. Runs are idempotent; missing/duplicate/outlier outcomes are reported; adjustment policy and source/as-of metadata are stored; snapshot IDs trace inputs.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-03

Implementation subtasks:

1. Define provider adapter and canonical instrument/time/currency mapping
2. Implement ingestion/query service, snapshots, quality checks and lineage
3. Expose safe API/UI with bounded queries and explicit freshness/error states
4. Test duplicates, gaps, provider failures, query limits and snapshot reproducibility

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-05-06 — Enforce least privilege, query safety and

Epic	E5 — Market Data Ingestion, Quality & Explorer	Priority	P0	Estimate	3 SP
Proposed assignee	Data / Backend Engineer	Reviewer / pair	QA Engineer	Release	Release 1 foundation/core

Goal / user outcome: Enforce least privilege, query safety and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Source credentials use minimum permissions; failed source does not take down unrelated features; sensitive query/model data follows policy; changes are auditable.

Acceptance criteria (testable):

1. Source credentials use minimum permissions; failed source does not take down unrelated features; sensitive query/model data follows policy; changes are auditable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-08-03

Implementation subtasks:

1. Define provider adapter and canonical instrument/time/currency mapping
2. Implement ingestion/query service, snapshots, quality checks and lineage
3. Expose safe API/UI with bounded queries and explicit freshness/error states
4. Test duplicates, gaps, provider failures, query limits and snapshot reproducibility

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-06-01 — Create, configure, validate, test and version

Epic	E6 — Screening, Strategies, Signals & Workflow	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Create, configure, validate, test and version. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Invalid workflows cannot run; version is immutable once used by a run; ownership and source selection are checked.

Acceptance criteria (testable):

1. Invalid workflows cannot run; version is immutable once used by a run; ownership and source selection are checked.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-03

Implementation subtasks:

1. Define versioned workflow/strategy/rule contract and state transitions
2. Implement validation, scheduler/worker and allowlisted execution service

3. Build strategy/workflow editor, approvals, signal history or status view
4. Test permissions, deterministic replay, retries, timeouts and no unintended side effects

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-06-02 — Run, schedule and monitor workflows with

Epic	E6 — Screening, Strategies, Signals & Workflow	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Run, schedule and monitor workflows with. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Each run has stable ID/status; bounded retries/timeouts; approval-required actions wait for approval; failures are visible and retryable.

Acceptance criteria (testable):

1. Each run has stable ID/status; bounded retries/timeouts; approval-required actions wait for approval; failures are visible and retryable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-03

Implementation subtasks:

1. Define versioned workflow/strategy/rule contract and state transitions
2. Implement validation, scheduler/worker and allowlisted execution service
3. Build strategy/workflow editor, approvals, signal history or status view
4. Test permissions, deterministic replay, retries, timeouts and no unintended side effects

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-06-03 — Build and save stock screens

Epic	E6 — Screening, Strategies, Signals & Workflow	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Build and save stock screens. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Filters validate against available fields; results use a data snapshot; saved screens can be edited, cloned and rerun.

Acceptance criteria (testable):

1. Filters validate against available fields; results use a data snapshot; saved screens can be edited, cloned and rerun.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-03

Implementation subtasks:

1. Define versioned workflow/strategy/rule contract and state transitions
2. Implement validation, scheduler/worker and allowlisted execution service
3. Build strategy/workflow editor, approvals, signal history or status view
4. Test permissions, deterministic replay, retries, timeouts and no unintended side effects

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-06-04 — Define versioned strategies, variants and

Epic	E6 — Screening, Strategies, Signals & Workflow	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Define versioned strategies, variants and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Version and parameters are saved; unsupported rules fail validation; readiness reports missing data and risk assumptions; variants are comparable.

Acceptance criteria (testable):

1. Version and parameters are saved; unsupported rules fail validation; readiness reports missing data and risk assumptions; variants are comparable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-03

Implementation subtasks:

1. Define versioned workflow/strategy/rule contract and state transitions
2. Implement validation, scheduler/worker and allowlisted execution service
3. Build strategy/workflow editor, approvals, signal history or status view
4. Test permissions, deterministic replay, retries, timeouts and no unintended side effects

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-06-05 — Generate explainable signals and alerts safely

Epic	E6 — Screening, Strategies, Signals & Workflow	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Generate explainable signals and alerts safely. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Each signal stores rule/input/time provenance; alerts honor preferences; signals cannot execute orders; scan failures are recorded.

Acceptance criteria (testable):

1. Each signal stores rule/input/time provenance; alerts honor preferences; signals cannot execute orders; scan failures are recorded.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.

4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-03

Implementation subtasks:

1. Define versioned workflow/strategy/rule contract and state transitions
2. Implement validation, scheduler/worker and allowlisted execution service
3. Build strategy/workflow editor, approvals, signal history or status view
4. Test permissions, deterministic replay, retries, timeouts and no unintended side effects

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-06-06 — Make workflow execution secure, bounded and

Epic	E6 — Screening, Strategies, Signals & Workflow	Priority	P1	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	Frontend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Make workflow execution secure, bounded and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Only allowlisted tools execute; run records retain workflow version and inputs; approval gates are enforced; retries do not duplicate side effects.

Acceptance criteria (testable):

1. Only allowlisted tools execute; run records retain workflow version and inputs; approval gates are enforced; retries do not duplicate side effects.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-05-03

Implementation subtasks:

1. Define versioned workflow/strategy/rule contract and state transitions
2. Implement validation, scheduler/worker and allowlisted execution service
3. Build strategy/workflow editor, approvals, signal history or status view
4. Test permissions, deterministic replay, retries, timeouts and no unintended side effects

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-07-01 — Inspect execution history and troubleshoot

Epic	E7 — Execution Monitoring, Backtesting & Future Trading	Priority	P1	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	QA / SRE Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Inspect execution history and troubleshoot. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Every run has a stable ID; status changes persist; retry/cancel rules are explicit; logs redact secrets; access is scoped.

Acceptance criteria (testable):

1. Every run has a stable ID; status changes persist; retry/cancel rules are explicit; logs redact secrets; access is scoped.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define run/backtest contract, status model and reproducible input snapshot
2. Implement worker/calculation flow with run IDs, cost/assumption metadata and logs
3. Expose run details, metrics, exports and failure diagnostics
4. Test retries/cancellation, numeric fixtures, look-ahead boundaries and release gating

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-07-02 — Configure backtests and calculate performance

Epic	E7 — Execution Monitoring, Backtesting & Future Trading	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	QA / SRE Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Configure backtests and calculate performance. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Backtest references strategy version and data snapshot; costs/assumptions are stored; metrics are reproducible.

Acceptance criteria (testable):

1. Backtest references strategy version and data snapshot; costs/assumptions are stored; metrics are reproducible.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-07-01

Implementation subtasks:

1. Define run/backtest contract, status model and reproducible input snapshot
2. Implement worker/calculation flow with run IDs, cost/assumption metadata and logs
3. Expose run details, metrics, exports and failure diagnostics
4. Test retries/cancellation, numeric fixtures, look-ahead boundaries and release gating

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-07-03 — Analyze, compare, validate and export

Epic	E7 — Execution Monitoring, Backtesting & Future Trading	Priority	P2	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	QA / SRE Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Analyze, compare, validate and export. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Look-ahead/survivorship issues are checked where supported; out-of-sample boundaries are explicit; saved runs retain parameters and data lineage.

Acceptance criteria (testable):

1. Look-ahead/survivorship issues are checked where supported; out-of-sample boundaries are explicit; saved runs retain parameters and data lineage.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02, FS-07-01

Implementation subtasks:

1. Define run/backtest contract, status model and reproducible input snapshot
2. Implement worker/calculation flow with run IDs, cost/assumption metadata and logs
3. Expose run details, metrics, exports and failure diagnostics
4. Test retries/cancellation, numeric fixtures, look-ahead boundaries and release gating

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-07-04 — Implement paper trading and broker execution

Epic	E7 — Execution Monitoring, Backtesting & Future Trading	Priority	Future	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	QA / SRE Engineer	Release	Release 2 only — do not implement or deploy in R1

Goal / user outcome: Implement paper trading and broker execution. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Trading schema is not applied in R1; any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation.

Acceptance criteria (testable):

1. Trading schema is not applied in R1; any future live order requires explicit confirmation, permissions, pre-trade checks and reconciliation.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: Release 2 approval; excluded from Release 1

Implementation subtasks:

1. Define run/backtest contract, status model and reproducible input snapshot
2. Implement worker/calculation flow with run IDs, cost/assumption metadata and logs
3. Expose run details, metrics, exports and failure diagnostics
4. Test retries/cancellation, numeric fixtures, look-ahead boundaries and release gating

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-07-05 — Secure execution logs and retain reliable run

Epic	E7 — Execution Monitoring, Backtesting & Future Trading	Priority	P1	Estimate	3 SP
Proposed assignee	Backend / Quant Engineer	Reviewer / pair	QA / SRE Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Secure execution logs and retain reliable run. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Run IDs link logs/steps; status freshness is measurable; transient UI failure cannot delete records; retention and pagination are configured.

Acceptance criteria (testable):

1. Run IDs link logs/steps; status freshness is measurable; transient UI failure cannot delete records; retention and pagination are configured.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define run/backtest contract, status model and reproducible input snapshot
2. Implement worker/calculation flow with run IDs, cost/assumption metadata and logs
3. Expose run details, metrics, exports and failure diagnostics
4. Test retries/cancellation, numeric fixtures, look-ahead boundaries and release gating

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-08-01 — Configure Ollama, model selection and

Epic	E8 — Models, Providers, RAG & Settings	Priority	P1	Estimate	3 SP
Proposed assignee	Backend / Platform Engineer	Reviewer / pair	DevOps / Security Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Configure ollama, model selection and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable.

Acceptance criteria (testable):

1. Invalid settings fail before activation; unavailable model yields a controlled state; model and parameters are traceable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define typed configuration schema, validation rules and secret references
2. Implement provider/model/settings adapter with safe test-connection and activation flow
3. Add configuration UI, audit event and compatibility checks

4. Test invalid config, unavailable provider, secret redaction, rollback and disabled trading defaults

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-08-02 — Configure embeddings, chunking and retrieval

Epic	E8 — Models, Providers, RAG & Settings	Priority	P0	Estimate	3 SP
Proposed assignee	Backend / Platform Engineer	Reviewer / pair	DevOps / Security Engineer	Release	Release 1 foundation/core

Goal / user outcome: Configure embeddings, chunking and retrieval. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Embedding model/dimension/index version match; metadata filters are tested; changes require re-index where needed; sample RAG test results are recorded.

Acceptance criteria (testable):

1. Embedding model/dimension/index version match; metadata filters are tested; changes require re-index where needed; sample RAG test results are recorded.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-08-01

Implementation subtasks:

1. Define typed configuration schema, validation rules and secret references
2. Implement provider/model/settings adapter with safe test-connection and activation flow
3. Add configuration UI, audit event and compatibility checks
4. Test invalid config, unavailable provider, secret redaction, rollback and disabled trading defaults

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-08-03 — Manage market providers, data coverage and

Epic	E8 — Models, Providers, RAG & Settings	Priority	P1	Estimate	3 SP
Proposed assignee	Backend / Platform Engineer	Reviewer / pair	DevOps / Security Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage market providers, data coverage and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Provider coverage and entitlements are visible; settings validate before activation; changes record actor/time; assumptions are versioned.

Acceptance criteria (testable):

1. Provider coverage and entitlements are visible; settings validate before activation; changes record actor/time; assumptions are versioned.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-08-01

Implementation subtasks:

1. Define typed configuration schema, validation rules and secret references
2. Implement provider/model/settings adapter with safe test-connection and activation flow
3. Add configuration UI, audit event and compatibility checks
4. Test invalid config, unavailable provider, secret redaction, rollback and disabled trading defaults

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-08-04 — Keep broker modes and trading safety controls

Epic	E8 — Models, Providers, RAG & Settings	Priority	Future	Estimate	3 SP
Proposed assignee	Backend / Platform Engineer	Reviewer / pair	DevOps / Security Engineer	Release	Release 2 only — do not implement or deploy in R1

Goal / user outcome: Keep broker modes and trading safety controls. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: R1 exposes no live execution; future mode changes require authorization and step-up confirmation; controls default to disabled.

Acceptance criteria (testable):

1. R1 exposes no live execution; future mode changes require authorization and step-up confirmation; controls default to disabled.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: Release 2 approval; excluded from Release 1

Implementation subtasks:

1. Define typed configuration schema, validation rules and secret references
2. Implement provider/model/settings adapter with safe test-connection and activation flow
3. Add configuration UI, audit event and compatibility checks
4. Test invalid config, unavailable provider, secret redaction, rollback and disabled trading defaults

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-08-05 — Secure and validate configuration changes

Epic	E8 — Models, Providers, RAG & Settings	Priority	P0	Estimate	3 SP
Proposed assignee	Backend / Platform Engineer	Reviewer / pair	DevOps / Security Engineer	Release	Release 1 foundation/core

Goal / user outcome: Secure and validate configuration changes. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Secrets are referenced securely; config changes are audited; validation precedes activation; retrieval/index compatibility is checked.

Acceptance criteria (testable):

1. Secrets are referenced securely; config changes are audited; validation precedes activation; retrieval/index compatibility is checked.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define typed configuration schema, validation rules and secret references
2. Implement provider/model/settings adapter with safe test-connection and activation flow
3. Add configuration UI, audit event and compatibility checks
4. Test invalid config, unavailable provider, secret redaction, rollback and disabled trading defaults

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-09-01 — Manage profile, security, interface and

Epic	E9 — Account, Workspace, Saved Research & Reporting	Priority	P2	Estimate	3 SP
Proposed assignee	Full-stack Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage profile, security, interface and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: Preferences persist across sessions; private fields are isolated; notification choices are honored. SP Acceptance criteria

Acceptance criteria (testable):

1. Preferences persist across sessions; private fields are isolated; notification choices are honored. SP Acceptance criteria
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define owner/workspace permission and saved-asset/report contract
2. Implement CRUD, sharing/export/deletion service and audit/lineage metadata
3. Build account/workspace/saved research/report UI states
4. Test cross-user access, permission revocation, export content and retention behavior

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-09-02 — Manage workspaces, members, roles and

Epic	E9 — Account, Workspace, Saved Research & Reporting	Priority	P1	Estimate	3 SP
Proposed assignee	Full-stack Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage workspaces, members, roles and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass.

Acceptance criteria (testable):

1. 3 Only authorized owners manage membership; shared items follow explicit grants; cross-workspace negative tests pass.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.

3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define owner/workspace permission and saved-asset/report contract
2. Implement CRUD, sharing/export/deletion service and audit/lineage metadata
3. Build account/workspace/saved research/report UI states
4. Test cross-user access, permission revocation, export content and retention behavior

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-09-03 — Manage API credentials, privacy, export,

Epic	E9 — Account, Workspace, Saved Research & Reporting	Priority	P1	Estimate	3 SP
Proposed assignee	Full-stack Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage api credentials, privacy, export,. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Secrets are never redisplayed; destructive actions require confirmation; export/deletion follow documented retention rules; audit records are scoped.

Acceptance criteria (testable):

1. 3 Secrets are never redisplayed; destructive actions require confirmation; export/deletion follow documented retention rules; audit records are scoped.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define owner/workspace permission and saved-asset/report contract
2. Implement CRUD, sharing/export/deletion service and audit/lineage metadata
3. Build account/workspace/saved research/report UI states
4. Test cross-user access, permission revocation, export content and retention behavior

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-09-04 — Save dashboards, watchlists, screens,

Epic	E9 — Account, Workspace, Saved Research & Reporting	Priority	P1	Estimate	3 SP
Proposed assignee	Full-stack Engineer	Reviewer / pair	Backend Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Save dashboards, watchlists, screens,. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Saved items retain owner/workspace, timestamps and relevant source/snapshot lineage; edits respect access grants.

Acceptance criteria (testable):

1. 3 Saved items retain owner/workspace, timestamps and relevant source/snapshot lineage; edits respect access grants.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define owner/workspace permission and saved-asset/report contract
2. Implement CRUD, sharing/export/deletion service and audit/lineage metadata
3. Build account/workspace/saved research/report UI states
4. Test cross-user access, permission revocation, export content and retention behavior

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-09-05 — Enforce privacy and safe account

Epic	E9 — Account, Workspace, Saved Research & Reporting	Priority	P0	Estimate	3 SP
Proposed assignee	Full-stack Engineer	Reviewer / pair	Backend Engineer	Release	Release 1 foundation/core

Goal / user outcome: Enforce privacy and safe account. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy.

Acceptance criteria (testable):

1. 3 Cross-user read/write attempts fail; privilege changes are auditable; data lifecycle follows retention policy.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-02

Implementation subtasks:

1. Define owner/workspace permission and saved-asset/report contract
2. Implement CRUD, sharing/export/deletion service and audit/lineage metadata
3. Build account/workspace/saved research/report UI states
4. Test cross-user access, permission revocation, export content and retention behavior

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-01 — Calculate DCF valuation with versioned

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P2	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Calculate dcf valuation with versioned. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 5 Run stores company, data snapshot, model version, assumptions, forecasts and outputs; sensitivity results link to the run; missing inputs are surfaced.

Acceptance criteria (testable):

1. 5 Run stores company, data snapshot, model version, assumptions, forecasts and outputs; sensitivity results link to the run; missing inputs are surfaced.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema
2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-02 — sk Calculate portfolio VaR/CVaR and drawdown

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P2	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Sk calculate portfolio var/cvar and drawdown. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 5 Risk run stores input snapshot, configuration, lookback, frequency, seed/method and limitations; test cases validate calculations.

Acceptance criteria (testable):

1. 5 Risk run stores input snapshot, configuration, lookback, frequency, seed/method and limitations; test cases validate calculations.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema
2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-03 — sk Run Monte Carlo and stress scenarios

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P2	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Sk run monte carlo and stress scenarios. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 5 Scenario parameters are versioned; outputs link to risk run and assumptions; invalid/incomplete data is flagged.

Acceptance criteria (testable):

1. 5 Scenario parameters are versioned; outputs link to risk run and assumptions; invalid/incomplete data is flagged.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema
2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-04 — Manage portfolios, transactions and snapshots

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P1	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage portfolios, transactions and snapshots. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 5 Transactions recalculate positions consistently; snapshots retain as-of and data snapshot; edits are auditable.

Acceptance criteria (testable):

1. 5 Transactions recalculate positions consistently; snapshots retain as-of and data snapshot; edits are auditable.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema
2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-05 — ma Calculate returns, attribution and allocation

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P2	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Ma calculate returns, attribution and allocation. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 5 Method and period are explicit; holdings reconcile to snapshot totals; results can be regenerated from saved inputs.

Acceptance criteria (testable):

1. 5 Method and period are explicit; holdings reconcile to snapshot totals; results can be regenerated from saved inputs.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema
2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-06 — Generate source-backed PDF/CSV reports

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P1	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Generate source-backed pdf/csv reports. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Report retains as-of timestamp, source citations and data snapshot; export status is tracked; access grants apply to generated files.

Acceptance criteria (testable):

1. 3 Report retains as-of timestamp, source citations and data snapshot; export status is tracked; access grants apply to generated files.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema

2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-10-07 — Share, reopen and version saved research

Epic	E10 — Quantitative Finance, Valuation & Portfolio Analytics	Priority	P2	Estimate	3 SP
Proposed assignee	Quant / Backend Engineer	Reviewer / pair	Data Engineer	Release	Release 1/later increment per source catalog

Goal / user outcome: Share, reopen and version saved research. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Owner/workspace permissions are enforced; duplicate/reopen behavior is defined; source and calculation lineage persists.

Acceptance criteria (testable):

1. 3 Owner/workspace permissions are enforced; duplicate/reopen behavior is defined; source and calculation lineage persists.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-05-03, FS-01-02

Implementation subtasks:

1. Define versioned financial formula, assumptions, snapshot and result schema
2. Implement deterministic calculator and reference test fixtures
3. Expose metrics, charts/report integration with provenance and limitations
4. Test numeric edge cases, reproducibility and missing-input handling

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-01 — Create reproducible repository and

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: Create reproducible repository and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 2 Clean clone starts with documented steps; .env.example has placeholders only; no secrets or generated junk are committed.

Acceptance criteria (testable):

1. 2 Clean clone starts with documented steps; .env.example has placeholders only; no secrets or generated junk are committed.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-02 — Run CI quality gates on every pull request

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: Run ci quality gates on every pull request. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 A deliberately failing test/check makes CI fail; default branch stays green; reports are retained.

Acceptance criteria (testable):

1. 3 A deliberately failing test/check makes CI fail; default branch stays green; reports are retained.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-03 — Build and deploy a versioned release artifact

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: Build and deploy a versioned release artifact. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Build artifact is tagged; configuration is environment-driven; deployment/rollback steps are documented and tested if hosting is available.

Acceptance criteria (testable):

1. 3 Build artifact is tagged; configuration is environment-driven; deployment/rollback steps are documented and tested if hosting is available.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.

3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-04 — Apply TDD and maintain unit/integration/E2E

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: Apply tdd and maintain unit/integration/e2e. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 5 Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably.

Acceptance criteria (testable):

1. 5 Critical validators, authorization filters, idempotency and API errors have automated tests; smoke path runs repeatably.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-05 — Measure line/branch coverage and test quality

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P1	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1/later increment per source catalog

Goal / user outcome: Measure line/branch coverage and test quality. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 2 Coverage report is generated; branch coverage is reported where tooling supports it; critical gaps have follow-up issues.

Acceptance criteria (testable):

1. 2 Coverage report is generated; branch coverage is reported where tooling supports it; critical gaps have follow-up issues.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-06 — Run security validation and dependency

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: Run security validation and dependency. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: 3 Auth, workspace isolation, file validation, prompt injection and secret-leak cases are tested; critical issues block release. cceptance criteria

Acceptance criteria (testable):

1. 3 Auth, workspace isolation, file validation, prompt injection and secret-leak cases are tested; critical issues block release. cceptance criteria
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-07 — Document architecture, APIs, ADRs and

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P1	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1/later increment per source catalog

Goal / user outcome: Document architecture, apis, adrs and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: rchitecture reflects implementation; PI examples and error codes exist; chema/API breaking changes have igration/version notes.

Acceptance criteria (testable):

1. rchitecture reflects implementation; PI examples and error codes exist; chema/API breaking changes have igration/version notes.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-08 — g Maintain SRS addendum and requirement

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: G maintain srs addendum and requirement. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: very MVP requirement maps to story nd test ID; deferred requirements ave release labels; changes trigger mpact analysis.

Acceptance criteria (testable):

1. very MVP requirement maps to story nd test ID; deferred requirements ave release labels; changes trigger mpact analysis.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-09 — Run planning, daily review, demo and

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P0	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1 foundation/core

Goal / user outcome: Run planning, daily review, demo and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: ach day has sprint goal, ccepted/rejected stories, demo vidence and one retro action; work in rogress is limited.

Acceptance criteria (testable):

1. ach day has sprint goal, ccepted/rejected stories, demo vidence and one retro action; work in rogress is limited.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-10 — Manage baselines, bugs, versions, SBOM and

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P1	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1/later increment per source catalog

Goal / user outcome: Manage baselines, bugs, versions, sbom and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: ersion baseline and changelog exist; ugs link to regression tests; SBOM is enerated if tooling/time permits or imitation recorded.

Acceptance criteria (testable):

1. ersion baseline and changelog exist; ugs link to regression tests; SBOM is enerated if tooling/time permits or imitation recorded.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-11 — en Document usability, AI use, licenses and data

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P1	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1/later increment per source catalog

Goal / user outcome: En document usability, ai use, licenses and data. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: I-generated code is reviewed and ested; license/data rights are ecorded; usability checks include ccessibility and understandable ailures.

Acceptance criteria (testable):

1. I-generated code is reviewed and ested; license/data rights are ecorded; usability checks include ccessibility and understandable ailures.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

FS-11-12 — Add health checks, structured logs, retry and

Epic	E11 — Engineering Quality, CI/CD, SCM & Evidence	Priority	P1	Estimate	3 SP
Proposed assignee	DevOps / QA Engineer	Reviewer / pair	All engineers	Release	Release 1/later increment per source catalog

Goal / user outcome: Add health checks, structured logs, retry and. The authenticated user or operator can complete this capability reliably, securely, and with traceable results.

Source acceptance baseline: ealth endpoints work; logs include un IDs and redact secrets; retries are ounded/idempotent; outage drill has ecorded outcome.

Acceptance criteria (testable):

1. ealth endpoints work; logs include un IDs and redact secrets; retries are ounded/idempotent; outage drill has ecorded outcome.
2. Given an authorized user and valid inputs, the expected result is persisted or returned with stable identifiers and the required source/version context.
3. Given invalid input or a dependency failure, the system returns a controlled error, preserves data integrity, and exposes a useful status without leaking secrets.
4. Automated unit/integration tests cover the primary success path, permission-denied path, boundary cases, and retry/idempotency behavior where applicable.
5. Changes pass code review, CI checks, and the relevant security/data-isolation checks; evidence is linked in Jira before Done.

Dependencies: FS-01-01

Implementation subtasks:

1. Define engineering policy, quality gate or evidence artifact and owner
2. Implement pipeline/tooling/documentation configuration in version control
3. Add automated verification and publish actionable failure output
4. Run clean-environment validation and document rollback/operational ownership

Jira fields: Component = domain matching epic; labels = xp, tdd, traceability plus security/performance/release-1 or release-2 as applicable. Link PR, tests, migration, screenshots/log evidence, and SRS references before Done.

Cross-cutting engineering and release gates

Data integrity

Use PostgreSQL as the structured source of truth. Preserve schema-defined PK/FK relationships, owner/workspace scope, provider/source metadata, data_snapshot_id, as-of timestamps, and immutable/versioned run inputs where relevant.

RAG and AI safety

Apply document/workspace authorization filters before retrieved content reaches the model. Treat retrieved content as untrusted. Persist citations and retrieval/model/tool traces; never fabricate a citation when evidence is absent.

Financial correctness

Calculations are implemented in deterministic backend services, not generated text. Store formula/version, assumptions, input snapshot, time range, source and limitations; test numeric outputs against fixed fixtures.

Jobs and resilience

Long-running ingestion, indexing, analytics and backtests use persisted run IDs and explicit state transitions. Retries are bounded and idempotent; logs are structured and redacted; transient UI failure does not erase run history.

Security

Enforce authentication and authorization on backend service/repository paths, not only in the UI. Use least-privilege DB roles, safe query allowlists, secret references, audit events, and negative cross-user/workspace tests.

CI/CD and XP

Every PR runs formatting/lint/type checks, unit and integration tests, dependency/security checks, frontend build and migration validation. Pair on auth, ingestion, RAG access filtering, schema changes and release pipeline. Prefer small vertical slices and refactoring.

Release 1 exclusion

FS-07-04 and FS-08-04 are future-only. Do not apply the optional 15-table trading schema, expose order endpoints, or enable broker execution in Release 1. Catalog presence is not authorization to ship.

Honest completion

Do not assume all 72 stories fit a short calendar window. Sprint assignment, team velocity and deployment readiness must be validated separately. Unfinished acceptance criteria remain open; record blockers and evidence honestly.

Traceability references

Prepared from the supplied FinSight AI Jira Backlog (72 story aliases), Software Requirements Specification, Database Schema & ERD Reference, and Technical Design & Implementation Plan. The original one-week/day-by-day plan has not been used to prioritize or sequence this backlog. Where source story acceptance text was available, it is retained as the baseline and supplemented with cross-cutting testability, authorization, error handling and delivery evidence criteria. Proposed assignee roles and implementation subtasks are engineering recommendations, not names or facts stated by the source documents.