

# Delegated Anonymous Credentials for IoT Service Chains

Sandeep Kiran Pinjala<sup>1,2</sup> and Krishna M. Sivalingam<sup>1</sup>

<sup>1</sup>*Dept. of Computer Science and Engineering, Indian Institute of Technology Madras, Chennai, India*

<sup>2</sup>*HCL Technologies, Chennai, India*

Email: sandeepkiranp@gmail.com, cs16s001@iitm.ac.in, skrishnam@iitm.ac.in,  
krishna.sivalingam@gmail.com

**Abstract**—The abstract goes here.

**Index Terms**—IEEE, IEEEtran, journal, L<sup>A</sup>T<sub>E</sub>X, paper, template.

## I. INTRODUCTION

Internet of Things (IoT) enables physical objects also called *Things* to communicate with each other and to their human operators. This opens up a myriad of use cases such as smart homes, smart factories, smart cities, smart healthcare etc. It is also expected that such connected devices could reach upto 50 billion by 2020 [1].

### A. Subsection Heading Here

Subsection text here. Hi there

1) *Subsubsection Heading Here*: Subsubsection text here.  
[1]

## II. CONCLUSION

The conclusion goes here.

## REFERENCES

- [1] D. Evans. The internet of things-how the next evolution of the internet is changing everything. April 2011. [http://www.cisco.com/web/about/ac79/docs/innov/IoT\\_IBSG\\_0411FINAL.pdf3](http://www.cisco.com/web/about/ac79/docs/innov/IoT_IBSG_0411FINAL.pdf3), last accessed on 01/01/20.