

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY — CONSERVATION DIVISION
USGS HISTORICAL NPRA WELL REPORT (CLEAN SCAN ARCHIVE)

WELL NAME	: Walakpa Test Well No. 2	REPORT DATE	: 1980-05-19
API NUMBER	: 50-089-20011	ELEVATION	: 45.0 FT KB
OPERATOR	: Husky Oil / USGS	TOTAL DEPTH	: 3660 FT (TVD 3660 FT)
LOCATION	: LAT 71.09889 N, LONG -156.91222 W	FORMATION	: Walakpa Sandstone

I. DRILLING CHRONOLOGY & FORMATION SUMMARY

The Walakpa Test Well No. 2 was spudded on 1980-03-02 and drilled to a total depth of 3660 feet. The well evaluated petroleum potential and reservoir continuity within the Walakpa Sandstone and underlying regional strata.

DRILLING LOG HIGHLIGHTS:

- Surface casing set at 1,450 ft with 650 sacks Class G cement to protect shallow permafrost/freshwater.
- Intermediate hole drilled with 9.8 ppg low-solids dispersed mud; stable hole conditions maintained.
- Target zone encountered from 2854 ft to 3660 ft with porous sand development.
- Core recovery averaged 94% across reservoir interval. Petrophysical analysis confirms good porosity.
- Electric logs (DIL-SFL, BHC-Sonic, FDC-CNL) and directional gyroscopic surveys recorded from TD to surface casing.

CASING AND COMPLETION RECORD:

String	Hole Size	Casing Size	Weight & Grade	Set Depth	Cement Sacks
Conductor	20.0 in	16.00 in	65# H-40	120 ft	150 sx neat
Surface	12.25 in	9.625 in	40# K-55	1,450 ft	650 sx Class G
Production/Liner	8.5 in	7.000 in	29# N-80	3660 ft	420 sx Posmix

CERTIFIED BY CHIEF GEOLOGIST:

J. R. Henderson, PE

Husky Oil NPR Operations / USGS Date: 1980-05-19

USGS ALASKA BRANCH

PUBLIC ARCHIVE — RELEASED

DEPT INTERIOR DOC # 50-089-20011