

main.c

main.c

Run ▶

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char p[10][10], c;
6     int n, i;
7
8     printf("Enter number of productions: ");
9     scanf("%d", &n);
10
11     printf("Enter productions (use # for epsilon):\n");
12
13     for (i = 0; i < n; i++)
14         scanf("%9s", p[i]);
15
16     printf("Enter the non-terminal: ");
17     scanf(" %c", &c);
18
19     printf("FIRST(%c) = { ", c);
20
21     for (i = 0; i < n; i++)
22     {
23         if (p[i][0] == c && p[i][1] == '=')
24             printf("%c ", p[i][2]);
25     }
26
27     printf("}\n");
```

Output

Enter number of productions:
3
E=a
E=b
E=#
E
Enter productions (use # for epsilon):
Enter the non-terminal: FIRST(E) = { a b # }

main.c

Run ▶

Output



```
4 {  
5     char p[10][10], c;  
6     int n, i;  
7  
8     printf("Enter number of productions: ");  
9     scanf("%d", &n);  
10  
11    printf("Enter productions (use # for epsilon):\n");  
12  
13    for (i = 0; i < n; i++)  
14        scanf("%9s", p[i]);  
15  
16    printf("Enter the non-terminal: ");  
17    scanf(" %c", &c);  
18  
19    printf("FIRST(%c) = { ", c);  
20  
21    for (i = 0; i < n; i++)  
22    {  
23        if (p[i][0] == c && p[i][1] == '=')  
24            printf("%c ", p[i][2]);  
25    }  
26  
27    printf("}\n");  
28  
29    return 0;  
30 }
```

Enter number of productions:

3

E=a

E=b

E=#

E

Enter productions (use # for epsilon):

Enter the non-terminal: FIRST(E) = { a b # }