

main.c

Run ▶

Output



```
1  #include <stdio.h>
2  #include <ctype.h>
3  #include <string.h>
4
5  int main()
6  {
7      char s[100];
8      int i, valid = 1;
9
10     printf("Enter an identifier: ");
11     scanf("%99s", s);
12
13     if (!isalpha(s[0]) && s[0] != '_')
14         valid = 0;
15
16     for (i = 1; s[i] != '\0'; i++)
17     {
18         if (!isalnum(s[i]) && s[i] != '_')
19         {
20             valid = 0;
21             break;
22         }
23     }
24
25     if (valid)
26         printf("Valid Identifier");
27     else
```

Enter an identifier: 2marks
Invalid Identifier

main.c

Run ▶

Output



```
5  int main()
6  {
7      char s[100];
8      int i, valid = 1;
9
10     printf("Enter an identifier: ");
11     scanf("%99s", s);
12
13     if (!isalpha(s[0]) && s[0] != '_')
14         valid = 0;
15
16     for (i = 1; s[i] != '\0'; i++)
17     {
18         if (!isalnum(s[i]) && s[i] != '_')
19         {
20             valid = 0;
21             break;
22         }
23     }
24
25     if (valid)
26         printf("Valid Identifier");
27     else
28         printf("Invalid Identifier");
29
30     return 0;
31 }
```

Enter an identifier: 2marks
Invalid Identifier