

StyleNova – Fashion Products E-Commerce Order Management System

1. Database Design

1.1 Payment Table

Attribute	Data Type	Constraint
Payment_ID	INT	Primary Key
Order_ID	INT	Foreign Key
Payment_Mode	VARCHAR2(20)	NOT NULL
Payment_Date	DATE	NOT NULL
Payment_Amount	NUMBER(10,2)	NOT NULL
Payment_Status	VARCHAR2(20)	NOT NULL

2. Table Relationships

The Payment table is related to the SN_Orders table through Order_ID. Each payment transaction is associated with a StyleNova customer order.

3. Table Creation

3.1 Create Payment Table

```
SQL> CREATE TABLE SN_Payment (  
2     Payment_ID INT PRIMARY KEY,  
3     Order_ID INT NOT NULL,  
4     Payment_Mode VARCHAR2(20) NOT NULL,  
5     Payment_Date DATE NOT NULL,  
6     Payment_Amount NUMBER(10,2) NOT NULL,  
7     Payment_Status VARCHAR2(20) NOT NULL,  
8     FOREIGN KEY (Order_ID) REFERENCES SN_Orders(Order_ID)  
9 );
```

Table created.

4. Payment Data Insertion

```
SQL> INSERT INTO SN_Payment VALUES (501, 1001, 'UPI', SYSDATE, 1898.00, 'Successful');
1 row created.

SQL> INSERT INTO SN_Payment VALUES (502, 1002, 'Card', SYSDATE, 1299.00, 'Successful');
1 row created.

SQL> INSERT INTO SN_Payment VALUES (503, 1003, 'Cash', SYSDATE, 1499.00, 'Failed');
1 row created.

SQL> COMMIT;
Commit complete.
```

5. Manage Payment Transactions

```
SQL> INSERT INTO SN_Payment VALUES (501, 1001, 'UPI', SYSDATE, 1898.00, 'Successful');
1 row created.

SQL> INSERT INTO SN_Payment VALUES (502, 1002, 'Card', SYSDATE, 1299.00, 'Successful');
1 row created.

SQL> INSERT INTO SN_Payment VALUES (503, 1003, 'Cash', SYSDATE, 1499.00, 'Failed');
1 row created.

SQL> COMMIT;
Commit complete.
```

5.1 Display Successful Payments

```
SQL> SELECT * FROM SN_Payment WHERE Payment_Status = 'Successful';
```

PAYMENT_ID	ORDER_ID	PAYMENT_MODE	PAYMENT_D	PAYMENT_AMOUNT
501	1001	UPI	30-SEP-26	1898
502	1002	Card	30-SEP-26	1299

5.2 Display Failed Payments

```
SQL> SELECT * FROM SN_Payment WHERE Payment_Status = 'Failed';
```

PAYMENT_ID	ORDER_ID	PAYMENT_MODE	PAYMENT_D	PAYMENT_AMOUNT
503	1003	Cash	30-SEP-26	1499

Failed

6. Modify Payment Status

```
SQL> UPDATE SN_Payment
  2  SET Payment_Status = 'Successful'
  3  WHERE Payment_ID = 503;
```

1 row updated.

```
SQL> COMMIT;
```

Commit complete.

7. Analyze Payment Methods

```
SQL> SELECT Payment_Mode, SUM(Payment_Amount) AS Total_Amount_Collected
  2  FROM SN_Payment
  3  WHERE Payment_Status = 'Successful'
  4  GROUP BY Payment_Mode
  5  ORDER BY Payment_Mode;
```

PAYMENT_MODE	TOTAL_AMOUNT_COLLECTED
Card	1299
Cash	1499
UPI	1898

8. Payment Transaction Report

```
SQL> SELECT p.Payment_ID, p.Order_ID, o.Customer_ID, p.Payment_Mode,  
2         p.Payment_Date, p.Payment_Amount, p.Payment_Status  
3 FROM SN_Payment p  
4 JOIN SN_Orders o ON p.Order_ID = o.Order_ID  
5 ORDER BY p.Payment_ID;
```

PAYMENT_ID	ORDER_ID	CUSTOMER_ID	PAYMENT_MODE	PAYMENT_D	PAYMENT_AMOUNT
501	1001	108	UPI	30-SEP-26	1898
502	1002	224	Card	30-SEP-26	1299
503	1003	567	Cash	30-SEP-26	1499