PRODUCT SPECIFICATION

Refined **Castor Oil — First Special Grade (FSG)**, BSS-75. Mill-direct, FOB Mundra.

PRODUCT	Refined castor oil, first special grade (FSG) / BSS-75
PACKING	200 kg HDPE drums on pallets · 16 MT net per 20-ft
PORT	FOB Mundra, India
MOQ	16 MT net · 1 × 20-ft
APPLICATIONS	Lubricants and greases · cosmetics · plastics · paints and resins · pharmaceuticals
STORAGE	Dry, ambient, away from direct sunlight; keep drums sealed
DOCUMENTS	Full mill COA with lot traceability released on request

PARAMETER	SPECIFICATION
Appearance	**Pale yellow, viscous, clear liquid**
Moisture	**0.25% max**
Free fatty acids (F.F.A.)	**1.00% max**
Acid value	**2.00% max**
Hydroxyl value	**160 – 168**
Iodine value	**82 – 90**
Saponification value	**175 – 187**
Insoluble impurities	**Nil**
Relative density @ 20 °C	**0.954 – 0.967**
Refractive index @ 20 °C	**1.4700 – 1.4810**
Unsaponifiable matter	**1.0 max**
Solubility in ethyl alcohol	**Complete, without turbidity**
Colour (1" cell, Lovibond)	**Y + 5R ≤ 2.2Y, 0.3R max**
Colour (5.25" cell, Lovibond)	**Y 20.0 max · R 2.0 max**

Specification values are the mill's declared limits for this grade. Every lot is released against a certificate of analysis; the signed original and the mill's name are shared with buyers on request.