Operating Systems



Module Introduction

- CCAT Exam
 - Section B Operating Systems: 5 Questions
 - Computer Fundamentals: 5 Questions
 - Networking: 5 Questions → Sechion A
- Quiz
 - Operating Systems: 4 Quizzes (10 marks)
 - Computer Fundamentals: 1 Quiz (10 marks)
 - Operating Systems: Module end quiz (20 marks)
- GitLab Repository
 - OS Galvin Slides
 - Practice MCQ
 - Notes/Diagrams
 - Reference Book: Operating System Concepts - Galvin.



Introduction

- Introduction to Operating System, What is OS, Booting the System

System Architecture Design of OS

- System Calls, Dual Mode Operation: System mode and Kernel mode

Process Management

- What is Process & PCB?
- States of the process
- CPU scheduling & CPU scheduling algorithms
- Inter Process Communication: Shared Memory Model & Message Passing Model
- Process Synchronization/Co-ordination
- Deadlocks & deadlock handling methods



* Memory Management

- Swapping
- Memory Allocation Methods
- Segmentation
- Paging
- Virtual Memory Management



File Management


- What is file?
- What is filesystem & filesystem structure?
- Disk space allocation methods
- Disk scheduling algorithms




Introduction:

- Why there is need of an OS?
- What is an OS?
- History of OS- Multi-threading, multiprocessing etc
- Functions of an OS
- What is Process?
- States of Process





appln. Software media Editor Browser player



4 CD/DVD Score 05 + appln prog + Utilines

(3) Kernel = Core OS.

CPU

RAM

HDD

Keybo ard

Monitor.

Hardware computer. Program. -> set of Inst" given computer system.

(executable tile).

Software -> Set of program.

Utility -> Prog. associated with OS.

Utility -> trog associated Development Environment.

IDE -> Integrated Development Environment.

Compiler C gcc.

pre-processor C+t.

Q. Why there is a need of an OS?

- Computer is a machine/hardware does different tasks efficiently & accurately.
- Basic functions of computer:
 - 1. Data Storage
 - 2. Data Processing
 - 3. Data Movement
 - 4. Control
- As any user cannot communicates/interacts directly with computer hardware to do different tasks, and hence there is need of some interface between user and hardware.



Q. What is an Operating System?

- An OS is a **system software** (i.e. collection of system programs) which acts as an interface between user and hardware.
- An OS also acts as an interface between programs and hardware.
- An OS allocates resources like main memory, CPU time, i/o devices access etc... to all running programs, hence it is also called as a resource allocator.
- An OS controls an execution of all programs and it also controls hardware devices which are connected to the computer system and hence it is also called as a control program.
- An OS manages limited available resources among all running programs, hence it is also called as a resource manager.



- From End User: An OS is a software (i.e. collection of programs) comes either in CD/DVD, has following main components:889IKM
- 1. Kernel: It is a core program/part of an OS which runs continuously into the main memory does basic minimal functionalities of it.
- e.g. Linux: vmlinuz, Windows: ntoskrnl.exe
- 2. Utility Softwares: e.g. disk manager, Control panel, windows firewall, anti-virus software etc...
- 3. Application Softwares: e.g. google chrome, shell, notepad, msoffice etc...



Q. What is a Software?

Software is a collection of programs.

Q. What is a Program?

- Program is a set of instructions written in any programming language (either low level or high level programming language) given to the machine to do specific task.
- Three types of programs are there:
- 1. "user programs": programs defined by the programmer user/developers e.g. main.c, hello.java, addition.cpp etc....
- 2. "application programs": programs which comes with an OS/can be installed later e.g. MS Office, Notepad, Compiler, IDE's, Google Chrome, Mozilla Firefox, Calculator, Games etc....
- 3. "System Programs": programs which are inbuilt in an OS/part of an OS. e.g. Kernel, Loader, Scheduler, Memory Manager etc...



Q. What is an IDE (Integrated Development Environment)?

- It is an application software i.e. collection of tools/programs like source code editor, pre-processor, compiler, linker, debugger etc... required for faster software development.
- e.g. VS code editor, MS Visual Studio, NetBeans, Android Studio, Turbo C etc....
- 1. "Editor": it is an application program used to write a source code.
- e.g. notepad, vi editor, gedit etc...
- 2. "Pre-processor": it is an application program gets executes before compilation and does two jobs it executes all pre-processor directives and removes all comments from the source code.
- e.g. cpp
- **3. "Compiler":** it is an application program which convert high level programming language code into low level programming language code i.e. human understandable language code into the machine understandable language code.
- e.g. gcc, tc, visual c etc...



- 4. "Assembler": it is an application program which converts assembly language code into machine language code/object code.
 - e.g. masm, tasm etc...
- Program written in any programming language is called as a "source code".
- **5. "Linker":** it is an application program which links object file/s in a program with precompiled object modules of library functions exists in a lib folder and creates final single executable file.
 - e.g. ld. link editor in Linux.



Functions of an OS:


Basic minimal functionalities/Kernel functionalities:

- 1. Process Management
 2. Memory Management
- 3. Hardware Abstraction
- A. CPU Scheduling
- 5. File & IO Management

Extra utility functionalities/optional:

- 6. Protection & Security
- 7. User Interfacing
- 8. Networking





int main()

{


o > succe srful,

any > unsuccentul,


value.

ehm 0;

Exit().








- 1. primary header/exe header: it contains information which is required to starts an execution of the program.
- e.g. addr of an entry point function --> main() function
- **magic number:** it is constant number generated by the compiler which is file format specific.
 - magic number in Linux starts with ELF in its eq hexadecimal format.
 - info about remaining sections.
- 2. bss(block started by symbol) section: it contains uninitialized global & static vars
- 3. data section: it contains initialized global & static vars
- 4. rodata (readonly data) section: it contains string literals and constants.
- 5. code/text section: it contains an executable instructions
- 6. symbol table: it contains info about functions and its vars in a tabular format.







Process

- Progam under execution.
- Process execute in RAM.
- Process control block contains information about the process (required for the execution of process).
 - Process id
 - Exit status
 - Scheduling information (State, Priority, Sched algorithm, Time, ...)
 - Memory information (Base & Limit, Segment table, or Page table)
 - File information (Open files, Current directory, ...)
 - IPC information (Signals, ...)
 - Execution context
 - Kernel stack
- PCB is also called as process descriptor (PD), uarea (UNIX), or task_struct (Linux).



Q. What is a Process?

User view:

- A program in execution is called a process.
- Running program is called a process.
- When a program gets loaded into the main memory it is referred to as a process.
- Running an instance of a program is referred to as a process.

System view:

- The process is a file loaded into the main memory which has got bss section, rodata section, code section, and two new sections added for the process:
- stack section: contains function activation records of called functions.
- heap section: dynamically allocated memory



- file format of an executable file in Windows is PE (Portable Executable), whereas file format of an executable file in Linux is ELF (Executable & Linkable Format).
- file format is a specific way to store data & instructions of a program inside an executable file, and it is different in diff OS.
- ELF file format divides an executable file logically into sections and inside each section specific contents can be kept in an organized manner:
- 1. elf header
- 2. bss section (block started by symbol)
- 3. data section
- 4. rodata (read only data)section
- 5. code/text section
- 6. symbol table



Memory Layout of Program and Process

Program Consist of

exe header/primary header

Block started by symbol (bss) section (un initialized static / global variables)

Data section (initialized static / global variables)

Rodata Section(Constant/literals)

code/text section (contains executable instructions)

Symbol Table

Process Consist of

Skipped

Block started by symbol (bss) section (un initialized static / global variables)

Data section (initialized static / global variables)

Rodata Section(Constant/literals)

code/text section (contains executable
instructions)

Skipped

Stack Section

Heap Section



Interaction with an OS: Two Types of Interface (CUI and GUI)

1. CUI/CLI: Command User Interface/Command Line Interface

- By using this kind of interface user can interact with an OS by means of entering commands onto the terminal/command line in a text format.

e.g. In Windows name of the program which provides CUI => cmd.exe command prompt

In Linux name of an application program which provides CUI => shell/terminal

In MSDOS name of the program which provides CUI => command.com (Microsoft Disk Operating System).

2. GUI: Graphical User Interface

- by using this kind of interface user can interact with an OS by means of making an event like click on buttons, left click/right click/double click, menu bar, menu list etc.....
- Windows = User-friendly GUI.
- e.g. In Windows name of an application program which provides GUI => explorer.exe
- In Linux name of an application program which provides GUI => GNOME/KDE (GNU Network Object Model Environment / Common Desktop Environment).



Old Computers - Maintrame computers. OS history/Evolution RAM (1) Resident Monitor , 2) Batch System. 3) Multi - Programming CPU schedular 4 multiple prog load RAM. 4 better utilization of CPU. CPU Control 4 mixed prog. Panel 4) time Sharing /multi-tasking

Sharing cpu time among multiple

tasks present in mem of ready HDD/Disk. For execution. Response < Isec multi-tasking process Based thread Based Punch card Machine

Process Based.			Thread Based.
Process. Stack. heap Data text	Process Stack · heap Data · text	Process Stack , heap Data , text	 Stack this weight process. Stack main thread heap Data text
PCB.	PCB,	PCB,	PCB. TCB1 - Hiread control Block, TCB2

History of Operating System

1. Resident monitor

2. Batch System

- The batch/group of similar programs is loaded in the computer, from which OS loads one program in the memory and execute it. The programs are executed one after another.
- In this case, if any process is performing IO, CPU will wait for that process and hence not utilized efficiently.

3. Multi-programming

- Better utilization of CPU
- Loading multiple Programs in memory
- Mixed program(CPU bound + IO bound)

4. Time-sharing/Multitasking

- Sharing CPU time among multiple process/task present in main memory and ready for execution
- Any process should have response time should be less then 1sec
- Multi-tasking is divided into two types
 - Process based multitasking
 - Thread based multitasking

Thread is a light weight process

- When new thread is created a new stack and new TCB is created.
- Thread Share text, data, heap sections with the parent process



- Process and thread
 - Process is a container for resources.
 - > Thread is unit of execution/schedular.
 - > For each process one thread is created by default it is called as main thread

5. Multi-user system

Multiple users runs multiple programs concurrently.

6. Multi-processor/Mutli-core system

System can run on a machine in which more than one CPU's are connected in a closed circuit.

Multiprocessing Advantage is it increased throughput (amount of work done in unit time)

- There are two types of multiprocessor systems:
- Asymmetric Multi-processing Symmetric Multi-processing

Asymmetric Multi-processing

- OS treats one of the processor as master processor and schedule task for it. The task is in turn divided into smaller tasks and get them done from other processors.

Symmetric Multi-processing

-OS considers all processors at same level and schedule tasks on each processor individually. All modern desktop systems are SMP.

