ARG Report

root

November 25, 2021

This document was generated on 2021-11-25, 16:50:46 with the Automatic Report Generator (ARG) version "develop" on the Linux system `runner-zxwgkjap-project-18732201-concurrent-0`.

Contents

List of Figures

List of Tables

Chapter 1

Hello, world! Chapter!

1.1 Hello, world! Section!

1.1.1 Hello, world! Subsection!

1.1.1.1 Hello, world! Subsubsection!

Just a string: [Hello hyperlink!](Chapter 1)(Chapter 1)

Just another string: [ARG's documentation](Chapter 2)(Chapter 2)

[ARG's documentation but no string before](Chapter 2)(Chapter 2)

Variable Name: Drag coefficient
Description: Projectile drag coefficient
Type: aleatory
Characterization: interval
Parameters: u_Drag
Model Feature: yes
Feasible Physical Range: 0.2 +/-5
Variable Name: Drag coefficient
Description: Projectile drag coefficient
Type: aleatory
Characterization: interval
Parameters: u_Drag
Model Feature: yes
Feasible Physical Range: 0.2 +/-5

1.1.2 HTML Subsection!

Heading

Heading 2

Heading 3

Heading 4

Heading 5

Heading 6

The text can be <u>underlined,</u>**bold**, *italic*, ~~striked~~, with a <mark>background color</mark> , with a font color.

It can be justified.

<div align="center">The text can be centered.</div>

<div align="right">Or right-aligned.</div>

The indentation can be part of the content.

It can contain lists:

- First element

- Second one

- Third

The list can be ordered:

1. My first number

2. The second one

3. The third

It can contain special CHARACTERS like french words "étymologie", 'règle', "façonner" or expressions "à l'envers", "où regarder ?".

Subscript: _{The subscript content}

1.1.3   HTML 2 Subsection!

Intended purpose header

The purpose of this model is to describe the CF features and capabilities.

Heading 1

Heading 2

Heading 3

Heading 4

Heading 5

Heading 6

The text can be <u>underlined,</u>**bold**, *italic*, ~~striked~~, with a <mark>background color</mark>, with a font color.

It can be justified.

<div align="center">The text can be centered.</div>

<div align="right">Or right-aligned.</div>

The indentation can be part of the content.

It can contain lists:

- First element

- Second one

- Third

The list can be ordered:

1. My first number

2. The second one

3. The third

It can contain special CHARACTERS like french words "étymologie", 'règle', "façonner" or expressions "à l'envers", "où regarder ?".

Subscript: _{The subscript content}

1.1.4 HTML 3 Subsection!

G_Yield heading 1

The server configuration is described in the report <mark style="background-color:darkred">above</mark>.

1.1.5 HTML 4 Subsection!

Intended purpose header

The purpose of this model is to describe the CF features and <mark style="background-color:darkred">capabilities</mark>.