SampleData.... ×

```
prompt,completion
Codio sign: I am so sad, -
Codio sign: I am so happy, +
Codio sign: I am in love, +
Codio sign: happiness, +
Codio sign: cryiing, -
Codio sign: Borderlands 2 is so good omg, +
Codio sign: YOOOOOOOOOO i'm actually so hyped for this movie, +
Codio sign: I hate this algorithm, -
Codio sign: I am crying,  -
Codio sign: I am  happy, +
Codio sign: I am in love, +
Codio sign: happiness, +
Codio sign: franklin , -
Codio sign: am I happy?, ?
Codio sign:love, +
Codio sign: estatic, +
Codio sign: I love these new @ GhostLifestyle cans!! Everyone else drinks ghost?...., +
Codio sign: Meet one of the lovely gambling goddesses., +
```

84% (41:26)

Terminal ×

```
codio@cricketsilence-methodanita:~/workspace$
```

Guide ×

Collapse

Preparing training

Now that we have installed the necessary tools in the back end we can start training our data. Training data is how you teach GPT-3 what you'd like it to say.

GPT-3 expects your fine-tune dataset to be in a specific JSONL file format:

```
{"prompt": "<prompt text>", "completion": "<ideal generated text>"}
{"prompt": "<prompt text>", "completion": "<ideal generated text>"}
{"prompt": "<prompt text>", "completion": "<ideal generated text>"}
```

The tool accepts different formats, with the only requirement that they contain a prompt and a completion column/key. Then simply run it through the OpenAI command-line tool to validate it.
You can pass a CSV, TSV, XLSX, JSON or JSONL file, and it will save the output into a JSONL file ready for fine-tuning. JSON Lines(.jsonl) is like JSON, but each line is a valid JSON object. This means that each line is a separate, independent data entry, which can be read, parsed, and processed independently of the others. It will bring up suggesting changes as you proceed.

A sample data, `SampleData.csv`, has been provided for this exercise. It has about 50 examples. When going about it on your own please note it usually recommends a few hundred examples. The sample data is a csv which we can see on the top left. Run the following code, replace `<LOCAL_FILE>` with `SampleData.csv`.

```
openai tools fine_tunes.prepare_data -f <LOCAL_FILE>
```

When you are done, we can run the following line of code on your terminal so we can peek at our newly generated JSONL file.

```
head -5 SampleData_prepared_valid.jsonl
```

The following assumes you have already prepared training data.The training file goes in the `< >` and the second one is for the BASE_MODEL that is the name of the base model you're starting from (ada, babbage, curie, or davinci).

Train a new fine-tuned model, replace train file `<TRAIN_FILE_ID_OR_PATH>` with `SampleData_prepared.jsonl` and `<BASE_MODEL>` with `curie`:

```
openai api fine_tunes.create -t <TRAIN_FILE_ID_OR_PATH> -m <BASE_MODEL>
```

This often takes a few minutes but can take longer depending on the data and the model.

Running the above command does several things:

1. Uploads the file using the files API
2. Creates a fine-tune job
3. Streams events until the job is done

If by any chance, the work is interrupted, you can run the following command to get it back on track.
`openai api fine_tunes.follow -i <YOUR_FINE_TUNE_JOB_ID>`
The command you need can be copied from the terminal if the stream is interrupted.

When your command is done running you should see the following message.

Please make sure you copy the model name in the response. In our case should be `curie: ft`
Hint: after the line saying `Try out your fine-tuned model`: the command you need can be copied in the terminal

To train GPT-3, what is the expected format of the fine-tune dataset that you provide, and what columns or keys must each row in the dataset contain?

The expected format of the fine-tune dataset is a JSONL file, and each row in the dataset must contain a “prompt” column/key and a completion column/key.

The expected format of the fine-tune dataset is a JSONL file, and each row in the dataset must contain a “prompt” column/key and a “completion” column/key.

Check It!

Next