

≡ Hide menu

Untitled Lesson

Week 15 Quiz

🕒 Quiz: Week 15 Quiz 30 min

Module 3 Test

Course Conclusion

🎉 Congratulations! You passed!

Grade received 90% Latest Submission Week 15 Quiz To pass 50% or higher Go to next item

📄 Submit your assignment To minimise shadowing in SAR imagery we should use (choose one): 1 / 1 point Try again

Due: Sep 29, 11:59 PM IST Attempts: 3 every 2 hours

- ☐ short wavelengths
- ☒ small look angles
- ☐ large look angles

📄 Receive grade

To Pass: 50% or higher

Your grade

90%

View Feedback

We keep your highest score

👍 Correct That is correct.

👍 Like 🗑 Dislike 📄 Report an issue

2. To minimise terrain relief distortion, including layover, in SAR imagery we should use (choose one): 0 / 1 point

- ☐ short wavelengths
- ☒ small look angles
- ☐ large look angles

👎 Incorrect That is incorrect. Small look angles will exaggerate relief distortion

3. Compressional distortion of SAR imagery in the near range (choose one): 1 / 1 point

- ☒ is not a problem for slant range imagery
- ☐ is not a problem for ground range imagery
- ☐ is a problem for both slant and ground range imagery.

👍 Correct That is correct.

4. radar interferometry involves (choose one): 1 / 1 point

- ☐ measuring the actual the phase angle of the transmitted signal at the point of reflection from the ground
- ☒ comparing (by subtraction) the phase angles between the scattered waves resulting from two different radar transmitters
- ☐ reducing speckle

👍 Correct That is correct.

5. Phase flattening is important in radar interferometry (choose one): 1 / 1 point

- ☐ to remove phase variations due to topographic height variations
- ☐ to ensure phase difference is expressed in radians
- ☒ to remove phase variations due to position across the swath

👍 Correct That is correct.

6. DInSAR (choose one): 1 / 1 point

- ☒ is a mechanism in which the effect of phase changes due to fixed topography can be compensated for when looking for phase changes resulting from changes in topography with time
- ☐ requires the use of several different polarisations
- ☐ cannot be used through clouds

👍 Correct That is correct.

7. Radar tomography is a technique that (choose one): 1 / 1 point

- ☐ Maps topographic change
- ☒ allows vertical structure to be detected
- ☐ allows imaging inside structures such as buildings

👍 Correct That is correct.

8. Spotlight mode SAR (choose one): 1 / 1 point

- ☐ uses a strong transmitter with which to irradiate the earth's surface
- ☐ uses several different radar platforms to irradiate the earth's surface
- ☒ allows higher spatial resolution in a smaller region of interest.

👍 Correct That is correct.

9. Use of optical and radar imagery of the same geographical region together is desirable because (choose one): 1 / 1 point

- ☒ we can often identify the class labels of pixels, unable to be found using either image type on its own
- ☐ one can fill in gaps in the spatial coverage of the other platform
- ☐ in fact, there is little benefit in using the two together

👍 Correct That is correct

10. Active radar calibrators can be used (choose the most appropriate): 1 / 1 point

- ☐ To provide artificial control points in radar imagery
- ☐ To provide a means for radiometrically calibrating radar imagery
- ☒ to provide artificial control points and a means for radiometrically calibrating radar imagery

👍 Correct That is correct.