Hide menu

Week 3: Uncalibrated Stereo

Ungraded Plugin: 3.1 Overview of Uncalibrated Stereo 6 min
Ungraded Plugin: 3.2 Problem of Uncalibrated Stereo 6 min
Practice Assignment: 3.2 Problem of Uncalibrated Stereo Self-Check Quiz Submitted
Ungraded Plugin: 3.3 Epipolar Geometry 15 min
Practice Assignment: 3.3 Epipolar Geometry Self-Check Quiz 3h
Ungraded Plugin: 3.4 Stereo Vision in Nature 14 min
Practice Assignment: 3.4 Stereo Vision in Nature Self-Check Quiz 3h
Reading: 3.5 Video Correction 10 min
Ungraded Plugin: 3.5 Estimating Fundamental Matrix 6 min
Practice Assignment: 3.5 Estimating Fundamental Matrix Self-Check Quiz 3h
Ungraded Plugin: 3.6 Finding Correspondences 7 min
Practice Assignment: 3.6 Finding Correspondences Self-Check Quiz 3h
Reading: 3.7 Video Correction 10 min
Ungraded Plugin: 3.7 Computing Depth 10 min
Practice Assignment: 3.7 Computing Depth Self-Check Quiz 3h
Discussion Prompt: Week 3 Simple Binocular Stereo System 10 min
Discussion Prompt: Week 3 Questions and Feedback

Week 3 Quiz

Your grade: 100%

Next item

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

3.2 Problem of Uncalibrated Stereo Self-Check Quiz

1. What is the minimum number of correspondence points required for the calibration process? **1 / 1 point**

- 4
- 6
- 8 (selected)
- 12

coach

Ready to review what you've learned before starting the assignment? I'm here to help.

Help me practice | Let's chat

Correct
At least 8 correspondence points are required for the calibration process.

Assignment details

Submitted	Attempts	Try again
Nov 13, 10:47 PM IST	Unlimited	

2. For the point **(x,y)** in the left image, which of the following pairs are the correct corresponding points in the right image? **1 / 1 point**

v submission | See feedback

- (1, 6)
- (3, 7)
- (2, 5)
- (1,7) (selected)

Correct

3. Which of the following methods can be used to select correspondence points in the uncalibrated stereo problem? **1 / 1 point**

- SIFT
- Hand-picking
- All of the above (selected)
- None of the above

Correct
Both SIFT and handpicking can be employed to select correspondence points in an uncalibrated stereo vision problem, depending on the specific requirements and constraints of the task.