

Your grade: **100%**

Your latest: **100%** • Your highest: **100%** • To pass you need at least 50%. We keep your highest score.

Next item →

1. Which of the following are steps required to split a dataset into training and testing sets in Python?

1 / 1 point

☒ Use the train_test_split function from Scikit-Learn



Correct

Correct! The train_test_split function from Scikit-Learn is commonly used for this purpose.

☒ Shuffle the dataset values



Correct

Correct! Shuffling ensures that the data is randomly distributed before splitting.

☒ Load the dataset into a DataFrame



Correct

Correct! Loading the dataset into a DataFrame is one of the initial steps.

☐ Visualize the dataset using Matplotlib

☐ Normalize the dataset values

2. Which of the following best describes the architecture of a fully connected GAN generator?

1 / 1 point

☐ It consists solely of convolutional layers

☐ It consists of multiple output layers and a single hidden layer

☐ It has only an input layer and an output layer

☒ It consists of an input layer, several hidden layers, and an output layer



Correct

Correct! A fully connected GAN generator typically has an input layer, multiple hidden layers, and an output layer.

3. Which of the following steps are involved in defining a function to create a fully connected layer generator using Python and Keras?

1 / 1 point

☐ Setting up callbacks for model checkpoints

☐ Adding dropout layers to prevent overfitting

☒ Importing necessary libraries



Correct

Correct! You need to import libraries such as TensorFlow and Keras.

☒ Defining the input shape



Correct

Correct! Defining the input shape is crucial for creating the generator.

☒ Compiling the model with an optimizer



Correct

Correct! Compiling the model with an optimizer is necessary for training.

4. What elements are part of the structure of a discriminator in a fully connected GAN?

1 / 1 point

☒ Hidden layers with neurons



Correct

Correct! Hidden layers with neurons are crucial for processing the input data.

☐ LSTM layers for sequence processing

☐ Batch normalization layers

☒ Input layer to receive the image



Correct

Correct! The input layer is essential to receive the image data.

☒ Output layer with a single neuron



Correct

Correct! The output layer typically has a single neuron to classify the input as real or fake.

5. Which activation function is commonly used in the discriminator model of a GAN to introduce non-linearity?

1 / 1 point

☐ softmax

☐ tanh

☐ ReLU

☒ sigmoid



Correct

Correct! The sigmoid activation function is commonly used in the discriminator model to introduce non-linearity.