


Unable to import execute function from qiskit library

Asked 9 months ago · Modified 5 months ago · Viewed 16k times



when I try to run this code, it gives me an error that it was unable to import `execute` from `qiskit` (error pasted below).

```
2 get_ipython().system('pip install --upgrade qiskit qiskit-aer')
3 import qiskit
----> 4 from qiskit import QuantumCircuit, execute
      5 from qiskit_aer import Aer
      6 from qiskit.visualization import plot_histogram

ImportError: cannot import name 'execute' from 'qiskit' (/usr/local/lib/python3.10/dist-packages/qiskit/.../init_.py)
```

I have tried upgrading `qiskit` which didn't work. I have also tried using `transpile` and the other functions but it changed my code too much and I didn't want that to happen.

quantum-computing qiskit Edit tags

Share Edit Follow Close Flag Protect

edited Feb 20 at 14:24
Milor Stojanovic
547 1 9 18

asked Feb 20 at 13:56
WakeTheNoob
69 1 1 5

1 Please see [Why should I not upload images of code/data/errors?](#) and how to create a [minimal reproducible example](#) – desermaut Feb 28 at 4:21

5 Answers

Sorted by Date modified (newest first)

Import section
from qiskit_aer import AerSimulator

For execution
simulator = AerSimulator()
compiled_circuit = transpile(qc, simulator)
sim_result = simulator.run(compiled_circuit).result()
counts = sim_result.get_counts()

No need to downgrade to the older version. Use the above code for newer version of qiskit. They don't use Qasm_simulator anymore.

Share Edit Follow Flag

edited Jul 7 at 8:28
Indov
20.7k 34 53 160

answered Jul 4 at 12:04
tooba qasim
43 3

Add in # Import section: from qiskit import transpile – Cyclical Obsessive Jul 30 at 2:43

You can use `transpile` in newer version. Refer: [qiskit v1.0 migration guide](#)

Share Edit Follow Flag

answered Mar 9 at 5:52
Raghav
139 4

One of the great things about qiskit is also one of the challenges, in that it updates quite quickly. The `execute` function has been deprecated since version 0.46.0 ([see notice here](#)) and it was removed in the 1.0 release.

If you need to use an older version, such as following along a tutorial or quickstart, you can rollback to earlier releases and use the syntax for that release. For example: <https://qiskit.org/docs/0.24/execute>

from qiskit import QuantumCircuit, execute, BasicAer

backend = BasicAer.get_backend('qasm_simulator')

qc = QuantumCircuit(5, 0)
qc.h(0)
qc.cx(0, range(1, 5))
qc.measure_all()

job = execute(qc, backend, shots=4321)

Share Edit Follow Flag

edited Feb 20 at 21:27

answered Feb 20 at 21:17
davidryan
2,315 23 36

2 The issue was due to qiskit 1.0 removing `execute` from its library and I had to downgrade to version 0.46 version. I appreciate your input! – WakeTheNoob Feb 20 at 21:31

4 The note about being able to roll back to follow along with tutorials is important given how many of the existing guides for Qiskit have broken as a result of this change – Tara Feb 22 at 2:52

The `execute` function in qiskit library is been removed from version 1.00 you can downgrade to version 0.46 and it will Run

Share Edit Follow Flag

answered Feb 20 at 21:13
H baghry
84 1

is not good idea because when you have higher version is raising the error – Marek Gziesiak Jun 11 at 10:24

This post is hidden. It was deleted 8 months ago by [Stanislav Machavsky](#).

Are simulator backends available on transpile?

Share Edit Follow **Delete** Flag

answered Apr 11 at 10:09
Arindam A Ganguly
1 1

Comments disabled on deleted / locked posts / reviews