

Method: images.annotate

Run image detection and annotation for a batch of images.

HTTP request

POST https://vision.googleapis.com/v1/images:annotate

The URL uses gRPC Transcoding (https://google.aip.dev/127) syntax.

Request body

The request body contains data with the following structure:

JSON representation

```
{
  "requests": [
    {
      object (AnnotateImageRequest) (/vision/docs/reference/rest/v1/AnnotateImageRequest)
    }
  ],
  "parent": string
}
```

Fields

requests[]	object (AnnotateImageRequest) (/vision/docs/reference/rest/v1/AnnotateImageRequest) Required. Individual image annotation requests for this batch.
parent	string Optional. Target project and location to make a call. Format: projects/{project-id}/locations/{location-id}. If no parent is specified, a region will be chosen automatically. Supported location-ids: us: USA country only, eu: The European Union. Example: projects/project-A/locations/eu.

Response body

If successful, the response body contains an instance of BatchAnnotateImagesResponse (/vision/docs/reference/rest/v1/BatchAnnotateImagesResponse).

Authorization Scopes

Requires one of the following OAuth scopes:

- https://www.googleapis.com/auth/cloud-platform
- https://www.googleapis.com/auth/cloud-vision

For more information, see the Authentication Overview (https://cloud.google.com/docs/authentication/).

Try this method

Call this method on live data and see the result.
Experiment with authorization and field settings.
For help, check the APis Explorer documentation.

Request parameters

No method-level parameters

Show standard parameters

Request body

```
{
  Add request body parameters
}
```

For suggestions, press control+space or click one of the blue "add" circles.

Credentials

☒ Google OAuth 2.0

OAuth 2.0 provides authenticated access to an API.

Show scopes

☒ API key

An API key is a unique string that lets you access an API.

Execute

By clicking above, I agree that my use of the APis Explorer is governed by the Terms and Privacy Policy.