Your grade: 100%

Your latest: **100%** • Your highest: **100%** • To pass you need at least 75%. We keep your highest score.

Next item →

1. Which of the following can be used to open a file “MOOC.csv” in read-mode only? 1 / 1 point

- (•) my_file = open('MOOC.csv', 'r')
- ( ) my_file = open('MOOC.csv', 'r+')
- ( ) my_file = open(my_file = 'MOOC.csv', 'r')
- ( ) my_file = open(my_file = 'MOOC.csv', 'r+')

Nice work

my_file = open('MOOC.csv', 'r') can be used to open a file “MOOC.csv” in read-mode only. The name of the file is a required parameter and 'r' opens a file for reading only. 'r+' opens a file for both reading and writing.

2. Which of the following statements is false? 1 / 1 point

- ( ) When you open a file for writing, if the file does not exist, a new file is created.
- ( ) When you open a file for writing, if the file exists, the existing file is overwritten with the new file.
- ( ) When you open a file for reading, if the file does not exist, an error occurs.
- (•) When you open a file for writing, if the file does not exist, an error occurs.

Nice work

This is false. When you open a file for writing, if the file does not exist, a new file is created.

3. Which of the following can be used to open a file “MOOC.csv” in append-mode only? 1 / 1 point

- ( ) my_file = open('MOOC.csv', 'w+')
- (•) my_file = open('MOOC.csv', 'a')
- ( ) my_file = open('MOOC.csv', 'rw')
- ( ) my_file = open('MOOC.csv', 'r+')

Nice work

my_file = open('MOOC.csv', 'a') can be used to open a file “MOOC.csv” in append-mode only. The name of the file is a required parameter and 'a' is for append-mode. This opens a file for appending with the cursor at the end of the file.

4. Which of the statements below is false for the following script? 1 / 1 point

```
import csv
with open('MOOC.csv', 'r') as csvfile:
    reader = csv.DictReader(csvfile)
```

- ( ) It can run without any error
- ( ) The type of 'reader' is DictReader
- (•) You can iterate over 'reader' more than once
- ( ) 'MOOC.csv' is opened for reading only

Nice work

This is false. By default, a DictReader only allows you to iterate over it once! This is because a DictReader reads the file directly (does not store the data in memory) .

5. There is a MOOC.csv file containing the following content. 1 / 1 point

```
id,name,height,weight,age
1,Melanie,72,130.6,30
2,Keenan,84,197.6,31
3,Tom,78,180.0,27
```

Which of the statements below is true for the following script?

```
import csv
youngest_student = None
min_age = None
with open('MOOC.csv', 'r') as csvfile:
    reader = csv.DictReader(csvfile)
    for row in reader:
        age = int(row["age"])
        if min_age == None or min_age > age:
            youngest_student = row["name"]
            min_age = age
if min_age == None:
    print("The file does not contain any students.")
else:
    print("The youngest student is " + str(youngest_student) + " who is " + str(min_age) + " years old.")
```

- ( ) The script cannot be run as there is an error with the usage of DictReader
- ( ) The script cannot be run as there is an error with iterating over the reader
- (•) The script can be run and what can be found is the youngest student and their age
- ( ) The script can be run and what can be found is the oldest student and their age

Nice work

This is true.

6. There is a MOOC.csv file containing the following content. 1 / 1 point

```
id,name,height,weight,age
1,Melanie,72,130.6,30
2,Keenan,84,197.6,31
3,Tom,78,180.0,27
```

Which of the statements below is true for the following script?

```
import csv
students = []
with open('MOOC.csv', 'r') as csvfile:
    reader = csv.DictReader(csvfile)
    for row in reader:
        students.append(row)
filtered_students = [row for row in students if (int(row["age"]) < 30 and float(row["weight"]) < 190)]
for student in filtered_students:
    print(student["name"], student["age"], student["weight"])

```

- ( ) The script cannot be run as there is an error with the code that filters the data (filtered_students)
- ( ) The script cannot be run as there is an error with the code that iterates over the filtered data (filtered_students)
- (•) The script can be run and what can be found is the list of students who are younger than 30 and weigh less than 190
- ( ) The script can be run and what can be found is the name, age, and weight of the students who are at least 30 and weigh 190

Nice work

This is true.