Your grade: 100%

Your latest: **100%** • Your highest: **100%** • To pass you need at least 75%. We keep your highest score.

Next item →

1. Assume you have imported the package pyplot as **plt** and created a histogram in the program. Now you want to display the histogram. What is the code you will write to show the plot? 1 / 1 point

plt.show()

Nice work

We use the method show() to display a figure. When running in Jupyter Notebook with its pylab mode, it displays all figures and returns to the Jupyter Notebook prompt.

Remember to re-call show() when a new figure is added.

2. Which method do we use to give an x-axis a label? 1 / 1 point

- xtitle()
- xlabel()
- xlegend()

Nice work

Correct. The method xlabel() is used to set the label for the x-axis.

3. Assume we want to add a legend in a histogram. Which parameter should we specify if we want to place the legend at the center of the figure? 1 / 1 point

- loc
- center
- xy

Nice work

Correct. The parameter "loc" is used to define the location of the legend. The default value is 'best'.

4. What does the following script do? 1 / 1 point

```
1
2   plt.hist([series_pitt, series_vegas], alpha=0.7, color=['red','blue'], label=['Pittsburgh','Las Vegas'], bins="auto")
3
```

- It creates two figures each containing a histogram plot.
- It creates two overlapping histograms in one figure.
- It plots two histograms whose bars are side by side in one figure.

Nice work

Correct. By specifying a list of values as the first parameter, it creates two histograms whose bars are placed side by side.

5. What do the first two arguments specify in the method scatter()? 1 / 1 point

- The labels for x and y axis.
- The data for the x and y axis
- The marker shape and color.

Nice work

Correct. The first two arguments in the scatter() method are the data for the x and y axis respectively

6. Is the following code the right way to set the scale of a y-axis as logarithmic? 1 / 1 point

```
1   import matplotlib.pyplot as plt
2   plt.set_yscale('log')
3
```

- Yes.
- No.

Nice work

Correct. The method set_yscale() is in the package matplotlib.axes. To call this method, first we need to get the current axes object using plt.gca(), then we can call the set_yscale() method using the axes object.