



It's very nice of you to give such further explanation,thank you again – LancelotHolmes Sep 16, 2016 at 4:39



This is a powershell issue as explained in [The '<' operator is reserved for future use \(PowerShell\)](#).

3

As explained in the first answer you can run your command like this;



```
Get-Content largeT.txt | java prac1_1_23 largeW.txt
```



Check out other answers for alternative ways to redirect input in powershell.



Share Edit Follow Flag

edited May 23, 2017 at 12:32

Community Bot 1 1

answered Sep 15, 2016 at 5:45

default locale 13.1k 13 57 62



Well, thank you, actually I have tried this method but my powershell just corrupt and finally I change the file to small files like **tinyW.txt** and **tinyT.txt** and it does work, thanks for your help – LancelotHolmes Sep 15, 2016 at 6:11



@LancelotHolmes also, you can put your command `java prac1_1_23 largeW.txt < largeT.txt` in a bat file as explained [here](#). By the way is there a specific reason to run java from powershell and not cmd, for example? – default locale Sep 15, 2016 at 6:14



Sorry, I thought that the powershell is more convinient than cmd which brings me such a problem, anyway, it's very nice of you to give me so much helpful information, thank you again! – LancelotHolmes Sep 15, 2016 at 6:27

1

Using Get-Content and piping the result to a native command doesn't work in some cases, I think it's because it ends up messing with the Unicode encoding the native program receives. – Burt_Harris Sep 16, 2016 at 3:06



-1

You can use this operation for powershell:



```
[int]$a = 2
[int]$b = 3
```



for equation example (a==b) :

```
if($a -eq $b)
{
    #some code
}
```

for not equation example (a!=b) :

```
if($a -ne $b)
{
    #some code
}
```

for Greater than example (a>b):

```
if ($a -gt $b)
{
    #some code
}
```

for less than example (a

```
if($a -lt $b)
{
    #some code
}
```

for greater than equal example (a>=b):

```
if($a -ge $b)
{
    #some code
}
```

for less than equal example (a<=b):

```
if($a -le $b)
{
    #some code
}
```

Share Edit Follow **Undelete** Flag

answered Sep 15, 2016 at 5:33

saftargholi 916 1 9 25



In this case `<` operator is used to redirect input, not to compare things. – default locale Sep 15, 2016 at 5:46



Comments disabled on deleted / locked posts / reviews