← Back **End of Module Quiz**
Graded Assignment • 10 min

Due Nov 11, 11:59 PM IST

Your grade: 100%

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

1. True/False. Bagging and boosting ensemble methods both use only decision trees as base classifiers. The difference is in the bias and variance of the individual trees. **1 / 1 point**

- (○) True
- (●) False

✓ **Nice work**

Correct!

2. True/False. A decision tree classifier is useful as a model for the AAVAIL subscriber churn data. **1 / 1 point**

- (●) True
- (○) False

✓ **Nice work**

Correct!

3. Which of the following was **not** discussed as a tunable parameter of a neural network? **1 / 1 point**

- (●) Hardware availability
- (○) Activation functions: sigmoid, tanh, softmax, ReLU, leaky ReLU
- (○) Regularization techniques: weight decay, early stopping, dropout
- (○) Training method: Loss function, learning rate, batch size, number of epochs
- (○) Structure: the number of hidden layers, the number of nodes in each layer

✓ **Nice work**

Correct!

4. True/False. Transfer learning is a recent advancement to come out of the field of reinforcement learning. **1 / 1 point**

- (○) True
- (●) False

✓ **Nice work**

Correct!

5. When training a custom classifier in Watson Visual Recognition the negative images should be: **1 / 1 point**

- (●) As visually similar as possible to the positive images
- (○) Background images without the positive images
- (○) As random as possible to establish a background
- (○) Randomly generated from the positive images
- (○) Visually distinct from the positive images

✓ **Nice work**

Correct!

6. True/False. The Watson Visual Recognition service can only be accessed using an API key via Python or curl. **1 / 1 point**

- (○) True
- (●) False

✓ **Nice work**

Correct!

7. Which of the following use cases is the **least** appropriate use case for a convolutional neural network? **1 / 1 point**

- (○) Image classification
- (○) Image retrieval
- (●) Image composition
- (○) Object detection
- (○) Image segmentation

✓ **Nice work**

Correct!

8. True/False. A typical convolutional neural network is constructed using a combination of convolutional, pooling and dense layers. **1 / 1 point**

- (●) True
- (○) False

✓ **Nice work**

Correct!