Your grade: 100%

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

Next item →

1. A developer is working with the Gemini API and needs to understand how it measures and processes text. They learn that both input prompts and output responses are measured in specific units. What is the primary unit the Gemini API uses to process language and calculate usage? Select the best answer. 1 / 1 point

- Characters
- Bytes
- Prompts
- Tokens (selected)

Nice work

Correct! Tokens are the fundamental units of text, like words or parts of words, that the model uses to understand and generate language. API usage is also measured in tokens.

2. A developer is building an application and needs to use their API key to authenticate requests. They plan to share their code on a public repository and want to avoid exposing the secret key. What is a secure method for managing API keys in a development environment to prevent them from being exposed in source code? Select the best answer. 1 / 1 point

- Emailing the key to team members when they need it
- Storing the key in a public text file for easy access
- Using environment variables to store the key (selected)
- Writing the key directly into the application code

Nice work

Correct! Environment variables keep sensitive data like API keys separate from the source code, which is a critical security best practice.

3. A developer's application uses the Gemini API, but it sometimes stops working when the internet connection is lost or an invalid request is sent. They want the application to handle these issues without crashing. What should a developer do to manage potential API errors and prevent the application from crashing? Select the best answer. 1 / 1 point

- Use a try-catch block to handle exceptions gracefully. (selected)
- Restart the application automatically when an error occurs.
- Ignore all error messages from the API.
- Check the API status manually on a website before each call.

Nice work

Correct! A try-catch block allows the code to attempt an operation that might fail and provides a way to handle the error condition without crashing the program.

4. A developer wants to experiment with different prompts for the Gemini model without writing any code. They are looking for a tool that provides a simple web interface for this purpose. Which tool is designed for rapid, code-free prototyping and experimentation with Gemini models? Select the best answer. 1 / 1 point

- GitHub Codespaces
- Google AI Studio (selected)
- JavaScript SDK
- Gemini API

Nice work

Correct! Google AI Studio provides a web-based interface that allows developers to test prompts and model settings quickly without needing to set up a coding environment.

5. After making a successful API call, a developer receives a response. The response is a structured object that contains the generated text, safety ratings, and other metadata. What is the next step the developer must take to get only the generated text from the API response object for use in their application? Select the best answer. 1 / 1 point

- Send a new API request asking for just the text.
- Print the entire response object directly to the screen.
- Check the response object's file size to confirm it is valid.
- Parse the response object to access the desired text property. (selected)

Nice work

Correct! The API returns a structured object, and parsing it means navigating that structure to extract the specific piece of data you need.