



⌵ Hide menu

Bootstrapping

✓ **Video:** Bootstrapping
9 min

✓ **Reading:** Summary
1h

Module Assignment

Summary

The bootstrap method is a resampling technique used for estimating the sampling distribution of a statistic or for assessing the uncertainty of a model. It involves generating multiple resamples of the original dataset by randomly sampling with replacement, and then performing the desired analysis on each resample.

When applying the bootstrap method to **Ridge** and **Lasso regression**, the general procedure is as follows:

1. Dataset preparation: Start with your original dataset, which consists of input features and corresponding target variables.
2. Bootstrap sampling: Generate multiple bootstrap samples by randomly selecting observations from the original dataset with replacement. Each bootstrap sample will have the same size as the original dataset, but some observations may be duplicated while others may be omitted.
3. Model training: Fit the **Ridge** or **Lasso** regression model to each bootstrap sample. This involves estimating the model coefficients and selecting the appropriate regularization parameter (alpha).
4. Model evaluation: Use each fitted model to make predictions on the original dataset or on new unseen data. Evaluate the model's performance metrics, such as mean squared error (MSE), root mean squared error (RMSE), mean absolute error (MAE), or R-squared, depending on the specific problem.
5. Aggregate results: Calculate the average or median values of the estimated coefficients from all the bootstrap samples. This provides a measure of central tendency and helps to stabilize the estimates.
6. Confidence intervals: Compute confidence intervals around the estimated coefficients to quantify the uncertainty associated with the model parameters. The confidence intervals can be obtained by calculating the percentiles of the coefficient values across the bootstrap samples.

By applying the bootstrap method to Ridge and Lasso regression, you can obtain more reliable estimates of the model coefficients and assess their uncertainty. This helps in understanding the stability and robustness of the models and can aid in selecting the appropriate regularization parameter (alpha) for better generalization performance. Additionally, the bootstrap method provides a way to evaluate the stability and variability of the model's predictions, allowing for a more comprehensive assessment of the model's performance. Please read the following link for further information pertaining to the bootstrap method:

[Balancing Performance and Interpretability: Selecting Features with Bootstrapped Ridge Regression](#)



Go to next item

✓ Completed

👍 Like 🗨 Dislike 🚩 Report an issue

