

☰ Hide menu

Neural Networks

- ✔ Video: Neural Networks: Part 1
24 min
- ✔ Video: Neural Networks: Part 2
14 min
- ✔ Video: Neural Networks: Part 3
13 min
- ✔ Video: Neural Networks: Part 4
6 min
- ✔ Video: Neural Networks And Its Application To Unsupervised Learning
10 min
- ✔ Reading: Neural Networks
1h 39m

Assignments

Neural Networks

Neural networks, also known as artificial neural networks or simply "neural nets," are a class of machine learning models inspired by the structure and functioning of biological neural networks in the human brain. They are designed to recognize patterns and learn from data in a way that mimics human learning and decision-making processes.

A neural network consists of interconnected nodes, called artificial neurons or "units," organized in layers. The three main types of layers are:

1. Input layer: The input layer receives the initial data or features and passes them forward to the next layer. Each input node represents a feature of the data.
2. Hidden layers: Hidden layers are intermediate layers between the input and output layers. They perform complex computations and transform the inputs into representations that the network can learn from. Multiple hidden layers can be present in a neural network, forming what is called a deep neural network or deep learning model.
3. Output layer: The output layer produces the final predictions or outputs based on the computations performed in the hidden layers. The number of nodes in the output layer depends on the type of task the neural network is designed for. For example, in a binary classification task, there would be one output node representing the probability or prediction for one class, while in multi-class classification, there would be multiple output nodes, each representing a different class.

Neural networks learn by adjusting the weights and biases associated with the connections between neurons. The weights determine the strength of the connections, while the biases provide an offset or threshold for each neuron's activation. The network uses an optimization algorithm, such as gradient descent, to iteratively update these weights and biases based on the error or loss between predicted outputs and the actual targets in the training data. This process is known as training or learning.

The power of neural networks lies in their ability to automatically learn and extract complex patterns from data. They can capture non-linear relationships and handle large and high-dimensional datasets. Deep neural networks, with their multiple hidden layers, are especially effective in learning hierarchical representations of data.

Neural networks have found success in various domains, including computer vision (image classification, object detection), natural language processing (sentiment analysis, machine translation), speech recognition, recommendation systems, and many other areas. However, training deep neural networks can be computationally expensive and requires a large amount of labeled training data. Techniques like convolutional neural networks (CNNs) and recurrent neural networks (RNNs) have been developed to handle specific types of data and tasks, further expanding the capabilities of neural networks.

Neural networks and Support Vector Machines (SVMs) are both popular machine learning algorithms but differ in their underlying principles, architecture, and training approaches. Here are some key differences between the two:

- Architecture:
 - Neural networks: Neural networks consist of interconnected layers of artificial neurons. The number of layers and the number of neurons in each layer can vary, including the presence of multiple hidden layers. The architecture of neural networks allows them to learn complex hierarchical representations of data.
 - SVMs: SVMs do not have a layered structure like neural networks. They are based on the concept of finding an optimal hyperplane that separates data points of different classes in feature space. SVMs focus on maximizing the margin around the decision boundary, with support vectors lying closest to the boundary.
- Learning Approach:
 - Neural networks: Neural networks learn through an iterative process called backpropagation, where the weights and biases of the network are adjusted based on the error between predicted and actual outputs. They update the parameters using gradient descent or its variants to minimize the loss function. Neural networks are capable of learning both linear and non-linear relationships in the data.
 - SVMs: SVMs learn by finding the optimal hyperplane that maximally separates the data points. The training of SVMs involves solving a convex optimization problem, where the aim is to minimize the hinge loss or maximize the margin. SVMs transform the data into a higher-dimensional space using kernel functions to handle non-linear decision boundaries (The Kernel Trick).
- Handling Non-Linearity:
 - Neural networks: Neural networks are inherently capable of capturing non-linear relationships in the data due to their layered structure and activation functions. By introducing non-linear activation functions, such as sigmoid, ReLU, or tanh, neural networks can model complex patterns and mappings between input and output.
 - SVMs: SVMs can handle non-linearity by employing kernel functions, such as polynomial, radial basis function (RBF), or sigmoid. These kernel functions map the original data into a higher-dimensional feature space, allowing SVMs to learn non-linear decision boundaries. However, the choice and tuning of the kernel function are important for achieving good performance.
- Interpretability:
 - Neural networks: Neural networks can be less interpretable compared to SVMs. With their complex and layered structure, understanding the exact relationship between input features and output predictions can be challenging. Deep neural networks, in particular, may have a large number of parameters, making it difficult to interpret their internal representations.
 - SVMs: SVMs offer better interpretability compared to neural networks. The decision boundary of an SVM is defined by a subset of the training samples (support vectors). The support vectors themselves provide insights into the importance and influence of specific data points on the model's decision-making process.
- Training Complexity:
 - Neural networks: Training neural networks, especially deep neural networks with many layers, can be computationally expensive and time-consuming. The optimization process requires a large amount of labeled training data and can benefit from high-performance computing resources such as GPUs.
 - SVMs: SVMs are generally less computationally demanding compared to deep neural networks, particularly for smaller datasets. The training time of SVMs primarily depends on the number of support vectors and the choice of kernel function.

The choice between neural networks and SVMs depends on various factors, including the nature of the data, the complexity of the problem, the availability of labeled data, and the interpretability requirements. Neural networks are well-suited for tasks involving complex patterns and large datasets, while SVMs can be effective in cases with smaller datasets and a need for interpretability.

Neural networks can be used for both supervised and unsupervised learning, depending on the specific task and the type of network architecture employed. The learning process and the availability of labeled data are the key factors that determine whether a neural network is used for supervised or unsupervised learning.

Supervised Learning: In supervised learning, neural networks are trained using labeled data, where the inputs are associated with corresponding target outputs. The goal is to learn a mapping between the inputs and outputs to make predictions or classify new, unseen data points. The network learns by adjusting its weights and biases based on the error or loss between the predicted outputs and the true labels. Most commonly, feedforward neural networks, such as multi-layer perceptrons (MLPs), are used for supervised learning tasks like image classification, speech recognition, and regression.

Unsupervised Learning: Unsupervised learning aims to discover patterns, structures, or relationships in the data without explicit target labels. Neural networks can also be used for unsupervised learning tasks, such as clustering, dimensionality reduction, and generative modeling. Here are a couple of examples:

- Autoencoders: Autoencoders are a type of neural network that can learn to reconstruct the input data by encoding it into a lower-dimensional representation (encoder) and decoding it back to the original space (decoder). Autoencoders are trained on unlabeled data, and the network tries to minimize the reconstruction error. They can learn useful representations of the data and are often used for dimensionality reduction or anomaly detection tasks.
- Generative Adversarial Networks (GANs): GANs consist of two neural networks, a generator and a discriminator, which are trained together in a competitive manner. The generator learns to generate synthetic data samples that resemble the real data distribution, while the discriminator learns to distinguish between real and fake samples. GANs are used for generating new samples, image synthesis, and data augmentation.

It's important to note that there are also semi-supervised learning approaches that combine labeled and unlabeled data, where neural networks can be employed as well. In semi-supervised learning, the neural network leverages both labeled and unlabeled data to improve performance.

In summary, while neural networks are widely known for their applications in supervised learning tasks, **they can also be utilized for various unsupervised learning tasks**, such as **clustering, dimensionality reduction, and generative modeling**. The choice of whether to use them for supervised or unsupervised learning depends on the specific problem and the type of network architecture and training setup employed.

Please see the following links for a clear explanation of Neural Networks and its applications both to supervised and unsupervised learning.

A Comprehensive Guide to Types of Neural Networks [↗](#)

Understanding and Building Neural Network (NN) Models [↗](#)

Autoencoders: Neural Networks for Unsupervised Learning [↗](#)

Unsupervised Learning [↗](#)

Go to next item

✔ Completed

👍 Like 🗑 Dislike 📄 Report an issue

