

[Courseware \(/courses/HumanitiesScience/StatLearning/Winter2014/courseware\)](/courses/HumanitiesScience/StatLearning/Winter2014/courseware)[Course Info \(/courses/HumanitiesScience/StatLearning/Winter2014/info\)](/courses/HumanitiesScience/StatLearning/Winter2014/info)[Discussion \(/courses/HumanitiesScience/StatLearning/Winter2014/discussion/forum\)](/courses/HumanitiesScience/StatLearning/Winter2014/discussion/forum)[Wiki \(/courses/HumanitiesScience/StatLearning/Winter2014/course_wiki\)](/courses/HumanitiesScience/StatLearning/Winter2014/course_wiki)[Progress \(/courses/HumanitiesScience/StatLearning/Winter2014/progress\)](/courses/HumanitiesScience/StatLearning/Winter2014/progress)[Lecture Slides \(pdf\) \(/courses/HumanitiesScience/StatLearning/Winter2014/ba1951b8f66c4cdca2fcaabcdc91b792/\)](/courses/HumanitiesScience/StatLearning/Winter2014/ba1951b8f66c4cdca2fcaabcdc91b792/)[R Sessions \(/courses/HumanitiesScience/StatLearning/Winter2014/0d68641c19484ef9aa6aeea03426dc68/\)](/courses/HumanitiesScience/StatLearning/Winter2014/0d68641c19484ef9aa6aeea03426dc68/)

5.2.R1 (1/1 point)

Suppose we want to use cross-validation to estimate the error of the following procedure:

Step 1: Find the k variables most correlated with y

Step 2: Fit a linear regression using those variables as predictors

We will estimate the error for each k from 1 to p , and then choose the best k .

True or false: a correct cross-validation procedure will possibly choose a different set of k variables for every fold.

- ☒ TRUE 
- ☐ FALSE

EXPLANATION

True: we need to replicate our entire procedure for each training/validation split. That means the decision about which k variables are the best must be made on the basis of the training set alone. In general, different training sets will disagree on which are the best k variables.

[Hide Answer](#)

You have used 1 of 5 submissions



