

7/25/23, 10:41 AM

CodeProjectFileEditFindViewToolsEducationHelpRunProject (expanded)Debug

Terminalx

(base) codio@ecologyopen-metrolfantasy:~/workspace\$ conda create --name learning-conda
collecting package metadata (current_repodata.json): done
Solving environment: done
conda activate learning-conda

=> WARNING: A newer version of conda exists. <==
current version: 4.12.0
latest version: 23.5.2

Please update conda by running

\$ conda update -n base -c defaults conda

Package Plan ##

environment location: /home/codio/anaconda3/envs/learning-conda

Proceed ([y]/n)? Invalid choice: conda activate learning-conda
Proceed ([y]/n)? y

Preparing transaction: done
Verifying transaction: done
Executing transaction: done

To activate this environment, use

\$ conda activate learning-conda

To deactivate an active environment, use

\$ conda deactivate

(base) codio@ecologyopen-metrolfantasy:~/workspace\$ conda activate learning-conda
(learning-conda) codio@ecologyopen-metrolfantasy:~/workspace\$ conda env list
conda environments:

base /home/codio/anaconda3
learning-conda * /home/codio/anaconda3/envs/learning-conda

(learning-conda) codio@ecologyopen-metrolfantasy:~/workspace\$

Codio - Conda

GuideCollapse

Virtual Environments

Creating a Virtual Environment

Aside from the base environment, Conda does not automatically create or activate any virtual environments. Just like using `pip`, you should create a separate virtual environment for each project.

Create the Conda environment called `learning-conda` by using the `create` command and the `--name` flag. Conda will ask you to type `yes` to confirm your environment creation.

```
conda create --name learning-conda
```

Notice, Conda does not immediately activate the new environment. You need to do this manually. Use the `activate` command followed by the name of virtual environment you want to activate.

```
conda activate learning-conda
```

You should now see the name of the virtual environment appear at the beginning of your prompt.

```
(learning-conda) codio@statichuman-typebeatles:~/workspace$
```

► Did you notice?

Try these variations:

- Create a copy of the `learning-conda` virtual environment.

```
conda create --clone learning-conda --name lc2
```

- List all of the virtual environments on your system.

```
conda env list
```

► Did you notice?

Deactivating and Removing Virtual Environments

Unlike Poetry, you have to manually manage your virtual environments in Conda. That means if you are currently using one virtual environment but need to use another, then you have to deactivate the first virtual environment and then active the other one.

If `conda activate` activates a virtual environment, then `conda deactivate` should deactivate it. You will now see `(base)` at the beginning of the prompt after deactivating a specific virtual environment.

```
conda deactivate
```

Up above, we made a copy of the `learning-conda` virtual environment. We don't really need this environment. It was only used to introduce how to clone an existing environment. So let's remove the `lc2` environment.

The command is `env remove`, but we need to specify the name of the environment to remove. Use the `--name` flag followed by `lc2`.

```
conda env remove --name lc2
```

► Did you notice?

You should no longer see `lc2` in the list of virtual environments on your system. It is also important to note that Conda removes all contents (packages and their dependencies) when deleting a virtual environment.

```
conda env list
```

Reading Question

Select the Conda command that creates the virtual environment named `my-project`.

☐ `conda new --name my-project`

☒ `conda create --name my-project`

☐ `conda create my-project`

☐ `conda create my-project --name`

The correct answer is:

```
conda create --name my-project
```

The Conda command is `create`. Use the `--name` flag to specify the name `my-project`. The name flag must come before the name of the virtual environment.

Check ID

Next