

Terminalx

```
(base) codio@cabinetchef-igloofocus:~/workspace/sw_characters$ cd ..
(base) codio@cabinetchef-igloofocus:~/workspace$ conda create -n sw -y
Collecting package metadata (current_repodata.json): done
Solving environment: done
conda activate sw

==> WARNING: A newer version of conda exists. <==
  current version: 4.10.3
  latest version: 23.5.2

Please update conda by running

    $ conda update -n base -c defaults conda

## Package Plan ##

  environment location: /home/codio/anaconda3/envs/sw

Preparing transaction: done
Verifying transaction: done
Executing transaction: done
#
# To activate this environment, use
#
#     $ conda activate sw
#
# To deactivate an active environment, use
#
#     $ conda deactivate

(base) codio@cabinetchef-igloofocus:~/workspace$ conda activate sw
(sw) codio@cabinetchef-igloofocus:~/workspace$ conda install requests -y
Collecting package metadata (current_repodata.json): done
Solving environment: done

==> WARNING: A newer version of conda exists. <==
  current version: 4.10.3
  latest version: 23.5.2

Please update conda by running

    $ conda update -n base -c defaults conda
```

Guidex

Collapse

<>⚙️☰

Star Wars Characters Project

Working with a Star Wars API

In many examples for installing package, the `requests` package was often used. This package allows you to more easily talk to web pages. We are going to use this package to query a Star Wars API and print a short description of a character that looks like the output below. In addition, the script should be able to handle a list of characters returned from the API.

```
Luke Skywalker is from the planet Tatooine. They appear in the following films:
* A New Hope
* The Empire Strikes Back
* Return of the Jedi
* Revenge of the Sith
```

Perhaps Star Wars isn't your thing, but it is a full-featured API that does not require authentication. This makes the API a useful tool to introduce these concepts with a little less complexity.

We are also going to use the `fire` package to create an easy command line interface for the end user. They can use the `--name` flag to identify the character to be searched.

```
python3 sw_character.py --name="boba"
```

Finally, we are going to use TinyDB a lightweight, document-based database to improve the performance by limiting the number of times the script needs to query the API.

Starting the Project

You may have noticed that `(base)` is at the beginning of the prompt. That means Conda is already installed. We will be using this package manager for this project. The first thing we need to do is create a virtual environment for this project.

```
conda create -n sw -y
```

Next, activate the new virtual environment.

```
conda activate sw
```

You should see `(sw)` replace `(base)` in the terminal. Then install the `requests` library with the `install` command.

```
conda install requests -y
```

Finally, change into the directory that stores the source code and create Python files for searching the API and creating the user interface.

```
touch sw_characters/search_api.py sw_characters/interface.py
```

To verify that your project is ready to go, use the `tree` command see the newly created files.

```
tree sw_characters/
```

You should see the following output for the `sw_search` directory:

```
sw_characters/
├── __init__.py
├── interface.py
└── search_api.py
```

Lab Question

Fill in the blanks below.

- `Poetry` - Uses the `add` command to install a new package.
- `Conda` - Uses the `install` command to add a new package.

Here are the correct answers:

- Poetry** - Uses the `add` command to install a new package.
- Conda** - Uses the `install` command to add a new package.

Check It!

Next

https://codio.com/sandipan-dey/lab-1/terminal/backend-guide

1/1