

You are located in service:
RWTH High Performance Computing (Linux)
Slurm environmental variables

Slurm environmental variables



Slurm Variable Name	Description	Example Value
\$SLURM_JOB_ID	Job ID	123456
\$SLURM_ARRAY_JOB_ID	Job ID if part of Array job	123456
\$SLURM_ARRAY_TASK_ID	Job Index within Array job	1
\$SLURM_JOB_NAME	Job Name	MyBatchJob
\$SLURM_SUBMIT_DIR	Submit Directory	/home/ab123456
\$SLURM_JOB_NODELIST	Nodes assigned to job	ncm[0001,0004,0074-0080]
\$SLURM_SUBMIT_HOST	Submitting host	login18-1.hpc.itc.rwth-aachen.de
\$SLURM_JOB_NUM_NODES	Number of nodes used by job	4
\$SLURM_JOB_CPUS_PER_NODE	Number of cores per node	8,8,8,6
\$SLURM_TASKS_PER_NODE	Number of tasks per node	1,1,1,1
\$SLURM_MEM_PER_CPU	Memory per CPU in MB	3000
\$SLURM_NTASKS	Total number of tasks for job	48
\$SLURM_NPROCS	Total number of processes for job	48
\$TEMPDIR	In that path is a copy of the job script used for the job	

last changed on 02/23/2024



This work is licensed under a Creative Commons Attribution - Share Alike 3.0 Germany License

[🏠 Research](#) | [RWTH High Performance Computing](#) | [RWTH High Performance Computing \(Linux\)](#) | [Submit jobs with Slurm](#) | [Slurm environmental variables](#) |

