Your grade: 100%

Your latest: 100% • Your highest: 100% • To pass you need at least 80%. We keep your highest score.

Next item →

1. Which of the following is true about the gradient in stochastic gradient descent? 1 / 1 point

- (•) It is an unbiased estimate of the true gradient
- ( ) It is always perpendicular to the decision boundary
- ( ) It is computed using the entire dataset in each iteration
- ( ) It always points in the direction of the steepest ascent

Nice work

2. Please complete the following statement: “The lower the loss…” 1 / 1 point

- ( ) The worse we are doing
- ( ) Slower is model training
- (•) The better we are doing
- ( ) Faster is model training

Nice work

3. Which of the following is the commonly used loss function for logistic regression? 1 / 1 point

- (•) Cross-entropy loss
- ( ) Accuracy loss
- ( ) Mean squared error
- ( ) Hinge loss

Nice work

4. During model training with stochastic gradient descent, which of the following is correct? 1 / 1 point

- (•) The loss is computed before the gradient
- ( ) Loss and gradient are computed simultaneously
- ( ) All of the above options are possible, depending on the model’s hyperparameters
- ( ) The gradient is computed before the loss

Nice work

5. True or False: Model parameters need to be initialized before the model can be trained. 1 / 1 point

- (•) True
- ( ) False

Nice work