Your grade: 100%

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

Next item →

1. Which of the following tasks is not typically a sequence-to-sequence task? 1 / 1 point

- (•) Sentiment analysis
- ( ) Machine translation
- ( ) Dialogue generation
- ( ) Summarization

Nice work

2. What problem does the attention mechanism primarily address in sequence-to-sequence models? 1 / 1 point

- ( ) Insufficient training data
- ( ) Lack of parallelism during training
- ( ) Overfitting
- (•) Difficulty in handling long sequences

Nice work

3. What NLP task was the attention mechanism first proposed for? 1 / 1 point

- (•) Machine translation
- ( ) Natural language inference
- ( ) Language modeling
- ( ) Dialogue generation

Nice work

4. True or False: Attention is only useful in the context of encoder-decoder models. 1 / 1 point

- (•) False
- ( ) True

Nice work

5. In an RNN sequence-to-sequence model with Bahdanau attention, how are the attention weights typically computed? 1 / 1 point

- ( ) By using a one-hot encoding of the input sequence
- ( ) By performing a max-pooling operation over the encoder states
- ( ) By averaging the encoder hidden states
- (•) By applying a softmax function to the output of a feedforward network whose input are the encoder and decoder hidden states

Nice work