

```
imageVar.py  x
28 image_url = response['data'][0]['url']
29
30 #using the url, we use the code below to save it as a file
31 img_data = requests.get(image_url).content
32 with open('bunny.png', 'wb') as handler:
33     handler.write(img_data)
34
35 response = openai.Image.create_variation(
36     image=open("bunny.png", "rb"),
37     n=1,
38     size="512x512"
39 )
40 image_url2= response['data'][0]['url']
41
42 img_data = requests.get(image_url2).content
43 with open('bunny_var.png', 'wb') as handler:
44     handler.write(img_data)
```

100% (44:28)

Terminal x

```
*
Last login: Mon Feb 27 20:05:42 2023 from 192.168.11.179
codio@cometsugar-horizonlegal:~/workspace$ ls
bunny.png      edits.py      masked.png    __pycache__  testVariation.png
bunny_var.png  exerc.py     mask.png     README.md    varTest.png
edited-copy1.png exercTest.py  mask.py      secret.py    varTests.png
edited-copy2.png imageGen.py  original-copy.png setting.py
edited.png      imageVar.py  original.png  test_image.png
codio@cometsugar-horizonlegal:~/workspace$ python exerc.py
codio@cometsugar-horizonlegal:~/workspace$ ls
bunny.png      edits.py      masked.png    __pycache__  testVariation.png
bunny_var.png  exerc.py     mask.png     README.md    varTest.png
edited-copy1.png exercTest.py  mask.py      secret.py    varTests.png
edited-copy2.png imageGen.py  original-copy.png setting.py
edited.png      imageVar.py  original.png  test_image.png
codio@cometsugar-horizonlegal:~/workspace$ ls exerc.py
exerc.py
codio@cometsugar-horizonlegal:~/workspace$ vi exerc.py
codio@cometsugar-horizonlegal:~/workspace$ python imageGen.py
Traceback (most recent call last):
```

Guide x

Collapse

Variation

Let's try creating an image variation of a bunny and a cat.

1. First we generate the original image of the bunny and cat.

```
#this code generates a new image from a prompt
response = openai.Image.create(
    prompt="bunny and a cat",
    n=1,
    size="512x512"
)
#from the response generated this puts the url in a separate variable
image_url = response['data'][0]['url']
```

2. We save the bunny and cat image.

```
#using the url, we use the code below to save it as a file
img_data = requests.get(image_url).content
with open('bunny.png', 'wb') as handler:
    handler.write(img_data)
```

3. We use the new image to generate a variation of the said image using our new file name we created in the previous step

```
response = openai.Image.create_variation(
    image=open("bunny.png", "rb"),
    n=1,
    size="512x512"
)
image_url2= response['data'][0]['url']
```

4. Now we have to save our new URL in a different file name.

```
img_data = requests.get(image_url2).content
with open('bunny_var.png', 'wb') as handler:
    handler.write(img_data)
```

TRY IT!

Command was successfully executed.

[Click here to refresh your first image](#)
[Click here to refresh your variation image](#)

Prompts and images are filtered based on OpenAI's content policy, returning an error when a prompt or image is flagged.

Fill in the blank:

To create a variation of an existing image, you need to pass the image file as an argument to the `create_variation` method using the `open` function.

To create a variation of an existing image, you need to pass the image file as an argument to the `create_variation` method using the `open` function. The `open` function is used to open the image file in binary mode (with the mode set to "rb") before passing it to the method. For example: `open("image_name.png", "rb")`.

Check It!

Next