

Your grade: 100%

Next item →

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

1. When implementing the particle-filter sequential-importance-sampling (SIS) algorithm, how do we find $f(x_k^{(i)} \mid x_{k-1}^{(i)})$?

1 / 1 point

- ☒ From the process model.
- ☐ From the measurement model.
- ☐ It is a design choice. We can choose whatever is most convenient.
- ☐ We use a zero-mean Gaussian pdf having covariance matrix equal to the identity matrix.

 **Correct**

Yes, this is correct.

2. When implementing the particle-filter sequential-importance-sampling (SIS) algorithm, how do we find $f(z_k \mid x_k^{(i)})$?

1 / 1 point

- ☐ From the process model.
- ☒ From the measurement model.
- ☐ It is a design choice. We can choose whatever is most convenient.
- ☐ We use a zero-mean Gaussian pdf having covariance matrix equal to the identity matrix.

 **Correct**

Yes, this is correct.

3. When implementing the particle-filter sequential-importance-sampling (SIS) algorithm, how do we find $q(x_k^{(i)} \mid x_{k-1}^{(i)}, z_k)$?

1 / 1 point

- ☐ From the process model.
- ☐ From the measurement model.
- ☒ It is a design choice. We can choose whatever is most convenient.
- ☐ We use a zero-mean Gaussian pdf having covariance matrix equal to the identity matrix.

 **Correct**

Yes, this is correct.