

# Checking a graph for acyclicity and finding a cycle in $O(M)$

## Table of Contents

- [Algorithm](#)
- [Implementation](#)
  - [Practice problems:](#)

Consider a directed or undirected graph without loops and multiple edges. We have to check whether it is acyclic, and if it is not, then find any cycle.

We can solve this problem by using [Depth First Search](#) in  $O(M)$  where  $M$  is number of edges.

## Algorithm

We will run a series of DFS in the graph. Initially all vertices are colored white (0). From each unvisited (white) vertex, start the DFS, mark it gray (1) while entering and mark it black (2) on exit. If DFS moves to a gray vertex, then we have found a cycle (if the graph is undirected, the edge to parent is not considered). The cycle itself can be reconstructed using parent array.

## Implementation

Here is an implementation for directed graph.

```
int n;
vector<vector<int>> adj;
vector<char> color;
vector<int> parent;
int cycle_start, cycle_end;
```

```

bool dfs(int v) {
    color[v] = 1;
    for (int u : adj[v]) {
        if (color[u] == 0) {
            parent[u] = v;
            if (dfs(u))
                return true;
        } else if (color[u] == 1) {
            cycle_end = v;
            cycle_start = u;
            return true;
        }
    }
    color[v] = 2;
    return false;
}

void find_cycle() {
    color.assign(n, 0);
    parent.assign(n, -1);
    cycle_start = -1;

    for (int v = 0; v < n; v++) {
        if (color[v] == 0 && dfs(v))
            break;
    }

    if (cycle_start == -1) {
        cout << "Acyclic" << endl;
    } else {
        vector<int> cycle;
        cycle.push_back(cycle_start);
        for (int v = cycle_end; v != cycle_start; v++)
            cycle.push_back(v);
        cycle.push_back(cycle_start);
        reverse(cycle.begin(), cycle.end());

        cout << "Cycle found: ";
        for (int v : cycle)
            cout << v << " ";
        cout << endl;
    }
}

```

Here is an implementation for undirected graph.

```
int n;
vector<vector<int>> adj;
vector<char> color;
vector<int> parent;
int cycle_start, cycle_end;

bool dfs(int v, int par) { // passing vertex a
    color[v] = 1;
    for (int u : adj[v]) {
        if(u == par) continue; // skipping edge
        if (color[u] == 0) {
            parent[u] = v;
            if (dfs(u, parent[u]))
                return true;
        } else if (color[u] == 1) {
            cycle_end = v;
            cycle_start = u;
            return true;
        }
    }
    color[v] = 2;
    return false;
}

void find_cycle() {
    color.assign(n, 0);
    parent.assign(n, -1);
    cycle_start = -1;

    for (int v = 0; v < n; v++) {
        if (color[v] == 0 && dfs(v, parent[v]))
            break;
    }

    if (cycle_start == -1) {
        cout << "Acyclic" << endl;
    } else {
        vector<int> cycle;
        cycle.push_back(cycle_start);
        for (int v = cycle_end; v != cycle_start; v++)
            cycle.push_back(v);
        cycle.push_back(cycle_start);
    }
}
```

```
reverse(cycle.begin(), cycle.end());

cout << "Cycle found: ";
for (int v : cycle)
    cout << v << " ";
cout << endl;
}
}
```

## Practice problems:

- [CSES : Round Trip](#)
- [CSES : Round Trip II](#)

(c) 2014-2020 translation by <http://github.com/e-maxx-eng> 29:12355/5554