

Stack Overflow is a question and answer site for professional and enthusiast programmers. It's 100% free, no registration required.

Take the 2-minute tour ×

ggplot2 Circular Heatmap that looks like a donut



I'm trying to create circular heatmap with ggplot2 so I can use a larger number of labels around the circumference of a circle. I'd like to have it look more like a donut with an empty hole in the middle but at the same time not losing any rows (they would need to be compressed). Any ideas? Code for what I have is below. Thanks!

```
library(reshape)
library(ggplot2)

nba <- read.csv("http://datasets.flowingdata.com/ppg2008.csv")


nba$Name <- with(nba, reorder(Name, PTS))
nba.m <- melt(nba)
nba.m <- ddply(nba.m, .(variable), transform, value = scale(value))

p = ggplot(nba.m, aes(Name,variable)) + geom_tile(aes(fill = value), colour = "whi
p<-p+opts(
panel.background=theme_blank(),
axis.title.x=theme_blank(),
axis.title.y=theme_blank(),
panel.grid.major=theme_blank(),
panel.grid.minor=theme_blank(),
axis.text.x=theme_blank(),
axis.ticks=theme_blank()
)

p = p + coord_polar()
plot(p)
```

r ggplot2 heatmap circular donut-chart

asked Dec 14 '12 at 22:51

 user1905004
123 5

[add a comment](#)

1 Answer

Here is a solution accomplished by (1) converting factor to numeric and adding an offset, (2) manually specifying y-limits and (3) manually setting y-axis breaks and labels:

```

library(reshape)
library(ggplot2)
# Using ggplot2 0.9.2.1

nba <- read.csv("http://datasets.flowingdata.com/ppg2008.csv")
nba$Name <- with(nba, reorder(Name, PTS))
nba.m <- melt(nba)
nba.m <- ddply(nba.m, .(variable), transform, value = scale(value))


# Convert the factor levels to numeric + quantity to determine size of hole.
nba.m$var2 = as.numeric(nba.m$variable) + 15

# Labels and breaks need to be added with scale_y_discrete.
y_labels = levels(nba.m$variable)
y_breaks = seq_along(y_labels) + 15


p2 = ggplot(nba.m, aes(x=Name, y=var2, fill=value)) +
  geom_tile(colour="white") +
  scale_fill_gradient(low = "white", high = "steelblue") +
  ylim(c(0, max(nba.m$var2) + 0.5)) +
  scale_y_discrete(breaks=y_breaks, labels=y_labels) +
  coord_polar(theta="x") +
  theme(panel.background=element_blank(),
        axis.title=element_blank(),
        panel.grid=element_blank(),
        axis.text.x=element_blank(),
        axis.ticks=element_blank(),
        axis.text.y=element_text(size=5))

ggsave(filename="plot_2.png", plot=p2, height=7, width=7)

```



answered Dec 15 '12 at 2:46

 **bdemarest**
5,195 12 21
[add a comment](#)

Not the answer you're looking for? Browse other questions tagged [r](#) [ggplot2](#) [heatmap](#) [circular](#) [donut-chart](#) or [ask your own question](#).