

Feedback — Week 3 Quiz

[Help Center](#)

Thank you. Your submission for this quiz was received.

You submitted this quiz on **Fri 27 Feb 2015 11:33 AM PST**. You got a score of **8.25** out of **9.00**. You can [attempt again](#), if you'd like.

Question 1

Given a sequence database, as shown in Table 2, with support threshold min-sup = 3, which of the following sequences are frequent?

SID	Sequence
1	$\langle a(bd)(aef)(bc) \rangle$
2	$\langle (cf)(abe)(bd)d \rangle$
3	$\langle (def)(abcde)(cde) \rangle$
4	$\langle a(abe)cd(ec) \rangle$

Table 2: Sequence database.

Your Answer	Score	Explanation
<input checked="" type="checkbox"/> $\langle (ae)c \rangle$	✓ 0.25	$\langle (ae)c \rangle$ is a subsequence of Sequences 1, 3, and 4, so its support is 3.
<input type="checkbox"/> $\langle (bd)b \rangle$	✓ 0.25	$\langle (bd)b \rangle$ is a subsequence of Sequence 1, so its support is 1.
<input type="checkbox"/> $\langle abd \rangle$	✓ 0.25	$\langle abd \rangle$ is a subsequence of Sequences 2 and 4, so its support is 2.
<input type="checkbox"/> $\langle f(ab) \rangle$	✓ 0.25	$\langle f(ab) \rangle$ is a subsequence of Sequences 2 and 3, so that the support is 2.
Total	1.00 / 1.00	

Question Explanation

The correct answer is: " $\langle (ae)c \rangle$ ".

Question 2

Given a sequence database, as shown in Table 4, and the support threshold $\text{min-sup} = 3$, use Generalized Sequential Patterns (GSP) to find the frequent sequential patterns. After scanning the database once, how many length-2 candidate sequences will be generated after Apriori pruning? How many length-2 candidate sequences will be generated if not using Apriori pruning?

SID	Sequence
1	$\langle a(ag)(bc ef)h \rangle$
2	$\langle (bfg)(ae)(bdf) \rangle$
3	$\langle (abd)c(be f)(dh) \rangle$
4	$\langle (af)(bdf)(ae) \rangle$

Table 4: Sequence database.

Your Answer	Score	Explanation
<input type="radio"/> None of the other options are correct.		
<input type="radio"/> 35; 128		
<input checked="" type="radio"/> 35; 92	✓ 1.00	
<input type="radio"/> 51; 128		
<input type="radio"/> 51; 92		
Total	1.00 / 1.00	

Question Explanation

The correct answer is: "35; 92".

Since the $\text{min-sup} = 3$, after scanning the database once we have the following 5 frequent items (length-1 sequences): a, b, d, e, f. However, we have 8 items (length-1 sequences) in total, namely a, b, c, d, e, f, g, h. Therefore, the number of length 2 candidates is $5 * 5 + 5 * 4 / 2 = 35$; Without Apriori pruning, the number of length 2 candidates is $8 * 8 + 8 * 7 / 2 = 92$.

Question 3

Given a sequence database, as shown in Table 8, and support threshold $\text{min-sup} = 4$, use Generalized Sequential Patterns (GSP) to find the frequent sequential patterns. What is the minimum number of times we need to scan the database in order to find all the frequent

sequential patterns?

SID	Sequence
1	$\langle ab(e)(be)cfg(abe) \rangle$
2	$\langle ad(bc)c(fg)(ch) \rangle$
3	$\langle bc(ad)ebf(cdfgh) \rangle$
4	$\langle c(ec)(eh) \rangle$

Your Answer	Score	Explanation
<input type="radio"/> 4		
<input type="radio"/> 3		
<input type="radio"/> > 4		
<input type="radio"/> 1		
<input checked="" type="radio"/> 2	✓ 1.00	
Total	1.00 / 1.00	

Question Explanation

The correct answer is: "2".

Since min-sup = 4, after scanning the database once we have the following one frequent item: c.

The length-2 candidate sequence is: <cc>, which is not frequent, so we only need to scan the sequence database twice.

Question 4

Given a sequence database, as shown in Table 11, and min-sup = 1, which of the following does not belong to the <d>-projected database?

SID	Sequence
1	$\langle af(e)(cdeh)cfg(abe) \rangle$
2	$\langle ad(bc)c(fg)(ch) \rangle$
3	$\langle bc(ad)ebf(cdfgh) \rangle$
4	$\langle ab(bd)de \rangle$

Table 11: Sequence database.

Your Answer	Score	Explanation
-------------	-------	-------------

☐ <ebf(cdfgh)>

☐ <de>

☐ <(bc)c(fg)(ch)>

☒ <(c_eh)cfg(abe)> ✓ 1.00

Total 1.00 / 1.00

Question Explanation

The correct answer is: "<(c_eh)cfg(abe)>".

The sequences in the database are projected in the <d>-projected database as follows:

- Seq 1. <(_eh)cfg(abe)>
- Seq 2. <(bc)c(fg)(ch)>
- Seq 3. <ebf(cdfgh)>
- Seq 4. <de>

By simple comparison, we have <(c_eh)cfg(abe) >does not belong to <d>-projected database.

Question 5

Given a sequence database, as shown in Table 15, which of the following sequential patterns are closed?

SID	Sequence	count
1	$\langle a(bc)(de)f \rangle$	20
2	$\langle bc(ad)ef \rangle$	20
3	$\langle a(bc)d(ab)ef \rangle$	20

Table 15: Sequence database.

Your Answer	Score	Explanation
<input type="checkbox"/> <abdf>	✓ 0.25	<abdf> has support 40, and its superset <a(bc)df> also has support 40, so it is NOT closed.
<input type="checkbox"/> <bef>	✗ 0.00	<bef> has support 60, and none of its supersets has support 60, so it is closed.
<input checked="" type="checkbox"/> <(bc)ef>	✗ 0.00	<(bc)ef> has support 40, and its superset <a(bc)ef> also has support 40, so it is NOT closed.

☐

☒

0.00

<bdef> has support 40, and none of its supersets has support 40, so it is closed.

Total

0.25 /


1.00

Question Explanation


The correct answers are: "<bdef>" and "<bef>".

Question 6

In our database, we have the following three graphs:



If we set the support threshold $\text{min-sup} = 3$, what is the length of the longest frequent chain graph? The chain graph refers to those graphs that have nodes that are connected one-by-one. The following is an example of a length-5 chain.



Your Answer	Score	Explanation
<input type="radio"/> 2		
<input type="radio"/> 4		
<input checked="" type="radio"/> 5	<div><div>✓</div></div> 1.00	
<input type="radio"/> 3		
Total	1.00 / 1.00	

Question Explanation


The correct answer is: "5".

The bottleneck is the first graph. We can only find a length-5 chain in the first graph (no length-

6 chain). A length-5 chain is available in the other two graphs as well.

Question 7

When we use the Apriori-based approach to find the frequent graph pattern for a candidate graph, we need to check all of its subgraphs. Given the following graph, how many distinct subgraphs with three vertices are there?



Your Answer	Score	Explanation
<input type="radio"/> 2		
<input type="radio"/> 3		
<input checked="" type="radio"/> 1	✓ 1.00	
<input type="radio"/> 4		
Total	1.00 / 1.00	




Question Explanation

The correct answer is: "1".


There are only four possible removes considering the connectivity. All of them lead to a triangle of three vertices. Therefore, there is only 1 distinct subgraph with three vertices.

Question 8

In our database, we have the following three graphs:



What is the support of the following graph?



Your Answer	Score	Explanation
<input type="radio"/> 0		
<input type="radio"/> 1		
<input type="radio"/> 3		
<input checked="" type="radio"/> 2	✓ 1.00	
Total	1.00 / 1.00	

Question Explanation

The correct answer is: "2".

The key is to find a node with degree 4. The second does not contain it; thus the support is 2.

Question 9

Suppose we have learned two ranked rules as follows (the default is Type 2):

- {"ipad", "iphone"} → Type 1
- {"kindle", "iphone"} → Type 2
- {"ipad"} → Type 1

For the people who have {"kindle", "iphone"}, which type will they be classified as by CBA algorithm?

Your Answer		Score	Explanation
<input checked="" type="radio"/> Type 2	✓	1.00	
<input type="radio"/> Type 1			
Total		1.00 / 1.00	

Question Explanation

The correct answer is: "Type 2".

The first rule does not fit the test case, but the second rule {"kindle", "iphone"} → Type 2 fits. Thus it will be classified as Type 2.